ParaliWatch: weekly paddy-residue burn mapping

Shuhul Razdan · Role 01 Data & Model Infrastructure Engineer assignment · reference 123456 (n = 3456) · **R1** Punjab Ludhiana–Patiala · **S4** MODIS · **D5** Burn scars · **T4** Multi-sensor fusion

1 Use-case

A weekly now-cast tells the district nodal officer / PPCB field coordinator for the Nabha–Amloh–Fatehgarh Sahib–Patiala belt which village clusters burnt paddy residue (parali) this week, how much, and how sure we are. Every Monday of the Oct–Nov season the officer picks about 8 clusters for the flying squad and for awareness and CRM-machinery visits. The product is a ranked, named list with newly burnt hectares, the change versus last week, and an evidence flag: MODIS-confirmed, Sentinel-2-only, or MODIS-only (Sentinel-2 blind). AOI: 76.10–76.45 E, 30.36–30.69 N (requested box about 1,229 km², tile 43RFP). Totals use the padded 1,330 km² analysis grid. Season: 2024-09-20 to 2024-11-30. This is a historical replay, not a live service. The student uses the next clear observation, so weekly estimates can use information acquired after that week. Operational Monday decisions have not been evaluated.

2 What I built

- **Decision:** Monday dispatch list of named clusters on a static dashboard.
- **Insight:** H3 × ISO-week feature store (burnt ha, confirmed ha, change vs last week, blind-spot score).
- **Model (v3):** teacher → student fusion. A logistic-regression *teacher* learns from MODIS active-fire weak labels on Sentinel-2 spectra; a gradient-boosted *student* is trained on 862 photo-interpreted labels (incl. an active-learning round) and takes MODIS as features.
- **ARD (v2):** 20 m stack of 6 bands (B8A, B11, B12, B02, B03, B04), cloud/shadow mask plus a haze mask; 1 km MODIS fire stack with an observed flag.
- **Ingestion:** STAC discovery of 27 Sentinel-2 L2A scenes, 20 MOD14A1/MYD14A1 files, 3 MCD64A1 files.
- **STAC lineage catalogue.** Every scene and derived file is a STAC item with `derived_from` links and a parameter hash. Ingestion and ARD reuse current scenes; fusion and later stages rebuild. Bumping the ARD version rebuilt all 27 scenes automatically.
- **Single grid.** A 20 m UTM 43N lattice whose extent is a multiple of 50 cells, so MODIS is an exact 50× coarsening.
- **Streaming fold** in date order; a new scene adds one step.
- **H3 / GeoParquet / DuckDB store** (res 8, exact roll-up to res 7, week-partition replacement); **static dashboard** in `site/index.html`; **manual publication** via `.github/workflows/refresh.yml`.
- **Haze mask.** Sen2Cor SCL does not flag smog. A Haze-Optimised Transform, HOT = B02 − 0.5·B04 > 0.06, marks pixels invalid: 1–2% of pixels in clear scenes, 30–46% in the smog scenes of Nov 9 and 12. It removed a fake week-47 “burn spike” (6,424 ha → 1,095 ha).
- **Label desk.** `paraliwatch label-page reference/testB` writes a self-contained labelling page (same chips, keys 1/0/9, CSV export in the pipeline's format) so a human can replace any AI interpreter.

3 Results

The v3 map classifies 9,722 ha as burnt over the season; 9.2% are MODIS-confirmed (median MODIS re-dating 1 day). v1 mapped 18,133 ha; the haze mask removed the week-47 spike, and the student rejects much of the tillage that v1 counted. Weekly hectares (MODIS column: fire cell-days):

Week	W39	W40	W41	W42	W43	W44	W45	W46	W47	W48
Confirmed ha	0	0	3	17	107	564	25	52	104	18
S2-only ha	84	115	928	1395	1536	1374	634	130	1268	1368
MCD64A1 ha	0	43	1223	451	237	386	43	21	0	0
MODIS fire cell-days	0	0	2	5	19	57	25	5	13	2

Week 47 holds burns from the Nov 9–17 smog gap first seen on the Nov 19 scene; MODIS re-dates the confirmed ones. **Late-season caveat:** W47–W48 Sentinel-2-only area (about 1,300 ha/week) coincides with the weakest

holdout-B interval (late November, F1 0.08) and is likely partly tilled or emerging-wheat commission; treat it as potentially inflated mapped area, not a statistical bound.




Fig. 1 Weekly mapped area and MODIS fire evidence.




Fig. 2 Dashboard, week 45: ranked clusters, evidence flags and weekly map.

4 Evaluation

Design. Design-based assessment (Olofsson et al. 2014), stratified on the map: mapped burn / teacher-only burn / other change / stable. **Holdout B** is the headline: 552 points on three new intervals (2024-10-13→10-23, 10-30→11-07, 11-19→11-29), 60/40/60/24 per interval (other change over-allocated, since missed burns there dominate the recall interval), in 1 km cells disjoint from all training and earlier test points. It was drawn from the v2 maps and sealed before any further model development, first scored at final v3 evaluation, according to the development record. Reproduction runs re-score the frozen references without tuning. Interpreters A and B labelled blind from chips (Cohen's κ 0.551); a blind adjudicator C resolved 155 of 158 disputed or unclear points. The earlier 360-point **test set 1** was scored four times during development and is now reported only as a development set. Values are stratum-weighted estimate [95% bootstrap CI], for eligible cells in the sampled clear-date intervals.

Map	Holdout B, adjudicated (549 points, 67 burns)			Unanimous A=B (394 pts, 24 burns)	Test set 1 (dev)
	Precision	Recall	F1	F1	F1
v3 student	0.272 [0.169, 0.403]	0.146 [0.082, 0.299]	**0.190** [0.117, 0.306]	**0.378** [0.239, 0.510]	0.339
teacher	0.109	0.068	0.084 [0.040, 0.151]	0.116	0.126
v1	0.340	0.120	0.178 [0.021, 0.425]	0.015	0.084
MODIS active fire	0.005	0.006	0.005	–	–
Sentinel-2 dNBR	0.006	0.016	0.008	–	–
MCD64A1	0	0	0.0	–	–

Student overall accuracy is 0.980; MCD64A1, which flags only 2 of 549 reference points, scores 0.984. Accuracy reflects the unburnt majority and is not informative.




Fig. 3 F1 with 95% intervals; left holdout B (spatially held out), right test set 1 (development).

Error analysis. κ was 0.55 against 0.87 on test set 1: in late November A read dull grey-green tilled patches as emerging wheat, B as char. Adjudicator C called burns on 28% of disputed points vs 6% of unanimous ones, so results depend on the reference: resolving disputes as A gives 0.374, as B 0.215. Unanimous-subset F1 (0.378) uses an easier cohort; it is not an upper confidence bound on 0.190. By interval (adjudicated): early 0.32, peak 0.18, late November 0.08. Omission dominates (1.38% of area vs 0.63% commission), concentrated in the "other change" stratum. The fall from 0.34 (test set 1) to 0.19 is the expected price of development-set reuse plus a harder late interval; holdout B's interval is also much tighter (width 0.19 vs 0.46–0.48), which was its purpose.

Training changes in v3. Active learning (round 3): 240 transitions nearest the student threshold (one per 1 km cell) plus 80 mapped-burn audits, 262 usable labels. They are not a probability sample, so they are never scored and enter training only outside each held-out spatial block. Student nested spatial-CV on the 600 scored labels (3 km blocks, teacher refit per fold): AUC 0.899, F1 0.573 → 0.592 with active learning, threshold 0.25. This CV F1 is mildly optimistic (the AL batch and threshold both use the labels it is scored on, and design weights only approximate inclusion probabilities); holdout B is the held-out estimate against AI-interpreted reference labels. A Codex verification found no holdout-B leakage, and `reference/testB/scoring_receipt.json` compares summary diagnostics only; it cannot establish model identity or enforce single use. Pseudo-labels are now excluded at 1 km-cell level from gold and sealed cells. *Self-training* (510 pseudo-labels) scored 0.581 < 0.592 and was rejected by the gate that adopted it in v2. Also rejected: field-object voting (`objects.py`, erased scars), the v1 char-albedo gate, and a 0.5 probability threshold (mapped about 80% of the AOI).

Limit of the reference. All interpreters were AI vision models (Claude Sonnet sub-agents A, B; Claude Opus adjudicator C) reading 20 m chips: a transparent stand-in, not field truth. Chips and label files are in `reference/`; the label desk lets a human relabel and `paraliwatch evaluate` recomputes everything.

Interpretation. The student improves on the teacher, but its holdout F1 is only 0.190. The retired v1 comparison is historical: its raster is not committed and is unavailable on a fresh clone. Reference and training label quality remain major constraints.

5 Configuration question: MODIS as the primary sensor

Strong: temporal. Four overpasses a day, thermal fire detection, a daily fire mask. **Weak:** spatial. 1 km fire pixels and 500 m burned area against fields of about 0.5–2 ha. MCD64A1 mapped 0.0 F1 here. Overpasses (about 10:30, 13:30 and night) miss late-afternoon burning, and short fires can occur between overpasses. VIIRS is a candidate for finer active-fire evidence.

Response: keep MODIS as the primary sensor for supervision and timing, and fuse Sentinel-2 (20 m) for field scale, in three roles:

- **Teacher.** MODIS fires weakly label Sentinel-2 transitions (MCD64A1 idea at 20 m). The teacher ranks well but its boundary is biased by tillage.
- **Features and clock.** Once the labels are photo-interpreted rather than MODIS-derived, MODIS can enter the student as features (own/near fire counts, high-confidence count, max FRP, visibility). MODIS also dates confirmed burns: Sentinel-2 says which field, MODIS says when.
- **Gap-filler.** Blind-spot score = MODIS fire cell-days × (1 − Sentinel-2 clear fraction), its own dispatch card for smog weeks.

6 Fitness for use

Verdict: a prototype for triage, requiring field validation. The workflow is suitable for planning verification visits; its operational usefulness still needs testing. Holdout-B precision of 0.272 [0.169, 0.403] with recall of 0.146 and AI-made reference labels (κ 0.55) cannot support action against an individual farmer. What it takes:

- Human-labelled training and reference sets via the label desk, replacing the AI interpreters (this is the binding constraint).
- Field boundaries, so detections aggregate to fields; the stable strata of the test set could also be enlarged.
- VIIRS 375 m active fire and Sentinel-1 SAR for smog weeks; a late-season tillage/emerging-wheat check, where F1 is 0.08.
- Validation against field or official reports; strict as-of-date evaluation, a rolling window and refresh monitoring.

7 Reproduce

```
git clone https://github.com/shuhulx/parali-watch.git
cd parali-watch
make run      # ingest, ARD, fusion, features, evaluation, dashboard (cold ~20 min)
make serve    # open http://localhost:8000
```

To view the committed demo without rebuilding: `make demo`, then open `http://localhost:8000`. The private repository requires reviewer access. Rebuilding requires `uv` and network access to Planetary Computer. Model, labels and limits: `docs/MODEL_CARD.md`; design: `docs/ARCHITECTURE.md`; AI usage: `docs/AI_LOG.md`.