Notes 6

MKDIR

- **Usage**
  - `mkdir` is used to create new directories (folders).
- **Formula**
  - `mkdir + directory name`
- **Examples**
  - Create a directory named Projects:
    - `mkdir Projects`
  - Create multiple directories:
    - `mkdir Folder1 Folder2`
  - Create a directory and its parent directories:
    - `mkdir -p Documents/School/Notes`

TOUCH

- **Usage**
  - `touch` is used to create a new empty file. It can also update the timestamp of an existing file.
- **Formula**
  - `touch + file name`
- **Examples**
  - Create a file named notes.txt:
    - `touch notes.txt`
  - Create multiple files:
    - `touch file1.txt file2.txt`
  - Create a file named homework:
    - `touch homework`

RM

- **Usage**
  - `rm` is used to remove or delete files and directories.
- **Formula**
  - `rm + option + file or directory name`
- **Examples**

    - Delete a file named notes.txt:
        - `rm notes.txt`
    - Delete a file without prompting:
        - `rm -f notes.txt`
    - Delete an empty directory:
        - `rmdir Folder1`
    - Delete a directory and its contents:
        - `rm -r Folder1`

CP

- **Usage**
    - `cp` is used to copy files and directories from one location to another.
- **Formula**
    - `cp + option + source + destination`
- **Examples**
    - Copy a file named notes.txt:
        - `cp notes.txt backup.txt`
    - Copy a file into the Documents directory:
        - `cp notes.txt Documents/`
    - Copy a directory and its contents:
        - `cp -r Projects Backup`

MV

- **Usage**
    - `mv` is used to move files and directories from one location to another. It can also rename files and directories.
- **Formula**
    - `mv + source + destination`
- **Examples**
    - Rename a file from old.txt to new.txt:
        - `mv old.txt new.txt`
    - Move a file into the Documents directory:
        - `mv notes.txt Documents/`
    - Move a directory into another directory:
        - `mv Projects Backup/`