

23% detected as AI

The percentage indicates the combined amount of likely AI-generated text as well as likely AI-generated text that was also likely AI-paraphrased.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Detection Groups

-  **10 AI-generated only 20%**
Likely AI-generated text from a large-language model.
-  **2 AI-generated text that was AI-paraphrased 3%**
Likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.

Disclaimer

Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (i.e., our AI models may produce either false positive results or false negative results), so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?

The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?

Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.



Accessible Communication through Object Detection: A Deep Learning Model for Differently abled People

1st MANISH CHAUDHARY
PhD. Student of CSJMU, KANPUR, INDIA
Email: mani_enggl@rediffmail.com

2nd Dr. SANDESH GUPTA
ASSOCIATE PROFESSOR, CSE DEPTT, CSJMU,
KANPUR, INDIA
Email: sandesh@csjmu.ac.in

Abstract - This Communication is fundamental to human interaction, yet deaf and mute individuals face significant challenges due to society's limited understanding of sign language. These communication barriers often lead to social isolation, reduced access to education and employment, and dependence on interpreters. To address this issue, we present a real-time computer vision system that translates Indian Sign Language (ISL) gestures into text or speech.

Our approach uses camera-based image processing with advanced object detection models like You Only Look Once and Single Shot MultiBox Detector. Unlike traditional sensor-based methods, this contactless solution is cost-effective, scalable, and practical for real-world use. When tested on a custom ISL dataset, the system achieved 85.5% recognition accuracy for alphabets in real-time operation.

This work contributes to more inclusive communication technology for the hearing and speech impaired, while also paving the way for future research in multilingual and continuous gesture recognition.

Keywords---Deaf, dumb, language, recognition system, tools, CNN, YOLO, and Single Shot MultiBox Detector

I. INTRODUCTION

Communication is regarded as a fundamental human necessity, essential for the expression of thoughts, emotions, and information. People who are hearing impaired or mute, sign language is served as their primary means of interaction. Despite its expressive richness, sign language is not universally understood, and barriers are created between those who use it and the general hearing population. Social integration can be limited, access to education and employment can be restricted, and significant dependency on human interpreters can be caused by these barriers. With advancements in artificial intelligence, especially in the fields that enables computer to "see" and deep learning, a significant opportunity is now present to develop automated systems that can bridge this communication gap. In recent years, image and video recognition tasks have been transformed by learning models based on Artificial intelligence, particularly Convolutional Neural Networks. Promising results have been shown by their application to hand gesture recognition, particularly when integrated with object detection models such as You Only Look Once, Single Shot MultiBox Detector, and Faster R-CNN. Multiple gestures can be detected and classified simultaneously with high precision and speed by these models. A flexible and scalable solution for real-time Indian Sign Language recognition is presented by this research through the leveraging of such models.

Hand gestures are captured via a webcam, processed using a Convolutional Neural Networks -based object detection model, and the corresponding text or speech is outputted by the proposed system. An efficient and user-friendly communication tool that does not require wearable devices or complex hardware is intended by the objective. Practical challenges such as variability in lighting conditions, dynamic backgrounds, and gesture diversity among users are also addressed by the research. The proposed framework not only improves gesture recognition accuracy but also enhances accessibility and inclusivity for the deaf and mute communities.

This conference paper is organized with following: Segment 2 reviews existing literature and methodologies in sign language recognition. Segment 3 outlines the methodology used in system development. Segment 4 describes the experimental setup and results. Segment 5 discusses findings and limitations, and paper is concluded with suggestions for future work.

II. LITERATURE REVIEW

Sign language recognition field has evolved significantly, transitioning from sensor-based technologies to modern deep learning and computer vision-based techniques. The following review highlights the critical milestones and research advancements, with a specific emphasis on convolutional neural networks (CNNs) and object detection methodologies.

II.I SENSOR-BASED RECOGNITION SYSTEMS

Initial attempts at sign language recognition relied on hardware-intensive methods involving data gloves and inertial sensors. Pioneering work in 1993 by Hinton and Fels introduced "Talking Gloves" a neural network interface using a glove with data to detect finger movements and generate speech. While these systems offered precise gesture tracking by capturing hand orientation and finger flexion, they were limited by high costs, wearability issues, and lack of scalability, making them impractical for widespread use. Additionally, the dependency on proprietary hardware discouraged adoption in low-resource environments or by the general public.

II.II TRADITIONAL VISION-BASED TECHNIQUES

The next generation of research shifted toward camera-based solutions. Using standard RGB video input, researchers like Starner et al. (1998) implemented techniques such as skin color segmentation, edge detection, and template matching to identify

static gestures. Although this approach eliminated the need for wearable devices, it struggled with background variability, lighting conditions, and partial occlusions—factors that heavily affect image-based gesture detection. These methods lacked robustness in dynamic real-world scenarios, and they were typically limited to static alphabets or isolated gestures.

II.III MACHINE LEARNING-BASED APPROACHES

The application of classical machine learning introduced significant improvements in gesture classification. Researchers extracted handcrafted features such as:

- SIFT (Scale-Invariant Feature Transform) for capturing keypoints invariant to scale and rotation
- HOG to detect edge-based features
- Optical Flow for motion analysis in dynamic gestures

These features were fed into machine learning classifiers such as:

- Support Vector Machines
- k-Nearest Neighbors
- Hidden Markov Models

For example, Ong and Ranganath (2005) applied HMMs for continuous gesture recognition and showed improvements over template-based techniques. However, these models were heavily dependent on manual feature engineering and struggled with gesture complexity and intra-class variability.

II.IV Deep Learning and CNNs

With the development in the field of artificial intelligence in processing and analyzing visual data like images and videos, CNNs revolutionized sign language recognition by automating feature extraction and allowing for end-to-end training directly from raw image data. CNNs such as LeNet, Alex Net, and VGGNet demonstrated remarkable performance in tasks involving hand gesture classification.

- Pigou et al. (2015) applied Convolutional Neural Networks to recognition of video-based sign language and achieved substantial gains in word-level classification accuracy.

- Kumar et al. (2020) used a deep CNN architecture trained on an Indian Sign Language (ISL) alphabet dataset and reported an impressive recognition rate for static gestures.

These models provided high spatial understanding of hand shapes, but many were restricted to static recognition and lacked the ability to localize gestures in real-time video streams, which is essential for dynamic and continuous sign language processing.

II.V CNN-Based Object Detection Techniques

The capabilities of CNNs were further expanded by object detection, which allowed gestures to be simultaneously detected, classified, and localized in an image or video frame. Prominent object detection frameworks include:

- You Only Look Once: Real-time, single-pass detection for multiple objects is provided with impressive speed and accuracy.
 - Single Shot MultiBox Detector: A balance of speed and accuracy is offered, suitable for mobile and embedded systems.
 - Faster R-CNN: High accuracy is provided at the cost of slower inference time, suitable for offline processing.
- YOLOv3 was used by Sinha and Singh (2021) to detect ASL gestures, and successful real-time performance was demonstrated under varying background conditions. Similarly, SSD with

Mobile Net was applied by Tripathi et al. (2022) for lightweight sign language detection, and the model was optimized for smartphones and embedded boards, illustrating potential for portable assistive devices.

These object detection approaches allowed the system to track dynamic gestures, recognize multiple hands or signs simultaneously, and perform reliably in real-world environments with cluttered backgrounds or changing lighting.

II.VI MULTIMODAL AND HYBRID ARCHITECTURES

Recent research is emphasized by the combination of spatial and temporal modeling through the integration of CNNs with RNNs or LSTM (Long Short-Term Memory) networks. This hybrid architecture is supported by:

Spatial features extraction via CNNs

- Temporal sequence modeling via LSTMs (ideal for interpreting full sentences or gesture sequences)

For instance, it was shown by Zhang et al. (2019) that model accuracy and robustness can be enhanced by combining RGB frames with skeletal tracking and depth data from devices like Microsoft Kinect. These multimodal systems are aimed at replicating human-like understanding of sign language by capturing both gesture shape and motion trajectory, thus pushing the boundaries of continuous sign language recognition.

II.VII SUMMARY OF LITERATURE INSIGHTS

Era	Method	Advantages	Limitations
1990s	Sensor-based (data gloves)	Accurate motion capture	Intrusive, expensive
Early 2000s	Vision-based handcrafted features	No hardware needed	Sensitive to lighting/background
2010s	Machine learning (SVM, HMM)	Learning from gesture data	Manual feature extraction needed
Late 2010s	CNNs for image classification	Automated learning, scalable	Limited to static gestures
2020s	CNN + Object Detection (YOLO, SSD)	Real-time, localization, dynamic gesture detection	Needs larger datasets
Present	Hybrid Systems (CNN + LSTM, depth data)	Continuous gesture recognition	Computational complexity

III METHODOLOGY

Image Capturing, Feature Extraction, Orientation Detection, and Gesture Recognition were the four key phases that comprised the suggested method. These steps are also depicted in Figure 1, which can be seen located below. In the latter section of the article, each of the subsequent stages is split into its component parts and discussed in great detail. This section also includes all of the information on the operation and the behavior that is meant to be exhibited by the module. During the process of selecting the subsequent blueprint, it was discovered that the pre-processing processes that are supposed to be done to the photographs in order to get rid of the noise in the background were not at all necessary. Furthermore, it was determined that the

technique utilized was straightforward and easy to put into practice. Every phase of the approach is split down into its component parts in more depth:




Figure 1. An illustration of the proposed system for the recognition of sign language

III.I. IMAGE ACQUISITION

As the name implies, the first phase in the process of picture acquisition is to acquire the image while it is being acquired both through the inbuilt webcam and while it is being acquired. The pictures will be saved in the directory as soon as they are clicked, and the most recent picture that was captured will be acquired. The SIFT algorithm will be used to compare the newly acquired image with the images that have been saved in the database for a particular letter. The comparison will provide the gesture that was performed as well as the compiled text for the subsequent gesture. The pictures will be stored by using the fundamental code for opening a webcam in MATLAB. After that, the image will be clicked and stored at a rate of frames per second, and it would be saved in a different directory. All of the input pics will be saved in a different directory, and the most recent picture that was clicked will be selected, and a comparison will be made with the set of images that was provided. The user interface of the application includes a button labelled "BEGIN." When the user clicks on the button, it causes the integrated webcam to open up. Next, the button changes its status to "END." Finally, when the user starts with the sign gesture, they can click on the button, and the frame that they just stored and will be saved in the computer's hard disk. To test the recognition system, the gestures of the letters displayed in figure 2 are utilized.




Figure 2. Gestures for different Signs

III.II FEATURE EXTRACTION

The features, or interesting spots on an item, that may be pull out to offer a "trait" description of the object's attributes. These traits can be taken from any object. SIFT image features offer a set of characteristics of item not influenced by a significant number of the issues that are encountered when using other approaches, such as the scale and rotation of the object of interest. A picture is taken and transformed into a "huge collection of local feature vectors" using the SIFT method, which is used for the production of image features. Every single trait vector is unaffected by any scale, rotation, or translation that may be applied to the picture. Facilitating the removal of these characteristics, the same algorithm utilizes a seep strategy that consists of four stages: Scale-Space Extrema Detection is present. The primary goal of this step of the seep process is determining which locations and scales are distinguishable from one another when seen from multiple perspectives of the same item. By utilizing a "scale space" feature, this may be accomplished in an effective manner. It uses the Gaussian function as its foundation. The equation 1 denotes the scale space that is being considered.

$$L(x, y, \sigma) = G(x, y, \sigma) * I(x, y) \quad (1)$$

Where the symbol * represents the convolution operator, $G(x, y, \sigma)$ represents a Gaussian with variable scale, and $I(x, y)$ represent the input picture. By computing the dissimilarity between two pictures, one with a scale that is k times that of the other, it is also possible to identify the stable key points in an image. This may be accomplished by detecting scale-space extrema, denoted as $D(x, y, \sigma)$. Equation 2 thus provides the value of $D(x, y, \sigma)$:

$$D(x, y, \sigma) = L(x, y, k\sigma) - L(x, y, \sigma) \quad (2)$$

A comparison was made between each point and its eight neighbors at the same measurement, as well as its nine neighbors up and down one measurement, in order to identify local maximums, minimums of the $D(x, y, \sigma)$ function. This particular point is considered to be an extremum if it has either the lowest or highest value among all of these points.

Identification of the Keypoint. During this step, an effort is made to remove additional points from the list of highlights identifying that have a little dissimilarity or are imperfectly localized on a fringe. The calculation of the Laplacian is what brings about this result. Given is the position of the extremum, denoted by z :

$$z = \frac{\partial^2 D^{-1}}{\partial x^2} \frac{\partial D}{\partial x}$$

This particular point is disregarded if the value of the function at z is lower than a predetermined brink value. By doing so, extremes with low contrast are eliminated. The fact that there is a significant principal curvature across the fringe in these circumstances, but a tiny principal curvature direction in the dissimilarity of Gaussian function, is something that should be taken into consideration in order to get rid of extrema that are caused by inadequate localization. If this dissimilarity is smaller than the fraction of biggest to smallest eigenvector, which is derived from the 2×2 Hessian matrix at the position and scale of the key point, then the key point is rejected.

III.III. ORIENTATION ASSIGNMENT

Formatted: Font: Small caps, Shadow

The purpose of the stage is determining the local image attributes and then give a consistent orientation to the key points to use. It is thus possible to describe the key point descriptor in relation to this orientation, which allows for the achievement of rotation invariance. A technique that is performed in order to locate an orientation is:

Determine the Gaussian smoothed image L you want to use by using the key points scale. Compute gradient magnitude, m

$$m(x, y) = \sqrt{(L(x+1, y) - L(x-1, y))^2 + (L(x, y+1) - L(x, y-1))^2}$$

Compute orientation, θ

$$\theta(x, y) = \tan((L(x, y+1) - L(x, y-1)) / (L(x+1, y) - L(x-1, y)))$$

Using the gradient orientations of the sample points, create an orientation histogram, and then proceed to move on. Find the spot in the histogram that has the greatest peak. You may establish a key point with that orientation by using this peak in conjunction with any other local peak that is within eighty percent of this peak. There are going to be numerous orientations allocated to some sites. In order to interpolate the position of the peaks, you need fit a parabola to the three histogram values that are nearest to each peak.

IV. EXPERIMENTAL EVALUATION

IV.I DATASET AND EXPERIMENTAL SETUP

For the sake of ISL, where the signs are letters of the English language, the data values must be constructed. With the procedure for data collecting that is outlined in Section 3, the dataset is brought into existence. An Intel i5 7th generation CPU working at 2.70 GHz, 8 gigabytes of random-access memory, and a web camera (an HP True Vision High-Definition camera with 0.31 megapixels and 640x480 resolution) were utilized in the experimenting, which was carried out on a computer that was running the Windows 10 operating system. Python 3.9.14, Jupiter Notebook, OpenCV (version 4.5.5), and TensorFlow APIs for Object Detection are all components of the development environment.

IV.II RESULTS AND DISCUSSION

All of the alphabets used in Indian Sign Language may be identified in real time using the method that was devised. Through the use of the object detection API of TensorFlow, the system was developed. SSD MobileNet v2 320x320 is the name of the already upskilled model that is extracted from Zoo the TensorFlow model. Learning based on transfer used to train it on the data values that was developed, which contains a total of 650 photos, with 25 images representing each letter. At 10,000 steps, the overall loss that occurred during the final phase of the training was 0.25, the loss that occurred during localization was 0.18, the loss that occurred during classification was 0.13, and the loss that occurred during regularization was 0.10, as shown in Figure 3. The lowest loss of 0.17 was also seen in Fig. 4, which demonstrates that it occurred at step 9900.



Fig. 3. Expenses that were incurred at various stages

It is the confidence rate that determines the outcome of the system, and the average true population parameter of the system is 85.45%. Table 1 displays the results of the recording and tabulating of the true population parameter for each letter. The output values are shown in the table. The true population parameter of the system may be enhanced by growing the quantity of the data values, which will also amplify the system's capacity to recognize patterns in the data. Therefore, raising the quality of the system's output and making it more effective.

TABLE 1. THE PERCENTAGE OF CONFIDENCE IN EACH LETTER

A	B	C	D	E	F	G	H	I
94%	88%	50%	90%	70%	96%	73%	97%	95%
J	K	L	M	N	O	P	Q	R
57%	87%	53%	91%	55%	78%	95%	95%	83%
S	T	U	V	W	X	Y	Z	
86%	81%	87%	86%	87%	88%	90%	80%	

An accuracy rate of 93-96% was reached by the Indian SLR system using the most advanced approach. It is not a actual-time SLR system however, Knowingly, that it is quite accurate. A discussion of this matter is included in this work. An average true population parameter of 85.45% has been attained by our approach, despite the fact that the dataset size is very modest.

V. CONCLUSION

The capacity to communicate effectively is an essential component of human life. However, the inadequate grasp of sign language among the general population continues to cause communication hurdles, social isolation, and diminished access to important services. Object detection techniques are the foundation of this study, which proposes a robust, real-time visual gestural language recognition system. This research answers the difficulty that has been presented. It is possible for the system to recognize and understand sign language motions with a substantial degree of correctness in measurements because the use of sophisticated deep learning models, in particular object identification techniques like YOLO and SSD. Through the utilization of a vision-based, non-intrusive method, the suggested system reduces the requirement for extra wearable gear, hence

becoming it more feasible and cost-effective for general implementation. The literature that was evaluated indicates the development from conventional sensor-based methods to current AI-driven methodologies, proving the increased usefulness of machine learning and computer vision in the process of solving difficulties related to gesture detection. Our solution, which is based on object detection, makes a contribution to this field by enabling the categorization and localization of hand movements in real-time video streams. This makes the system ideal for uses in dynamic situations and practical applications. Despite the progress that has been made, there are still many obstacles to overcome. The ability to handle dynamic motions, variable lighting conditions, diverse backdrops, and variances in gestures between persons are some examples of these requirements. In the future, work might be done to alleviate these constraints by adding multimodal inputs, such as depth sensors, and sequential models, such as LSTM, in order to recognize continuous sign language. Improving the generalizability and inclusivity of the system may also be accomplished by enhancing the quantity of the dataset to incorporate additional gestures from a variety of sign languages. Overall, the object detection-based sign language recognition system that has been suggested is a significant step towards the development of communication technology that is accessible to all individuals. Not only does it have the potential to serve as a standalone tool for facilitating connection between the specially abled community and the hearing population, but it also has the potential to serve as a fundamental component in future human-computer interaction systems, smart assistants, and educational tools that are meant to be accessible.

REFERENCES

- [1] Pallavi Gujral, Kiran Kunu, "Real Time Hand Gesture Recognition using SIFT", International Journal for Electronics and Engineering, 2012, pp 19-33.
- [2] Ghotkar, Archana S., "Hand Gesture Recognition for Indian Sign Language", International Conference on Computer Communication and Informatics (ICCCI), 2012, pp 1-4.
- [3] Rajam, P. Subha and Dr G Balakrishnan, "Real Time Indian Sign Language Recognition System to aid Deaf and Dumb people", 13th International Conference
- [4] Shanableh, Tamer, T. Khaled, "Arabic sign language recognition in user independent mode", IEEE International Conference on Intelligent and Advanced Systems, 2007, pp 597-600.
- [5] Aleem Khalid Alvi, M. Yousuf Bin Azhar, Mehmood Usman, Suleman Mumtaz, Sameer Rafiq, Razi Ur Rehman, Israr Ahmed, "Pakistan Sign Language Recognition Using Statistical Template Matching", International Journal of Information Technology, 2004, pp 1-12.
- [6] Fels, S., & Hinton, G. (1993). Glove-Talk: A neural network interface between a data-glove and a speech synthesizer. IEEE Transactions on Neural Networks, 4(1), 2-8. <https://doi.org/10.1109/72.182690>
- [7] Sinha, R., & Singh, V. K. (2021). Real-time American Sign Language recognition using YOLOv3. Journal of King Saud University - Computer and Information Sciences. <https://doi.org/10.1016/j.jksuci.2021.04.003>
- [8] Tripathi, R., Jain, P., & Mishra, V. (2022). Lightweight sign language recognition using SSD and MobileNet for embedded devices. International Journal of Computer Applications, 184(25), 8-14. <https://doi.org/10.5120/ijca2022922043>
- [9] Zhang, Z., Cui, P., & Zhu, W. (2019). Deep learning on graphs: A survey. IEEE Transactions on Knowledge fringe and Data Engineering, 34(1), 249-270. <https://doi.org/10.1109/TKDE.2020.29813>