

Project 3 - TPC-C with XML: XSLT

INSTRUCTIONS

1. This project is an individual project.
2. Submit a modified text file “`tpcc.xml`” with your answer to the folder “Submissions: XSLT” in Luminus “Files > Projects > TPC-C with XML by **Friday 2 April 2021, 18:30**.”
3. There is no late submission.

The Transaction Processing Performance Council (TPC) proposes the TPC-C benchmark¹ to measure the performance of online transaction processing systems. In the TPC-C business model, a wholesale parts (items) supplier operates out of a number of warehouses. TPC-C simulates a complete environment where a population of terminal operators executes transactions against a database. The benchmark is centred around the principal activities (transactions) of an order-entry environment. These transactions include entering and delivering orders, checking the status of orders, and updating and monitoring the level of stock at the warehouses.

We consider a simplified version of the TPC-C database. The simplified schema consists of the three tables `item`, `warehouse`, and `stock` that has been converted into an XML file called `TPCC.xml`.

Download the following file from Luminus “Luminus Files > Projects > TPC-C with XML > Code.

`TPCC.xml`,

`tpcc.xml`.

The document’s root element is `warehouses`. Each warehouse record is represented by an element `warehouse` that is a sub-element of `warehouses`. There might be no warehouse. Each `warehouse` element consists of a sequence of four sub-elements: `id`, `name`, `address`, and `items` corresponding to the five attributes of the warehouse record. The address element consists of three sub-elements `street`, `city` and `country`. The `items` element contains one sub-element `item` for each of the items stocked in the warehouse. There might be no item in the warehouse. Each `item` element consists of a sequence of five sub-elements: `id`, `im_id`, `name`, `price`, and `qty`. The first four sub-elements correspond to the four attributes of the item record and the `qty` element represents the quantity of that item stocked in the warehouse.

Your answers to the questions should be general enough to work for other similar documents (namely other documents following the same design logic).

¹The TPC Benchmark™C (TPC-C). www.tpc.org/tpcc. Visited on 06 January 2021

Your answers to the questions should prefer an XPath query with the full syntax to the one using the shorthand syntax. Your answers to the questions should prefer an XPath query with a complete path to the one with a more concise path.

Prefer XSLT template matching with “`value-of`” and “`apply-template`” to imperative control structures (e.g. “`for-each`”).

Modify the XSLT file “`tpcc.xsl`” by writing the XSLT stylesheet in the space indicated.

1. (4 points) Write an XSLT stylesheet that displays in a table or a list of an HTML document the names of the warehouses in Singapore or Malaysia and the name of the items available in the largest quantity in that warehouse. Make the XSLT stylesheet above an external stylesheet for the “`TPCC.xml`” file.

– END OF PAPER –