The Skipped Candidates in the NIST and ANSI X9.62 Curve Seed Runs: A Negative Result, and a Structural Observation on the K-163 Generator

Dan Shumow*

October 2026 — draft

Abstract

In October 2026 Anthropic recovered the NIST and ANSI prime-curve seeds as C-library `lrand48` output seeded by Unix timestamps. The reproduction exposes a loose end: in four prime-field runs, eleven unpublished candidates give prime-order curves of the right size, while eight were published. We regenerate the runs, check the group orders, and compare roughly fifty properties of the nineteen viable curves (including, after review, the complete factorization of b as an integer and deep ECM on the cubic, quartic and sextic extension-order cofactors), together with models of the generating program and a set-cover search for unions of small defects. No tested rule separates the groups. An exact comparison preserving the published counts and the final published candidate in each run admits a cover as small as the observed one in 88 of 126 relabellings. These exploratory negative results do not exclude untested numerical criteria, run-specific code, or variable RNG consumption. Seven published coefficients match the textbook square-root convention; recovered seed offsets constrain cumulative RNG alignment, not every call. Separately, the subgroup half of the K-163 generator has a 126-bit x-coordinate on a 163-bit curve. A coefficient-order error in the original decimal export has been corrected without changing that bit length. The short coordinate survives independent Python and PARI checks and remains a concrete provenance lead, but its source and construction are unidentified.

1 Introduction

ECDSA's standard curves were handed to NIST in 1997–98 with seed values and no account of their origin [7, 8]. Koblitz and Menezes catalogued the resulting unease [5]; Bernstein, Lange and coauthors showed how much freedom a seed-search would have given a malicious designer [6]; Valsorda posted a bounty for the seeds' derivation [4]. In October 2026 Anthropic's Frontier Red Team reported that the seeds are `lrand48` output: five NIST prime-curve seeds and five ANSI X9.62 example-curve seeds are 20 consecutive bytes of `lrand48`() $\gg 23$ after `srand48`(t) with t a Unix timestamp between May 1997 and April 1998, and four of the five binary-curve seeds are five 31-bit `lrand48` words from one sitting on 17 April 1998 [1]. The B-163 seed remains unexplained. Valsorda reproduced the result; the Anthropic team claimed the bounty and directed it to ISRG [3]. The work is one output of a broader programme of model-assisted cryptanalysis at Anthropic [2], whose authors identify human validation of model-found results as the current bottleneck; the

*[affiliation]; `shumow@gmail.com`. Computations and drafting assisted by Claude (Anthropic).

present paper is, among other things, such a validation. The same Anthropic post [1] also explained six of the base points: for P-192 and the five ANSI X9.62 example curves prime192v2, prime192v3, prime239v1, v2 and v3, the generator's x-coordinate is output of the `zrandom` generator in Lenstra's FreeLIP library [9] (state $\times 3^{121} \bmod 2^{107} - 1$), seeded with a small integer, with the first on-curve x taken; those six were generated in May 1997. We rely on that finding below (Sections 4 and 6) and claim no part of it. The base points of P-224, P-256, P-384, P-521 and all ten binary curves were left unexplained there.

Both write-ups note a residue. A run produces candidates in order; a candidate is *valid* if $-27/c$ is a square mod p (so a coefficient b exists), *viable* if the resulting curve has prime order n with $\lceil \log_2 n \rceil \leq \lceil \log_2 p \rceil$ (an undocumented but evidently applied rule [3]). In the P-256 run, candidate 876 is viable but candidate 1842 was published; the P-224 run passed over three viable candidates and the two ANSI runs seven more. Valsorda summarizes: "roughly twice as many valid seeds as were published," with a second undocumented criterion that "still escapes us."

This paper attempts to find that criterion. The tested properties and program models do not provide a separator. This does not exhaust cheaply computable properties or establish statistical equivalence. Section 2 fixes the data. Section 3 reports the invariant sweep, Section 4 the program models, Section 5 the set-cover test. Section 6 reports the K-163 observation. Section 7 lists what remains open.

2 Setup and reproduction

Runs. The four prime-field runs and their published candidates are: P-256 (`srand48` 1997-08-16 01:52:34 UTC, candidate 1842); P-224 (1998-04-03 12:52:07, candidate 7026); the prime192 run (1997-05-18 14:45:34; P-192 at 139, prime192v3 at 5228, prime192v2 at 6013); the prime239 run (1997-05-15 15:49:03; prime239v1/v2/v3 at 2185, 2320, 3048).

Reproduction. For every candidate we derive c by the X9.62 SHA-1 expansion and both square roots of $-27/c$. Candidates with 2-torsion (the cubic has a root) are discarded without counting. Group orders were computed with full SEA in PARI/GP 2.10 built from source and checked by $n \cdot P = O$ on random points. For prime $n > 4\sqrt{p}$ in the Hasse interval, one nonzero point killed by n determines $\#E$; for composite orders these are consistency checks, not independent certificates. (An early-abort pass produced trace-sign errors in that build and was discarded.) Review checks with PARI/GP 2.19.0 certify all nineteen viable prime orders by primality, the Hasse bound, and scalar multiplication.

Square-root convention. For every published curve over $p \equiv 3 \pmod 4$—P-256, P-192, prime192v2, prime192v3, prime239v1, v2, v3—the published b equals $(-27/c)^{(p+1)/4} \bmod p$, never the other root. This is consistent with the textbook square-root routine, but does not establish that the other root was never tested. Using this convention reproduces the source posts' viable lists; accepting either root adds $4 + 10 + 9$ candidates across those three runs. For P-224 ($p \equiv 1 \pmod 4$) the roots give isomorphic curves.

The nineteen. With that convention and the size rule, the viable candidates are

run	viable	published	skipped
P-256	876, 1842	1842	876
P-224	777, 1485, 5736, 7026	7026	777, 1485, 5736
prime192	139, 2198, 5228, 5405, 6013	139, 5228, 6013	2198, 5405
prime239	36, 1562, 2185, 2320, 2491, 2682, 2863, 3048	2185, 2320, 3048	36, 1562, 2491, 2682, 2863

eight published, eleven skipped—exactly the lists in [1, 3]. In every run the published candidate with the largest index is the last viable candidate of the run; this is where runs stopped, not a selection rule, since 139 and 5228 (and 2185, 2320) were published with later viable candidates skipped.

Calibration. The unknown criterion rejected about half of the viable candidates, not one in a thousand of all candidates. Any proposed rule must fail at that rate.

3 Curve invariants

Every property below was computed for all nineteen curves and compared between the published and skipped groups. The strongest form of the negative evidence is in the two runs that published three curves each: there the published curves disagree *with one another* on most binary properties, so no such property can have been required. Tables are in Appendix A; the full record with scripts is in the repository.

3.1 Arithmetic of n and t

Twist order $n' = 2p+2-n$: small-factor structure and cofactor primality interleave (published P-224: $3^2 \cdot 11 \cdot 47\times$ 212-bit composite; skipped 1485: $3 \cdot 31\times$ 218-bit composite). Complete factorizations of $n \pm 1$ (PARI MPQS; all cofactors fell in seconds): the published P-256 has the smoothest $n-1$ of its run (largest prime factor 92 bits) while the candidate it displaced has $n - 1 = 2 \cdot 3 \cdot 7 \cdot 11 \cdot 43 \times P_{242}$; in prime239 the published largest prime factors (69, 128, 110 bits) sit inside the skipped range (76–219). Congruences of t, n, b modulo 2, 3, 4, 5, 8, 16; $b < p/2$; $(n-1)/2$ prime: nothing.

3.2 CM structure

With $D = t^2 - 4p = fs^2$, f fundamental, the conductor s of $\mathbb{Z}[\pi]$ in $\mathcal{O}_K$ is 1 for sixteen curves, 3 for the published P-224, and 5 for one published (prime239v2) and one skipped (2682) prime239 curve. The class number, estimated as $\sqrt{|f|}\, L(1, \chi_f)/\pi$ with the Euler product to 10^6, is *smallest* in its run for the published P-224 and *larger* for the published P-256 than for its skipped competitor; in the ANSI runs the estimates interleave. No tested universal floor or ceiling separates the groups. These estimates have no certified truncation error; stability at two Euler-product cutoffs is not an error bound. The heuristic $\Pr(s \geq X) \approx 1/X$ is a random-discriminant model, not a proved distribution for fixed-p, prime-order, root-conditioned curves.

3.3 Isogeny structure

For $s = 1$, $\mathrm{End}(E) = \mathcal{O}_K$ is forced; small rational ℓ-isogenies are read from roots of $\Phi_\ell(j(E), X)$ modulo p. The published P-224 ($s = 3$) has four roots at $\ell = 3$, locating it on the crater of a height-one 3-volcano. Across all nineteen curves it is not the only nontrivial volcano: prime239

candidates 2320 and 2682 have $s = 5$ and only one rational 5-isogeny each. They are on the floors, with $\mathrm{End}(E) = \mathbb{Z}[\pi]$, not $\mathcal{O}_K$; one is published and one skipped. Over $\mathbb{F}_{p^k}$ the Frobenius conductor becomes sU_k and the volcano height is $v_\ell(sU_k)$. The geometric endomorphism ring is unchanged; its conductor fixes the vertex's distance from the crater. Thus not every curve is on the crater over extensions. The tested heights and positions do not yield a separator.

3.4 Extension-field group orders

$\#E(\mathbb{F}_{p^k})/n$ for $k \le 12$, trial-divided to 10^6: smooth parts of 1–150 bits, as for random integers of these sizes, interleaving at every k. Going deeper on the genuinely new pieces—$C_3 = \#E(\mathbb{F}_{p^3})/n$, $C_4 = \#E(\mathbb{F}_{p^4})/\#E(\mathbb{F}_{p^2}) = (p-1)^2 + t^2$, and the sextic piece $C_6 = \#E(\mathbb{F}_{p^6})\, n/(\#E(\mathbb{F}_{p^3})\#E(\mathbb{F}_{p^2}))$, each 384–512 bits—with GMP-ECM at a full $t25$ level plus half of $t30$ (which finds every prime factor below $\approx 2^{80}$ and most below 2^{100}): 2^{40}-smooth parts, largest factors found, and primality of the 180–490-bit remainders all interleave. The largest contrast anywhere is a mildly smoother C_6 on the published side (median smooth part 56 bits against 28; rank-sum $z \approx 2.2$), the expected size of the best coincidence among this many statistics, and C_6 is not a quantity a 1997 program would have computed ($n \nmid C_6$ for every candidate).

3.5 Embedding degree, gcds, symbols

$\mathrm{ord}_n(p) > 20{,}000$ for every viable curve; exact values were obtained for some. In particular, a 2^{222} lower bound cannot hold for a 192-bit subgroup. No tested gcd statistic (value, odd part, largest prime factor) ranks published above or below skipped consistently across the four runs. Within prime192 the published curves have $(n/p) = +1, -1, +1$ and $n \equiv 1, 3, 1 \pmod 8$; within prime239, $n \equiv 3, 3, 1 \pmod 8$. No tested symbol or residue separates all four runs.

3.6 The coefficient b as an integer

b is the one seed-derived integer in a candidate ($a = -3$ is fixed), so a program inspecting b itself would have a hook invisible to the point-count tests. All nineteen b were factored completely (msieve QS/ECM; cofactors primality-tested, products checked). Number of prime factors runs 5–9 on the published side and 2–13 on the skipped side; largest prime factors 50–201 bits against 77–219, interleaving within every run (the published P-224 b has the largest prime factor of its four; the published prime192 values 50, 76, 96 bits bracket the skipped 77, 95); four of eight published and five of eleven skipped b are square-free; residues mod 3, 4, 5, 8 are scattered on both sides. The published b avoid $\{1, 2, 6\}$ mod 7, a $\approx 1\%$ coincidence before correcting for the moduli tried, and those predicates were already in the set-cover library of Section 5. The quadratic character (b/p) adds nothing: it is forced to $+1$ on the fifteen $p \equiv 3 \pmod 4$ curves (below), and on the four P-224 candidates it is a fair coin that fell $+1$ once, on the skipped 777; the three non-squares (skipped 1485 and 5736, published 7026) have factorizations inside the range of the sixteen squares.

3.7 Point structure

The smallest $x \ge 0$ with a point is 0 for sixteen curves, 1 for two skipped P-224 curves, and 3 for the published P-224. Fifteen of the sixteen zeros are forced: the textbook root $b = r^{(p+1)/4}$ is itself a square when $r = -27/c$ is a square. Thus $x = 0$ is not an independent coin flip in those runs. The on-curve bitmaps have 118–148 entries set, but a fair-independent-bit null ignores this conditioning and other algebraic dependencies. The tested bitmaps and small-scalar relations do not give a separator.

4 Models of the program

RNG alignment. Published seeds occur at draw offsets $20(i-1)$ from the recovered initialization. Under a shared-stream model with nonoverlapping 20-draw candidate blocks, extra consumption must be a multiple of 20 *cumulatively at those checkpoints*, not at each event. One extra draw followed later by nineteen can restore alignment; intervening candidates need not be aligned. None of the tested fixed-block, event-triggered skip rules fits all nineteen labels. This does not exclude variable-consumption state machines.

Simulated early-abort bugs. Eleven simple abort rules were tried: the correct abort (control), trace sign flipped, order of the other root, both flipped, $t \equiv 0$, $t \equiv \pm 1, \pm 2$, off-by-one on n in both directions, signed/unsigned confusion, and a twist-order abort. None separates (Appendix A). Bounded versions and the tested single-residue rules likewise fail. These results exclude those models, not every consistent implementation bug or dependence on intermediate arithmetic.

Time limit. Elkies/Atkin balance for $\ell \leq 97$: published curves average 9.9 Elkies primes of 24 against 12.5 for skipped. This points against a simple unweighted-count proxy for timeout rejection. Actual historical timings depend on the degrees processed, arithmetic paths, caches, and implementation; no historical runtime measurements were made.

Index-dependent bugs, seed-byte mangling, base-point step, human sorting. The eleven skipped indices share no residue class, bit, popcount or buffer-offset property disjoint from the eight published. Two skipped seeds (and no published seed) contain a 0x00 byte—consistent with a C-string bug for those two and no others; 0x0A appears on both sides; a bit-length check is excluded by the published P-192 seed (158-bit value). The FreeLIP base-point recipe recovered in [1], run on every viable prime192/prime239 curve with the published seeds and 600 nearby ones, behaves identically on published and skipped curves (control: the six published seeds reproduce the six published G_x). In the three-curve runs the published curves are not the top-3 or bottom-3 under index, seed, b, n, t or $n - p$.

5 A union of small bugs? Set cover

From 135 cheap binary predicates, 29 are false on all eight published curves; the smallest union covering all eleven skipped has size 4, with ten such covers. The original exploratory comparison used 300 count-preserving random relabellings and gave 35% with cover size at most 4. Because the observed windows end at published candidates, we now also condition on those endpoints. There are only $\binom{4}{2}\binom{7}{2} = 126$ possible relabellings: minimum cover sizes 2, 3, 4, 5, or greater than 5 occur 1, 35, 52, 23, and 15 times. Thus 88/126 (69.8%) do at least as well as the observed labels under this explicit null. The predicate library was developed adaptively, so this is an exploratory diagnostic, not a confirmatory test against arbitrary selection criteria.

6 The K-163 generator

The base points of P-224, P-256, P-384 and P-521 remain unexplained [1]; the six that are explained (P-192 and the ANSI example curves) come from FreeLIP's `zrandom`, as described in the Introduction. Hashing a phrase directly to x and doubling predicts a short coordinate at $G/2$. For the ten prime-field generators, the reported minimum x among kG and G/k for $2 \leq k \leq 2^{16}$ is within

two bits of the rough uniform-coordinate minimum. The scan also tested both y signs against a 32-bit-shortness threshold; it did not record their exact minima.

Over $\mathbb{F}_{2^m}$ the same scan on the ten NIST binary curves (kG, $k \le 2^{16}$; G/k, $k \le 2^{12}$; parameters verified by $G \in E$ and $nG = O$) finds nine random-looking curves and one that is not. On K-163 ($y^2 + xy = x^3 + x^2 + 1$, cofactor $h = 2$),

$$G/2 = \tfrac{n+1}{2}\,G \quad \text{has} \quad x = \texttt{0x23e21d6019e1211f6bd47ec180256e97},$$

a 126-bit value—128 bits with two leading zeros—while y is 161 bits. Under a uniform-coordinate heuristic the threshold has probability 2^{-37} for a specified x. The binary scans contain 69,630 points *per curve*, or 696,300 in total, giving about $5.1 \cdot 10^{-6}$ expected x-hits under that heuristic. Other coordinates, prime-field scans, and post-hoc choices widen the search; this is not a calibrated discovery probability. Choosing a 128-bit x, solving for y, and multiplying by the cofactor is plausible but unproved.

The original `binpts.gp` export used `fromdigits(Vecrev(Vec(f.pol)),2)`: reversing coefficients before interpreting the binary integer. Removing `Vecrev` gives the standard polynomial-basis coordinate above. Its 126-bit length, computed from the polynomial degree, was unaffected. All ten decimal exports and the hash-search target have been corrected. Earlier negative phrase searches used the wrong target and do not apply to this one.

The subgroup inverse $Q = [h^{-1} \bmod n]G$ is only one possible cofactor-clearing input. All rational preimages are $Q + T$ with $T \in E(\mathbb{F}_{2^m})[h]$. Checking these on all ten curves gives no additional 128-bit-x hit; K-163's other half has 162-bit x. The larger subgroup scans do not inspect every such torsion coset.

We have not identified the value or established its novelty. The short half-point is a concrete lead for the separate base-point provenance problem. Anthropic recovered fourteen of fifteen NIST/ANSI seeds, not B-163's, and explained six prime-field generators. A recovered recipe for K-163 would not by itself establish the recipe or date for every binary generator.

7 Open problems

1. The eleven skips: seek archival code and printouts, while testing explicit variable-consumption state machines, run-specific criteria, and historical point-counter implementations. Untested numerical rules remain possible.

2. The 128-bit value behind K-163's $G/2$: hash preimage search over 1997-era phrases, encodings and hash functions; or an RNG stream. A match would date and explain the binary-curve base points as the `lrand48` result did the seeds.

3. Base points of P-224, P-256, P-384, P-521, the five B curves and the four other K curves. Extend the search over complete cofactor-preimage sets, field encodings, hash expansions, and RNG layouts rather than only subgroup inverse-multiples.

4. The B-163 seed, which fits no RNG tried in [1].

Reproducibility

Scripts, verified orders for all candidates in the four runs, and raw outputs are in the accompanying repository. Point counting uses PARI/GP 2.10 built from `https://github.com/jpflori/pari` (no `seadata`; modular polynomials computed on the fly). Binary-field arithmetic uses PARI's `ffgen`. All group orders carry an independent $nP = O$ check.

Acknowledgements

[Nadia Heninger for the half-point observation on base points; others.]

References

[1] Anthropic Frontier Red Team. Claude reveals ECDSA curve origins. 16 Oct 2026. https://www.anthropic.com/research/ecdsa-curve-origins

[2] Anthropic Frontier Red Team. Discovering cryptographic weaknesses with Claude. 28 Jul 2026. https://www.anthropic.com/research/discovering-cryptographic-weaknesses

[3] F. Valsorda. The NIST elliptic curves seeds bounty has been claimed. 16 Oct 2026. https://words.filippo.io/seeds-solved/

[4] F. Valsorda. The NIST elliptic curves seeds bounty. https://words.filippo.io/seeds-bounty/

[5] N. Koblitz, A. Menezes. A riddle wrapped in an enigma. IACR ePrint 2015/1018.

[6] D. J. Bernstein, T. Chou, C. Chuengsatiansup, A. Hülsing, E. Lambooij, T. Lange, R. Niederhagen, C. van Vredendaal. How to manipulate curve standards: a white paper for the black hat. IACR ePrint 2014/571.

[7] NIST. FIPS PUB 186-2, Digital Signature Standard. 2000.

[8] ANSI X9.62-1998. Public key cryptography for the financial services industry: the elliptic curve digital signature algorithm (ECDSA).

[9] A. K. Lenstra. FreeLIP. https://cr.yp.to/speed/mult/freelip.html

A Tables

A.1 Class number and $n \pm 1$ for all viable curves

Generic $\log_2 h \approx \log_2 \sqrt{4p}$: 129.0 (P-256), 113.0 (P-224), 97.0 (prime192), 120.5 (prime239). s is the conductor of $\mathbb{Z}[\pi]$; L is $L(1, \chi_f)$ by the Euler product to 10^6; LPF = largest prime factor, in bits.

run	cand	s	$L(1,\chi)$	$\log_2 h$	LPF($n-1$)	LPF($n+1$)	Elkies/24
P-256	876	1	0.530	126.4	242	232	10
P-256	**1842**	1	0.723	126.9	92	215	13
P-224	777	1	0.607	110.5	145	182	14
P-224	1485	1	0.495	110.3	74	102	13
P-224	5736	1	0.540	110.4	204	142	11
P-224	**7026**	3	0.359	108.1	196	177	8
192	**139**	1	0.411	94.0	92	108	9
192	2198	1	0.498	93.6	176	149	11
192	**5228**	1	0.352	93.8	157	161	6
192	5405	1	0.434	94.0	132	177	10
192	**6013**	1	0.529	93.6	64	145	13
239	36	1	0.436	117.1	105	153	12
239	1562	1	0.590	118.1	219	136	17
239	**2185**	1	0.246	116.8	69	136	8
239	**2320**	5	0.476	115.2	128	123	10
239	2491	1	0.415	117.6	76	131	11
239	2682	5	0.558	115.7	170	227	17
239	2863	1	0.505	117.7	183	72	13
239	**3048**	1	0.410	117.5	110	151	12

Published curves in bold.

A.2 Legendre symbols and residues

run	cand	(n/p)	(p/n)	(t/p)	(t/n)	(b/p)	$(-3/n)$	$(-1/n)$	$(2/n)$	$n \% 8$	$p \% 8$	$t \% 4$
P-256	876	+	−	+	−	+	+	−	+	7	7	1
P-256	**1842**	−	−	+	−	+	+	+	+	1	7	3
P-224	777	+	+	−	+	+	+	−	−	3	1	3
P-224	1485	−	−	+	−	−	+	+	+	1	1	1
P-224	5736	−	−	+	−	−	+	+	+	1	1	1
P-224	**7026**	−	−	+	−	−	+	+	−	5	1	1
192	**139**	+	+	+	+	+	−	+	+	1	7	3
192	2198	+	+	+	+	+	+	+	+	1	7	3
192	**5228**	−	+	+	−	+	+	−	−	3	7	1
192	5405	+	+	−	+	+	+	+	+	1	7	3
192	**6013**	+	+	+	+	+	+	+	+	1	7	3
239	36	+	−	+	−	+	+	−	−	3	7	1
239	1562	−	+	−	+	+	+	−	+	7	7	1
239	**2185**	−	+	−	+	+	+	−	−	3	7	1
239	**2320**	−	+	+	+	+	+	−	−	3	7	1
239	2491	+	+	−	+	+	+	+	−	5	7	3
239	2682	+	−	+	−	+	−	−	+	7	7	1
239	2863	+	−	+	−	+	−	−	+	7	7	1
239	**3048**	+	+	+	+	+	−	+	+	1	7	3

A.3 Simulated early-abort rules ($\ell \leq 100$)

rule	skipped rejected	published rejected
(a) $n \equiv 0$ — correct abort (control)	0/11	0/8
(b) $p + 1 + t \equiv 0$ — trace sign flipped	9/11	7/8
(c) order of the other root of b	6/11	6/8
(d) sign and root both flipped	3/11	1/8
(e) $t \equiv 0$	5/11	4/8
(f) $t \equiv \pm 1, \pm 2$	11/11	8/8
(g1) $n \equiv 1$ (tests $n - 1$)	11/11	8/8
(g2) $n \equiv -1$ (tests $n + 1$)	10/11	7/8
(g3) $\lvert t \rvert \equiv 0$	5/11	4/8
(h) twist order $\equiv 0$	9/11	7/8

A.4 Small multiples of the published generators

Shortest x among kG ($k \leq 2^{16}$) and G/k ($k \leq 2^{16}$ prime-field, $\leq 2^{12}$ binary); "expected" is a rough minimum for that many uniform field elements. Both y signs were tested for 32-bit shortness, but their minima were not recorded.

curve	h	$x(G/h)$ bits	shortest x (bits)	expected
P-192	1	–	174	175
prime192v2	1	–	175	175
prime192v3	1	–	176	175
P-224	1	–	208	207
prime239v1	1	–	222	222
prime239v2	1	–	220	222
prime239v3	1	–	221	222
P-256	1	–	237	239
P-384	1	–	367	367
P-521	1	–	502	504
B-163	2	163	147	147
K-163	2	**126**	**126** ($G/2$)	147
B-233	2	232	215	217
K-233	4	full	219	217
B-283	2	283	267	267
K-283	4	full	267	267
B-409	2	408	391	393
K-409	4	full	393	393
B-571	2	571	554	555
K-571	4	full	555	555

For the $h = 4$ Koblitz curves $G/4$ lies inside the G/k scan and no coordinate within 32 bits of the field size was found ("full").