

EPITA–École Pour l’Informatique et les Techniques Avancées
CSI–Calcul Scientifique et Image
LRDE–Laboratoire de Recherche et Développement de l’EPITA

**Improving point cloud support of *ContextCapture*TM :
Scan Finder, Point Cloud Visibility and Point Cloud
Compression**

Alexandre Gbaguidi Aïsse

Supervised by Cyril Novel

Submitted in part fulfilment of the requirements for the degree of
Software Engineer of EPITA, Paris, August 2018.

Abstract

Text of the Abstract.

Acknowledgements

I would like to express (whatever feelings I have) to:

- My supervisor
- My second supervisor
- Other researchers
- My family and friends

Dedication

Dedication here.

Contents

Abstract	i
Acknowledgements	iii
1 Introduction	1
2 The company	4
2.1 Bentley Systems	4
2.2 Acute3D	5
2.3 <i>ContextCaptureTM</i>	6
3 Background	7
3.1 Point Cloud	7
3.2 Core algorithms	8
3.2.1 Principal Component Analysis (PCA)	8
3.2.2 Least Square Methods	9
3.2.3 RANSAC	10
4 Scan Finder	12
4.1 Specifications	12
4.1.1 Context	12
4.1.2 Objective	13
4.2 Related Work	13
4.3 Clustering high-density area	14
4.3.1 LiDAR scanner and context	14
4.3.2 Clustering and dense area extraction	16

4.4	The grid-pattern method	18
4.4.1	Intuition	18
4.4.2	Grid-pattern matching	19
4.4.3	Equation to solve	21
4.4.4	Results and discussions	22
4.5	The elliptic method	24
4.5.1	Intuition	24
4.5.2	Fitting ellipse	25
4.5.3	Equation to solve	26
4.5.4	Results and discussions	27
5	Point Cloud Visibility	30
5.1	Specifications	30
5.1.1	Context	30
5.1.2	Objective	31
5.2	Related work	31
5.2.1	Previous work	31
5.2.2	An interesting approach: Visibility of Noisy Point Cloud Data	32
5.3	A custom disk-based approach	33
5.3.1	Overview	33
5.3.2	Implementation	33
5.3.3	Results and discussions	33
6	Point Cloud Compression	34
6.1	Specifications	34
6.1.1	Problem being addressed	34
6.1.2	Objective	34
6.1.3	Scope	34
6.2	Related work	34
6.3	A custom arithmetic approach	34
6.3.1	Overview	34

6.3.2	Implementation	34
6.3.3	Comparison with Brotli, 7Z and Zip	34
6.4	Integration	34
7	Conclusion	35
7.1	Summary of Internship Achievements	35
7.2	Applications	35
7.3	Future Work	35
	Bibliography	35

List of Tables

List of Figures

4.1	Example of a LiDAR scanner.	14
4.2	Variation of density as we go further away from the scanner source (the empty circular space).	15
4.3	The result of the high density extraction of a point cloud.	16
4.4	The result after clustering dense points of Figure 4.3.	17
4.5	The result after trying to identify circular clusters of Figure 4.4.	17
4.6	Example of a grid pattern. As you can see there is a constant offset between each vertical line and each horizontal lines. Note that the offset between columns is not necessary the same than between lines.	19
4.7	Function using least-square to fit a line to the given set of points.	21
4.8	Example of columns and lines clustering in order to identify grid-patterns.	21
4.9	A top view over four (4) vertical grid lines (a , b , c and d) and a scanner (s).	22
4.10	Illustration of the problem preventing the grid-pattern method from finding the scanner location. Note that this is a top view over four (4) vertical grid lines (a , b , c and d), the apprixmation (s') and the real scanner (s).	23
4.11	An approximation of the scanner location using the grid-pattern method. The real scanner location is highlighted by the upper arrow while the approximation is highlighted by the lower one.	23
4.12	Ellipse fitted on a circular cluster.	25
4.13	A side view of the ellipse and two spheres intersecting at the scanner position s and their respective centers a and b . We have the relation $\frac{d_a \times r_a^2}{\cos(\alpha_a)} = \frac{d_b \times r_b^2}{\cos(\alpha_b)}$ where d_a is the density of a and d_b the density of b	27
4.14	Green point in the box is the correct position, light blue point next to it is our estimation.	28
4.15	Multiple locations detected in a large point cloud.	29
4.16	Multiple locations detected in another large point cloud.	29

Chapter 1

Introduction

The need of 3D realistic models is increasingly present in several fields such as architecture, digital simulation or civil and structural engineering. One way to obtain a 3D model might be to build it by hand using specialized modeling softwares. In this case, the realistic aspect of the model could be doubtful. A more reliable way is to use *photogrammetry* or *surface reconstruction* or both at the same time. *ContextCaptureTM* is a reality modeling software that can produce highly detailed 3D models. It creates models of all types or scales from simple photographs of a scene to point clouds or both of them thanks to its hybrid processing. The usage of point clouds gained wide popularity because of the emergence of devices such as optical laser-based range scanners, structured light scanners, LiDAR scanners, Microsoft Kinect, etc. Actually, it is only in the past two years that *ContextCaptureTM* has started to support point clouds and the common goal between each part of this internship is to improve *ContextCaptureTM* point cloud support.

The general problem being solved by *surface reconstruction* is: given a point cloud P assuming to lie near an unknown shape S , construct a digital representation D approximating S . In order to reconstruct point clouds acquired from static¹ LiDAR scanners, possibly multi-scan², *ContextCaptureTM* needs to know the position of each scanner in the scene, on the one hand, and the attribution of each point to a scanner on the other. The scanners location information is not always present in point clouds metadatas, for instance LAS file format does not provide it. Moreover, some users of *ContextCaptureTM* sometimes lost this information due to a prior export with no metadata. Detecting the positions of multiple scanners exclusively from a point cloud is a subject not identified as inter-

¹As opposed to mobile LiDAR scanners.

²Point cloud made of several laser scans.

esting by academics, and thus not tackled since this information is almost always available from the outset. The same holds true on the industry side, it is only recently that scanner position information is relevant for a few applications like *ContextCaptureTM*. This is the main contribution presented in this internship report: a method able to detect automatically multiple scanners in a single point cloud without prior knowledge of the scene.

Knowing scanners position is one step toward supporting LAS point cloud format. *ContextCaptureTM* still needs to know for each point which scanner sees it best³. This enters into the realm of visibility of point clouds. One way to retrieve visibility of point clouds is to reconstruct the surface and use the underlying mesh to compute visibility. But to reconstruct the surface we need to orient the normals; a chicken-and-egg problem in our case. After some literature review on the subject, we did not find accurate method for LiDAR point clouds. Also, most papers try to find which points are visible from a precise viewpoint but in our case, as different scanners can see the same points, we want to know for each point which scanner best sees it. We introduce a custom point cloud visibility method that serves our purpose and works well with LiDAR point clouds, regardless of the sampling density.

ScanFinder and PointCloudVisibility are two contributions which serves mainly the same purpose: expand *ContextCaptureTM* input point cloud formats. Another improvement made in *ContextCaptureTM* is point cloud compression. *ContextCaptureTM* provides a cloud service which gives the opportunity for people not having any clusters or high-performance machine to do the job; reconstructing a large surface requires effective machines. The problem is that, point clouds can be very huge, up to one hundred (100) gibabyte and more. And if something happens while uploading, the upload restarts from scratch. Being able to divide by two point cloud sizes and then reduce uploading time is an interesting point for *ContextCaptureTM* cloud services. Point cloud compression can be addressed in two ways: geometric compression [GKIS05, SK06] or pure arithmetic compression regardless of the kind of file being compressed. We compared different compressor such as Brotli, LZMA (7Zip), Zip before integrating one of them into the product.

This report is organised as follows. Chapter 2 present Bentley Systems, Acute3D, *ContextCaptureTM* and how the achieved work is positioned in the company's business line. After introducing in Chapter 3 some useful definitions for a better understanding of the report, we describe the achieved work of Scan Finder, Point Cloud Visibility and Point Cloud Compression respectively in Chapter 4, Chapter 5 and Chapter 6. Note that in each chapter, we recall the context, the issue addressed and the expected

³There is no need to know exactly which scanner generated it.

result before going into details. Finally Chapter 7 summarizes all the work, evaluates my contributions to *ContextCaptureTM* and assess what this experience has brought to me.

Chapter 2

The company

This chapter shed more light on *ContextCaptureTM*, the software I contributed to during these six (6) months internship as well as Bentley Systems, the company.

2.1 Bentley Systems

Bentley Systems is an American-based software development company founded by Keith A. Bentley and Barry J. Bentley in 1984.

For a bit of history¹, they introduced the commercial version of PseudoStation in 1985, which allowed users of Intergraph's VAX systems to use low-cost graphics terminals to view and modify the designs on their Intergraph IGDS (Interactive Graphics Design System) installations. Their first product was shown to potential users who were polled as to what they would be willing to pay for it. They averaged the answers, arriving at a price of \$7,943. A DOS-based version of MicroStation was introduced in 1986. Later the two other brothers joined them in the business. Today, Bentley Systems is considered to have four (4) founders: Greg Bentley (CEO), Keith A. Bentley (EVP, CTO), Barry J. Bentley, Ph.D. (EVP) and Raymond B. Bentley (EVP).

At its core, Bentley Systems is a software development company that supports the professional needs of those responsible for creating and managing the world's infrastructure, including roadways, bridges, airports, skyscrapers, industrial and power plants as well as utility networks. Bentley delivers solutions for the entire lifecycle of the infrastructure asset, tailored to the needs of the various professions –

¹Derived from [ben]

the engineers, architects, planners, contractors, fabricators, IT managers, operators and maintenance engineers – who will work on and work with that asset over its lifetime. Comprised of integrated applications and services built on an open platform, each solution is designed to ensure that information flows between workflow processes and project team members to enable interoperability and collaboration.

Bentley’s commitment to their user community extends beyond delivering the most complete and integrated software – it pairs their products with exceptional service and support. Access to technical support teams 24/7, a global professional services organization and continuous learning opportunities through product training, online seminars and academic programs define their commitment to current and future generations of infrastructure professionals.

With their broad product range, strong global presence, and pronounced emphasis on their commitment to their neighbors, Bentley is much more than a software company – they are engaged functioning members of the global community. Their successes are determined by the skills, dedication, and involvement of extraordinary Bentley colleagues around the world.

Bentley has more than 3,500 colleagues in over 50 countries, and is on track to surpass an annual revenue run rate of \$700 million. Since 2012, Bentley has invested more than \$1 billion in research, development, and acquisitions.

2.2 *Acute3D*

Acquired by Bentley Systems in February 2015, *Acute3D* is now developing *ContextCaptureTM*, as part of Bentley Systems’ Reality Modeling solutions.

Acute3D is a technological software company created in January 2011 by Jean-Philippe Pons and Renaud Keriven, by leveraging on 25 man-years of research at two major European research institutes, École des Ponts ParisTech and Centre Scientifique et Technique du Bâtiment. It won the French “most innovative startup” Awards. In 2011, *Acute3D* signed an industrial partnership with Autodesk, while keeping to advance its R&D work on city-scale 3D reconstruction. In 2012, *Acute3D* signed industrial partnerships with other industry leaders, including Skyline Software Systems and InterAtlas. In parallel, it started to commercialize its own Smart3DCapture® (now replaced by *ContextCaptureTM*) standalone software solution, optimized for highly detailed and large-scale automatic 3D reconstruction

from photographs. In 2015, Acute3D is acquired by Bentley Systems, and becomes part of their end-to-end Reality Modeling solutions.

2.3 *ContextCaptureTM*

With *ContextCaptureTM*, you can quickly produce even the most challenging 3D models of existing conditions for infrastructure projects of all types. Without the need for expensive, specialized equipment, you can quickly create and use these highly detailed, 3D reality meshes to provide precise real-world context for design, construction, and operations decisions for use throughout the lifecycle of a project.

Hybrid processing in ContextCapture enables the creation of engineering-ready reality meshes that incorporate the best of both worlds – the versatility and convenience of high-resolution photography supplemented, where needed, by additional accuracy of point clouds from laser scanning.

Develop precise reality meshes affordably with less investment of time and resources in specialized acquisition devices and associated training. You can easily produce 3D models using up to 300 gigapixels of photos taken with an ordinary camera and/or 500 million points from a laser scanner, resulting in fine details, sharp edges, and geometric accuracy.

Extend your capabilities to extract value from reality modeling data with ContextCapture Editor, a 3D CAD module for editing and analyzing reality data, included with ContextCapture. ContextCapture Editor enables fast and easy manipulation of meshes of any scale as well as the generation of cross sections, extraction of ground and breaklines, and production of orthophotos, 3D PDFs, and iModels. You can integrate your meshes with GIS and engineering data to enable the intuitive search, navigation, visualization, and animation of that information within the visual context of the mesh to quickly and efficiently support the design process.

Chapter 3

Background

This chapter introduces the necessary concepts and definitions for a better understanding of the report.

3.1 Point Cloud

Definition 3.1 : *Point*

A point p_i is a tuple $\langle x_i, y_i, z_i, \vec{n}_i \rangle$ where:

- i is an unique integer identifying p_i ,
- x_i, y_i and z_i are the coordinates of p_i ,
- \vec{n}_i is the normal at p_i .

Definition 3.2 : *Point Cloud*

A point cloud P of size s is a set $P = \{p_i \mid i \in [0, s]\}$.

A point cloud is said to be whether *static* or *mobile* depending on the *static* nature of the scanner. Mobile scanner means that the instrument is either handheld (like some units used for LIDAR speed detection) or mounted on a vehicle (from SUVs to trailer-mounted instruments to airborne instruments). It generates a point cloud by following a trajectory. Static scanner instead means that the scanner is set up in a location and turns on itself.

3.2 Core algorithms

3.2.1 Principal Component Analysis (PCA)

PCA is a common algorithm of data analysis. It is used to project data with n dimensions into a space with reduced dimensions while keeping the most relevant information – the directions where there is the most variance, where the data is most spread out. As its name suggests, it finds the principal components from the most important to the less one. We say that the first principal component is a rotation of x -axis to maximize the variance of the data projected onto it and the last axis (component) is the one with less variance, with redundant information.

We are not going to explain in detail what a PCA is as it is very common and not the core of our work here. But let us remind the methodology in the specific case of 3D data.

Definition 3.3 : *Principal Component Analysis (PCA)*

Let P_a be a set of points of size s_a . To perform $PCA(P_a)$:

- we compute the centroid of P_a , noted \bar{p}_a
- we compute the covariance matrix C which is the symmetric 3×3 positive semi-definite matrix:

$$C = \sum_{p \in P_a} (p - \bar{p}_a) \otimes (p - \bar{p}_a), \text{ where } \otimes \text{ denotes the outer product vector operator.}$$

- we compute the eigenvalues of C with their corresponding eigenvectors. The eigenvector \vec{v}_1 associated with the greatest eigenvalue λ_1 is the principal component axis. And the axis having less variation of data, when it is projected onto it is \vec{v}_3 ; the one associated with the lowest eigenvalue λ_3 .
- we return a pair of $\langle \mu, \vec{v}_3 \rangle$ where $\mu = \frac{\lambda_3}{\lambda_1 + \lambda_2 + \lambda_3}$ can be used as a confidence level. The smaller it is, the more \vec{v}_1 and \vec{v}_2 explain on their own our data.

In [HDD⁺92], Hoppe et al. use PCA to determine the normal of a tangent plane. Similarly in this report, we use PCA for two purposes: detect if a set of points are planar by computing their normal's direction or simply find the normal's direction at a specific point using its neighbours. If a set of points forms a plane, we choose its normal to be either \vec{v}_3 or $-\vec{v}_3$. It is the direction with less data variation

and in a perfect word, that is a perfect plane alignment, the projection of all points onto it gives the same value. This means that $\mu = 0$. Now if P_a is formed of p_i and its k -neighbouring points, then \vec{v}_3 or $-\vec{v}_3$ is the normal at p_i . We empirically deduced fifty (50) to be the ideal value for k .

3.2.2 Least Square Methods

Least Square solving is a usual approach of regression analysis to approximate the solution of over-determined systems (with more equations than unknowns). The problem can be described as follows.

Let us assume a model of the form

$$y = f(z; x_1; \dots, x_n) \quad (3.1)$$

where f describes a relation between x_1, \dots, x_n , z is the control variable and y is the expected response to z . After m experiments, ($m \geq n$), m observed quantities $(z_i, y_i), i \in [1, m]$ are collected. The purpose therefore is to find the parameters x_1, \dots, x_n so that all z_i, y_i satisfy at best (3.1). “Least squares” means that the overall solution minimizes the sum of the squares of the residuals made in the results of every single equation. The most important application is in data fitting. The best fit in the least-squares sense minimizes the sum of squared residuals, a residual being: the difference between an observed value, and the fitted value provided by a model.

Least-squares fall into two categories: linear and non-linear least squares, depending on whether or not the residuals are linear in all unknowns.

Linear

To solve linear least square problems, we use the Eigen library [GJ⁺10]. Consider an overdetermined system of equations, say $Ax = b$. Although it has no precise solution, it makes sense to search for the vector x which is closest to being a solution, in the sense that the difference $Ax - b$ is as small as possible. This x is called the least square solution (if the Euclidean norm is used). Provide Eigen with A and b and it will approximate the solution x .

Non-linear

In case of non-linear least square problems, we use the Ceres Solver [AMO]. Ceres Solver is an open source C++ library for modeling and solving large, complicated optimization problems. Ceres can

solve bounds constrained robustified non-linear least squares problems of the form:

$$\min_x \frac{1}{2} \sum_i \rho_i \left(\|f_i(x_{i_1}, \dots, x_{i_k})\|^2 \right), \text{ such that } l_j \leq x_j \leq u_j$$

Ceres solver considers the expression $\rho_i \left(\|f_i(x_{i_1}, \dots, x_{i_k})\|^2 \right)$ as a *Residual Block*, where $f_i(\cdot)$ is a *Cost function* that depends on the parameter blocks $[x_{i_1}, \dots, x_{i_k}]$. We only need to specify the parameters, write the *Cost function* and Ceres does the job.

3.2.3 RANSAC

According to [ran]: RANSAC is the abbreviation of Random Sample Consensus. It is a general algorithm that can be used with other parameter estimation methods in order to obtain robust models with a certain probability when the noise in the data doesn't obey the general noise assumption.

Various versions of this algorithm exist, this is why it is said to be *general*. Algorithm 1 shows the version used in this report. Generally, RANSAC selects a subset of data samples and uses it to estimate model parameters. Then it determines the samples that are within an error tolerance of the generated model. These samples are considered as agreed with the generated model and called as consensus set of the chosen data samples. Here, the data samples in the consensus are behaved as inliers and the rest as outliers by RANSAC. If the count of the samples in the consensus is high enough, the new model is saved. Actually, it repeats this process for a number of iterations and returns the model which has the smallest average error among the generated models.

Function RANSAC(P, k, n, t)

Input:

- a set of points $P = \{p_i \mid i \in [0, s]\}$,
- the number k of iteration,
- the required sample number n for fitting parameters to the mathematical model,
- the tolerated error threshold t when testing parameters on one sample.

Output: A tuple $\langle m, l \rangle$ where m is the final parameter estimation and l the associated set of inliers.

```

 $m \leftarrow \vec{0}$  // parameter vector
 $l \leftarrow \emptyset$  // inliers set
 $\delta_n \leftarrow \emptyset$  // set of extracted samples
for (  $i = 0$ ;  $i < k$ ;  $i = i + 1$  ) {
     $\delta_n \leftarrow \text{random\_sample}(P, n)$  // Extract  $n$  random points from  $P$ 
     $m' \leftarrow \text{fit\_parameters}(n, \delta_n)$  // Use an estimation method to fit  $m'$  to the mathematical model
     $l' \leftarrow \emptyset$ 
    for (  $j = 0$ ;  $j < s$ ;  $j = j + 1$  ) {
         $e \leftarrow \text{compute\_error}(m', p_j)$  // get model error when applied on point  $p_j$ 
        if  $e^2 \leq t^2$  then
             $l' \leftarrow l' \cup \{p_j\}$ 
    }
    /* If it is the most satisfied mathematical model up to now */
    if  $\text{size\_of}(l') \leq \text{size\_of}(l)$  then
         $l \leftarrow l'$ 
         $m \leftarrow m'$ 
}
return  $\langle m, l \rangle$ 

```

Algorithm 1: A variation of the RANSAC algorithm used in this report

Chapter 4

Scan Finder

This chapter describes *Scan Finder*, an algorithm that can be used to retrieve all scanners position of a point cloud, if there are any, as long as it is static. Firstly, Section 4.1 reviews the context which brings this need and describes some characteristics of the expected solution. Then, Section 4.2 reminds that there is no previous work related to this subject. Finally, Section 4.3 describes a first step toward scanner location finding before showing and discussing the results of two different approaches described respectively in Section 4.4 and Section 4.5. To be clear, Section 4.3 is a common first step to both methods.

4.1 Specifications

4.1.1 Context

ContextCaptureTM started to support point cloud reconstruction two (2) years ago. Today it even provides a hybrid processing mode which gives the opportunity to combine the best of both worlds, photos and point clouds, in order to have a better precision. However, a recurring problem observed among *ContextCaptureTM* users is the impossibility to use the software after losing some metadata, specifically, scanners location. This is particularly problematic because usually, *ContextCaptureTM* users subcontract point cloud production to private companies which can charge them again for new exports (provided that they still have the point clouds). To enable customers to use their *defective* point clouds, the graphic interface of *ContextCaptureTM* allows to specify a scanner location by hand by positioning it in a 3D representation of the point cloud. But, it does not work with merged scans;

only one scanner location can be specified. Usually, users do not know the location and even if they know, the reconstruction is subjected to too much errors.

This is how the need for an algorithm to automatically find scanners positions in a point cloud is born. In addition, with such algorithm, *ContextCaptureTM* will have the possibility to enhance the set of supported file formats. Currently, it supports file formats such as *PTX*, *e57*, *PLY*, *POD*, each of them being able to store scanners positions. But not all file formats are able to do it. For instance, *LAS* file format is not currently accepted as input because it does not provide any means of storing scanners location in metadata. Supporting more input file formats is also a good point of interest for *ContextCaptureTM* users.

4.1.2 Objective

In summary, the purpose here is to improve *ContextCaptureTM* point cloud support in two ways: support more file formats and allow users who lose scanners location to still use their point clouds. To do so, the algorithm must:

- take as input any 3D point cloud captured from static scanners,
- be invariant to the number of scanners in the point cloud,
- be invariant to differences between scanners, such as: density, noise, rotation angle,
- find all scanners locations,
- have a reasonable running time.

Let us emphasize here that as a first step, the algorithm is expected to work only with static point clouds. It would be difficult to have the same approach with static and mobile point clouds. Extending it to mobile point clouds is certainly the next step.

4.2 Related Work

As said in the introduction, to the best of our knowledge, there have been no previous work on the subject.




Figure 4.1: Example of a LiDAR scanner.

“Detecting the positions of multiple scanners exclusively from a point cloud is a subject not identified as interesting by academics, and thus not tackled since this information is almost always available from the outset. The same holds true on the industry side, it is only recently that scanner position information is relevant for a few applications like ContextCaptureTM .”

The closest publications on the topic are [TM15, SQLG15, KGC15, KC15, NS17]. They use learning techniques to estimate the point of view of one particular photo based on other photos. But this belongs more to the photogrammetry domain and therefore is not applicable in a point cloud context.

4.3 Clustering high-density area

This section explains a common first step to methods described in Section 4.4 and Section 4.5. For a better understanding, a quick introduction to LiDAR scanners is necessary.

4.3.1 LiDAR scanner and context

LiDAR¹ is an acronym of Light Detection and Ranging. It is a remote sensing technology which uses the pulse from a laser to collect measurements. The principle is simple: it works in a similar way to Radar and Sonar but uses light waves from a laser, instead of radio or sound waves. A LiDAR system calculates how long it takes for the light to hit an object or surface and reflect back to the scanner and

¹This paragraph is inspired by [lid].




Figure 4.2: Variation of density as we go further away from the scanner source (the empty circular space).

then, uses the velocity of light² to calculate the distance. LiDAR systems can fire around 1,000,000 pulses per second.

When scanning, there are two kind of rotations that a LiDAR scanner performs. They are indicated by black arrows in Figure 4.1. Not only a LiDAR scanner has a constant rotation angle when turning on itself but it also has a constant vertical rotation angle when scanning the environment. Because of these constant rotation angles, the further we go, the lower the point density is. On the contrary, the closer to the scanner we are, the higher the point density is. This density variation can be observed in Figure 4.2. To conclude, extracting the most dense areas is interesting as they always are around scanner locations and then, reduce the global search area.

²The velocity, or speed of light is 299,792,458 metres per second.




Figure 4.3: The result of the high density extraction of a point cloud.

4.3.2 Clustering and dense area extraction

The first step of the algorithm is to detect high density regions in the point cloud. For each point, we compute its density based on the mean distance to its k neighbors ($k \in [15, 50]$). We extract high density regions by selecting a percentage of the densest points (percentage between 1 and 5%). Figure 4.3 shows some results of this high density point extraction. As you can see, they always are around the scanner's location. Note that the scanner is not able to scan below himself leading to an elliptic empty form³ appearing in all point clouds.

Once these points are extracted, a clustering step is applied. The clustering is needed so that points from the point clouds corresponding to potentially different parts of the scene around the scanner can be separated. For each point, we compute its non-oriented normal and the associated *confidence level* by performing a principal component analysis (PCA) on its local neighborhood. Section 3.2.1 gives more details on how this PCA works. Then, as long as points are not attributed to a cluster, we select the point on the flattest surface, and iteratively add its neighbors that share a coherent normal orientation (the dot product of the two normals must be superior to 0.8 in our experiments). Note

³This elliptic form is the key point of the method described in Section 4.5.




Figure 4.4: The result after clustering dense points of Figure 4.3.




Figure 4.5: The result after trying to identify circular clusters of Figure 4.4.

that the flattest surface is determined using confidence levels, they tell which point belongs to a planar region. Figure 4.4 shows the result of such clustering.

Once every point is clustered, we discard clusters with too few points (in our experiments, we use a threshold of 0.2% of the number of high density points). We then detect clusters that are circular. A cluster is considered circular if its centroid, i.e. the average of all the points it contains, is far away from the points of the cluster. Figure 4.5 shows a circular cluster identified.

At this point, we have computed a rough estimate of the scanner's location. Methods described in Section 4.4 and Section 4.5 use it in their own way in order to find scanner locations.

4.4 The grid-pattern method

This section explains one approach we tried in order to solve the problem. Before explaining the method in detail, let us first give the intuition behind this idea.

4.4.1 Intuition

As said in Section 4.3.1, LiDAR scanners perform two kind of rotations. These constant vertical and horizontal rotation angles reveal some grid patterns on surfaces perpendicular to the ground⁴. Figure 4.6 shows an example of a grid pattern that can be found in point clouds. The purpose here is to find, for a single grid pattern, a relation between all constant rotation angles and the scanner's position. Therefore, this relation can be applied with all possible grid patterns in the point clouds, leading to a problem with a huge set of constraints to solve. The idea is that only the real scanner's location is able to explain in the best way these constant rotation angles.

This algorithm can be divided into two parts. The first step is to find *accurate* grid patterns in point clouds. Once this is done, the second step is to build the equation that will be solved. These two parts are explained in the following subsections. Note that this approach does not work in multiscan mode, compare to the other approach described in Section 4.5. It assumes there is only one scanner which explains all grid-patterns in the point cloud.

⁴To be precise, perpendicular to the surface on which the scanner is installed.




Figure 4.6: Example of a grid pattern. As you can see there is a constant offset between each vertical line and each horizontal lines. Note that the offset between columns is not necessary the same than between lines.

4.4.2 Grid-pattern matching

This subsection explains how to find *accurate* grid patterns in point clouds in order to reduce as much as possible the noise and its impact during the problem resolution described in Section 4.4.3. A set of point is considered as an *accurate* grid-pattern when:

- it is planar as much as possible⁵,
- the underlying planar surface is orthogonal to the surface of the ground,
- the gap between columns is consistent enough,
- the gap between lines is consistent enough.

Algorithm 2 shows how to extract some planar patches in a point cloud. A preprocessing step already done and explained in Section 4.3.2 is to compute for each point of the point cloud, the normal and its *confidence level*. This *confidence level* plays a key role in the algorithm as it tells how planar the region around each point is. By browsing all points, each time we find a point with a good *confidence level* (> 0.001), we start to build a patch around it. To do so, we extract its 50 closest neighbours

⁵Because of the noise.

Function GetPlanarPatches(P)**Input:** a pointcloud $P = \{p_i \mid i \in [0, s]\}$.**Output:** a set of potential grid-pattern patches.

```

/* We compute the normal of each point and keep both confidence level and normal  $\langle \mu_i, \vec{v}_i \rangle$ . */
/* See Section 3.2.1 for more details on PCA algorithm. */
/* From here,  $\forall i \in [0, s]$  we assume  $\vec{v}_i$  to be the normal at  $i$  and  $\mu_i$  its confidence level. */
for (  $i = 0$ ;  $i < s$ ;  $i = i + 1$  ) {
     $\langle \mu_i, \vec{v}_i \rangle \leftarrow PCA(50 \text{ closest neighbours of } i)$ 
     $R \leftarrow \emptyset$ 
    visited  $\leftarrow \emptyset$ 
    for (  $i = 0$ ;  $i < s$ ;  $i = i + 1$  ) {
        /* Continue if already visited or is not planar enough. */
        if  $i \in \text{visited}$  or  $\mu_i > 0.001$  then
            continue
        tmp  $\leftarrow \{p_i\}$ 
        foreach  $j \in 50 \text{ closest neighbours of } i$  do
            /* If  $\vec{v}_j$  and  $\vec{v}_i$  are almost colinear and  $j$  has not been seen yet. */
            if  $\text{abs}(\vec{v}_j \times \vec{v}_i) > 0.9$  and  $j \notin \text{visited}$  then
                tmp  $\leftarrow \text{tmp} \cup p_j$ 
                visited  $\leftarrow \text{visited} \cup j$ 
            /* If there is enough point for a grid-pattern patch. */
            if size of tmp  $> 0.9 \times 200$  then
                 $R \leftarrow R \cup \text{tmp}$ 
    }
}
return  $R$ 

```

Algorithm 2: Find various not-overlapping planar patches in a point cloud.

and consider only those having their normal almost colinear to the normal of the starting point. If the size of the obtained set is bigger enough ($> 0.9 \times 200$), the set is kept and otherwise, not. Also, in order to avoid overlapping or patches too close, we keep track of visited points.

Although planar, this set of patches potentially contains: **(a)** patches whose underlying surfaces are not orthogonal to the surface of the ground and **(b)** patches without grid patterns. To filter out each **(a)** patch, we use a dot product between its normal and the normal of the circular cluster found in the high-density area⁶ (see Section 4.3). For **(b)** patches, the objectif is to indentify grid-patterns. To do so, we use least square method in order to fit lines. Least-square is explained in Section 3.2.2. Fitting a line fall into linear least square problems. Figure 4.7 shows how to fit a line to a set of points using the Eigen library [GJ⁺10]. The purpose is to use this line fitting in order to cluster lines and columns. Figure 4.8 shows results of a clustering performed on two patches after several fittings and adjustments. We only keep firstly patches containing a grid-pattern and then, patches having a regular gap between columns and lines. The rest is discarded.


⁶The circular cluster describes the surface on which the scanner is positioned.

```


Eigen::VectorXf FitLine(std::vector<A3D::Point_3dPlus> const& points)
{
    Eigen::MatrixXf mat(points.size(), 2);
    Eigen::VectorXf vec(points.size());
    int count = 0;
    for (auto it = points.begin(); it != points.end(); ++it)
    {
        mat(count, 0) = static_cast<float>(it->x());
        mat(count, 1) = static_cast<float>(it->y());
        vec(count++) = 1.0;
    }
    return mat.fullPivHouseholderQR().solve(vec);
}

```

Figure 4.7: Function using least-square to fit a line to the given set of points.



(a) Lines clustering performed on two patch.



(b) Column clustering performed on two patches.

Figure 4.8: Example of columns and lines clustering in order to identify grid-patterns.

Once only *accurate* patches are kept, columns and lines are identified, the problem can be formalised.

4.4.3 Equation to solve

For a little recall of Section 4.4, the purpose here is to find a relation between the scanner's position (what we are looking for) and the regular gaps between lines and columns. At this point, we already have a reduced area of research which is around the circular cluster obtained in Section 4.3.2. What we need, is a set of constraints that will help to set the scanner at a specific position within this area.

Look at Figure 4.9. There are four (4) vertical lines viewed from a bird's eye: a , b , c and d . They are represented as points because of the point of view. A regular between them can be observed. As explained in the introduction to LiDAR scanners (Section 4.3.1) this regular gap is due to the consistent angle of rotation of the scanner $\alpha_1 = \alpha_2 = \alpha_3$.




Figure 4.9: A top view over four (4) vertical grid lines (a , b , c and d) and a scanner (s).

These angles directly involve the scanner location in all equations. Here is how the problem is built: each time the scanner location is set, we minimize for each grid-pattern, and for each pair of two consecutive lines (or columns), the absolute difference between their respective angles. In our case we minimize:

$$d_1 = |\alpha_1 - \alpha_2|$$

$$d_2 = |\alpha_2 - \alpha_3|$$

This is a non-linear least-square problem which can be resolved using the Ceres Solver [AMO] (Section 3.2.2).

4.4.4 Results and discussions

Figure 4.11 shows a result of grid-pattern approximation of scanner location. This method does not perform quite well. One would think that the approximation is not far from the real scanner location but reducing the area of research to a cube around the circular cluster can be misleading. We tried to remove the area constraints and observed that the approximation moves entirely away from the real location and even the point cloud itself. It can stoop pretty low, go to really high altitude, on the left, on the right. It completely depends on the distribution of the grid-patterns in the point cloud.

Let us take one grid-pattern in order to illustrate the problem: Figure 4.10. As our method tries to minimize the differences between all pairs of angles, here α_1 , α_2 and α_3 , the ideal case is if the scanner




Figure 4.10: Illustration of the problem preventing the grid-pattern method from finding the scanner location. Note that this is a top view over four (4) vertical grid lines (a , b , c and d), the approximation (s') and the real scanner (s).




Figure 4.11: An approximation of the scanner location using the grid-pattern method. The real scanner location is highlighted by the upper arrow while the approximation is highlighted by the lower one.

location belongs to the underlying surface of the grid-pattern in which case:

$$|\alpha_1 - \alpha_2| = 0$$

$$|\alpha_2 - \alpha_3| = 0$$

Therefore, with a huge set of equations involving several grid-patterns, the optimal solution for the solver is to put the scanner on the *mean plan of all grid-pattern's underlying planes*. This is why, without the reduced area constraint, the approximated scanner is far away from the point cloud as the

solver tries to reduce all angle differences and then, satisfy all grid-patterns. Another problem found is that this method is too much subjected to noise. We are talking about really small values for angle differences that we want to minimize. A small noise can have huge effects during the solving.

To conclude, angles differences are not discriminating enough. We believe there is a way to express the problem, in order to bypass this behaviour but we decided to try another approach presented in Section 4.5. The current approach is limited to one scanner whereas the other one works with multiple scanners, therefore, is more interesting for *ContextCaptureTM*.

4.5 The elliptic method

This section describes the second approach to solve the scanner location finding problem. This approach is more interesting than the one of Section 4.4 because it works natively with merged point clouds (multiple scanners within a point cloud). Let us have the intuition of this method.

4.5.1 Intuition

Recall that a first common step to both methods is performed. This step finds all circular clusters around all scanner locations of the point cloud. It is described in Section 4.3. As said in Section 4.3, these empty circles appears because the scanner is not able to scan below itself.

This method tries to find the scanner location in two steps:

- find the z axis on which the scanner is
- set the scanner on this axis by estimating its height

The z axis on which the scanner is is simply the axis perpendicular to the circular cluster which runs through its center. In order to find this axis, we fit an ellipse around the circular cluster before finding its center. Once the axis is known, we try to estimate the scanners height.

The first key point of this method is that the scanner location is necessary on the axis perpendicular to this elliptic form and which runs through its center. The intuition is that the density of a local point is linked to its distance from the scanner. Figure 4.2 shows the variation of density as we go further away from the scanner location. Using multiple points in the high density area, we are able to

triangulate the position of the scanner. The real scanner location is the best position able to explain the link between the local density of each point and its distance from the scanner.

In Section 4.5.2 we describe how the scanner's axis is found and in Section 4.5.3 we show how to formalise the non-linear least square problem to solve.

4.5.2 Fitting ellipse




Figure 4.12: Ellipse fitted on a circular cluster.

This section describes how we fit an ellipse on a circular cluster before finding its center. We need the ellipse to be as close as possible to the cluster interior. For this, the following procedure is followed:

- Extract the closest points Δ to the cluster interior. We first compute the cluster's centroid c . Then, for each point p_i of the cluster, we extract its k nearest neighbors and compute their centroid c_i . If p_i is closer to c than c_i with a percentage of error, then it is considered as part of the ellipse edge.

- Perform a PCA on Δ to compute its normal. This normal is considered as the ellipse normal.
- Align the normal with the z axis using geometric transformation so that the future ellipse is completely horizontal. This is an important step as we need to use the elliptic two-dimensional equation:

$$Ax^2 + Bxy + Cy^2 + Dx + Ey + F = 0 \quad (4.1)$$

This alignment allows us to ignore the last dimension while fitting the ellipse.

- Try to fit an ellipse using a RANSAC algorithm. This enables to filter out outlying points in order to only keep *good* points. The RANSAC algorithm is described in Section 3.2.3. We call the algorithm with $k = 3000$ iterations, $n = 6$ unknowns and $t = d_e * 6$ where d_e is the mean density of Δ .
- As the equation of the ellipse in this 2D projection is known, we compute its center's location.

A result of such procedure can be observed in Figure 4.12. The circular cluster has a red color while the fitted ellipse is in green.

4.5.3 Equation to solve

To estimate the height of the scanner, we will use the slight variation in density of the points in the circular cluster. For a point p in the high density circular cluster, we note r the distance between the scanner and the point, d the density of the point, and α the angle between the normal of the point and the direction from the point to the scanner. Using the fact that point density decreases proportionally as moving away from the scanner, the following relation should be verified for any pair of points.

$$\frac{d_a \times r_a^2}{\cos(\alpha_a)} = \frac{d_b \times r_b^2}{\cos(\alpha_b)} \quad (4.2)$$

where d_a is the spatial density of a and d_b the spatial density of b . We normalize each spatial density by the cosinus of each normal's point and the optic beam in order to obtain the scanner's point of view density which is different from the spatial density. Look at Figure 4.13 for a visual understanding. The local density of points a and b are known but of course their distances from the scanner are not because they depend on the scanner position. This is why knowing the axis on which the scanner is is interesting because it helps to restrain the area of research. Note that two solutions can be found but we easily discriminate the other one as it is under the point cloud.




Figure 4.13: A side view of the ellipse and two spheres intersecting at the scanner position s and their respective centers a and b . We have the relation $\frac{d_a \times r_a^2}{\cos(\alpha_a)} = \frac{d_b \times r_b^2}{\cos(\alpha_b)}$ where d_a is the density of a and d_b the density of b .

For each circular cluster, we pick a sample of n points (in our experiments, $n = 6$ points) with different densities. We then build a system of (4.2) equations using all possible combinations of the n points in pairs. We then use Ceres [AMO] which is a non-linear least square solver to determine the position of the scanner. As a result, we retrieve an estimated position of the scanner location.

4.5.4 Results and discussions

This method happens to achieve good results. Figure 4.14 shows an approximation (light blue point) of the real scanner location (green) point. As you can see our approximation is very close to the real scanner's location. By testing on various reference datasets, we found that the error between the correct position and our estimation ranges between 2 and 20 cm.

This pipeline is particularly suited for multi-scan point clouds. Terrestrial scanners tend to generate most of the points close to their positions. If we consider that scans are not taken in the same close vicinity, high density clusters are disjoint. We confirm with hypothesis in our experiments. Therefore, the rough detection works well in the multi-scan hypothesis. The same idea applies for the fine position algorithm: most points in the circular cluster come from a single scanner. The few other points coming from different scanners don't have a significant impact on the local density of the points. That way, the scanner height is correctly detected in a multi-scan setting. Figure 4.15 and Figure 4.16 show




Figure 4.14: Green point in the box is the correct position, light blue point next to it is our estimation.

some results of this approach on multiscan point clouds.




Figure 4.15: Multiple locations detected in a large point cloud.




Figure 4.16: Multiple locations detected in another large point cloud.

Chapter 5

Point Cloud Visibility

This chapter introduces our custom point cloud visibility algorithm. It starts by giving in Section 5.1, a clear context for the presented work. Then, Section 5.2 gives an overview of the previous related work and describes some experimentations of a previously-published point cloud visibility algorithm. Finally, as nothing seems to be well adjusted for our specific case we implemented a custom point cloud visibility algorithm described in Section 5.3.

5.1 Specifications

5.1.1 Context

Currently in *ContextCaptureTM*, there is a way to still use a point cloud for reconstructing purposes even if the scanner's location information is lost. It gives the user the opportunity to manually set the scanners position on a 3D representation of the point cloud. But, only one position can be set. It requires that the point cloud contains points resulting from *one and only one* scanner¹. This is because, during the reconstruction, *ContextCaptureTM* uses the scanner location to orient the normals at each point. In a monoscan point cloud case, it simply orients each normal toward the scanner. But in case of multiscan point cloud, it needs to know for each point, toward which scanner the normal must be oriented, which is difficult to find.

¹Also known as monoscan point cloud.

Therefore, even if *ScanFinder* (Chapter 4) is applied on a LAS format² multiscan point cloud in order to retrieve all scanner positions, the reconstruction is still infeasible for *ContextCaptureTM*. This is where a point cloud visibility algorithm is useful in order to attribute each point to a scanner. Have in mind that a point can be seen by two scanners, especially if there is no physical barrier between them. In this case it is difficult to exactly know which scanner produced the point. But, as this point-scanner attribution is only required for normal orientations, we only need to know which scanner best sees it.

5.1.2 Objective

As a final step toward supporting point clouds without scanner locations, the algorithm must:

- take as input any 3D point cloud captured from static scanners as well as the location of all scanners,
- be invariant to differences between scanners, such as: density, noise, rotation angle,
- find for each point the scanner which best sees it, not necessary the scanner which produced it,
- have a reasonable running time.

As for *ScanFinder* described in Chapter 4, the algorithm is not expected to work with mobile point clouds.

5.2 Related work

This section highlight some previous work on the subject of *Point cloud visibility* before describing in detail one approach that we tried and the obtained results.

5.2.1 Previous work

Visibility in point clouds is a topic that experienced several publications since the 1960s [App68, SSS74, FST92, GKM93, BW03]. Some methods solve this problem in a 3D rendering context by estimating normals and reconstructing surfaces [SP04, SPL04, WS05, WK04]. This contrasts with our case as we

²A point cloud format that *ContextCaptureTM* wants to support and which does not store scanner locations in its metadata.

need visible points in order to reconstruct surfaces. Another common approach is to use z-buffering techniques based on point depths [DVS03] to reconstruct surfaces in a real-time rendering context. Even if this approach can be adapted to compute visibility of all points from all scanner location viewpoints, it is not robust to noisy point clouds.

One elegant approach compute point cloud visibility without surface reconstruction: [KTB07]. This approach is invariant to point cloud density and only point coordinates are needed (no normal estimation). It uses simple operations: an inversion followed by a convex hull computation. However, it is not robust enough against LiDAR point cloud noises. An improved version [MTSM10] has been implemented, see Section 5.2.2. Although it brings concavity robustness, the same observation is made; it is not robust enough against LiDAR point cloud noise. In both papers, only small³ and enclosed surfaces are reconstructed. They seems to not be fitted for LiDAR point clouds.

In Section 5.3 we describe a custom point cloud visibility algorithm suited for our needs (Section 5.1.2). It is robust to point cloud noise, avoid point occlusions and assign each point to a scanner.

5.2.2 An interesting approach: Visibility of Noisy Point Cloud Data

As previously said, the *Visibility of Noisy Point Cloud Data* [KTB07] paper describes some improvements of *Direct visibility of point sets* [KTB07] for a better handling of noise and concave surfaces in point clouds. This section summerizes both papers.

Intuition

The purpose of ?? is to find indentify which point of the point cloud are hidden directly from the point cloud itself. The problem being solved is: Given a set of points P (considered a sampling of continuous surface S) and a viewpoint C , determine the points in P visible from C .

³Compare to LiDAR point clouds.

The algorithm

Results and discussions

5.3 A custom disk-based approach

5.3.1 Overview

5.3.2 Implementation

5.3.3 Results and discussions

Chapter 6

Point Cloud Compression

6.1 Specifications

6.1.1 Problem being addressed

6.1.2 Objective

6.1.3 Scope

6.2 Related work

6.3 A custom arithmetic approach

6.3.1 Overview

6.3.2 Implementation

6.3.3 Comparison with Brotli, 7Z and Zip

6.4 Integration

Chapter 7

Conclusion

7.1 Summary of Internship Achievements

Summary.

7.2 Applications

Applications.

7.3 Future Work

Future Work.

Bibliography

- [AMO] Sameer Agarwal, Keir Mierle, and Others. Ceres solver. <http://ceres-solver.org>.
- [App68] Arthur Appel. Some techniques for shading machine renderings of solids. In *Proceedings of the April 30–May 2, 1968, spring joint computer conference*, pages 37–45. ACM, 1968.
- [ben] Bentley systems by wikipedia. https://en.wikipedia.org/wiki/Bentley_Systems#History. Accessed: 2018-07-06.
- [BW03] Jiří Bittner and Peter Wonka. Visibility in computer graphics. *Environment and Planning B: Planning and Design*, 30(5):729–755, 2003.
- [DVS03] Carsten Dachsbacher, Christian Vogelsgang, and Marc Stamminger. Sequential point trees. In *ACM Transactions on Graphics (TOG)*, volume 22, pages 657–662. ACM, 2003.
- [FST92] Thomas A Funkhouser, Carlo H Sequin, and Seth J Teller. Management of large amounts of data in interactive building walkthroughs. In *Proceedings of the 1992 symposium on Interactive 3D graphics*, pages 11–20. ACM, 1992.
- [GJ⁺10] Gaël Guennebaud, Benoît Jacob, et al. Eigen v3. <http://eigen.tuxfamily.org>, 2010.
- [GKIS05] Stefan Gumhold, Zachi Kami, Martin Isenburg, and Hans-Peter Seidel. Predictive point-cloud compression. In *ACM SIGGRAPH 2005 Sketches*, page 137. ACM, 2005.
- [GKM93] Ned Greene, Michael Kass, and Gavin Miller. Hierarchical z-buffer visibility. In *Proceedings of the 20th annual conference on Computer graphics and interactive techniques*, pages 231–238. ACM, 1993.
- [HDD⁺92] Hugues Hoppe, Tony DeRose, Tom Duchamp, John McDonald, and Werner Stuetzle. *Surface reconstruction from unorganized points*, volume 26. ACM, 1992.

- [KC15] Alex Kendall and Roberto Cipolla. Modelling uncertainty in deep learning for camera relocalization. *arXiv preprint arXiv:1509.05909*, 2015.
- [KGC15] Alex Kendall, Matthew Grimes, and Roberto Cipolla. Posenet: A convolutional network for real-time 6-dof camera relocalization. In *Proceedings of the IEEE international conference on computer vision*, pages 2938–2946, 2015.
- [KTB07] Sagi Katz, Ayellet Tal, and Ronen Basri. Direct visibility of point sets. In *ACM Transactions on Graphics (TOG)*, volume 26, page 24. ACM, 2007.
- [lid] What is lidar? <https://www.3dlasermapping.com/what-is-lidar-and-how-does-it-work/>. Accessed: 2018-07-06.
- [MTSM10] Ravish Mehra, Pushkar Tripathi, Alla Sheffer, and Niloy J Mitra. Visibility of noisy point cloud data. *Computers & Graphics*, 34(3):219–230, 2010.
- [NS17] Yoshikatsu Nakajima and Hideo Saito. Robust camera pose estimation by viewpoint classification using deep learning. *Computational Visual Media*, 3(2):189–198, 2017.
- [ran] Ransac. <http://www.math-info.univ-paris5.fr/~lomn/Cours/CV/SeqVideo/Material/RANSAC-tutorial.pdf>. Accessed: 2018-07-06.
- [SK06] Ruwen Schnabel and Reinhard Klein. Octree-based point-cloud compression. *Spbg*, 6:111–120, 2006.
- [SP04] Miguel Sainz and Renato Pajarola. Point-based rendering techniques. *Computers & Graphics*, 28(6):869–879, 2004.
- [SPL04] Miguel Sainz, Renato Pajarola, and Roberto Lario. Points reloaded: Point-based rendering revisited. *SPBG*, 4:121–128, 2004.
- [SQLG15] Hao Su, Charles R Qi, Yangyan Li, and Leonidas J Guibas. Render for cnn: Viewpoint estimation in images using cnns trained with rendered 3d model views. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2686–2694, 2015.
- [SSS74] Ivan E Sutherland, Robert F Sproull, and Robert A Schumacker. A characterization of ten hidden-surface algorithms. *ACM Computing Surveys (CSUR)*, 6(1):1–55, 1974.
- [TM15] Shubham Tulsiani and Jitendra Malik. Viewpoints and keypoints. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1510–1519, 2015.

- [WK04] Jainhua Wu and Leif Kobbelt. Optimized sub-sampling of point sets for surface splatting. In *Computer Graphics Forum*, volume 23, pages 643–652. Wiley Online Library, 2004.
- [WS05] Ingo Wald and H-P Seidel. Interactive ray tracing of point-based models. In *Point-Based Graphics, 2005. Eurographics/IEEE VGTC Symposium Proceedings*, pages 9–16. IEEE, 2005.