



UNIVERSITY OF TWENTE.

Postconditions

Topic of Software Systems (TCS module 2)

Lecturer: Marieke Huisman




DEFINITION OF POSTCONDITION

A postcondition **belongs to a method**

- **Condition** that should always hold **after the method terminates**
 - Method implementation should ensure this
 - Caller can rely on this
- Condition expressed using **method result**, method arguments, and/or **public** methods (evaluated at beginning and end of method)

POSTCONDITION

RESPONSIBILITY OF THE CALLED OBJECT (IMPLEMENTER)



Question

What should be the
postcondition of `getValue()`?

Answer

It should **return a positive number!**
`ensures \result >= 0;`

```
public class Skater {
    private Counter laps;


    public static final int LAPSIZE = 600;

    public void passFinish() {
        laps.increment();
    }

    public int distance() {
        return laps.getValue() * LAPSIZE;
    }
}
```

POSTCONDITION

RESPONSIBILITY OF THE CALLED OBJECT (IMPLEMENTER)



Question

What should be the
postcondition of increment()?

Answer

The result of `getValue()` should equal to the result of `getValue()`
before the call plus 1

`ensures getValue() == \old(getValue()) + 1;`

UNIVERSITY OF TWENTE.

```
public class Skater {
    private Counter laps;

    public static final int LAPSIZE = 600;

    public void passFinish() {
        laps.increment();
    }

    public int distance() {
        return laps.getValue() * LAPSIZE;
    }
}
```