

Threads in Java: an example

Topic of Software Systems (TCS module 2)

Lecturer: Marieke Huisman



EXAMPLE: BANK ACCOUNT


```
public class BankAccount {  
    private double amount = 0.0;  
    public void deposit(double val) { amount = amount + val; }  
    public void withdraw(double val) { amount = amount - val; }  
    public double getAmount() { return amount; }  
}
```

WHAT WILL THIS PROGRAM PRINT?


```
public class Deposit100ATM implements Runnable {
    private BankAccount acc;
    public Deposit100ATM(BankAccount acc) { this.acc = acc; }
    public void run() { acc.deposit(100.0); }
}

public static void main(String[] args) {
    BankAccount acc = new BankAccount();
    Deposit100ATM a1 = new Deposit100ATM(acc);
    Deposit100ATM a2 = new Deposit100ATM(acc);
    new Thread(a1).start();
    new Thread(a2).start();
    System.out.println("Amount on account is " + acc.getAmount());
}
```


A POSSIBLE EXECUTION



A POSSIBLE EXECUTION



A POSSIBLE EXECUTION



WHAT WILL THIS PROGRAM PRINT?

```
public static void main(String[] args) {  
    BankAccount acc = new BankAccount();  
    Deposit100ATM a1 = new Deposit100ATM(acc);  
    Deposit100ATM a2 = new Deposit100ATM(acc);  
    a1.start();  
    a2.start();  
    try {  
        a1.join();  
        a2.join();  
    } catch (InterruptedException e) { ... }  
    System.out.println("Amount on account is " + acc.getAmount());  
}
```

A POSSIBLE EXECUTION

Always?
No, not always!

