For your Jetson AGX Orin running RHEL 9.4, the working installation sequence is:

Bash

```
# Install pip if neededsudo dnf install -y python3-pip

# Install jetson-stats system-widesudo-H python3 -m pip install --no-cache-dir-U jetson-stats

# Verify jtop
/usr/local/bin/jtop --version
```

If the PyPI installation reports that it cannot locate the `jtop_env.sh` template, reinstall directly from the upstream source:

Bash

```
sudo python3 -m pip uninstall -y jetson-stats

sudo-H python3 -m pip install \
  --no-cache-dir \
  git+https://github.com/rbonghi/jetson_stats.git
```

Then verify that the environment and service files exist:

Bash

```
ls-l /etc/profile.d/jtop_env.sh
ls-l /etc/systemd/system/jtop.service
```

On RHEL with SELinux, restore their contexts and reload systemd:

Bash

```
sudo restorecon -v /etc/profile.d/jtop_env.sh
sudo restorecon -v /etc/systemd/system/jtop.service

sudo systemctl daemon-reload
```

Because `jtop` installs environment variables and service configuration that may not be available to the existing login session, **reboot the Orin**:

Bash

```
sudo reboot
```

After reboot, log back in as your normal user and run:

Bash

```
jtop
```

If needed, verify the service with:

Bash

```
systemctl status jtop.service
```

The key issue we encountered was that the **PyPI jetson-stats 7.2.1 wheel installed the jtop executable but initially failed to provide/find the jtop_env.sh service-install template correctly**. Installing from the upstream source resolved the missing files on this RHEL environment.