

Intersection Management with Constraint-Based Reservation Systems

Tsz-Chiu Au², Shun Zhang¹, and Peter Stone¹

¹Department of Computer Science. The University of Texas at Austin.


²School of Electrical and Computer Engineering. Ulsan National Institute of Science and Technology. South Korea.

Intersection Management: Present and Future

- Today's transportation infrastructure is designed for human drivers.
- In the future: **Autonomous Intersection Management.** Utilize the capacity of autonomous vehicles to improve traffic in transportation systems.




Previous Work: Autonomous Intersection Management





- First Come First Serve (FCFS) [Dresner and Stone, 2008].
- Use Grid-Based Collision Detection.

Previous Work: Autonomous Intersection Management




- First Come First Serve (FCFS) [Dresner and Stone, 2008].
- Use Grid-Based Collision Detection.
- Dramatically reduce the traffic delay.
- Reduce the overhead of fuel consumption by approximately two thirds.


Grid-Based Collision Detection



Accept



Reject




Sharing the Road with Human Drivers

- AIM is designed for the time when vehicles are autonomous.
- Autonomous vehicles won't displace manual-controlled vehicles in one day. Some people enjoy driving.

Sharing the Road with Human Drivers

- AIM is designed for the time when vehicles are autonomous.
- Autonomous vehicles won't displace manual-controlled vehicles in one day. Some people enjoy driving.
- One solution: FCFS-light = First-Come First-Served Policy + Traffic Signals [Dresner and Stone, 2008]



Observation

- This ignores the possible equipments of human-driven vehicles (e.g. cruise control).

Observation

- This ignores the possible equipments of human-driven vehicles (e.g. cruise control).
- **Goal:** find a way to make all types of vehicles to achieve the benefits (better than traffic signal, may not be as good as 100% fully autonomous vehicles).

Definition

Semi-autonomous vehicles: vehicles with limited autonomous driving and wireless communication capabilities.

Definition

Semi-autonomous vehicles: vehicles with limited autonomous driving and wireless communication capabilities.

They are able to follow a *limited number* of predictable trajectories at intersections more precisely than human drivers.

Set of Equipments

- **Communication Device (Com):** a component in a vehicle's on-board electronic system that enables the vehicle to wirelessly communicate with the transportation infrastructure including the IM.

Set of Equipments

- **Communication Device (Com):** a component in a vehicle's on-board electronic system that enables the vehicle to wirelessly communicate with the transportation infrastructure including the IM.
- **Simple Cruise Control (CC):** An optional speed control subsystem in vehicles' drivetrain that automatically controls the vehicle speed by taking over the throttle of the vehicles.

Set of Equipments

- **Communication Device (Com):** a component in a vehicle's on-board electronic system that enables the vehicle to wirelessly communicate with the transportation infrastructure including the IM.
- **Simple Cruise Control (CC):** An optional speed control subsystem in vehicles' drivetrain that automatically controls the vehicle speed by taking over the throttle of the vehicles.
- **Adaptive Cruise Control (ACC):** an advanced cruise control system that automatically adjusts the speed of a vehicle in order to maintain a certain distance from vehicles ahead.

Type of Semi-Autonomous Vehicles


Vehicle Type	Communication Device	Cruise Control	Adaptive Cruise Control
SA-ACC	X	X	X
SA-CC	X	X	
SA-Com	X		

Interaction Model

For safety, we need to define a simple and clean interface between the human driver and the vehicle.

Interaction Model

For safety, we need to define a simple and clean interface between the human driver and the vehicle.



Constraint-Based Reservation

We turn AIM into a *constraint-based reservation system*, which allows vehicles to make reservations in terms of constraints over

- their driving profiles such as their arrival time and arrival velocity
- the relationships with other vehicles.

Basic Elements

- **Intention:** The direction in which the vehicle intends to move.

Basic Elements

- **Intention:** The direction in which the vehicle intends to move.
- **Vehicle Type:** The type of vehicle.

Basic Elements

- **Intention:** The direction in which the vehicle intends to move.
- **Vehicle Type:** The type of vehicle.
- **Entry Condition:** The condition under which the vehicle will enter the intersection.

Basic Elements

- **Intention:** The direction in which the vehicle intends to move.
- **Vehicle Type:** The type of vehicle.
- **Entry Condition:** The condition under which the vehicle will enter the intersection.
- **Acceleration Profile List:** The list of possible acceleration schedules from among which the vehicle will choose one to follow during the traversal of the intersection.

Constant-Velocity Request

- Intent = $(l_1 \vee l_2 \vee \dots \vee l_n)$ in which l_i is a possible lane from which the vehicle exits the intersection;
- Type is the vehicle type;
- Entry = $((l'_1 \vee l'_2 \vee \dots \vee l'_n), [t_1, t_2], [v_1, v_2])$ is the entry statement; and
- AP = $(\langle(t_1, 0)\rangle)$

This is particularly used by Simple Cruise Control.

Whole-Row Request

- $\text{Intent} = (l_1 \vee l_2 \vee \dots \vee l_n)$ l_i is a possible lane from which the vehicle exits the intersection;
- Type is the vehicle type;
- $\text{Entry} = ((l'_1 \vee l'_2 \vee \dots \vee l'_n), [t_1, t_2], [v_1, v_2])$ is the entry statement; and
- AP is the acceleration profile list, and may not be provided.

This is particularly used by Communication Device.

Anchor Request

Semi-autonomous vehicles with adaptive cruise control can use a special constraint-based request called *anchor requests* to make reservations.

Anchor Request

Semi-autonomous vehicles with adaptive cruise control can use a special constraint-based request called *anchor requests* to make reservations.


An anchor request is $\langle \text{Type}, \text{vin}, d \rangle$

A General Request

In Lisp syntax,

```
(cc-profile (v verror angle)
  (is-auto-speed-control)
  (not is-auto-steering)
  (< velocity (+ v verror))
  (> velocity (- v verror))
  (< steer-angle angle) (> steer-angle -angle))
```

Evaluation on AIM (Previous Work)



[Dresner and Stone, 2008]

Implementation

Vehicle Type	Communication Device	Cruise Control	Adaptive Cruise Control
SA-ACC	X	X	X
SA-CC	X	X	
SA-Com	X		

For each type of vehicle - always try the most *advanced* type of request first.


Goal

Recall, our **goal**:

Goal


Recall, our **goal**: find a way to make all types of vehicles to achieve the benefits (better than traffic signal, may not be as good as 100% fully autonomous vehicles).

Evaluation on SemiAIM



(Semi-)Autonomous vehicles vs. Human-Driven vehicles. Traffic level = 360 vehicles/lane/hour.


Evaluation on SemiAIM



Type H	SemiAuto	Type A
90%	9%	1%
87%	11%	2%
84%	13%	3%
...
0%	69%	31%

The average delay according to a deployment schedule. Traffic level = 360 vehicles/lane/hour.

Evaluation on SemiAIM



Type H	SemiAuto	Type A
10%	85%	5%
10%	80%	10%
10%	75%	15%
...
10%	5%	85%

The average delay according to a deployment schedule. Traffic level = 360 vehicles/lane/hour.

Related Works

- The main context of our work is an extension to the FCFS policy proposed by Dresner and Stone [Dresner and Stone, 2008].
- Similar to the analysis of adaptive cruise control performance by Jerath and Brennan [Jerath and Brennan, 2010].
- Part of a series of robotic car competitions such as the *DARPA Grand Challenges* [DAR,].
- Jointly optimizing autonomous vehicles and road infrastructure, for example, the PATH program [Shladover et al., 1991].
- Vehicle-to-Vehicle (V2V) forms of autonomous intersection management [Naumann and Rasche, 1997, VanMiddlesworth et al., 2008].

Conclusion

- SemiAIM is the first multiagent protocol to enable smooth interactions between human-driven, fully autonomous, and semiautonomous vehicles.

Conclusion

- SemiAIM is the first multiagent protocol to enable smooth interactions between human-driven, fully autonomous, and semiautonomous vehicles.
- Our experiments showed that our system can greatly decrease traffic delay when most vehicles are semiautonomous, even when few (if any) are fully autonomous.

Bibliography



DARPA grand challenge.

http://en.wikipedia.org/wiki/DARPA_Grand_Challenge.



Dresner, K. and Stone, P. (2008).

A multiagent approach to autonomous intersection management.
Journal of Artificial Intelligence Research (JAIR).



Jerath, K. and Brennan, S. N. (2010).

Adaptive cruise control: Towards higher traffic flows, at the cost of increased susceptibility to congestion.
In *AVEC'10*.



Naumann, R. and Rasche, R. (1997).

Intersection collision avoidance by means of decentralized security and communication management of autonomous vehicles.
In *Proceedings of the 30th ISATA - ATT/IST Conference*.



Shladover, S., Desoer, C., Hedrick, J., Tomizuka, M., Walrand, J., Zhang, W.-B., McMahon, D., Peng, H., Sheikholeslam, S., and McKeown, N. (1991).
Automated vehicle control developments in the path program.
IEEE Transactions on Vehicular Technology, 40(1):114–130.



VanMiddlesworth, M., Dresner, K., and Stone, P. (2008).

Replacing the stop sign: Unmanaged intersection control for autonomous vehicles.
In *AAMAS Workshop on Agents in Traffic and Transportation*, pages 94–101, Estoril, Portugal.