


Knowledge Base

- [Same-Day Shipping](#)
  - [Clippard DV Series High Flow Electronic Valves](#)
  - [Electronic Valve Series Flow Chart](#)
  - [Clippard Analytical Series Electronic Valves](#)
  - [Clippard Oxygen Clean Electronic Valves](#)
  - [Clippard EW Series Electronic Valves Press Release](#)
- [more...](#)



More Views



EV-2-12-H

<b>Series</b> Standard ▼	<b>Valve Porting</b> 2-Way Normally-Closer ▼
<b>Mount</b> Standard In-Line Moun ▼	<b>Connection Type</b> 18" Wire Leads Side (F ▼
<b>Pressure Range</b> 28" Hg Vac. to 25 psig ▼	<b>Voltage</b> 12 VDC ▼
<b>Seals</b> Nitrile ▼	

Product will ship within 1 to 2 business days

Get CAD files:

Qty:

Details

2-Way Elec. Valve, N-C, In-Line Mount, Wire Leads, 12 VDC

See Catalog: [Page 183](#)

Additional Information

Available Seals	FKM Standard, Nitrile, EPR & Silicone Available
Connection Type	18" Wire Leads Side (Radial)
Cycles	Over 1 Billion
Flow	0.45 scfm @ 25 psig (13 L/min @ 1.8 bar)
Material	Nickel Plated Brass Body & Core (CR-: Stainless Steel Core)
Medium	Clean, Dry Air (40 micron filter)
Mount	Standard In-Line Mount
Mounting	#6-32 thd. Mounting Holes
Orifice	0.060"
Poppet Travel	0.007"
Ports	#10-32 Female In-Line Ports
Power Consumption	0.67 Watts
Pressure Range	28" Hg Vac. to 25 psig
Response Time	5 to 10 milliseconds (nominal) @ 25 psig
Seals	Nitrile
Series	Standard
Valve Porting	2-Way Normally-Closed
Voltage	12 VDC
Wire Size	26 Gauge

