# Choosing the Regularization Parameter

At our disposal: several regularization methods, based on filtering of the SVD components.

Often fairly straightforward to "eyeball" a good TSVD truncation parameter from the Picard plot.

Need: a reliable and automated technique for choosing the regularization parameter, such as k (for TSVD) or  $\lambda$  (for Tikhonov).

- 1. Perspectives on regularization
- 2. The discrepancy principle
- 3. Generalized cross validation (GCV)
- 4. The L-curve criterion
- 5. The NCP method

02906 - DIP - Chapter 5: Parameter Choice Methods

# Once Again: Tikhonov Regularization

Focus on Tikhonov regularization; the ideas carry over to many other methods.

Recall that the Tikhonov solution  $x_{\lambda}$  solves the problem

$$\min_{x} \left\{ \|Ax - b\|_{2}^{2} + \lambda^{2} \|x\|_{2}^{2} \right\},\,$$

and that it is formally given by

$$x_{\lambda} = (A^T A + \lambda^2 I)^{-1} A^T b = A_{\lambda}^{\#} b,$$

where  $A_{\lambda}^{\#} = (A^TA + \lambda^2 I)^{-1}A^T$  is a "regularized inverse."

Our noise model

$$b = b^{\text{exact}} + e$$

where  $b^{\text{exact}} = A x^{\text{exact}}$  and e is the error.

# Classical and Pragmatic Parameter-Choice

Assume we are given the problem Ax = b with  $b = b^{\text{exact}} + e$ , and that we have a strategy for choosing the regularization parameter  $\lambda$  as a function of the "noise level"  $||e||_2$ .

Then *classical* parameter-choice analysis is concerned with the convergence rates of

$$x_{\lambda} \to x^{\text{exact}}$$
 as  $||e||_2 \to 0$  and  $\lambda \to 0$ .

The typical situation in practice is different:


- The norm  $||e||_2$  is not known, and
- the errors are fixed (not practical to repeat the measurements).

The *pragmatic* approach to choosing the regularization parameter is based on the forward/prediction error, or the backward error.

02906 - DIP - Chapter 5: Parameter Choice Methods

4

# An Example (Image of Io, a Moon of Saturn)



## Perspectives on Regularization

Problem formulation: balance fit (residual) and size of solution.

$$x_{\lambda} = \arg\min \{ ||Ax - b||_{2}^{2} + \lambda^{2} ||Lx||_{2}^{2} \}$$

Cannot be used for choosing  $\lambda$ .

Forward error: balance regularization and perturbation errors.

$$x^{\text{exact}} - x_{\lambda} = x^{\text{exact}} - A_{\lambda}^{\#}(b^{\text{exact}} + e)$$
$$= \left(I - A_{\lambda}^{\#}A\right)x^{\text{exact}} - A_{\lambda}^{\#}e .$$

Backward/prediction error: balance residual and perturbation.

$$b^{\text{exact}} - A x_{\lambda} = b^{\text{exact}} - A A_{\lambda}^{\#} (b^{\text{exact}} + e)$$
$$= \left( I - A A_{\lambda}^{\#} \right) b^{\text{exact}} - A A_{\lambda}^{\#} e .$$

02906 - DIP - Chapter 5: Parameter Choice Methods

#### More About the Forward Error

The forward error in the SVD basis:

$$\begin{split} x^{\text{exact}} - x_{\lambda} &= x^{\text{exact}} - V \Phi^{[\lambda]} \Sigma^{-1} U^{T} b \\ &= x^{\text{exact}} - V \Phi^{[\lambda]} \Sigma^{-1} U^{T} A x^{\text{exact}} - V \Phi^{[\lambda]} \Sigma^{-1} U^{T} e \\ &= V \left( I - \Phi^{[\lambda]} \right) V^{T} x^{\text{exact}} - V \Phi^{[\lambda]} \Sigma^{-1} U^{T} e. \end{split}$$

The first term is the regularization error:

$$\Delta x_{\text{bias}} = V \left( I - \Phi^{[\lambda]} \right) V^T x^{\text{exact}} = \sum_{i=1}^{n} \left( 1 - \varphi_i^{[\lambda]} \right) \left( v_i^T x^{\text{exact}} \right) v_i,$$

and we recognize this as (minus) the bias term.

The second error term is the *perturbation error*:

$$\Delta x_{\text{pert}} = V \Phi^{[\lambda]} \Sigma^{-1} U^T e.$$

#### Regularization and Perturbation Errors – TSVD

For TSVD solutions, the regularization and perturbation errors take the form

$$\Delta x_{\text{bias}} = \sum_{i=k+1}^{n} (v_i^T x^{\text{exact}}) v_i, \qquad \Delta x_{\text{pert}} = \sum_{i=1}^{k} \frac{u_i^T e}{\sigma_i} v_i.$$


We use the truncation parameter k to prevent the perturbation error from blowing up (due to the division by the small singular values), at the cost of introducing bias in the regularized solution.

A "good" choice of the truncation parameter k should balance these two components of the forward error (see next slide).

The behavior of  $||x_k||_2$  and  $||Ax_k - b||_2$  is closely related to these errors – see the analysis in §5.1.

02906 - DIP - Chapter 5: Parameter Choice Methods

# The Regularization and Perturbation Errors



The norm of the regularization and perturbation error for TSVD as a function of the truncation parameter k. The two different errors approximately balance each other for k = 11.

#### The TSVD Residual

Let  $k_{\eta}$  denote the index that marks the transition between decaying and flat coefficients  $|u_i^T b|$ .

Due to the discrete Picard condition, the coefficients  $|u_i^T b|/\sigma_i$  will also decay, on the average, for all  $i < k_{\eta}$ .

$$k < k_{\eta}: \|Ax_k - b\|_2^2 \approx \sum_{i=k+1}^{k_{\eta}} (u_i^T b)^2 + (n - k_{\eta})\eta^2 \approx \sum_{i=k+1}^{k_{\eta}} (u_i^T b^{\text{exact}})^2$$

$$k > k_{\eta} : \|A x_k - b\|_2^2 \approx (n - k) \eta^2.$$

For  $k < k_{\eta}$  the residual norm decreases steadily with k.

For  $k > k_{\eta}$  it decreases much more slowly.

The transition between the two types of behavior occurs at  $k = k_{\eta}$  when the regularization and perturbation errors are balanced.

02906 - DIP - Chapter 5: Parameter Choice Methods

#### The Discrepancy Principle

Recall that  $\mathcal{E}(\|e\|_2) \approx n^{1/2} \eta$ .

We should ideally choose k such that  $||A x_k - b||_2 \approx (n - k)^{1/2} \eta$ .

The discrepancy principle (DP) seeks to combine this:

Assume we have an upper bound  $\delta_e$  for the noise level, then solve

$$||A x_{\lambda} - b||_2 = \tau \, \delta_e$$
, where  $||e||_2 \le \delta_e$ 

and  $\tau$  is some parameter  $\tau = O(1)$ . See next slide.


**A statistician's point of view.** Write  $x_{\lambda} = A_{\lambda}^{\#}b$  and assume  $Cov(b) = \eta^{2}I$ ; choose the  $\lambda$  that solves

$$||A x_{\lambda} - b||_2 = (||e||_2^2 - \eta^2 \operatorname{trace}(A A_{\lambda}^{\#}))^{1/2}$$

Note that the right-hand side now depends on  $\lambda$ .

Both versions of the DP are very sensitive to the estimate  $\delta_e$ .

# Illustration of the Discrepancy Principle




The choice  $||A x_k - b||_2 \approx (n - k_\eta)^{1/2} \eta$  leads to a too large value of the truncation parameter k, while the more conservative choice  $||A x_k - b||_2 \approx ||e||_2$  leads to a better value of k.

02906 - DIP - Chapter 5: Parameter Choice Methods

# The L-Curve for Tikhonov Regularization

Recall that the L-curve is a log-log-plot of the solution norm versus the residual norm, with  $\lambda$  as the parameter.



#### Parameter-Choice and the L-Curve

Recall that the L-curve basically consists of two parts.

- A "flat" part where the regularization errors dominates.
- A "steep" part where the perturbation error dominates.

The optimal regularization parameter (in the pragmatic sense) must lie somewhere near the L-curve's corner.

The component  $b^{\text{exact}}$  dominates when  $\lambda$  is large:

$$||x_{\lambda}||_2 \approx ||x^{\text{exact}}||_2 \text{ (constant)}$$

$$||b - A x_{\lambda}||_2$$
 increases with  $\lambda$ .

The error e dominates when  $\lambda$  is small:

$$||x_{\lambda}||_2$$
 increases with  $\lambda^{-1}$ 

$$||b - A x_{\lambda}||_2 \approx ||e||_2$$
 (constant.)

02906 - DIP - Chapter 5: Parameter Choice Methods

#### The L-Curve Criterion

The flat and the steep parts of the L-curve represent solutions that are dominated by regularization errors and perturbation errors.

- The balance between these two errors must occur near the L-curve's corner.
- The two parts and the corner are emphasized in log-log scale.
- Log-log scale is insensitive to scalings of A and b.

An operational definition of the corner is required.

Write the L-curve as

$$(\log ||A x_{\lambda} - b||_2, \log ||x_{\lambda}||_2)$$

and seek the point with maximum curvature.

#### The Curvature of the L-Curve

We want to derive an analytical expression for the L-curve's curvature  $\zeta$  in log-log scale. Define

$$\xi = ||x_{\lambda}||_{2}^{2}, \qquad \rho = ||A x_{\lambda} - b||_{2}^{2}$$

and

$$\hat{\xi} = \log \eta , \qquad \hat{\rho} = \log \rho .$$

Then the curvature is given by


$$\hat{c}_{\lambda} = 2 \frac{\hat{\rho}' \hat{\xi}'' - \hat{\rho}'' \hat{\xi}'}{((\hat{\rho}')^2 + (\hat{\xi}')^2)^{3/2}} ,$$


where a prime denotes differentiation with respect to  $\lambda$ .


This can be used to define the "corner" of the L-curve as the point with maximum curvature.

02906 – DIP – Chapter 5: Parameter Choice Methods









An L-curve and the corresponding curvature  $\hat{c}_{\lambda}$  as a function of  $\lambda$ . The corner, which corresponds to the point with maximum curvature, is marked by the red circle; it occurs for  $\lambda_{\rm L} = 4.86 \cdot 10^{-3}$ .

#### A More Practical Formula

The first derivatives of  $\hat{\xi}$  and  $\hat{\rho}$  satisfy

$$\hat{\xi}' = \xi'/\xi$$
,  $\hat{\rho}' = \rho'/\rho$ ,  $\rho' = -\lambda^2 \xi'$ .

The second derivatives satisfy

$$\hat{\xi}'' = \frac{\xi''\xi - (\xi')^2}{\xi^2}, \qquad \hat{\rho}'' = \frac{\rho''\rho - (\rho')^2}{\rho^2},$$

as they are interrelated by

$$\rho'' = \frac{d}{d\lambda} \left( -\lambda^2 \xi' \right) = -2 \lambda \xi' - \lambda^2 \xi'' .$$

When all this is inserted into the equation for  $\hat{c}_{\lambda}$ , we get

$$\hat{c}_{\lambda} = 2 \, \frac{\xi \, \rho}{\xi'} \, \frac{\lambda^2 \xi' \rho + 2 \, \lambda \, \xi \, \rho + \lambda^4 \xi \, \xi'}{(\lambda^2 \xi^2 + \rho^2)^{3/2}} \; .$$

02906 - DIP - Chapter 5: Parameter Choice Methods

#### Efficient Computation of the Curvature

The quantities  $\xi$  and  $\rho$  readily available.

Straightforward to show that

$$\xi' = \frac{4}{\lambda} x_{\lambda}^T z_{\lambda}$$

where  $z_{\lambda}$  is given by

$$z_{\lambda} = \left(A^T A + \lambda^2 I\right)^{-1} A^T (A x_{\lambda} - b) ,$$

i.e.,  $z_{\lambda}$  is the solution to the problem

$$\min \left\| \begin{pmatrix} A \\ \lambda I \end{pmatrix} z - \begin{pmatrix} A x_{\lambda} - b \\ 0 \end{pmatrix} \right\|_{2}.$$

This can be used to compute  $z_{\lambda}$  efficiently, when we already have a factorization of the coefficient matrix.

#### Discrete L-Curves

The L-curve may be discrete – corresponding to a discrete regularization parameter k. May have local, fine-grained "corners" (that do not appear with a continuous parameter).

Two-step approach (older versions of Reg. Tools):

- 1. Perform a local smoothing of the L-curve points.
- 2. Use the smoothed points as control points for a cubic spline curve, compute its "corner," and return the original point closest to this corner.

Another two-step approach (current version of Reg. Tools):

- 1. Prune the discrete L-curve for small local corners.
- 2. Use the remaining points to determine the largest angle between neighbor points.

02906 - DIP - Chapter 5: Parameter Choice Methods

The Prediction Error

A different kind of goal: find the value of  $\lambda$  or k such that  $A x_{\lambda}$  or  $A x_k$  predicts the exact data  $b^{\text{exact}} = A x^{\text{exact}}$  as well as possible.

We split the analysis in two cases, depending on k:

$$k < k_{\eta}:$$
  $||A x_{k} - b^{\text{exact}}||_{2}^{2} \approx k \eta^{2} + \sum_{i=k+1}^{k_{\eta}} (u_{i}^{T} b^{\text{exact}})^{2}$   
 $k > k_{\eta}:$   $||A x_{k} - b^{\text{exact}}||_{2}^{2} \approx k \eta^{2}.$ 

For  $k < k_{\eta}$  the norm of the prediction error decreases with k.

For  $k > k_{\eta}$  the norm increases with k.

The minimum arises near the transition, i.e., for  $k \approx k_{\eta}$ . Hence it makes good sense to search for the regularization parameter that minimizes the prediction error. But  $b^{\text{exact}}$  is unknown ...

# (Ordinary) Cross-Validation

Leave-one-out approach:

skip *i*th element  $b_i$  and predict this element.

$$\begin{array}{rcl} A^{(i)} &=& A([1:i-1,i+1:m],:) \\ b^{(i)} &=& b([1:i-1,i+1:m]) \\ x_{\lambda}^{(i)} &=& \left(A^{(i)}\right)_{\lambda}^{\#}b^{(i)} \quad \text{(Tikh. sol. to reduced problem)} \\ b_{i}^{\text{predict}} &=& A(i,:)\,x_{\lambda}^{(i)} \quad \text{(prediction of "missing" element.)} \end{array}$$

The optimal  $\lambda$  minimizes the quantity

$$C(\lambda) = \sum_{i=1}^{m} (b_i - b_i^{\text{predict}})^2.$$

But  $\lambda$  is hard to compute, and depends on the ordering of the data.

02906 - DIP - Chapter 5: Parameter Choice Methods

## Generalized Cross-Validation

Want a scheme for which  $\lambda$  is independent of any orthogonal transformation of b (incl. a permutation of the elements).

Minimize the GCV function

$$G(\lambda) = \frac{\|A x_{\lambda} - b\|_{2}^{2}}{\operatorname{trace}(I_{m} - A A_{\lambda}^{\#})^{2}}$$

where


$$\operatorname{trace}(I_m - A A_{\lambda}^{\#}) = m - \sum_{i=1}^{n} \varphi_i^{[\lambda]}.$$

Easy to compute the trace term when the SVD is available.

For TSVD the trace term is particularly simple:

$$m - \sum_{i=1}^{n} \varphi_i^{[\lambda]} = m - k .$$

# The GCV Function




The GCV function  $G(\lambda)$  for Tikhonov regularization; the red circle shows the parameter  $\lambda_{\text{GCV}}$  as the minimum of the GCV function, while the cross indicates the location of the optimal parameter.

02906 - DIP - Chapter 5: Parameter Choice Methods

24

## Occasional Failure

Occasional failure leading to a too small  $\lambda$ ; more pronounced for correlated noise.



#### Extracting Signal in Noise

An observation about the residual vector.

- If  $\lambda$  is too large, not all information in b has not been extracted.
- If  $\lambda$  is too small, only noise is left in the residual.

Choose the  $\lambda$  for which the residual vector changes character from "signal" to "noise."

Our tool: the **normalized cumulative periodogram** (NCP). Let  $p_{\lambda} \in \mathbb{R}^{n/2}$  be the residual's power spectrum, with elements

$$(p_{\lambda})_k = |\operatorname{dft}(A x_{\lambda} - b)_k|^2, \qquad k = 1, 2, \dots, n/2.$$

Then the vector  $c(r_{\lambda}) \in \mathbb{R}^{n/2-1}$  with elements


$$c(r_{\lambda}) = \frac{\|p_{\lambda}(2:k+1)\|_{1}}{\|p_{\lambda}(2:n)\|_{1}}, \qquad k = 1, \dots, n/2 - 1$$

is the NCP for the residual vector.

02906 - DIP - Chapter 5: Parameter Choice Methods

26


# NCP Analysis



Left to right: 10 instances of white-noise residuals, 10 instances of residuals dominated by low-frequency components, and 10 instances of residuals dominated by high-frequency components.

The dashed lines show the Kolmogorov-Smirnoff limits  $\pm 1.35\,q^{-1/2}\approx \pm 0.12$  for a 5% significance level, with q=n/2-1.

#### The Transition of the NCPs



Plots of NCPs for various regularization parameters  $\lambda$ , for the test problem deriv2(128,2) with rel. noise level  $||e||_2/||b^{\text{exact}}||_2 = 10^{-5}$ .

02906 - DIP - Chapter 5: Parameter Choice Methods

# Implementation of NCP Criterion

Two ways to implement a pragmatic NCP criterion.

- Adjust the regularization parameter until the NCP lies solely within the K-S limits.
- Choose the regularization parameter for which the NCP is closest to a straight line  $c_{\text{white}} = (1/q, 2/q, \dots, 1)^T$ .

The latter is implemented in Regularization Tools.

# Summary of Methods (Tikhonov)

Discrepancy principle (discrep):

Choose  $\lambda = \lambda_{DP}$  such that  $||A x_{\lambda} - b||_2 = \nu_{dp} ||e||_2$ .

L-curve criterion (l\_curve):

Choose  $\lambda = \lambda_{\rm L}$  such that the curvature  $\hat{c}_{\lambda}$  is maximum.

GCV criterion (gcv):

Choose 
$$\lambda = \lambda_{\text{GCV}}$$
 as the minimizer of  $G(\lambda) = \frac{\|A x_{\lambda} - b\|_{2}^{2}}{\left(m - \sum_{i=1}^{n} \varphi_{i}^{[\lambda]}\right)^{2}}$ .

NCP criterion (ncp):

Choose  $\lambda = \lambda_{\text{NCP}}$  as the minimizer of  $d(\lambda) = ||c(r_{\lambda}) - c_{\text{white}}||_2$ .

02906 - DIP - Chapter 5: Parameter Choice Methods

# Comparison of Methods

To evaluate the performance of the four methods, we need the optimal regularization parameter  $\lambda_{\text{opt}}$ :


$$\lambda_{\text{opt}} = \operatorname{argmin}_{\lambda} ||x^{\text{exact}} - x_{\lambda}||_2.$$

This allows us to compute the four ratios


$$R_{\mathrm{DP}} = \frac{\lambda_{\mathrm{DP}}}{\lambda_{\mathrm{opt}}}, \qquad R_{\mathrm{L}} = \frac{\lambda_{\mathrm{L}}}{\lambda_{\mathrm{opt}}}, \qquad R_{\mathrm{GCV}} = \frac{\lambda_{\mathrm{GCV}}}{\lambda_{\mathrm{opt}}}, \qquad R_{\mathrm{NCP}} = \frac{\lambda_{\mathrm{NCP}}}{\lambda_{\mathrm{opt}}},$$

one for each parameter-choice method, and study their distributions via plots of their histograms (in log scale).

The closer these ratios are to one, the better, so a spiked histogram located at one is preferable.



02906 - DIP - Chapter 5: Parameter Choice Methods



#### Summary

- The discrepancy principle is a simple method that seeks to reveal when the residual vector is noise-only. It relies on a good estimate of  $||e||_2$  which may be difficult to obtain in practise.
- The *L-curve criterion* is based on an intuitive heuristic and seeks to balance the two error components via inspection (manually or automated) of the L-curve. This method fails when the solution is very smooth.
- The GCV criterion seeks to minimize the prediction error, and it is often a very robust method with occasional failure, often leading to ridiculous under-smoothing that reveals itself.
- The NCP criterion is a statistically-based method for revealing when the residual vector is noise-only, based on the power spectrum. It can mistake LF noise for signal and thus lead to under-smoothing.