

Advanced Search

Admissible heuristics

E.g., for the 8-puzzle:

- $h_1(n)$ = number of misplaced tiles
- $h_2(n)$ = total Manhattan distance
(i.e., no. of squares from desired location of each tile)

7	2	4
5		6
8	3	1

Start State

	1	2
3	4	5
6	7	8

Goal State

- $h_1(S) = ?$
- $h_2(S) = ?$

Admissible heuristics

E.g., for the 8-puzzle:

- $h_1(n)$ = number of misplaced tiles
- $h_2(n)$ = total Manhattan distance
(i.e., no. of squares from desired location of each tile)

7	2	4
5		6
8	3	1

Start State

	1	2
3	4	5
6	7	8

Goal State

- $h_1(S) = ?$ 8
- $h_2(S) = ?$ $3+1+2+2+2+3+3+2 = 18$

Relaxed problems


- A problem with fewer restrictions on the actions is called a **relaxed problem**
- The cost of an optimal solution to a relaxed problem is an admissible heuristic for the original problem
- If the rules of the 8-puzzle are relaxed so that a tile can move **anywhere**, then $h_1(n)$ gives the shortest solution
- If the rules are relaxed so that a tile can move to **any adjacent square**, then $h_2(n)$ gives the shortest solution

Local search algorithms

- In many optimization problems, the **path** to the goal is irrelevant; the goal state itself is the solution
- State space = set of "complete" configurations
- Find configuration satisfying constraints, e.g., n-queens
- In such cases, we can use **local search algorithms** that keep a single "current" state, try to improve it

Example: n -queens

- Put n queens on an $n \times n$ board with no two queens on the same row, column, or diagonal



Hill-climbing search


- "Like climbing Everest in thick fog with amnesia"

```
function HILL-CLIMBING(problem) returns a state that is a local maximum
  inputs: problem, a problem
  local variables: current, a node
                  neighbor, a node

  current ← MAKE-NODE(INITIAL-STATE[problem])
  loop do
    neighbor ← a highest-valued successor of current
    if VALUE[neighbor] ≤ VALUE[current] then return STATE[current]
    current ← neighbor
```

Hill-climbing search

- Problem: depending on initial state, can get stuck in local maxima




Hill-climbing search: 8-queens problem

18	12	14	13	13	12	14	14
14	16	13	15	12	14	12	16
14	12	18	13	15	12	14	14
15	14	14	♙	13	16	13	16
♙	14	17	15	♙	14	16	16
17	♙	16	18	15	♙	15	♙
18	14	♙	15	15	14	♙	16
14	14	13	17	12	14	12	18

- h = number of pairs of queens that are attacking each other, either directly or indirectly
- $h = 17$ for the above state

Hill-climbing search: 8-queens problem



- A local minimum with $h = 1$

Simulated annealing search

- Idea: escape local maxima by allowing some "bad" moves but **gradually decrease** their frequency

```
function SIMULATED-ANNEALING(problem, schedule) returns a solution state
  inputs: problem, a problem
           schedule, a mapping from time to "temperature"
  local variables: current, a node
                   next, a node
                   T, a "temperature" controlling prob. of downward steps

  current ← MAKE-NODE(INITIAL-STATE[problem])
  for t ← 1 to ∞ do
    T ← schedule[t]
    if T = 0 then return current
    next ← a randomly selected successor of current
     $\Delta E \leftarrow \text{VALUE}[\textit{next}] - \text{VALUE}[\textit{current}]$ 
    if  $\Delta E > 0$  then current ← next
    else current ← next only with probability  $e^{\Delta E/T}$ 
```

Properties of simulated annealing search

- One can prove: If T decreases slowly enough, then simulated annealing search will find a global optimum with probability approaching 1
- Widely used in VLSI layout, airline scheduling, etc


Local beam search

- Keep track of k states rather than just one
- Start with k randomly generated states
- At each iteration, all the successors of all k states are generated
- If any one is a goal state, stop; else select the k best successors from the complete list and repeat.

Genetic algorithms

- A successor state is generated by combining two parent states
- Start with k randomly generated states (**population**)
- A state is represented as a string over a finite alphabet (often a string of 0s and 1s)
- Evaluation function (**fitness function**). Higher values for better states
- Produce the next generation of states by selection, crossover, and mutation

Genetic algorithms



- Fitness function: number of non-attacking pairs of queens (min = 0, max = $8 \times 7/2 = 28$)
- $24/(24+23+20+11) = 31\%$
- $23/(24+23+20+11) = 29\%$ etc

Genetic algorithms

