0. Get a canvas

Two cards make a canvas and paint it. `createCanvas` takes two numbers: the width and the height, in pixels. `background` takes one colour card.

Everything in setup goes in a column under the `define setup` card.

Lay the cards like this

See the virtual cards on the table

> **You should see:** a blue square in the canvas space.

Try these

- Make the canvas a different shape. Try `num 500` `num 200`, then `num 200` `num 500`. Which of the two numbers is the width?
- Swap the `mediumblue` card for a different colour card.
- Take the `background` row off the table and watch the canvas. Put it back.

What just happened

A card like `createCanvas` **calls a function**: it runs a named piece of behaviour that somebody else wrote. The cards to its right are its **arguments**, the information the function needs to do its job.

1. Put something on it

rect draws a rectangle. It takes four numbers, and the order they sit in tells the function which is which: `rect x y width height`.

x is how far across from the left edge. **y** is how far **down** from the top edge: a bigger y is lower, not higher. The x and y are the rectangle's **top-left corner**, not its middle.

Lay the cards like this

See the virtual cards on the table

> **You should see:** a small white rectangle, below and to the right of the middle.

Try these

- Change the first two numbers of rect to num 0 num 0. Where does it go?
- Change them to num 250 num 250. Is the rectangle in the middle? If not, why not?
- Build a **second** rect row under the first, with different numbers.

Before you turn the page

Make sure everyone at the table can put a finger on the card that decides how far **down** a rectangle sits.