

Project : P-01 Jessore

Area	923.32 SQM							
Sl. No.	Item	Material Type	Specification	Minimum Yield Strength	Quantity	Unit	Total Wt	Unit
Main Frame								
01	Column, Rafter, Main Beam including Base Plate, Joint Plate & Girt cleat (I/C 17% CP,BP)	Build-up Members, MS Plates, Hot Rolled Angles & Beams	ASTM A-572; Grade 50 or equivalent.	$F_y = 34.5 \text{ kN/cm}^2$	22,421.84	Kg	22,421.84	Kg
02	Joist (I/C 6% CP)	Build-up Members, MS Plates, Hot Rolled Angles & Beams	ASTM A-572; Grade 50 or equivalent.	$F_y = 34.5 \text{ kN/cm}^2$	648.31	Kg	648.31	Kg
03	Bracing & Strut member including connection plate, purlin cleat (I/C 12% CP)	Ms Pipe	ASTM A-36 or equivalent.	$F_y = 24.8 \text{ kN/cm}^2$	4,680.90	Kg	4,680.90	Kg
04	Anchor Bolt	30mm & 24 mm	ASTM A-36 or equivalent.	$F_u = 40.0 \text{ kN/cm}^2$	556.08	Kg	556.08	Kg
05	Purlin & Girt	200Z18& 200Z15	ASTM A-572; Grade 50 or equivalent.	$F_y = 34.5 \text{ kN/cm}^2$	8,175.00	Kg	8,175.00	Kg
06	Cable Bracing	16mm dia	ASTM A-572; Grade 50 or equivalent.	$F_y = 34.5 \text{ kN/cm}^2$	317.00	RM	634.00	Kg
07	High Strenth Nut Bolt	Hot Dip Galvanized	ASTM A-325M Type 1 or equivalent	$F_u = 83 \text{ kN/cm}^2$	628.71	Kg	628.71	Kg
8	Flange Brace	50x50x4	ASTM A-36 or equivalent.	$F_u = 40.0 \text{ kN/cm}^2$	1,163.00	Kg	1,163.00	Kg
9	Sag Rod	12 mm	ASTM A-36 or equivalent.	$F_y = 24.8 \text{ kN/cm}^2$	469.00	Kg	469.00	Kg
10	Shear Stud	16*90 mm	ASTM A-36 or equivalent.	$F_y = 24.8 \text{ kN/cm}^2$	125.00	Kg	237.50	Kg
Sheeting								Kg
11	Roof Sheet	.5 mm Thick			1,007.00	Sqm	4,823.53	Kg
12	Wall Sheet	.5 mm Thick			970.00	Sqm	4,646.30	Kg
13	Decking Sheet	.7 mm Thick			45.96	Sqm	220.15	Kg
Trims								Kg
14	Ridge Panel	.5 mm Thick (Profile Width 650 mm)			41.91	RM	107.29	Kg
15	Eave Gutter	.5 mm Thick (Profile Width 650 mm)			83.85	RM	362.23	Kg
16	Eave Trim	.5 mm Thick (Profile Width 450 mm)			83.85	RM	148.41	Kg
17	Gable Trim	.5 mm Thick (Profile Width 520 mm)			56.45	RM	115.72	Kg
18	Gable Angle	75x75x1.5			56.45	RM	99.92	Kg
19	Drip Trim	.5 mm Thick (Profile Width 450mm)			137.48	RM	243.34	Kg
20	Corner Trim	.5 mm Thick (Profile Width 450mm)			31.03	RM	54.93	Kg
21	Metal Down Pipe	.5 mm Thick (Profile Width 600 mm)			161.07	RM	380.13	Kg
22	Sheeting Screw				20,111.86	pcs	201.12	kg
Stair								
23	1 Nos Steel Stair				2,200.00	kg	2,200.00	kg
Canopy								
24	2 Nos Canopy				1,300.00	kg	1,300.00	kg
Accessories								
25	5 mm double Bubble insulation at roof				1,087.56	Sqm	1,087.56	SQM