Natural Language Processing and Large Language Models
NLP & LLMs – IASD App

Course 1

September 21, 2026

Shuyu Dong

Dauphine | PSL UNIVERSITÉ PARIS LAMSADE UMR 7243

Course Plan

- Machine learning for natural language processing (NLP)
- Attention and transformers
- Transformers and pre-training
- TP: GPT
- TP: GPT (Part 2), BERT
- Evaluation of LLMs

Evaluation:

- 2 homeworks
- 1 graded TP
- 1 project

References and sources:

- Course slides on large language models (LLMs, IASD) by Alexandre Allauzen and Florian Le Bronnec.
- Other references to be detailed.

Evaluation: registration form

Registration : NLP&LLMs course 2026-2027 (IASD App)



Plan du cours

- 1.1 – LLMs: applications, number of parameters
- 1.2 – Machine learning for natural language processing (NLP)
- 1.3 – TP: IMDB dataset, word embeddings

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works

3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention


4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch


Large language models: applications



Large language models: applications




Large language models: number of parameters




Source: https://hai.stanford.edu/ai-index/2025-ai-index-report

Large language models: number of parameters



Source: https://hai.stanford.edu/ai-index/2025-ai-index-report

Large language models: training compute



Source: https://hai.stanford.edu/ai-index/2025-ai-index-report

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works

3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch

Natural language

The goal of natural language (human language) is communication.

- For the speaker:
  - Intention: what is the message?
  - Generation: transform the message into a sequence.
  - Synthesis: output the sequence (speech, written text, signs, . . .)
- For the hearer:
  - Perception
  - Analysis
  - Incorporation

Natural language processing: processing of natural language by a computer.

Natural language processing (NLP): challenges

Implicity: natural language is implicit, which enables conciseness (ellipsis, anaphora, ...), but implicity entails potential **ambiguities**.

Why does this happen for natural language?

- Shared world knowledge
- Cognitive efficiency
- Social pragmatics

Having a unique linguistic expression for every possible conceptualization would make language overly complex and linguistic expressions unnecessarily long.
(R. Mooney)

Natural language processing (NLP): challenges

Why is natural language ambiguous?

- Lexical / word-level reasons: synonymes (e.g., bank, plant, . . .)
- Structural ambiguity (syntax):
  e.g., *"I saw the man on the hill with a telescope."*
  (From the course of R. Mooney)
- Referential ambiguity:
  e.g., *"Amy told Anna that she was late."*
- Context dependence:
  e.g., *"It's over there."*

This is hard for machines and for AI:

- No shared knowledge/experience (or lack of shared knowledge for AIs)
- No physical grounding
- No social intuition

NLP is a starting point for machines to understand natural language.

Machine learning for NLP

Model NLP tasks as machine learning problems:

- Text classification (our focus today)

$$X = (w_1, w_2, \ldots, w_L) \rightarrow y(\text{class label})$$

- Word tagging

$$X = (w_1, w_2, \ldots, w_L) \rightarrow (y_1, y_2, \ldots, y_L)$$

Text classification

A supervised learning problem:

Training data:

	review	sentiment
0	One of the other reviewers has mentioned that ...	positive
1	A wonderful little production. The...	positive
2	I thought this was a wonderful way to spend ti...	positive
3	Basically there's a family where a little boy ...	negative
4	Petter Mattei's "Love in the Time of Money" is...	positive

Test data:

"My wonderful friend took me to see this movie for our anniversary, it was terrible."

→ negative or positive?

Questions:

- How to represent the input text?
  Unlike images, sounds or other numerical signals, natural language **does not** have straightforward representations in a vector space.
- How to perform classification?

On Colab:

- Tokenization
- Vectorization

Natural Language Processing and Large Language Models
NLP & LLMs – IASD App

Course 2

28 September, 2026

Shuyu Dong

Dauphine | PSL UNIVERSITÉ PARIS LAMSADE UMR 7243

Plan du cours

- 2.1 – Word embeddings for text classification
- 2.2 – Word2vec
- 2.3 – TP: Word embeddings for text classification (IMDB dataset)

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works

3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch

Text classification using word counts

Train:

- Build document-term matrix $C \in \mathbb{R}^{n \times V}$ from training texts:

	w_1	w_2	$\dots$	w_V
t_1	C_{11}	C_{12}		C_{1V}
t_2	C_{21}	C_{22}		C_{2V}
$\vdots$				
t_n	C_{n1}	C_{n2}		C_{nV}

V: vocabulary size
n: number of documents (e.g., reviews)

- Consider word count by class $S = {W_y}^{\mathrm{T}} C \in \mathbb{R}^{2 \times V}$, where W_y is the class indicator matrix:

$${W_y}^{\mathrm{T}} = \left(\begin{array}{c|cccc} & t_1 & t_2 & \dots & t_n \\ \hline \text{Class “1”} & 0 & 1 & \dots & 1 \\ \text{Class “2”} & 1 & 0 & \dots & 0 \end{array} \right) \Rightarrow \quad S = \left(\begin{array}{c|ccc} & \dots & w_j & \dots \\ \hline \text{Class “1”} & \dots & \sum_{k \text{ s.t. } t_k \in \text{Class “1”}} C_{kj} & \dots \\ \text{Class “2”} & \dots & \sum_{k \text{ s.t. } t_k \in \text{Class “2”}} C_{kj} & \dots \end{array} \right)$$

Test:

- For a test document t: compute the score of “t in class 1 (resp. 2)”

$$s(1,t) = \sum_{w \in t} S(1,w), \quad s(2,t) = \sum_{w \in t} S(2,w).$$

Finally, get prediction value $f(t) = \arg\max_i (s(i,t))$.

Text classification using word embeddings

Supervised learning framework:

- Random variables: $(T, y) \in \mathcal{T} \times \mathcal{Y}$
  - $\mathcal{T}$: space of texts, each text is a sequence of words.
  - Note: the length (number of words) of any text in $\mathcal{T}$ is bounded by a constant L.
    (Related questions: padding, TP1)
  - $\mathcal{Y} \simeq \{1, \ldots, K\}$: set of labels
- Training data: $\mathcal{D} = \{T_i, y_i\}_{i=1,\ldots,n}$ with $T_i \in \mathcal{T}$ and $y_i \in \mathcal{Y}$.

Text classification using word embeddings

Supervised learning framework:

- Random variables: $(T, y) \in \mathcal{T} \times \mathcal{Y}$
  - $\mathcal{T}$: space of texts, each text is a sequence of words.
  - Note: the length (number of words) of any text in $\mathcal{T}$ is bounded by a constant L.
    (Related questions: padding, TP1)
  - $\mathcal{Y} \simeq \{1, \ldots, K\}$: set of labels
- Training data: $\mathcal{D} = \{T_i, y_i\}_{i=1,\ldots,n}$ with $T_i \in \mathcal{T}$ and $y_i \in \mathcal{Y}$.
- Model $P(y|T)$ with a set of parameters θ:

$$P(y|T) = p_\theta(y, T).$$

Text classification using word embeddings

Supervised learning framework:

- Random variables: $(T, y) \in \mathcal{T} \times \mathcal{Y}$
  - $\mathcal{T}$: space of texts, each text is a sequence of words.
  - Note: the length (number of words) of any text in $\mathcal{T}$ is bounded by a constant L.
    (Related questions: padding, TP1)
  - $\mathcal{Y} \simeq \{1, \ldots, K\}$: set of labels
- Training data: $\mathcal{D} = \{T_i, y_i\}_{i=1,\ldots,n}$ with $T_i \in \mathcal{T}$ and $y_i \in \mathcal{Y}$.
- Model $P(y|T)$ with a set of parameters θ:

$$P(y|T) = p_\theta(y, T).$$

- Determine the prediction function $f_\theta : \mathcal{T} \to \mathcal{Y}$: $\hat{y} = f_\theta(T)$.
  - Example: $f_\theta(T) = \underset{k \in \{1,\ldots,K\}}{\arg\max}\ p_\theta(k, T)$.

Text classification using word embeddings

Supervised learning framework:

- Random variables: $(T, y) \in \mathcal{T} \times \mathcal{Y}$
  - $\mathcal{T}$: space of texts, each text is a sequence of words.
  - Note: the length (number of words) of any text in $\mathcal{T}$ is bounded by a constant L.
    (Related questions: padding, TP1)
  - $\mathcal{Y} \simeq \{1, \ldots, K\}$: set of labels
- Training data: $\mathcal{D} = \{T_i, y_i\}_{i=1,\ldots,n}$ with $T_i \in \mathcal{T}$ and $y_i \in \mathcal{Y}$.
- Model $P(y|T)$ with a set of parameters θ:

$$P(y|T) = p_\theta(y, T).$$

- Determine the prediction function $f_\theta : \mathcal{T} \to \mathcal{Y}$: $\hat{y} = f_\theta(T)$.
  - Example: $f_\theta(T) = \underset{k \in \{1,\ldots,K\}}{\arg\max}\ p_\theta(k, T)$.

Questions:

- How to define a parametric function $p_\theta(y, T)$ on $\mathcal{Y} \times \mathcal{T}$ to model $P(y|T)$?

Text classification using word embeddings

Supervised learning framework:

- Random variables: $(T, y) \in \mathcal{T} \times \mathcal{Y}$
  - $\mathcal{T}$: space of texts, each text is a sequence of words.
  - Note: the length (number of words) of any text in $\mathcal{T}$ is bounded by a constant L.
    (Related questions: padding, TP1)
  - $\mathcal{Y} \simeq \{1, \ldots, K\}$: set of labels
- Training data: $\mathcal{D} = \{T_i, y_i\}_{i=1,\ldots,n}$ with $T_i \in \mathcal{T}$ and $y_i \in \mathcal{Y}$.
- Model $P(y|T)$ with a set of parameters θ:

$$P(y|T) = p_\theta(y, T).$$

- Determine the prediction function $f_\theta : \mathcal{T} \to \mathcal{Y}$: $\hat{y} = f_\theta(T)$.
  - Example: $f_\theta(T) = \underset{k \in \{1,\ldots,K\}}{\arg\max}\, p_\theta(k, T)$.

Questions:

- How to define a parametric function $p_\theta(y, T)$ on $\mathcal{Y} \times \mathcal{T}$ to model $P(y|T)$?
  - Remark: a vector representation of T is needed to interact with parameters θ.

Text classification using word embeddings

Supervised learning framework:

- Random variables: $(T, y) \in \mathcal{T} \times \mathcal{Y}$
  - $\mathcal{T}$: space of texts, each text is a sequence of words.
  - Note: the length (number of words) of any text in $\mathcal{T}$ is bounded by a constant L.
    (Related questions: padding, TP1)
  - $\mathcal{Y} \simeq \{1, \ldots, K\}$: set of labels
- Training data: $\mathcal{D} = \{T_i, y_i\}_{i=1,\ldots,n}$ with $T_i \in \mathcal{T}$ and $y_i \in \mathcal{Y}$.
- Model $P(y|T)$ with a set of parameters θ:

$$P(y|T) = p_\theta(y, T).$$

- Determine the prediction function $f_\theta : \mathcal{T} \to \mathcal{Y}$: $\hat{y} = f_\theta(T)$.
  - Example: $f_\theta(T) = \underset{k \in \{1,\ldots,K\}}{\arg\max}\, p_\theta(k, T)$.

Questions:

- How to define a parametric function $p_\theta(y, T)$ on $\mathcal{Y} \times \mathcal{T}$ to model $P(y|T)$?
  - Remark: a vector representation of T is needed to interact with parameters θ.
  - Preliminary question: *How to map T into a vector space?* (word embedding)

Text classification using word embeddings

Supervised learning framework:

- Random variables: $(T, y) \in \mathcal{T} \times \mathcal{Y}$
  - $\mathcal{T}$: space of texts, each text is a sequence of words.
  - Note: the length (number of words) of any text in $\mathcal{T}$ is bounded by a constant L.
    (Related questions: padding, TP1)
  - $\mathcal{Y} \simeq \{1, \ldots, K\}$: set of labels
- Training data: $\mathcal{D} = \{T_i, y_i\}_{i=1,\ldots,n}$ with $T_i \in \mathcal{T}$ and $y_i \in \mathcal{Y}$.
- Model $P(y|T)$ with a set of parameters θ:

$$P(y|T) = p_\theta(y, T).$$

- Determine the prediction function $f_\theta : \mathcal{T} \to \mathcal{Y}$: $\hat{y} = f_\theta(T)$.
  - Example: $f_\theta(T) = \underset{k \in \{1,\ldots,K\}}{\arg\max}\, p_\theta(k, T)$.


Questions:

- How to define a parametric function $p_\theta(y, T)$ on $\mathcal{Y} \times \mathcal{T}$ to model $P(y|T)$?
  - Remark: a vector representation of T is needed to interact with parameters θ.
  - Preliminary question: *How to map T into a vector space?* (word embedding)
- How to define the training objective?
  - Loss function: $L(\hat{y}, y)$
  - Empirical risk: $R(\theta; \mathcal{D}) = \sum_{i=1}^{n} L(\hat{y}_i, y_i)$.

Text classification: word embeddings

- **Word embedding matrix** R. For each text $T \in \mathcal{T}$, build $X \in \mathbb{R}^{L \times d}$: $X_{i,:} \leftarrow$ look up $w_i \in \mathcal{T}$ in the embedding matrix $R \in \mathbb{R}^{V \times d}$.
- **Text embedding:** aggregation by mean pooling over the text's words

$$\tilde{x}^{\mathrm{T}} \leftarrow \frac{1}{L} \sum_{i=1}^{L} X_{i,:} = \frac{1}{L} \mathbf{1}^{\mathrm{T}} X$$



Text classification: word embeddings


- **Word embedding matrix** R. For each text $T \in \mathcal{T}$, build $X \in \mathbb{R}^{L \times d}$: $X_{i,:} \leftarrow$ look up $w_i \in \mathcal{T}$ in the embedding matrix $R \in \mathbb{R}^{V \times d}$.
- **Text embedding:** aggregation by mean pooling over the text's words

$$\tilde{x}^{\mathrm{T}} \leftarrow \frac{1}{L} \sum_{i=1}^{L} X_{i,:} = \frac{1}{L} \mathbf{1}^{\mathrm{T}} X$$

- **Prediction function:** $\hat{y} = \sigma(W^{\mathrm{T}} \tilde{x})$ where $\sigma(\cdot)$ is the sigmoid or the softmax function:

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

$$\sigma((z_1, \ldots, z_K)) = \left(\frac{e^{z_1}}{\sum_i e^{z_i}}, \ldots, \frac{e^{z_K}}{\sum_i e^{z_i}}\right).$$



Text classification: word embeddings


- **Word embedding matrix** R. For each text $T \in \mathcal{T}$, build $X \in \mathbb{R}^{L \times d}$:
  $X_{i,:} \leftarrow$ look up $w_i \in \mathcal{T}$ in the embedding matrix $R \in \mathbb{R}^{V \times d}$.
- **Text embedding:** aggregation by mean pooling over the text's words

$$\tilde{x}^{\mathrm{T}} \leftarrow \frac{1}{L} \sum_{i=1}^{L} X_{i,:} = \frac{1}{L} \mathbf{1}^{\mathrm{T}} X$$

- **Prediction function:** $\hat{y} = \sigma(W^{\mathrm{T}} \tilde{x})$ where $\sigma(\cdot)$ is the sigmoid or the softmax function:

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

$$\sigma((z_1, \ldots, z_K)) = \left(\frac{e^{z_1}}{\sum_i e^{z_i}}, \ldots, \frac{e^{z_K}}{\sum_i e^{z_i}}\right).$$



Training objective:

- Model parameters: $\theta = (R, W)$.
- Empirical risk (multiclass case $K \geq 3$):
  $L(\theta) = -\sum_{i=1}^{N_{\text{train}}} \sum_{k=1}^{K} y_k^{(i)} \log(\hat{y}_k^{(i)})$, for $\hat{y} = \sigma(W^{\mathrm{T}} \tilde{x})$ with softmax.


Text classification: word embeddings

- **Word embedding matrix** R**.** For each text $T \in \mathcal{T}$, build $X \in \mathbb{R}^{L \times d}$: $X_{i,:} \leftarrow$ look up $w_i \in \mathcal{T}$ in the embedding matrix $R \in \mathbb{R}^{V \times d}$.
- **Text embedding:** aggregation by mean pooling over the text's words

$$\tilde{x}^{\mathrm{T}} \leftarrow \frac{1}{L} \sum_{i=1}^{L} X_{i,:} = \frac{1}{L} \mathbf{1}^{\mathrm{T}} X$$

- **Prediction function:** $\hat{y} = \sigma(W^{\mathrm{T}} \tilde{x})$ where $\sigma(\cdot)$ is the sigmoid or the softmax function:

$$\sigma(z) = \frac{1}{1 + e^{-z}}, \quad \sigma((z_1, \ldots, z_K)) = \left(\frac{e^{z_1}}{\sum_i e^{z_i}}, \ldots, \frac{e^{z_K}}{\sum_i e^{z_i}}\right).$$



Text lengths: handle different text lengths without truncation

- Build $X \in \mathbb{R}^{b \times L \times d}$ where L is the maximal length of the texts in the batch (of b samples).


Text classification: word embeddings

- **Word embedding matrix** R. For each text $T \in \mathcal{T}$, build $X \in \mathbb{R}^{L \times d}$: $X_{i,:} \leftarrow$ look up $w_i \in \mathcal{T}$ in the embedding matrix $R \in \mathbb{R}^{V \times d}$.
- **Text embedding:** aggregation by mean pooling over the text's words

$$\tilde{x}^{\mathrm{T}} \leftarrow \frac{1}{L} \sum_{i=1}^{L} X_{i,:} = \frac{1}{L} \mathbf{1}^{\mathrm{T}} X$$

- **Prediction function:** $\hat{y} = \sigma(W^{\mathrm{T}} \tilde{x})$ where $\sigma(\cdot)$ is the sigmoid or the softmax function:

$$\sigma(z) = \frac{1}{1 + e^{-z}}, \quad \sigma((z_1, \ldots, z_K)) = \left(\frac{e^{z_1}}{\sum_i e^{z_i}}, \ldots, \frac{e^{z_K}}{\sum_i e^{z_i}}\right).$$



Text lengths: handle different text lengths without truncation

- Build $X \in \mathbb{R}^{b \times L \times d}$ where L is the maximal length of the texts in the batch (of b samples).
- For texts shorter than the longest text: append padding values to fill up to length L


Text classification: word embeddings

- **Word embedding matrix** R. For each text $T \in \mathcal{T}$, build $X \in \mathbb{R}^{L \times d}$: $X_{i,:} \leftarrow$ look up $w_i \in \mathcal{T}$ in the embedding matrix $R \in \mathbb{R}^{V \times d}$.
- **Text embedding:** aggregation by mean pooling over the text's words

$$\tilde{x}^{\mathrm{T}} \leftarrow \frac{1}{L} \sum_{i=1}^{L} X_{i,:} = \frac{1}{L} \mathbf{1}^{\mathrm{T}} X$$

- **Prediction function:** $\hat{y} = \sigma(W^{\mathrm{T}} \tilde{x})$ where $\sigma(\cdot)$ is the sigmoid or the softmax function:

$$\sigma(z) = \frac{1}{1 + e^{-z}}, \quad \sigma((z_1, \ldots, z_K)) = \left(\frac{e^{z_1}}{\sum_i e^{z_i}}, \ldots, \frac{e^{z_K}}{\sum_i e^{z_i}}\right).$$



Text lengths: handle different text lengths without truncation

- Build $X \in \mathbb{R}^{b \times L \times d}$ where L is the maximal length of the texts in the batch (of b samples).
- For texts shorter than the longest text: append padding values to fill up to length L
- Update text embedding rule: for each sample $X \in \mathbb{R}^{L \times d}$, $\tilde{x} = \frac{1}{L_i} \sum_{i=1}^{L} X_{i,:}$ where L_i is the real length of text T_i.

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works

3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch


Word2vec: word embedding with contextualization

Word2vec (Mikolov et al., 2013a,b):

- Mikolov, T., Chen, K., Corrado, G., and Dean, J. (2013a). Efficient estimation of word representations in vector space. arXiv preprint arXiv:1301.3781.
- Mikolov, T., Sutskever, I., Chen, K., Corrado, G. S., and Dean, J. (2013b). Distributed representations of words and phrases and their compositionality. Advances in neural information processing systems, 26.

Word2vec: word embedding with contextualization

Context window:




Skip-gram model:

- A collection $\mathcal{T}$ of texts, each text is a sequence of words.
- Vocabulary: $\mathcal{V}$ of V words.
- Context window size: c

For each word w_j that is considered as a center word, we want to maximize the likelihood of the context words of w_j given w_j:

$$P(w_{j-c}, \ldots, w_{j-1}, w_{j+1}, \ldots, w_{j+c} | w_j).$$



Word2vec: contextualization by the skip-gram model


Goal: maximize $P(w_{j-c}, \ldots, w_{j-1}, w_{j+1}, \ldots, w_{j+c} | w_j)$.

- Embedding matrix $W \in \mathbb{R}^{V \times d}$ (to train)
- For each word w: encode w with an one-hot vector


$$x_w \in \mathbb{R}^V, (x_w)_i = \begin{cases} 1 & \text{if token id of w is } i \\ 0 & \text{otherwise} \end{cases}.$$

- Word embedding: $v_w = W^{\mathrm{T}} x_w$.

Context window:



Skip-gram model:



Word2vec: contextualization by the skip-gram model

Goal: maximize $P(w_{j-c}, \ldots, w_{j-1}, w_{j+1}, \ldots, w_{j+c} | w_j)$.

- Embedding matrix $W \in \mathbb{R}^{V \times d}$ (to train)
- For each word w: encode w with an one-hot vector


$$x_w \in \mathbb{R}^V, (x_w)_i = \begin{cases} 1 & \text{if token id of w is } i \\ 0 & \text{otherwise} \end{cases}.$$

- Word embedding: $v_w = W^{\mathrm{T}} x_w$.
- For context words $w_{j+\ell}$ of word w_j, define $P(w_{j+\ell} | w_j)$ with softmax:


$$P(w_{j+\ell} | w_j) = \frac{\exp({v_{w_{j+\ell}}}^{\mathrm{T}} v_{w_j})}{\sum_{w \in \mathcal{V}} \exp({v_w}^{\mathrm{T}} v_{w_j})}.$$

(based on the whole vocabulary)

Context window:



Skip-gram model:




Word2vec: contextualization by the skip-gram model

Goal: maximize $P(w_{j-c}, \ldots, w_{j-1}, w_{j+1}, \ldots, w_{j+c} | w_j)$.


- Word embedding: $v_w = W^{\mathrm{T}} x_w$.
- For context words $w_{j+\ell}$ of word w_j, define $P(w_{j+\ell}|w_j)$ with softmax:

$$P(w_{j+\ell}|w_j) = \frac{\exp({v_{w_{j+\ell}}}^{\mathrm{T}} v_{w_j})}{\sum_{w \in \mathcal{V}} \exp({v_w}^{\mathrm{T}} v_{w_j})} \quad \text{(whole vocab.)}$$

Context window



Skip-gram model:



Word2vec: contextualization by the skip-gram model

Goal: maximize $P(w_{j-c}, \ldots, w_{j-1}, w_{j+1}, \ldots, w_{j+c} | w_j)$.

- Word embedding: $v_w = W^{\mathrm{T}} x_w$.
- For context words $w_{j+\ell}$ of word w_j, define $P(w_{j+\ell}|w_j)$ with softmax:


$$P(w_{j+\ell}|w_j) = \frac{\exp({v_{w_{j+\ell}}}^{\mathrm{T}} v_{w_j})}{\sum_{w \in \mathcal{V}} \exp({v_w}^{\mathrm{T}} v_{w_j})} \quad \text{(whole vocab.)}$$

- $P(w_{j+\ell}|w_j) = \dfrac{\exp({v_{w_{j+\ell}}}^{\mathrm{T}} v_{w_j})}{\sum_{w \in \mathcal{N} \cup \mathcal{P}} \exp({v_w}^{\mathrm{T}} v_{w_j})}$ (negative sampling)


where

- $\mathcal{N}$ contains a number of words sampled randomly and independently of w_j.
- $\mathcal{P}$ contains the context words of w_j.

Context window



Skip-gram model:



Word2vec: contextualization by the skip-gram model

Goal: maximize $P(w_{j-c}, \ldots, w_{j-1}, w_{j+1}, \ldots, w_{j+c} | w_j)$.

- Word embedding: $v_w = W^{\mathrm{T}} x_w$.
- For context words $w_{j+\ell}$ of word w_j, define $P(w_{j+\ell}|w_j)$ with softmax:

$$P(w_{j+\ell}|w_j) = \frac{\exp({v_{w_{j+\ell}}}^{\mathrm{T}} v_{w_j})}{\sum_{w \in \mathcal{V}} \exp({v_w}^{\mathrm{T}} v_{w_j})} \quad \text{(whole vocab.)}$$

- $P(w_{j+\ell}|w_j) = \dfrac{\exp({v_{w_{j+\ell}}}^{\mathrm{T}} v_{w_j})}{\sum_{w \in \mathcal{N} \cup \mathcal{P}} \exp({v_w}^{\mathrm{T}} v_{w_j})}$ (negative sampling)


where

- $\mathcal{N}$ contains a number of words sampled randomly and independently of w_j.
- $\mathcal{P}$ contains the context words of w_j.


- Maximize the log-likelihood over training data $\mathcal{T}$:

$$\mathcal{L}(W) = \sum_{T \in \mathcal{T}, w_j \in T} \sum_{-c \le \ell \le c, \ell \neq 0} \log P(w_{j+\ell}|w_j).$$

Context window



Skip-gram model:



Word2vec: contextualization by the skip-gram model

(Mikolov et al., 2013b):




Figure 2: Two-dimensional PCA projection of the 1000-dimensional Skip-gram vectors of countries and their capital cities. The figure illustrates ability of the model to automatically organize concepts and learn implicitly the relationships between them, as during the training we did not provide any supervised information about what a capital city means.

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works

3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch

Natural Language Processing and Large Language Models
NLP & LLMs – IASD App

Course 3

November 2, 2026

Shuyu Dong

Dauphine | PSL UNIVERSITÉ PARIS LAMSADE UMR 7243

Plan du cours

- 3.1 – Sequence processing: Transformer and a few previous works
- 3.2 – Sequence processing: the attention mechanism
- 3.3 – TP: agnews, TP: attention

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works

3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch

Sequence processing

Tasks:

- Prediction of the next word: *"My name" [?] → "My name [is]"*
- Prediction of masked words: *"His [?] is Bert." → "His [name] is Bert."*

Sequence processing

Tasks:

- Prediction of the next word: *"My name" [?] → "My name [is]"*
- Prediction of masked words: *"His [?] is Bert." → "His [name] is Bert."*

Recurrent neural networks (RNNs)

- Markov chain model: the next word's embedding depends on the previous one

$$(h_1, y_1) = (0, 0), \quad (h_i, y_i) = F_\theta(h_{i-1}, x_i),$$

such as

$$h_i = \tanh(W_h h_{i-1} + W_x x_i),$$
$$y_i = W_y h_i.$$

Sequence processing

Tasks:

- Prediction of the next word: *"My name" [?] → "My name [is]"*
- Prediction of masked words: *"His [?] is Bert." → "His [name] is Bert."*

Recurrent neural networks (RNNs)

- Markov chain model: the next word's embedding depends on the previous one

$$(h_1, y_1) = (0, 0), \quad (h_i, y_i) = F_\theta(h_{i-1}, x_i),$$

such as

$$h_i = \tanh(W_h h_{i-1} + W_x x_i),$$
$$y_i = W_y h_i.$$

- **Advantages:** receptive field is infinitely large.
- **Limitation:**
  - Slow to train.
  - Decay of signal strength along the chain, hard to learn long-range dependencies.

Sequence processing

Tasks:

- Prediction of the next word: *"My name" [?]* $\rightarrow$ *"My name [is]"*
- Prediction of masked words: *"His [?] is Bert."* $\rightarrow$ *"His [name] is Bert."*

1D convolutional networks

- Transform input embeddings via a weighted sum (or weighted average) of the context embeddings:

$$\begin{aligned} y_i &= F_w(x_{i-k}, \ldots, x_i, \ldots, x_{i+k}) \\ &= \sum_{-k \leq \ell \leq k} w_\ell x_{i+\ell}. \end{aligned}$$

  - Window/kernel size: $2k + 1$.

Sequence processing

Tasks:

- Prediction of the next word: *"My name" [?] → "My name [is]"*
- Prediction of masked words: *"His [?] is Bert." → "His [name] is Bert."*

1D convolutional networks

- Transform input embeddings via a weighted sum (or weighted average) of the context embeddings:

$$\begin{aligned} y_i &= F_w(x_{i-k}, \ldots, x_i, \ldots, x_{i+k}) \\ &= \sum_{-k \le \ell \le k} w_\ell x_{i+\ell}. \end{aligned}$$

  - Window/kernel size: $2k + 1$.
- **Advantages:** fast/parallelizable, work well with images (CNNs, with 2D convolution)
- **Limitation:**
  - Receptive field has a fixed window size $\rightsquigarrow$ loses capacity in capturing long-range contexts.

Transformers


(Vaswani et al., 2017) Attention is all you need.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., & Polosukhin, I. (2017). Attention is all you need. Advances in neural information processing systems, 30.

Transformers

After (Vaswani et al., 2017) "Attention is all you need":

- **Transformer models:**
  - GPT-Generative Pretrained Transformer (Radford et al., 2018) (OpenAI)




(Radford et al., 2018), Figure 1.

Transformers

After (Vaswani et al., 2017) "Attention is all you need":

- **Transformer models:**
  - GPT-Generative Pretrained Transformer (Radford et al., 2018) (OpenAI)
  - BERT-Bidirectional Encoder Representations from Transformers (Devlin et al., 2019) (Google)



Transformers

After (Vaswani et al., 2017) "Attention is all you need":

- **Transformer models:**
  - GPT-Generative Pretrained Transformer (Radford et al., 2018) (OpenAI)
  - BERT-Bidirectional Encoder Representations from Transformers (Devlin et al., 2019) (Google)

  The Transformer models overtook more traditional models (RNNs, CNNs), first in language translation, and then in almost all other NLP tasks.
- **Self-supervised learning**: learning based on texts only, no need of labels.

Transformers

After (Vaswani et al., 2017) "Attention is all you need":


- **Transformer models:**
  - GPT-Generative Pretrained Transformer (Radford et al., 2018) (OpenAI)
  - BERT-Bidirectional Encoder Representations from Transformers (Devlin et al., 2019) (Google)

  The Transformer models overtook more traditional models (RNNs, CNNs), first in language translation, and then in almost all other NLP tasks.
- **Self-supervised learning**: learning based on texts only, no need of labels.

Attention layer:

- Allow each word (embedding) to **selectively** attend to other words in the sequence.
- Word representations with separate different roles: *query, key, value*.

The transformer model



Feed forward:

- $Y = W^{(2)}\phi_{\text{ReLU}}(W^{(1)}Z + b^{(1)}) + b^{(2)}$

↑

Feed forward input: Skip-connection(x) + Attention(x)

- $Z = \text{LayerNorm}(x_i + \text{Attention}(x_1, \ldots, x_L))$

where the layer normalization is $\text{LayerNorm}(x) = \frac{x-\mu}{\sqrt{\sigma^2}}$ with

$$\mu = \frac{1}{d}\sum_{i=j}^{d} x_j, \quad \sigma^2 = \frac{1}{d}\sum_{j=1}^{d}(x_j - \mu)^2.$$

↑

Self-attention layer:

- (to study today)

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works


3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch


From 1D convolution to self-attention



1D convolution:


- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Not cool: fixed-size receptive field

Wanted effect:



Self-attention:

From 1D convolution to self-attention



1D convolution:


- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Not cool: fixed-size receptive field

Self-attention: we want to build something like


$$y_i = \sum_{j=1}^{L} s(x_i, x_j) x_j.$$

- Good: $x_i \leftarrow$ Weighted sum of the input

Wanted effect:



From 1D convolution to self-attention



1D convolution:


- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Not cool: fixed-size receptive field

Self-attention: we want to build something like


$$y_i = \sum_{j=1}^{L} s(x_i, x_j) x_j.$$

- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words

Wanted effect:



From 1D convolution to self-attention



1D convolution:


- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Not cool: fixed-size receptive field

Self-attention: we want to build something like


$$y_i = \sum_{j=1}^{L} s(x_i, x_j) x_j.$$

- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Good: large enough receptive field

Wanted effect:



From 1D convolution to self-attention



1D convolution:


- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Not cool: fixed-size receptive field

Self-attention: we want to build something like

$$y_i = \sum_{j=1}^{L} s(x_i, x_j) x_j.$$


- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Good: large enough receptive field
- Good: adjust weights dynamically based on input x_i!

Wanted effect:



Note: the transformation depends on the context of the sequence
$\rightsquigarrow$ more dynamic word embedding than Word2vec, which produces static embeddings.

From 1D convolution to self-attention




Self-attention: we want to build something like


$$y_i = \sum_{j=1}^{L} s(x_i, x_j) x_j.$$

- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Good: large enough receptive field
- Good: adjust weights dynamically based on input x_i!

Wanted effect:



From 1D convolution to self-attention




Self-attention: we want to build something like

$$y_i = \sum_{j=1}^{L} s(x_i, x_j) x_j.$$


- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Good: large enough receptive field
- Good: adjust weights dynamically based on input x_i!

Question: what kind of function $s(\cdot, \cdot)$ to achieve this effect?

Wanted effect:



From 1D convolution to self-attention




Self-attention: we want to build something like

$$y_i = \sum_{j=1}^{L} s(x_i, x_j) x_j.$$

- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Good: large enough receptive field
- Good: adjust weights dynamically based on input x_i!

Wanted effect:




Question: what kind of function $s(\cdot, \cdot)$ to achieve this effect?

Idea: similarity matrix with scalar products between word embeddings

$$x_i{}^{\mathrm{T}} x_j \rightsquigarrow s(x_i, x_j)$$

From 1D convolution to self-attention




Self-attention: we want to build something like

$$y_i = \sum_{j=1}^{L} s(x_i, x_j) x_j.$$

- Good: $x_i \leftarrow$ Weighted sum of the input
- Good: Explicit dependency on the context words
- Good: large enough receptive field
- Good: adjust weights dynamically based on input x_i!

Wanted effect:




Question: what kind of function $s(\cdot, \cdot)$ to achieve this effect?

Idea: similarity matrix with scalar products between word embeddings

$$x_i{}^{\mathrm{T}} x_j \rightsquigarrow s(x_i, x_j)$$

- Embeddings such that similar words should have similar vectors.


The QKV self-attention




Source: https://learnopencv.com/attention-mechanism-in-transformer-neural-networks/

Self-attention

- $y_i = \sum_{j=1}^{L} s(x_i, x_j)\mathrm{vec}(x_j)$.



Self-attention




- $y_i = \sum_{j=1}^{L} s(x_i, x_j)\text{vec}(x_j)$.
- Mappings for **queries, keys,** and **values**: 3 linear applications Q, K, V
- Similarities:

$$s_{ij} = \langle \text{vec}_{\text{query}}(x_i), \text{vec}_{\text{key}}(x_j) \rangle$$

Note: this is not symmetric in general

Self-attention



- $y_i = \sum_{j=1}^{L} s(x_i, x_j)\text{vec}(x_j)$.
- Mappings for **queries, keys,** and **values**: 3 linear applications Q, K, V
- Similarities:


$$s_{ij} = \langle \text{vec}_{\text{query}}(x_i), \text{vec}_{\text{key}}(x_j) \rangle$$

Note: this is not symmetric in general

- Vectors of queries, keys, and values:

$$q_i = Qx_i \in \mathbb{R}^d, \quad 1 \le i \le L$$
$$k_j = Kx_j \in \mathbb{R}^d, \quad 1 \le j \le L$$
$$v_j = Vx_j \in \mathbb{R}^d, \quad 1 \le j \le L.$$

Self-attention



- $y_i = \sum_{j=1}^{L} s(x_i, x_j)\mathrm{vec}(x_j)$.
- Mappings for **queries, keys,** and **values**: 3 linear applications Q, K, V
- Similarities:

$$s_{ij} = \langle \mathrm{vec}_{\mathrm{query}}(x_i), \mathrm{vec}_{\mathrm{key}}(x_j) \rangle$$


Note: this is not symmetric in general

- Vectors of queries, keys, and values:

$$q_i = Qx_i \in \mathbb{R}^d, \quad 1 \le i \le L$$
$$k_j = Kx_j \in \mathbb{R}^d, \quad 1 \le j \le L$$
$$v_j = Vx_j \in \mathbb{R}^d, \quad 1 \le j \le L.$$

- $s_{ij} = \frac{q_i{}^{\mathrm{T}} k_j}{\sqrt{d}} = x_i{}^{\mathrm{T}} \left(\frac{Q^{\mathrm{T}} K}{\sqrt{d}} \right) x_j$

Self-attention



Note: self-attention has L queries $(q_i)_{i=1,\dots,L}$, which are the words of the sequence itself.

- $y_i = \sum_{j=1}^{L} s(x_i, x_j)\mathrm{vec}(x_j)$.
- Mappings for **queries, keys,** and **values**: 3 linear applications Q, K, V
- Similarities:

$$s_{ij} = \langle \mathrm{vec}_{\mathrm{query}}(x_i), \mathrm{vec}_{\mathrm{key}}(x_j) \rangle$$

Note: this is not symmetric in general

- Vectors of queries, keys, and values:

$$q_i = Qx_i \in \mathbb{R}^d, \quad 1 \le i \le L$$
$$k_j = Kx_j \in \mathbb{R}^d, \quad 1 \le j \le L$$
$$v_j = Vx_j \in \mathbb{R}^d, \quad 1 \le j \le L.$$

- $s_{ij} = \frac{q_i{}^{\mathrm{T}} k_j}{\sqrt{d}} = x_i{}^{\mathrm{T}} \left(\frac{Q^{\mathrm{T}} K}{\sqrt{d}}\right) x_j$
- $\alpha_{ij} = \mathrm{softmax}(s_{ij})$
- $y_i = \sum_{j=1}^{L} \alpha_{ij} v_j$

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works

3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch

Natural Language Processing and Large Language Models
NLP & LLMs – IASD App

Course 4

November 9, 2026

Shuyu Dong

Dauphine | PSL UNIVERSITÉ PARIS LAMSADE UMR 7243

Plan du cours

- 4.1 – Attention, Transformer, GPT
- 4.2 – TP: GPT from scratch

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works


3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch

The transformer model



Feed forward:

- $Y = W^{(2)}\phi_{\text{ReLU}}(W^{(1)}Z + b^{(1)}) + b^{(2)}$

↑

Feed forward input: Skip-connection(x) + Attention(x)

- $Z = \text{LayerNorm}(x_i + \text{Attention}(x_1, \ldots, x_L))$

where the layer normalization is $\text{LayerNorm}(x) = \frac{x-\mu}{\sqrt{\sigma^2}}$ with

$$\mu = \frac{1}{d}\sum_{i=j}^{d} x_j, \quad \sigma^2 = \frac{1}{d}\sum_{j=1}^{d}(x_j - \mu)^2.$$

↑


Self-attention layer:

- (Cours 3)

GPT for prediction of next tokens

Token	Logits (Top score)	Prediction	Loss
[BOS]	–	The	$-\log(0.6)$
The	{movie: 0.8, football: 0.6, ...}	movie	$-\log(0.8)$
movie	{was: 0.6, is: 0.5, ...}	was	$-\log(0.6)$
was	{nice: 0.6, aweful: 0.59, ...}	nice	$-\log(0.59)$
aweful	{[END]: 0.9, but: 0.2, ...}	[END]	$-\log(0.9)$

GPT for prediction of next tokens




Remark

Unlike text classification, the input text for training our GPT must be understood as a sequence (with a strictly increasing order). Otherwise, the model training will fail, as the next token can predict itself perfectly, if it is known to the model.

- Position embedding in addition to input words embedding.
- Position embedding map $P \in \mathbb{R}^{L \times V}$: $x_i \mapsto Px_i$ where x_i is the token id of the word w_i.

GPT for prediction of next tokens: causal mask



Causal mask:
For x_i, the **causal mask** must be applied to tokens x_j for $j \geq i$.
For $S = \frac{Q^{\mathrm{T}}K}{\sqrt{d}}$:

$$S \leftarrow S + M \quad \text{where } M_{ij} = \begin{cases} -\infty & \text{if } j \geq i \\ 0 & j < i \end{cases} \quad \text{for all } i.$$


Note that $\exp(-\infty) = 0$.
Therefore:

$$\text{Attention}(Q, K, V) = \text{softmax}(\frac{Q^{\mathrm{T}}K}{\sqrt{d}} + M)V,$$

so that each token pays attention only to precedent tokens in the sequence.

```
1    mask = torch.triu(  )
```

GPT for prediction of next tokens: causal mask



Causal mask:

Attention$(Q, K, V) = \text{softmax}(\frac{Q^{\mathrm{T}}K}{\sqrt{d}} + M)V$, where $M_{ij} = \begin{cases} -\infty & \text{if } j \geq i \\ 0 & j < i \end{cases}$ for all i.

Why are position embeddings still needed?


Without position embeddings, the attention $\alpha_{ij} = \sum_j \text{softmax}(\frac{q_i^{\mathrm{T}} k_j}{\sqrt{d}} + M_{ij})v_j$ would still be a function of the (unordered) set $\{w_1, \ldots, w_{i-1}\}$, instead of the sequence $(w_1, \ldots, w_{i-1})$.

Example:


- *"A invited B to be his leading actor in the latest movie ..."* would be similar to *"B invited A to be his leading actor in the latest movie ..."* for pre-training.

(suppose that A and B are both common and frequent words in the training text)


From attention to multihead attention



From attention to multihead attention (cont.)



GPT: training (pre-training)



Training objectif:
minimize

$$f_\theta(X) = -\sum_i \log P_\theta(\hat{y}(x_i) = y_i | x_i)$$

where $P_\theta(\hat{y}(x_i) = y_i|x_i)$ is the output of the GPT.

$\rightsquigarrow$ The objective function is the **cross-entropy** given that $y_i = x_i$ for the pre-training (self-supervised learning).

Feed forward:

$$\bullet\ Y = W^{(2)}\phi_{\text{ReLU}}(W^{(1)}Z + b^{(1)}) + b^{(2)}$$

$\uparrow$

Feed forward input: Skip-connection(x) + Attention(x)

$$\bullet\ Z = \text{LayerNorm}(x_i + \text{Attention}(x_1, \ldots, x_L))$$

$\uparrow$

Self-attention layer: (Cours 3).

Inference for next token generation

Pre-training objectif:
minimize

$$f_\theta(X) = -\sum_i \log P_\theta(\hat{y}(x_i) = y_i | x_i)$$

where $P_\theta(\hat{y}(x_i) = y_i | x_i)$ is the output of the GPT.

$\rightsquigarrow$ The objective function is the **cross-entropy** given that $y_i = x_i$ for the pre-training (self-supervised learning).

Inference after pre-training:
Ideally, we would consider

$$\tilde{y} = \arg\max_y P_\theta(y|x) = \arg\max_{y_1,\ldots,y_L} \prod_{i=1}^{L} P_\theta(y_i | y_1, \ldots, y_{i-1}).$$

But this is **intractable**, since the above decision rule defined over V^L combinations.

Inference for next token generation

Pre-training objectif:
minimize

$$f_\theta(X) = -\sum_i \log P_\theta(\hat{y}(x_i) = y_i | x_i)$$

where $P_\theta(\hat{y}(x_i) = y_i | x_i)$ is the output of the GPT.

The objective function is the **cross-entropy** given that $y_i = x_i$ for the pre-training (self-supervised learning).

Inference after pre-training:
Greedy decoding: compute iteratively

1. $\tilde{y}_1 = \arg\max_y P_\theta(y)$
2. $\tilde{y}_2 = \arg\max_y P_\theta(y | \tilde{y}_1)$
3. $\tilde{y}_3 = \arg\max_y P_\theta(y | \tilde{y}_1, \tilde{y}_2)$
4. $\vdots$

t $\tilde{y}_t = \arg\max_y P_\theta(y | \tilde{y}_1, \ldots, \tilde{y}_{t-1})$

Plan du cours

1.1 – LLMs: applications, number of parameters

1.2 – Machine learning for natural language processing (NLP)

2.1 – Word embeddings for text classification

2.2 – Word2vec

2.3 – TP: Word embeddings for text classification (IMDB dataset)

3.1 – Sequence processing: Transformer and a few previous works

3.2 – Sequence processing: the attention mechanism

3.3 – TP: agnews, TP: attention

4.1 – Attention, Transformer, GPT

4.2 – TP: GPT from scratch

Thank You !

References

Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2019). Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pages 4171–4186.

Mikolov, T., Chen, K., Corrado, G., and Dean, J. (2013a). Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*.

Mikolov, T., Sutskever, I., Chen, K., Corrado, G. S., and Dean, J. (2013b). Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems*, 26.

Radford, A., Narasimhan, K., Salimans, T., Sutskever, I., et al. (2018). Improving language understanding by generative pre-training.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. (2017). Attention is all you need. *Advances in neural information processing systems*, 30.