

function arguments

Type of function arguments:

1. Positional argument.
2. Default positional argument.
3. Variable length positional argument.
4. Keyword argument.
5. Default keyword argument.
6. Variable length keyword argument.

1. Positional argument:-

Syntax:

```
def fun_name(param1, param2, param3):  
    function body  
    function body  
    function body  
fun_name(arg1, arg2, arg3)  
fun_name() # error  
fun_name(arg1) # error  
fun_name(arg1, arg2) # error
```

2. Default positional argument:-

Syntax:

```
def fun_name(param1=0, param2=0, param3=0):  
    function body  
    function body  
    function body  
fun_name()  
fun_name(arg1)  
fun_name(arg1, arg2)  
fun_name(arg1, arg2, arg3)  
fun_name(arg1, arg2, arg3, arg4) # error
```

3. Variable length positional argument:-

Syntax:

```
def fun_name(*args):  
    print(args)  
    print(type(args))
```

```

    function body
fun_name()
fun_name(arg1)
fun_name(arg1, arg2)
fun_name(arg1, arg2, arg3)
fun_name(arg1, arg2, arg3, arg4)

```

4. Keyword argument:-

Syntax:

```

def fun_name(param1, param2, param3):
    function body
    function body
    function body
fun_name(param1=arg1, param2=arg3, param3=arg2)
fun_name()
# error
fun_name(param1=arg1) # error
fun_name(param1=arg1, param2=arg3) # error

```

5. Default keyword argument:-

Syntax:

```

def fun_name(param1=0, param2=0, param3=0):
    function body
    function body
    function body
fun_name()
fun_name(param1=arg1)
fun_name(param1=arg1, param2=arg3)
fun_name(param1=arg1, param2=arg3, param3=arg2)
fun_name(param1=arg1, param2=arg3, param3=arg2, param4=arg4) #error

```

6. Variable length keyword argument:-

Syntax:

```

def fun_name(**kwargs):
    print(kwargs) # {'key': 'value'}
    print(type(kwargs)) # <class 'dict'>
    function body
fun_name()
fun_name(param1=arg1)
fun_name(param1=arg1, param2=arg3)
fun_name(param1=arg1, param2=arg3, param3=arg2)
fun_name(param1=arg1, param2=arg3, param3=arg2, param4=arg4)

```

