

Postman Fundamentals – 1-Day Practical Guide (QA Reality)

Scope: Just enough Postman to be effective in real projects

Focus: CRUD APIs, Collections, Environments, Variables

Rule: ❌ No hardcoding. Ever.

0. First, a hard truth (read this)

If you:

- Hardcode URLs
- Hardcode tokens
- Copy-paste request bodies per API

👉 You are **not using Postman properly**. You're just sending HTTP calls.

This guide fixes that in **one day**.

1. What you must learn today (no extras)

You only need **3 Postman concepts**:

1. **Collections** – group APIs logically
2. **Environments** – control where APIs run
3. **Variables** – remove hardcoding

Everything else is noise for now.

2. Simple CRUD API we'll use

Assume a basic REST API:

```
POST /users
GET /users/{id}
PUT /users/{id}
DELETE /users/{id}
```

Base URL changes per environment.

3. Collections (how seniors structure it)

Bad structure

Random APIs
Login API
Some test API

Correct structure

Postman Basics – CRUD

- |— Create User (POST)
- |— Get User (GET)
- |— Update User (PUT)
- |— Delete User (DELETE)

A **collection** = **one feature / one service**.

4. Environments (this is mandatory)

Why environments exist

Because this changes:

- Base URL

- Tokens
- Test data IDs

Example environments

Variable	Dev	QA
baseUrl	https://dev.api.com	https://qa.api.com
token	dev-token	qa-token
userId	(empty)	(empty)


Create these in **Postman** → **Environments**.

5. Variables (this removes hardcoding)

Variable syntax

{{variableName}}

Base URL usage

 Hardcoded

https://qa.api.com/users

 Correct

{{baseUrl}}/users

6. CRUD requests – how they work together

6.1 Create User (POST)

URL

{{baseUrl}}/users

Body (raw JSON)

```
{  
  "name": "Test User",  
  "email": "testuser@mail.com"  
}
```

Tests tab (VERY important)

```
var response = pm.response.json();  
pm.environment.set("userId", response.id);  
pm.test("User created", function () {  
  pm.response.to.have.status(201);  
});
```

 This stores `userId` dynamically.

6.2 Get User (GET)

URL

{{baseUrl}}/users/{{userId}}

Test

```
pm.test("User fetched", function () {  
  pm.response.to.have.status(200);  
});
```

6.3 Update User (PUT)

URL

{{baseUrl}}/users/{{userId}}

Body

```
{  
  "name": "Updated User"  
}
```

6.4 Delete User (DELETE)

URL

{{baseUrl}}/users/{{userId}}

Test

```
pm.test("User deleted", function () {  
  pm.response.to.have.status(200);  
});
```

7. How to run it properly

1. Select environment (Dev / QA)
2. Run collection in order:
 - Create → Get → Update → Delete
3. No manual ID copy-paste

If you're copying IDs manually → **you failed the basics.**

8. Sample collection file (for understanding)

File name:

/postman-basics/collection.json

```
{
  "info": {
    "name": "Postman Basics – CRUD",
    "schema": "https://schema.getpostman.com/json/collection/v2.1.0/collection.json"
  },
  "item": [
    {
      "name": "Create User",
      "request": {
        "method": "POST",
        "url": "{{baseUrl}}/users",
        "body": {
          "mode": "raw",
          "raw": "{\"name\": \"Test User\", \"email\": \"test@mail.com\"}"
        }
      }
    },
    {
      "name": "Get User",
      "request": {
        "method": "GET",
        "url": "{{baseUrl}}/users/{{userId}}"
      }
    }
  ]
}
```

You don't need to memorize this — just understand the structure.

9. What reviewers look for (important)

- ✓ Uses environment variables
 - ✓ IDs passed dynamically
 - ✓ Collection can run end-to-end
 - ✗ Hardcoded URLs
 - ✗ Manual copy-paste
 - ✗ One request = one collection
-

10. Final takeaway

Postman is a testing tool, not a curl replacement.

If your collection can't run end-to-end without manual work — it's not production-ready.

If you want next:

- Auth token handling (login → token → reuse)
- Negative CRUD test cases
- Postman → Newman → CI flow

Say what you want.