Rajalakshmi Engineering College

Name: shyam ganesh
Email: 241801266@rajalakshmi.edu.in
Roll no: 241801266
Phone: 9342892812
Branch: REC
Department: I AI & DS FD
Batch: 2028
Degree: B.E - AI & DS

Scan to verify results

NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

Input Format

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

Output Format

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 20 30 40 50
Output: 10 20 30 40 50

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
typedef struct node{
   int data;
   struct node *prev,*next;
}node;
node* cnode(int data)
{
   node* newn=(node*)malloc(sizeof(node));
   newn->data=data;
   newn->prev=NULL;
   newn->next=NULL;
   return newn;
}
void insert(node** head,int val)
{
   node* newn=cnode(val);
   if(*head==NULL){
      *head=newn;
   }
   else{
      node* temp=*head;
      while(temp->next!=NULL){
```

```
            temp=temp->next;
        }
        temp->next=newn;
    }

}
void dis(node* head){
    node* temp=head;
    while(temp!=NULL){
        printf("%d",temp->data);
        temp=temp->next;
    }
}
int main()
{
    node* head=NULL;
    int n,val;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        scanf("%d",&val);
        insert(&head,val);
    }
    dis(head);
}
```

Status : Correct **Marks : 10/10**