Status	Finished
Started	Tuesday, 20 October 2026, 9:31 AM
Completed	Tuesday, 20 October 2026, 9:36 AM
Duration	4 mins 53 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

- a. read(size) ✓
- b. readlines()
- c. readline()
- d. readchar()

The correct answer is: read(size)

Question **2**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

- a. Closes the file
- b. Moves the file cursor to the beginning
- c. Flushes the internal buffer to the file ✓
- d. Deletes the file content

The correct answer is: Flushes the internal buffer to the file

Question **3**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

- a. move the file pointer five characters ahead from the current position ✓
- b. move the file pointer five characters behind from the current position
- c. moves the file pointer to the end of a file
- d. move the file pointer to beginning of the file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **4**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

- a. infile = open(file = “a.txt”, “r”)
- b. infile = open(file = “a.txt”, “r”)
- c. infile = open(“a.txt”, “r”) ✓
- d. infile = open(file, “a.txt”, “r”)

The correct answer is:
infile = open(“a.txt”, “r”)

Question **5**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

- a. open_file()
- b. file()
- c. open() ✓
- d. openfile()

The correct answer is: open()

Question **6**

Correct

Mark 1.00 out of 1.00

What is the purpose of the with statement in Python file handling?

a. To write data to a file
b. To automatically close the file after its suite finishes ✓
c. To delete a file
d. To read data from a file

The correct answer is: To automatically close the file after its suite finishes

Question **7**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readlines() ✓
b. read()
c. readlist()
d. readline()

The correct answer is: readlines()

Question **8**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It clears the old data and starts fresh ✓
b. It does nothing
c. It appends data to the file
d. It raises an error

The correct answer is: It clears the old data and starts fresh

Question **9**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

a. read()
b. insert()
c. write() ✓
d. append()

The correct answer is: write()

Question **10**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

a. current()
b. tell() ✓
c. position()
d. locate()

The correct answer is: tell()

Question **11**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

a. truncate() ✓
b. resize()
c. reduce()
d. shrink()

The correct answer is: truncate()

Question **12**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

- True ✓
- False

The correct answer is 'True'.

Question **13**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

- a. readline(size)
- b. read()
- c. readlines()
- d. readline() ✓

The correct answer is: readline()

Question **14**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

- a. seek() ✓
- b. ftell()
- c. tell()
- d. fseek()

The correct answer is: seek()

Question **15**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

a. readlines(1)
b. read(1)
c. line()
d. readline() ✓

The correct answer is: readline()