

**Aim:**

Write a C program to reverse all the elements in the array.

**Input Format:**

First line of input contains an integer **N** representing the size of array  
Second line of input contains N no.of space separated integers representing the array elements

**Output Format:**

Print the elements of the array in reverse order

**Constraints:**

1 <= N <= 1000  
0 <= arr[i] <= 1000

**Source Code:**

ArrayReverse.c

```
#include<stdio.h>
int main()
{
    int arr[10],n,i;
    scanf("%d",&n);
    for(i=0;i<n;i++)
        scanf("%d",&arr[i]);
    for(i=n-1;i>=0;i--)
        printf("%d ",arr[i]);
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
3
15 24 62
62 24 15

Test Case - 2
User Output
4
-54 63 -21 51
51 -21 63 -54

Test Case - 3
User Output

5
-50 -60 -70 100 80
80 100 -70 -60 -50

<b>Test Case - 4</b>
<b>User Output</b>
6
12 15 19 8 63 -78
-78 63 8 19 15 12

<b>Test Case - 5</b>
<b>User Output</b>
5
-5 -10 -15 -20 -25
-25 -20 -15 -10 -5

**Aim:**

Write a C program to check whether the given element is present or not in the array of elements using linear search.

**Source Code:**

SearchEle.c

```
#include<stdio.h>
int main()
{
    int arr[10],key,n,i,flag=0,pos=i;
    printf("Enter size: ");
    scanf("%d",&n);
    printf("Enter %d element: ",n);
    for(i=0;i<n;i++)
        scanf("%d",&arr[i]);

    printf("Enter search element: ");
    scanf("%d",&key);
    for(i=0;i<n;i++)
    {
        if(arr[i]==key)
        {
            flag=1;
            pos=i;
            break;
        }
    }
    if(flag==1)
        printf("Found at position %d\n",i);

    else{
        printf("%d is not found\n",key);
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
Enter size:
6
Enter 6 element:
2 4 8 1 3 5
Enter search element:
6
6 is not found

Test Case - 2
<b>User Output</b>
Enter size:
6
Enter 6 element:
2 4 8 1 3 5
Enter search element:
2
Found at position 0

Test Case - 3
<b>User Output</b>
Enter size:
6
Enter 6 element:
2 4 8 1 3 5
Enter search element:
9
9 is not found

**Aim:**

Write a C program that reads n integer numbers and arrange them in ascending order using Bubble Sort.

**Source Code:**

bubbleSort.c

```
#include <stdio.h>
int main()
{
    int i,n,temp,j,arr[10];
    printf("n: ");
    scanf("%d",&n);
    printf("Elements: ");
    for(i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
    }

    {
        printf("Before sorting: ");
        for(i=0;i<n;i++)
            printf("%d ",arr[i]);
    }

    for(i=0;i<n;i++)
    {
        for(j=0;j<n-i-1;j++)
        {
            if(arr[j]>arr[j+1])
            {
                temp=arr[j];
                arr[j]=arr[j+1];
                arr[j+1]=temp;
            }
        }
    }

    printf("\nAfter sorting: ");
    for(i=0;i<n;i++)
        printf("%d ",arr[i]);
    printf("\n");
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
n:
4
Elements:
44 22 66 11

Before sorting: 44 22 66 11
After sorting: 11 22 44 66

Test Case - 2
User Output
n:
5
Elements:
9 2 7 1 6
Before sorting: 9 2 7 1 6
After sorting: 1 2 6 7 9

**Aim:**

Write a C program that use non-recursive functions to perform the Binary search operation for a Key value in a given list of integers.

**Source Code:**

recursiveBinarySearch.c

```
#include<stdio.h>
int main()
{
    int arr[10],num,i,n,beg,end,mid,found=0;
    printf("size: ");
    scanf("%d",&n);
    printf("elements: ");
    for(i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    printf("search element: ");
    scanf("%d",&num);
    beg=0,end=n-1;
    while(beg<=end)
    {
        mid=(beg+end)/2;
        if(arr[mid]==num){

            printf("found at %d",mid+1);

            break;

        }
        else if(arr[mid]>num)
            end=mid-1;
        else
            beg=mid+1;

        if(beg>end&&found==0)
            printf("not found");
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
size:
3
elements:
3 6 9
search element:
6

found at 2
------------

Test Case - 2
User Output
size:
3
elements:
3 6 9
search element:
2
not found



**Aim:**

Write a C program that implements the Insertion sort to sort a given list of integers in ascending order.

**Source Code:**

insertionSort.c

```
#include <stdio.h>
void insertionsort(int arr[],int n);
void main()
{
    int arr[10],i,n;
    printf("Enter no of elements: ");
    scanf("%d",&n);
    printf("Enter the elements: ");
    for(i=0;i<n;i++)
        scanf("%d",&arr[i]);
    printf("Array before sort: ");
    for(i=0;i<n;i++)
        printf("%d ",arr[i]);
    insertionsort(arr,n);
    printf("\nArray after insertion sort: ");
    for(i=0;i<n;i++)
        printf("%d ",arr[i]);
}
void insertionsort(int arr[],int n)
{
    int i,j,temp;
    for(i=1;i<n;i++)
    {
        temp=arr[i];
        j=i-1;
        while((temp<arr[j])&&(j>=0))
        {
            arr[j+1]=arr[j];
            j--;
        }
        arr[j+1]=temp;
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
Enter no of elements:
6
Enter the elements:
1 5 4 2 6 8

Array before sort: 1 5 4 2 6 8
Array after insertion sort: 1 2 4 5 6 8

<b>Test Case - 2</b>
<b>User Output</b>
Enter no of elements:
8
Enter the elements:
5 2 10 36 95 14 10 23
Array before sort: 5 2 10 36 95 14 10 23
Array after insertion sort: 2 5 10 10 14 23 36 95

**Aim:**

Write a C program that implements the Selection sort to sort a given list of integers in ascending order.

**Source Code:**

selectionSort.c

```
#include <stdio.h>
void main()
{
    int i,n,min,temp,j,a[20];
    printf("Enter no of elements: ");
    scanf("%d",&n);
    printf("Enter the elements: ");
    for(i=0;i<n;i++)
    {
        scanf("%d",&a[i]);
    }
    printf("Array before sort: ");
    for(i=0;i<n;i++)
        printf("%d ",a[i]);
    for(i=0;i<n-1;i++)
    {
        min=i;
        for(j=i+1;j<n;j++)
        {
            if(a[j]<a[min])
            {
                min=j;
            }
        }
        temp=a[i];
        a[i]=a[min];
        a[min]=temp;
    }
    printf("\nArray after sort: ");
    for(i=0;i<n;i++)
        printf("%d ",a[i]);
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
Enter no of elements:
5
Enter the elements:
2 6 1 5 7
Array before sort: 2 6 1 5 7

Array after sort: 1 2 5 6 7
-----------------------------

<b>Test Case - 2</b>
<b>User Output</b>
Enter no of elements:
6
Enter the elements:
62 51 58 96 32 14
Array before sort: 62 51 58 96 32 14
Array after sort: 14 32 51 58 62 96

<b>Test Case - 3</b>
<b>User Output</b>
Enter no of elements:
5
Enter the elements:
64 25 12 22 11
Array before sort: 64 25 12 22 11
Array after sort: 11 12 22 25 64

**Aim:**

Write a c program to perform insertion at end and display the elements of the single linked list.

**Note:** Driver code is already given for you.

**Source Code:**

SingleLL3.c

```
#include<stdio.h>
#include<stdlib.h>

#include "InsAtEnding.c"

void main() {
    NODE first = NULL;
    int x, op;
    while(1) {
        printf("1.Insert At End 2.Traverse the List 3.Exit\n");
        printf("Enter your option : ");
        scanf("%d", &op);
        switch(op) {
            case 1: printf("Enter an element : ");
                    scanf("%d", &x);
                    first = insertAtEnd(first, x);
                    break;
            case 2: if (first == NULL) {
                        printf("Single Linked List is empty\n");
                    } else {
                        printf("The elements in SLL are : ");
                        traverseList(first);
                    }
                    break;
            case 3: exit(0);
        }
    }
}
```

InsAtEnding.c

```

struct node{
int data;
struct node *next;
};
typedef struct node *NODE;
NODE createNode(){
    NODE temp;
    temp=(NODE)malloc(sizeof(struct node));
    temp->next=NULL;
    return temp;
}
NODE insertAtEnd(NODE first,int x){
    NODE temp,p;
    temp = createNode();
    temp->data=x;
    if(first==NULL)
        first=temp;
    else{
        p=first;
        while(p->next!=NULL)
            p=p->next;
        p->next=temp;
    }
    return first;
}
void traverseList(NODE first){
    NODE p;
    p = first;
    while(p!=NULL)
    {
        printf("%d --> ",p->data);
        p=p->next;
    }
    printf("NULL\n");
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
10
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
20
1.Insert At End 2.Traverse the List 3.Exit

Enter your option :
1
Enter an element :
30
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
2
The elements in SLL are : 10 --> 20 --> 30 --> NULL
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
3

<b>Test Case - 2</b>
<b>User Output</b>
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
2
Single Linked List is empty
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
99
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
29
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
59
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
2
The elements in SLL are : 99 --> 29 --> 59 --> NULL
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
3

S.No: 8	Exp. Name: <b>Write a C program to Insert an element at Begin and Delete at End in Singly Linked List.</b>	Date: 2024-03-15
---------	--	------------------

**Aim:**

Fill in the missing code in the below functions `insertAtBegin(NODE first, int x)` and `deleteAtEnd(NODE first)` in the file `InsAtBeginAndDelEnd.c`.

**Source Code:**

SingleLL2.c

```
#include<stdio.h>
#include<stdlib.h>

#include "InsAtBeginAndDelEnd.c"

void main() {
    NODE first = NULL;
    int x, op;
    while(1) {
        printf("1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit\n");
        printf("Enter your option : ");
        scanf("%d", &op);
        switch(op) {
            case 1: printf("Enter an element : ");
                    scanf("%d", &x);
                    first = insertAtBegin(first, x);
                    break;
            case 2:if (first == NULL) {
                    printf("Single Linked List is empty so
deletion is not possible\n");
                } else {
                    first = deleteAtEnd(first);
                }
                break;
            case 3: if (first == NULL) {
                    printf("Single Linked List is empty\n");
                } else {
                    printf("The elements in SLL are : ");
                    traverseList(first);
                }
                break;
            case 4: exit(0);
        }
    }
}
```

InsAtBeginAndDelEnd.c



```

struct node {
    int data;
    struct node *next;
};
typedef struct node *NODE;

NODE createNode() {
    NODE temp;
    temp=(NODE)malloc(sizeof(struct node));
    temp->next=NULL;
    return temp;
}

NODE insertAtBegin(NODE first, int x) {
    NODE temp;
    temp= createNode();
    temp->data=x;
    temp->next=first;
    return temp;
}

NODE deleteAtEnd(NODE first)
{
    NODE temp=first,t1;
    int value;
    if(first->next==NULL)
    {
        value=first ->data;
        free(first);
        first=NULL;
    }
    else{
        while(temp->next!=NULL){
            t1=temp;
            temp=temp->next;
        }
        value=temp->data;
        free(temp);
        t1->next=NULL;
    }
    printf("The deleted item from SLL : %d\n",value);
    return first;
}

void traverseList(NODE first) {
    NODE temp = first;
    while (temp != NULL) {
        printf("%d --> ",temp -> data);
        temp = temp -> next;
    }
    printf("NULL\n");
}

```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :
15
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :
49
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :
26
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
3
The elements in SLL are : 26 --> 49 --> 15 --> NULL
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
2
The deleted item from SLL : 15
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
3
The elements in SLL are : 26 --> 49 --> NULL
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
4

Test Case - 2
<b>User Output</b>
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
2
Single Linked List is empty so deletion is not possible
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
3
Single Linked List is empty
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :

15
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
2
The deleted item from SLL : 15
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
3
Single Linked List is empty
1.Insert At Begin 2.Delete at End 3.Traverse the List 4.Exit
Enter your option :
4

S.No: 9	Exp. Name: <b><i>Write a C program to reverse the Singly Linked List.</i></b>	Date: 2024-03-22
---------	---	------------------

**Aim:**

Write a C program to reverse the elements of a single linked list.

**Source Code:**

```
ReverseList.c
```

```

#include<stdio.h>
#include<stdlib.h>
void createList(int n);
void reverseList();
void displayList();
struct Node {
int data;
struct Node*next;
}*head=NULL;
void reverse_list(){
    struct Node*current=head;
    struct Node*prev=NULL,*next=NULL;
    while(current!=NULL)
        {
            next=current->next;
            current->next=prev;
            prev=current;
            current=next;
        }
    head=prev;
}
void createList(int n){
    struct Node*newnode,*temp;
    int data,i;
    head=(struct Node*)malloc(sizeof(struct Node));
    if(head==NULL)
        printf("unable to allocate memory");
    else{
        printf("Enter data: ");
        scanf("%d",&data);
        head->data=data;
        head->next=NULL;
        temp=head;
        for(i=2;i<=n;i++)
            {
                newnode=(struct Node*)malloc(sizeof(struct Node));
                if(newnode==NULL)
                {
                    printf("unable to allocate the memory");
                    break;
                }
                else{
                    scanf("%d",&data);
                    newnode->data=data;
                    newnode->next=NULL;
                    temp->next=newnode;
                    temp=temp->next;
                }
            }
    }
}
void displayList()
{
    struct Node*temp;
    if(head==NULL)

```

```

        temp=head;
        while(temp!=NULL)
        {
            printf("%d ",temp->data);
            temp=temp->next;
        }
        printf("\n");
    }
}
int main()
{
    int n;
    do{
        printf("Enter no.of nodes: ");
        scanf("%d",&n);
        if(n<=0)
            printf("List size must be greater than zero:\n");
    }
    while(n<=0);
    createList(n);
    reverse_list();
    printf("Reversed the list: ");
    displayList();
    return 0;
}

```

### Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Enter no.of nodes:
4
Enter data:
1 2 3 4
Reversed the list: 4 3 2 1

Test Case - 2
<b>User Output</b>
Enter no.of nodes:
0
List size must be greater than zero:
Enter no.of nodes:
10
Enter data:
15 12 31 14 158 140 465 235 48 49
Reversed the list: 49 48 235 465 140 158 14 31 12 15

S.No: 10	Exp. Name: <b><i>Reverse of a single linked list recursively.</i></b>	Date: 2024-03-22
----------	---	------------------

**Aim:**

Write a C program to reverse a single linked list recursively.

**Source Code:**

RecursiveReverse.c

```

#include <stdio.h>
#include <stdlib.h>

struct Node {
    int data;
    struct Node* next;
};
struct Node*head;
void Reverse(struct Node*q,struct Node*p)
{
    if(p!=NULL)
    {
        Reverse(p,p->next);
        p->next=q;
    }
    else
        head=q;
}
void createList(int n)
{
    struct Node*newNode,*temp;
    int data,i;
    head=(struct Node*)malloc(sizeof(struct Node));
    if(head==NULL)
        printf("Unable to allocate memory.");
    else{
        printf("Data for node 1: ");
        scanf("%d",&data);
        head->data=data;
        head->next=NULL;
        temp=head;
        for(i=2;i<=n;i++)
        {
            newNode=(struct Node*)malloc(sizeof(struct Node));
            if(newNode==NULL)
            {
                printf("Unable to allocate memory.");
                break;
            }
            else
            {
                printf("Data for node %d: ",i);
                scanf("%d",&data);

                newNode->data=data;
                newNode->next=NULL;
                temp->next=newNode;
                temp=temp->next;
            }
        }
    }
}
void displayList()
{
    struct Node*temp;

```



```

else{
    temp=head;
    while(temp!=NULL)
    {
        printf("%d -> ",temp->data);
        temp=temp->next;
    }
    printf("Null\n");
}
}
int main()
{
    int n;
    do
    {
        printf("No of nodes: ");
        scanf("%d", &n);
        if(n<=0)
            printf("List size must be greater than zero:\n");
    }
    while(n<=0);
    createList(n);
    printf("Original linked list: ");
    displayList();
    printf("Reversed linked list: ");
    Reverse(NULL,head);
    displayList();
    return 0;
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
No of nodes:
5
Data for node 1:
5
Data for node 2:
4
Data for node 3:
3
Data for node 4:
2
Data for node 5:
1
Original linked list: 5 -> 4 -> 3 -> 2 -> 1 -> Null
Reversed linked list: 1 -> 2 -> 3 -> 4 -> 5 -> Null

Test Case - 2
<b>User Output</b>
No of nodes:
7
Data for node 1:
1
Data for node 2:
2
Data for node 3:
3
Data for node 4:
4
Data for node 5:
3
Data for node 6:
2
Data for node 7:
1
Original linked list: 1 -> 2 -> 3 -> 4 -> 3 -> 2 -> 1 -> Null
Reversed linked list: 1 -> 2 -> 3 -> 4 -> 3 -> 2 -> 1 -> Null

<b>S.No: 11</b>	Exp. Name: <b><i>Single Linked List operations</i></b>	<b>Date: 2024-04-19</b>
-----------------	--	-------------------------

**Aim:**

Write a C program to implement a menu driven Program for the following operations on Singly Linked List (SLL)

1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display

**Source Code:**

sll0perations.c

```

#include<stdio.h>
#include<stdlib.h>
struct node
{
int data;
struct node * next;
};
typedef struct node * Node;
Node insert_begin(Node,int);
Node insert_end(Node,int);
Node insert_pos(Node,int);
Node del_pos(Node);
Node del_end(Node);
Node del_begin(Node);
void display(Node);
Node createNode();
int main()
{
    int x,op;
    Node first=NULL;
    Node prev=NULL;
    while(1)
    {
        printf("1. Insert at the beginning\n2. Insert at the end\n3. Insert
at a position\n4. Delete at a position\n5. Delete from the beginning\n6. Delete from the
end\n7. Display\n8. Exit\n");
        printf("Enter option: ");
        scanf("%d",&op);
        switch(op)
        {
            case 1:
                printf("Enter the element to insert at the
beginning: ");
                scanf("%d",&x);
                first=insert_begin(first,x);
                break;
            case 2:
                printf("Enter the element to insert at the end: ");
                scanf("%d",&x);
                first=insert_end(first,x);
                break;
            case 3:
                printf("Enter the element to insert and position:
");
                scanf("%d",&x);
                first=insert_pos(first,x);
                break;
            case 4:
                first=del_pos(first);
                break;
            case 5:
                first=del_begin(first);
                break;
            case 6:
                first=del_end(first);

```

```

                                display(first);
                                break;
                                case 8:
                                exit(0);
                                }
                                }
                                }
Node createNode()
{
    Node new_node;
    new_node=(Node)malloc(sizeof(struct node));
    new_node->next=NULL;
    return new_node;
}
Node insert_begin(Node first,int x)
{
    Node new_node;
    new_node=createNode();
    new_node->data=x;
    if(first==NULL)
    {
        first=new_node;
        first->next=NULL;
    }
    else
    {
        new_node->next=first;
        first=new_node;
    }
    return first;
}
Node insert_pos(Node first,int x)
{
    Node new_node,temp,prev;
    int pos,i;
    new_node=createNode();
    new_node->data=x;
    printf("Enter position: ");
    scanf("%d",&pos);
    temp=first;
    prev=first;
    if(pos<=0)
    {
        printf("Invalid position\n");
        return first;
    }
    for(i=1;i<pos;i++)
    {
        prev=temp;
        temp=temp->next;
        if(temp==NULL)
        {
            printf("Invalid position\n");
            return first;
        }
    }

```

```

{
    new_node->next=first;
    first=new_node;
}
else
{
    new_node->next=prev->next;
    prev->next=new_node;
}
return first;
}
Node insert_end(Node first,int x)
{
    Node new_node,temp;
    new_node=createNode();
    new_node->data=x;
    if(first==NULL)
    {
        first=new_node;
    }
    else
    {
        temp=first;
        while(temp->next!=NULL)
        {
            temp=temp->next;
        }
        temp->next=new_node;
    }
    return first;
}
Node del_pos(Node first)
{
    Node prev,ptr=first;
    int pos,i=1;
    if(first==NULL)
        printf("List is empty\n");
    else
    {
        printf("Enter position to delete: ");
        scanf("%d",&pos);
        if(pos==1)
        {
            first=first->next;
            printf("Delete element is %d",ptr->data);
        }
        else
        {
            while(i<pos)
            {
                prev=ptr;
                ptr=ptr->next;
                i++;
            }
            if(ptr==NULL)

```

```

        {
            prev->next=ptr->next;
            printf("Deleted element is %d\n",ptr->data);
        }
    }
    free(ptr);
}

return first;
}

Node del_begin(Node first)
{
    Node temp;
    if(first==NULL)
    {
        printf("List is empty\n");
    }
    else{
        temp=first;
        first=temp->next;
        printf("Deleted element is %d\n",temp->data);
        free(temp);
    }
    return first;
}

Node del_end(Node first)
{
    Node cur,prev;
    cur=first;
    if(first==NULL)
        printf("List is empty\n");
    else
    {
        while(cur->next!=NULL)
        {
            prev=cur;
            cur=cur->next;
        }
        printf("Deleted element is %d\n",cur->data);
        free(cur);
        prev->next=NULL;
    }
    return first;
}

void display(Node first)
{
    Node temp;
    temp=first;
    if(first==NULL)
    {
        printf("List is empty\n");
    }
    else
    {
        printf("Elements in the list: ");
        while(temp!=NULL)

```

```

        temp=temp->next;
    }
    printf("NULL\n");
}
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
7
List is empty
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
6
List is empty
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
5
List is empty
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning



6. Delete from the end
7. Display
8. Exit
Enter option:
4
List is empty
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
1
Enter the element to insert at the beginning:
1
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
1
Enter the element to insert at the beginning:
2
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
1
Enter the element to insert at the beginning:
3
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:

7
Elements in the list: 3 -> 2 -> 1 -> NULL
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
2
Enter the element to insert at the end:
4
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
7
Elements in the list: 3 -> 2 -> 1 -> 4 -> NULL
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
3
Enter the element to insert and position:
22
Enter position:
6
Invalid position
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
3

Enter the element to insert and position:
22
Enter position:
2
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
7
Elements in the list: 3 -> 22 -> 2 -> 1 -> 4 -> NULL
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
4
Enter position to delete:
6
Invalid position
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
4
Enter position to delete:
2
Deleted element is 22
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:

7
Elements in the list: 3 -> 2 -> 1 -> 4 -> NULL
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
5
Deleted element is 3
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
7
Elements in the list: 2 -> 1 -> 4 -> NULL
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
6
Deleted element is 4
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning
6. Delete from the end
7. Display
8. Exit
Enter option:
7
Elements in the list: 2 -> 1 -> NULL
1. Insert at the beginning
2. Insert at the end
3. Insert at a position
4. Delete at a position
5. Delete from the beginning

6. Delete from the end
7. Display
8. Exit
Enter option:
8

**Aim:**

Write a program to remove all the duplicate elements that are present in the given singly linked lists.

**Sample Input and Output:**

```
Enter list elements :  
Enter element : 5  
Enter element : 4  
Enter element : 3  
Enter element : 3  
Enter element : 5  
Enter element : 6  
Enter element : -1  
List before removing duplicates : 3 3 4 5 5 6  
List after removing duplicates : 3 4 5 6
```

The algorithm is as follows:

```
Step-1: Take input elements of the linked list.  
Step-2: Arrange the elements in sorted order.  
Step-3: Traverse from the head of the sorted linked list  
Step-4: While traversing, compare the current node with the next node.  
Step-5: If data of the next node is the same as the current node then delete the next node.  
Step-6: Print the resultant list elements
```

Fill the missing code in the `NODE removeDuplicates` function in the file RemoveLL.c

**Source Code:**

SingleLL10.c

```
#include <stdio.h>  
#include <stdlib.h>  
#include "RemoveLL.c"  
  
int main() {  
    NODE l1;  
    l1 = NULL;  
    printf("Enter list elements :\n");  
    l1 = createAndAddNodes(l1);  
    sort(l1);  
    printf("List before removing duplicates : ");  
    print(l1);  
    printf("\n");  
    printf("List after removing duplicates : ");  
    removeDuplicates(l1);  
    print(l1);  
}
```

RemoveLL.c

```

struct node {
    int data;
    struct node *next;
};
typedef struct node * NODE;

NODE createAndAddNodes(NODE first) {
    NODE temp, q;
    int x;
    printf("Enter element : ");
    scanf("%d", &x);
    while(x != -1) {
        temp = (NODE)malloc(sizeof(struct node));
        temp->data = x;
        temp->next = NULL;
        if(first == NULL) {
            first = temp;
        } else {
            q->next = temp;
        }
        q = temp;
        printf("Enter element : ");
        scanf("%d", &x);
    }
    return first;
}

void print(NODE node) {
    while (node != NULL) {
        printf("%d ", node->data);
        node = node -> next;
    }
}

NODE sort(NODE first) {
    NODE t1, t2;
    int x;
    for(t1 = first; t1 -> next != NULL; t1 = t1 -> next) {
        for(t2 = t1 -> next; t2 != NULL; t2 = t2 -> next) {
            if (t1 -> data > t2 -> data) {
                x = t1 -> data;
                t1 -> data = t2 -> data;
                t2 -> data = x;
            }
        }
    }
    return first;
}

NODE removeDuplicates(NODE head) {
    NODE p=head;
    NODE q=head->next;
    while (q!=NULL)
    {
        if(p->data!=q->data)
        {
            p=q;
            q=p->next;
        }
    }
}

```

```

        p->next=q->next;
        free(q);
        q=p->next;
    }
}
return 0;
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Enter list elements :
Enter element :
5
Enter element :
4
Enter element :
3
Enter element :
3
Enter element :
5
Enter element :
6
Enter element :
-1
List before removing duplicates : 3 3 4 5 5 6
List after removing duplicates : 3 4 5 6



**Aim:**

Fill in the missing code in the below program to create and print polynomial using linked lists.

Sample Input and Output:

```
Enter coeff and exp of node : 4 3
Do u want another node (y/n) : y
Enter coeff and exp of node : 5 2
Do u want another node (y/n) : y
Enter coeff and exp of node : 6 1
Do u want another node (y/n) : y
Enter coeff and exp of node : 2 0
Do u want another node (y/n) : n
The polynomial is : 4 X^ 3 ---> 5 X^ 2 ---> 6 X^ 1 ---> 2 X^ 0 ---> NULL
```

**Source Code:**

PolyLLMain.c

```
#include <stdio.h>
#include <stdlib.h>
#define max 20

#include "CreateAndPrintPolyLL.c"

poly create(poly head) {
    poly temp;
    char ch;
    int coeff, exp;
    do {
        temp = (poly)malloc(sizeof(struct polynomial));
        printf("Enter coeff and exp of node : ");
        scanf("%d%d", &coeff, &exp);
        temp -> coeff = coeff;
        temp -> exp = exp;
        temp -> next = NULL;
        head = addTerm(head, temp);
        printf("Do u want another node (y/n) : ");
        scanf(" %c", &ch);
    } while(ch != 'n');
    return head;
}

void main() {
    poly head = NULL;
    int ch;
    head = create(head);
    printf("The polynomial is : ");
    print(head);
}
```

```
struct polynomial {
    int coeff;
    int exp;
    struct polynomial *next;
};
typedef struct polynomial *poly;

poly addTerm(poly head, poly temp) {
    poly p1,p2;
    p1=p2=head;
    if(p1==NULL)
    {
        head=temp;
    }
    else{
        while(p1!=NULL&& p1->exp>temp->exp)
        {
            p2=p1;
            p1=p1->next;
        }
        if(p1==NULL)
        {
            p2->next=temp;
        }
        else if(p1->exp==temp->exp)
            p1->coeff=p1->coeff+temp->coeff;
        else if(p1->exp<temp->exp)
        {
            if(p2==p1)
            {
                temp->next=p1;
                head=temp;
            }
            else
            {
                temp->next=p1;
                p2->next=temp;
            }
        }
    }
    return head;
}

void print(poly head) {
    poly p1=head;
    while(p1!=NULL)
    {
        printf("%d X^ %d ---> ",p1->coeff,p1->exp);
        p1=p1->next;
    }
    printf("NULL\n");
}
```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Enter coeff and exp of node :
3 2
Do u want another node (y/n) :
y
Enter coeff and exp of node :
5 1
Do u want another node (y/n) :
y
Enter coeff and exp of node :
4 0
Do u want another node (y/n) :
n
The polynomial is : 3 X <sup>2</sup> ---> 5 X <sup>1</sup> ---> 4 X <sup>0</sup> ---> NULL

Page No: 43

ID: 23K61A4748

Test Case - 2
<b>User Output</b>
Enter coeff and exp of node :
4 3
Do u want another node (y/n) :
y
Enter coeff and exp of node :
5 2
Do u want another node (y/n) :
y
Enter coeff and exp of node :
3 3
Do u want another node (y/n) :
y
Enter coeff and exp of node :
2 1
Do u want another node (y/n) :
y
Enter coeff and exp of node :
7 2
Do u want another node (y/n) :
n
The polynomial is : 7 X <sup>3</sup> ---> 12 X <sup>2</sup> ---> 2 X <sup>1</sup> ---> NULL

2023-2027-CIC

Sasi Institute of Technology and Engineering (Autonomous)

S.No: 14	Exp. Name: <b>Polynomial Operations - Adding Polynomials using Linked List</b>	Date: 2024-04-26
----------	--	------------------

**Aim:**

Write a C program to **add** two polynomials using linked lists.

**Note:** Driver code is provided to you in the editor.

**Source Code:**

PolyLLMain1.c

```
#include <stdio.h>
#include <stdlib.h>
#include "AddPolyLL.c"

poly create(poly head) {
    poly temp;
    char ch;
    int coeff, exp;
    do {
        temp = (poly)malloc(sizeof(struct polynomial));
        printf("Coeff and Power of the term: ");
        scanf("%d%d", &coeff, &exp);
        temp -> coeff = coeff;
        temp -> exp = exp;
        temp -> next = NULL;
        head = addTerm(head, temp);
        printf("Want to add more terms?(y/n): ");
        scanf(" %c", &ch);
    } while(ch != 'n');
    return head;
}

void main() {
    poly head1=NULL, head2= NULL, result = NULL;
    int ch;
    printf("First polynomial: \n");
    head1 = create(head1);
    printf("Second polynomial: \n");
    head2 = create(head2);
    result = add(head1, head2);
    printf("First polynomial: ");
    print(head1);
    printf("Second polynomial: ");
    print(head2);
    printf("Addition: ");
    print(result);
}
```

AddPolyLL.c

```

struct polynomial {
int coeff;
int exp;
struct polynomial *next;
};
typedef struct polynomial *poly;
poly addTerm(poly head,poly temp) {
    poly p1,p2;
    p1=p2=head;
    if(p1 == NULL) {
        head = temp;
    }
    else {
        while(p1 != NULL && p1->exp>temp->exp) {
            p2 = p1;
            p1 = p1->next;
        }
        if(p1 == NULL) {
            p2->next = temp;
        } else if(p1->exp == temp->exp) {
            p1->coeff = p1->coeff + temp->coeff;
        } else if(p1->exp<temp->exp) {
            if(p2 == p1) {
                temp->next = p1;
                head = temp;
            } else {
                temp->next = p1;
                p2->next = temp;
            }
        }
    }
    return head;
}

void print(poly head) {
    poly p1 = head;
    int k = 1;
    while(p1 != NULL)
    {
        if(k==1)
        {
            k--;
            printf("%d X^%d",p1->coeff,p1->exp);
        }
        else
            printf(" + %d X^%d",p1->coeff,p1->exp);
        p1 = p1->next;
    }
    printf("\n");
}

poly insert(poly head,int coeff,int exp)
{
    poly temp =(poly)malloc(sizeof(struct polynomial));
    poly t1;
    t1 = head;
    temp->coeff = coeff;

```

```

        head=temp;
    else{
        while(t1->next!=NULL)
            t1=t1->next;
        t1->next=temp;
    }
    return head;
}
poly add(poly poly1,poly poly2) {
    poly result = NULL;
    while(poly1!=NULL && poly2!=NULL) {
        if(poly1->exp==poly2->exp) {
            result= insert(result,poly1->coeff+poly2->coeff,poly1->exp);
            poly1=poly1->next;
            poly2=poly2->next;
        } else if(poly1->exp>poly2->exp) {
            result = insert(result,poly1->coeff,poly1->exp);
            poly1 = poly1->next;
        } else {
            result = insert(result,poly2->coeff,poly2->exp);
            poly2=poly2->next;
        }
    }
    while(poly1 != NULL) {
        result = insert(result,poly1->coeff,poly1->exp);
        poly1 = poly1->next;
    }
    while(poly2!=NULL) {
        result=insert(result,poly2->coeff,poly2->exp);
        poly2=poly2->next;
    }
    return result;
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
First polynomial:
Coeff and Power of the term:
2 3
Want to add more terms?(y/n):
y
Coeff and Power of the term:
4 2
Want to add more terms?(y/n):
y
Coeff and Power of the term:
6 1
Want to add more terms?(y/n):
y

Coeff and Power of the term:
8 0
Want to add more terms?(y/n):
n
Second polynomial:
Coeff and Power of the term:
1 3
Want to add more terms?(y/n):
y
Coeff and Power of the term:
3 2
Want to add more terms?(y/n):
y
Coeff and Power of the term:
5 1
Want to add more terms?(y/n):
y
Coeff and Power of the term:
7 0
Want to add more terms?(y/n):
n
First polynomial: $2 X^3 + 4 X^2 + 6 X^1 + 8 X^0$
Second polynomial: $1 X^3 + 3 X^2 + 5 X^1 + 7 X^0$
Addition: $3 X^3 + 7 X^2 + 11 X^1 + 15 X^0$

<b>Test Case - 2</b>	
<b>User Output</b>	
First polynomial:	
Coeff and Power of the term:	
1 3	
Want to add more terms?(y/n):	
y	
Coeff and Power of the term:	
2 3	
Want to add more terms?(y/n):	
n	
Second polynomial:	
Coeff and Power of the term:	
3 4	
Want to add more terms?(y/n):	
y	
Coeff and Power of the term:	
4 4	
Want to add more terms?(y/n):	
n	
First polynomial: $3 X^3$	
Second polynomial: $7 X^4$	
Addition: $7 X^4 + 3 X^3$	

<b>S.No: 15</b>	Exp. Name: <b><i>Implementation of double ended queue using linked list</i></b>	<b>Date: 2024-04-26</b>
-----------------	---	-------------------------

**Aim:**

Implementation of double ended queue using linked list to perform the following operations

- 1.Insert at Front
- 2.Insert at Rear
- 3.Delete from Front
- 4.Delete from Rear
- 5.Display
- 6.Exit

**Source Code:**

dooublyLinkedList.c



```

#include<stdio.h>
#include<stdlib.h>
struct node {
int data;
struct node*next;
};
typedef struct node*NODE;
NODE rear=NULL,front=NULL;
NODE createNode() {
    NODE temp;
    temp=(NODE)malloc(sizeof(struct node));
    temp->next=NULL;
    return temp;
}
void insertRear(int x) {
    NODE temp, p;
    temp=createNode();
    temp->data=x;
    if(rear==NULL)
        rear=front=temp;
    else {
        rear->next=temp;
        rear=temp;
    }
}
void insertFront(int x) {
    NODE temp, p;
    temp=createNode();
    temp->data=x;
    if(front==NULL)
        rear=front=temp;
    else {
        temp->next=front;
        front=temp;
    }
}
void deleteFront() {
    NODE temp = front;
    if(front == rear)
        front = rear = NULL;
    else
        front = front->next;
    printf("The deleted element from Front : %d\n",temp->data);
    free(temp);
}
void deleteRear() {
    NODE temp=rear;
    if(front==rear)
        front = rear = NULL;
    else {
        NODE p1;
        p1=front;
        while(p1->next!=rear)
            p1=p1->next;
        rear=p1;
    }
}

```

```

        printf("The deleted element from Rear : %d\n", temp->data);
        free(temp);
    }
    void print() {
        NODE temp = front;
        while(temp) {
            printf("%d->", temp->data);
            temp = temp->next;
        }
        printf("NULL\n");
    }
    void main() {
        int data, choice;
        while(1) {
            printf("1.Insert at Front\n2.Insert at Rear\n3.Delete from Front\n4.Delete
from Rear\n5.Display\n6.Exit\n");
            printf("Enter your choice:\n");
            scanf("%d",&choice);
            switch(choice) {
                case 1:
                    printf("Enter an element to Insert at Front:");
                    scanf("%d", &data);
                    insertFront(data);
                    break;
                case 2:
                    printf("Enter an element to Insert at Rear:");
                    scanf("%d", &data);
                    insertRear(data);
                    break;
                case 3:
                    if(front == NULL)
                        printf("Deque is empty\n");
                    else
                        deleteFront();
                    break;
                case 4:
                    if(rear == NULL)
                        printf("Deque is empty\n");
                    else
                        deleteRear();
                    break;
                case 5:
                    if(front == NULL)
                        printf("Deque is empty\n");
                    else
                        print();
                    break;
                case 6:
                    exit(0);
                default:
                    printf("Enter a valid chice");
                    break;
            }
        }
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
5
Deque is empty
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
3
Deque is empty
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
4
Deque is empty
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
1
Enter an element to Insert at Front:
3
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
5
3->NULL

1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
2
Enter an element to Insert at Rear:
5
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
5
3->5->NULL
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
3
The deleted element from Front : 3
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
5
5->NULL
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
4
The deleted element from Rear : 5
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display

6.Exit
Enter your choice:
5
Deque is empty
1.Insert at Front
2.Insert at Rear
3.Delete from Front
4.Delete from Rear
5.Display
6.Exit
Enter your choice:
6

**Aim:**

Fill in the missing code in the `insertAtEndInDLL(NODE first, int x)` and `traverseListInDLL(NODE first)` methods.

The `insertAtEndInDLL()` function adds an element to the end of the list.

The `traverseListInDLL()` function traverses and prints all the elements of the list.

**Source Code:**

DoubleLL1.c

```
#include<stdio.h>
#include<stdlib.h>

#include "InsertEndAndTraverseInDLL.c"

void main() {
    NODE first = NULL;
    int x, op;
    while(1) {
        printf("1.Insert At End 2.Traverse the List 3.Exit\n");
        printf("Enter your option : ");
        scanf("%d", &op);
        switch(op) {
            case 1: printf("Enter an element : ");
                    scanf("%d", &x);
                    first = insertAtEndInDLL(first, x);
                    break;
            case 2: if (first == NULL) {
                        printf("Double Linked List is empty\n");
                    } else {
                        printf("The elements in DLL are : ");
                        traverseListInDLL(first);
                    }
                    break;
            case 3: exit(0);
        }
    }
}
```

InsertEndAndTraverseInDLL.c

```

struct node {
    int data;
    struct node *prev;
    struct node *next;
};
typedef struct node * NODE;

NODE createNodeInDLL() {
    NODE temp;
    temp = (NODE)malloc(sizeof(struct node));
    temp->prev = NULL;
    temp->next = NULL;
    return temp;
}

NODE insertAtEndInDLL(NODE first, int x) {
    NODE temp;
    temp=(NODE)malloc(sizeof(struct node));
    temp->data=x;
    if(first==NULL)
    {
        first=temp;
        temp->prev=NULL;
        temp->next=NULL;
    }
    else{
        NODE next_node;
        next_node=first;
        while(next_node->next!=NULL)
        {
            next_node=next_node->next;
        }
        next_node->next=temp;
        temp->prev=next_node;
        temp->next=NULL;
    }
    return first;
}

void traverseListInDLL(NODE first) {
    NODE temp;
    temp=first;
    while(temp!=NULL)
    {
        printf("%d <--> ",temp->data);
        temp=temp->next;
    }
    printf("NULL\n");
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1

User Output
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
14
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
67
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
56
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
2
The elements in DLL are : 14 <--> 67 <--> 56 <--> NULL
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
1
Enter an element :
34
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
2
The elements in DLL are : 14 <--> 67 <--> 56 <--> 34 <--> NULL
1.Insert At End 2.Traverse the List 3.Exit
Enter your option :
3



S.No: 17	Exp. Name: <b><i>Implement double linked list</i></b>	Date: 2024-04-26
----------	---	------------------

**Aim:**

Write a C program to implement double linked list and its operations

**Source Code:**

AllOperationsDLL.c

```

#include<stdio.h>
#include<stdlib.h>
struct node {
int data;
struct node *next, *prev;
};
typedef struct node *NODE;
NODE createNode() {
    NODE temp;
    temp = (NODE)malloc(sizeof(struct node));
    temp->next = NULL;
    temp->prev = NULL;
    return temp;
}
NODE insertAtBegin(NODE first, int X) {
    NODE temp;
    temp = createNode();
    temp->data = X;
    temp->next = first;
    if(first != NULL)
        first->prev = temp;
    return temp;
}
NODE deleteAtBegin(NODE first) {
    NODE temp = first;
    int value;
    value = first->data;
    if(first->next == NULL)
    {
        free(first);
        first = NULL;
    }
    else
    {
        first = first->next;
        first->prev = NULL;
        free(temp);
    }
    printf("The deleted element from DLL : %d\n", value);
    return first;
}
void search(NODE first, int X) {
    NODE temp = first;
    int pos = 0;
    while(temp!=NULL) {
        pos++;
        if(temp->data == X)
            break;
        temp = temp->next;
    }
    if(temp == NULL)
        printf("The given element %d is not found in the given DLL\n", X);
    else
        printf("The given element %d is found at position : %d\n",X, pos);
}

```

```

        while(temp !=NULL) {
            printf("%d <--> ", temp->data);
            temp = temp->next;
        }
        printf("NULL\n");
    }
}

void main() {
    NODE first = NULL;
    int X, op;
    while(1) {
        printf("1.Insert At Begin\n2.Delete at Begin\n3.Search an element\n4.Traverse the List\n5.Exit\n");
        printf("Enter your option : ");
        scanf("%d", &op);
        switch(op) {
            case 1:
                printf("Enter an element: ");
                scanf("%d", &X);
                first = insertAtBegin(first, X);
                break;
            case 2:
                if(first == NULL) {
                    printf("Double Linked List is empty so deletion is not\n");
                } else {
                    first = deleteAtBegin(first);
                }
                break;
            case 3:
                printf("Enter search element: ");
                scanf("%d", &X);
                search(first, X);
                break;
            case 4:
                if(first == NULL) {
                    printf("Double Linked List is empty\n");
                } else {
                    printf("The elements in DLL are: ");
                    traverseList(first);
                }
                break;
            case 5:
                exit(0);
        }
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
User Output
1.Insert At Begin
2.Delete at Begin

3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
1
Enter an element:
15
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
2
The deleted element from DLL : 15
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
1
Enter an element:
12
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
1
Enter an element:
16
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
1
Enter an element:
17
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
4
The elements in DLL are: 17 <--> 16 <--> 12 <--> NULL

1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
3
Enter search element:
16
The given element 16 is found at position : 2
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
4
The elements in DLL are: 17 <--> 16 <--> 12 <--> NULL
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
5

Test Case - 2
User Output
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
2
Double Linked List is empty so deletion is not possible
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
4
Double Linked List is empty
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit

Enter your option :
1
Enter an element:
101
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
1
Enter an element:
102
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
1
Enter an element:
103
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
6
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
2
The deleted element from DLL : 103
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
4
The elements in DLL are: 102 <--> 101 <--> NULL
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit

Enter your option :
3
Enter search element:
103
The given element 103 is not found in the given DLL
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
4
The elements in DLL are: 102 <--> 101 <--> NULL
1.Insert At Begin
2.Delete at Begin
3.Search an element Position
4.Traverse the List
5.Exit
Enter your option :
5

S.No: 18	Exp. Name: <b>Double Linked List Operations</b>	Date: 2024-04-26
----------	---	------------------

**Aim:**

Write a C program to implement a menu-driven program for the following operations on Doubly Linked List (DLL) of Employee Data with the fields:

SSN, Name, Dept, Designation, Salary, PhNo

- 8. Create a DLL of N Employees Data by using end insertion.
- 9. Display the status of DLL and count the number of nodes in it
- 10. Perform Insertion and Deletion at End of DLL
- 11. Perform Insertion and Deletion at Front of DLL
- 12. Exit

**Source Code:**

dll0ps.c



```

#include<stdio.h>
#include<stdlib.h>
#include<conio.h>
struct node{
char ssn[25],name[25],dept[50],designation[25];
int sal;
long long int phone;
struct node *llink;
struct node *rlink;
};
typedef struct node *NODE;
NODE first = NULL;
int count=0;
NODE create()
{
    NODE enode;
    enode = (NODE)malloc(sizeof(struct node));
    if(enode==NULL)
    {
        printf("\nRunning out of memory");
        exit(0);
    }
    printf("Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee: ");
    scanf("%s %s %s %s %d %lld",enode->:ssn,enode->name,enode->dept,enode->
>designation,&enode->sal,&enode->phone);
    enode->llink=NULL;
    enode->rlink=NULL;
    count++;
    return enode;
}
NODE insertfront(){
    NODE temp;
    temp=create();
    if(first==NULL)
        return temp;
    temp->rlink=first;
    first->llink=temp;
    return temp;
}
void display()
{
    NODE cur;
    cur=first;
    if(cur==NULL)
        printf("DLL is Empty\n");
    else{
        while(cur!=NULL)
        {
            printf("SSN:%s| Name:%s| Department:%s| Designation:%s|
Salary:%d| Phone no:%lld",cur->:ssn,cur->name,cur->dept,cur->designation,cur->sal,cur-
>phone);
            cur=cur->rlink;
            printf("\n");
        }printf("No of employees: %d\n",count);
    }
}

```

```

{
    NODE temp;
    if(first==NULL)
    {
        printf("DLL is empty\n");
        return NULL;
    }
    if(first->rlink==NULL)
    {
        printf("employee with ssn: %s is deleted\n",first->:ssn);
        free(first);
        count--;
        return NULL;
    }
    temp=first;
    first=first->rlink;
    temp->rlink=NULL;
    first->llink=NULL;
    printf("employee with ssn: %s is deleted\n",temp->:ssn);
    free(temp);
    count--;
    return first;
}

NODE insertend()
{
    NODE cur,temp;
    temp=create();
    if(first==NULL)
    {
        return temp;
    }
    cur=first;
    while(cur->rlink!=NULL){
        cur=cur->rlink;
    }
    cur->rlink=temp;
    temp->llink=cur;
    return first;
}

NODE deleteend()
{
    NODE prev,cur;
    if(first==NULL)
    {
        printf("DLL is empty\n");
        return NULL;
    }
    if(first->rlink==NULL)
    {
        printf("employee with ssn: %s is deleted\n",first->:ssn);
        free(first);
        count--;
        return NULL;
    }
    prev=NULL;

```

```

        {
            prev=cur;
            cur=cur->rlink;
        }
        cur->llink=NULL;
        printf("employee with ssn: %s is deleted\n",cur->:ssn);
        free(cur);
        prev->rlink=NULL;
        count--;
        return first;
    }
    void main()
    {
        int ch,i,n;
        while(1){
            printf("1: Create DLL of Employee Nodes");
            printf("\n2: DisplayStatus");
            printf("\n3: InsertAtEnd");
            printf("\n4: DeleteAtEnd");
            printf("\n5: InsertAtFront");
            printf("\n6: DeleteAtFront");
            printf("\n7: Exit");
            printf("\nPlease enter your choice: ");
            scanf("%d",&ch);
            switch(ch)
            {
                case 1:printf("Enter no of Employees: ");
                    scanf("%d",&n);
                    for(i=1;i<=n;i++)
                        first=insertend();
                    break;
                case 2:display();
                    break;
                case 3:first=insertend();
                    break;
                case 4:first=deleteend();
                    break;
                case 5:first=insertfront();
                    break;
                case 6:first=deletefront();
                    break;
                case 7:exit(0);
                default :printf("Please Enter valid choice\n");
            }
        }
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
User Output
1: Create DLL of Employee Nodes

2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
DLL is Empty
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
1
Enter no of Employees:
2
Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee:
CT156 Hema Support PSE 30000 1234567890
Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee:
CT188 Prasanth Support PSE 30000 1234567890
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:CT156  Name:Hema  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
SSN:CT188  Name:Prasanth  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
No of employees: 2
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
3
Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee:
CT226 Swathi Support PSE 30000 1234567890
1: Create DLL of Employee Nodes

2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:CT156  Name:Hema  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
SSN:CT188  Name:Prasanth  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
SSN:CT226  Name:Swathi  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
No of employees: 3
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
4
employee with ssn: CT226 is deleted
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:CT156  Name:Hema  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
SSN:CT188  Name:Prasanth  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
No of employees: 2
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
5
Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee:
CT156 Bhanu Support PSE 34000 1234567890
1: Create DLL of Employee Nodes

2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:CT156  Name:Bhanu  Department:Support  Designation:PSE  Salary:34000  Phone no:1234567890
SSN:CT156  Name:Hema  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
SSN:CT188  Name:Prasanth  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
No of employees: 3
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:CT156  Name:Bhanu  Department:Support  Designation:PSE  Salary:34000  Phone no:1234567890
SSN:CT156  Name:Hema  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
SSN:CT188  Name:Prasanth  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
No of employees: 3
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
6
employee with ssn: CT156 is deleted
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
4
employee with ssn: CT188 is deleted
1: Create DLL of Employee Nodes

2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:CT156  Name:Hema  Department:Support  Designation:PSE  Salary:30000  Phone no:1234567890
No of employees: 1
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
6
employee with ssn: CT156 is deleted
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
DLL is Empty
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
4
DLL is empty
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
6
DLL is empty

1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
3
Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee:
198 Tanjiro Anime Hero 49000 1029384756
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:198  Name:Tanjiro  Department:Anime  Designation:Hero  Salary:49000  Phone no:1029384756
No of employees: 1
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
4
employee with ssn: 198 is deleted
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
7

Test Case - 2
User Output
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd



5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
3
Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee:
CT590 Japan Korea Indonesia 39000
0987654321
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:CT590  Name:Japan  Department:Korea  Designation:Indonesia  Salary:39000  Phone no:987654321
No of employees: 1
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
6
employee with ssn: CT590 is deleted
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
DLL is Empty
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
5
Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee:

AP996 Sampath Support PSE 15000 9086745231
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:AP996  Name:Sampath  Department:Support  Designation:PSE  Salary:15000  Phone no:9086745231
No of employees: 1
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
4
employee with ssn: AP996 is deleted
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
DLL is Empty
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
1
Enter no of Employees:
1
Enter ssn, Name, Department, Designation, Salary, PhoneNo of employee:
TS289 Kalkanrat PublicSector Government 58000 1029238845
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd

4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
2
SSN:TS289  Name:Kalkanrat  Department:PublicSector  Designation:Government  Salary:58000  Phone no:1029238845
No of employees: 1
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
8
Please Enter valid choice
1: Create DLL of Employee Nodes
2: DisplayStatus
3: InsertAtEnd
4: DeleteAtEnd
5: InsertAtFront
6: DeleteAtFront
7: Exit
Please enter your choice:
7

S.No: 19	Exp. Name: <b>Write Code for insertAtBeginInCLL() and countInCLL() functions in CLL</b>	Date: 2024-04-19
----------	---	------------------

**Aim:**

Fill in the missing code in the below functions `insertAtBeginInCLL(NODE first, int x)` and `countInCLL(NODE first)` in the file `InsAtBeginAndCountInCLL.c`.

The `insertAtBeginInCLL(NODE first, int x)` function inserts a new node at the beginning of the circular linked list.

The `countInCLL(NODE first)` function counts the number of nodes linked in a circular linked list.

**Source Code:**

CircularLL2.c

```
#include <stdio.h>
#include <stdlib.h>

#include "InsAtBeginAndCountInCLL.c"

void main() {
    NODE first = NULL;
    int x, op;
    while(1) {
        printf("1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List\n");
        printf("Enter your option : ");
        scanf("%d", &op);
        switch(op) {
            case 1: printf("Enter an element : ");
                    scanf("%d", &x);
                    first = insertAtBeginInCLL(first, x);
                    break;
            case 2: printf("The number of nodes in a CLL are : %d\n",
countInCLL(first));
                    break;
            case 3: if (first == NULL) {
                        printf("Circular Linked List is empty\n");
                    } else {
                        printf("The elements in CLL are : ");
                        traverseListInCLL(first);
                    }
                    break;
            case 4: exit(0);
        }
    }
}
```

InsAtBeginAndCountInCLL.c

```

struct node {
    int data;
    struct node *next;
};
typedef struct node *NODE;

NODE createNodeInCLL() {
    NODE temp;
    temp = (NODE) malloc(sizeof(struct node));
    temp -> next = NULL;
    return temp;
}

NODE insertAtBeginInCLL(NODE first, int x) {
    NODE newnode=createNodeInCLL();
    NODE ptr=first;
    newnode->data=x;
    if(first==NULL)
    {
        first=newnode;
        newnode->next=newnode;
    }
    else
    {
        do{
            ptr=ptr->next;
        }
        while(ptr->next!=first);
        newnode->next=first;
        first=newnode;
        ptr->next=newnode;
    }
    return first;
}

int countInCLL(NODE first) {
    int cnt=1;
    NODE ptr=first;
    if(first==NULL)
        return 0;
    while(ptr->next!=first)
    {
        ptr=ptr->next;
        cnt++;
    }
    return cnt;
}

void traverseListInCLL(NODE first) {
    NODE temp = first;
    do {
        printf("%d --> ", temp -> data);
        temp = temp -> next;
    } while (temp != first);
    printf("\n");
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :
11
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :
22
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
2
The number of nodes in a CLL are : 2
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
3
The elements in CLL are : 22 --> 11 -->
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :
33
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :
44
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
3
The elements in CLL are : 44 --> 33 --> 22 --> 11 -->
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
2
The number of nodes in a CLL are : 4
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
4

Test Case - 2
<b>User Output</b>
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit

Enter your option :
3
Circular Linked List is empty
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
2
The number of nodes in a CLL are : 0
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
1
Enter an element :
99
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
2
The number of nodes in a CLL are : 1
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
3
The elements in CLL are : 99 -->
1.Insert At Begin 2.Count Number of Nodes 3.Traverse the List 4.Exit
Enter your option :
4

<b>S.No: 20</b>	Exp. Name: <b><i>C program which performs all operations in Circular linked list.</i></b>	<b>Date: 2024-06-08</b>
-----------------	---	-------------------------

**Aim:**

Write a program that uses functions to perform the following operations on circularlinked list.

- i) Creation
- ii) Insertion
- iii) Deletion
- iv) Traversal

**Source Code:**

AlloperationsinCLL.c



```

#include<stdio.h>
#include<stdlib.h>
struct node
{
int data;
struct node *next;
};
typedef struct node*NODE;
NODE createNodeInCLL()
{
    NODE temp;
    temp=(NODE)malloc(sizeof(struct node));
    return temp;
}
NODE insertAtBeginInCLL(NODE first,int x)
{
    NODE newnode=createNodeInCLL();
    NODE ptr=first;
    newnode->data=x;
    if(first==NULL)
    {
        first=newnode;
        newnode->next=newnode;
    }
    else
    {
        do{
            ptr=ptr->next;
        }while(ptr->next!=first);
        newnode->next=first;
        first=newnode;
        ptr->next=newnode;
    }
    return first;
}
NODE deleteFromBeginInCLL(NODE first)
{
    NODE ptr=first;
    if(ptr->next==first)
    {
        printf("The deleted element from CLL : %d\n",ptr->data);
        free(ptr);
        first=NULL;
    }
    else
    {
        do{
            ptr=ptr->next;
        }while(ptr->next!=first);
        ptr->next=first->next;
        printf("The deleted element from CLL : %d\n",first->data);
        free(first);
        first=ptr->next;
    }
    return first;
}

```

```

{
    NODE ptr=first,preptr;
    if(ptr->next==first)
    {
        printf("The deleted element from CLL : %d\n",preptr->data);
        free(ptr);
        first=NULL;
    }
    else
    {
        do{
            preptr=ptr;
            ptr=ptr->next;
        }while(ptr->next!=first);
        preptr->next=ptr->next;
        printf("The deleted element from CLL : %d\n",ptr->data);
        free(ptr);
    }
    return first;
}

NODE insertAtEndInCLL(NODE first,int x)
{
    NODE newnode=createNodeInCLL();
    NODE ptr=first;
    newnode->data=x;
    if(first==NULL)
    {
        first=newnode;
        newnode->next=newnode;
    }
    else
    {
        do{
            ptr=ptr->next;
        }while(ptr->next!=first);
        newnode->next=first;
        ptr->next=newnode;
    }
    return first;
}

int countInCLL(NODE first)
{
    int cnt=1;
    NODE ptr=first;
    if(first==NULL)
        return 0;
    while(ptr->next!=first)
    {
        ptr=ptr->next;
        cnt++;
    }
    return cnt;
}

NODE insertAtPos(NODE first,int x,int pos)
{

```

```

        else if(pos==countInCLL(first)+1)
            first=insertAtEndInCLL(first,x);
        else{
            NODE newnode=createNodeInCLL();
            newnode->data=x;
            NODE preptr=first;
            for(int i=1;i<pos-1;i++)
                preptr=preptr->next;
            newnode->next=preptr->next;
            preptr->next=newnode;
        }
        return first;
    }
}
NODE deleteFromPos(NODE first,int pos)
{
    if(pos==1)
        first=deleteFromBeginInCLL(first);
    else if(pos==countInCLL(first))
        first=deleteFromEndInCLL(first);
    else
    {
        NODE preptr=first,pre;
        for(int i=1;i<pos;i++)
        {
            pre=preptr;
            preptr=preptr->next;
        }
        printf("The deleted element from CLL : %d\n",preptr->data);
        pre->next=preptr->next;
        free(preptr);
    }
    return first;
}
void traverseListInCLL(NODE first)
{
    NODE temp=first;
    do{
        printf("%d --> ",temp->data);
        temp=temp->next;
    }while(temp!=first);
    printf("\n");
}
void main()
{
    NODE first=NULL;
    int x,op,pos;
    while(1)
    {
        printf("1.Insert 2.Delete 3.Print 4.Exit\n");
        printf("Enter your option: ");
        scanf("%d",&op);
        switch(op)
        {
            case 3: if(first==NULL)
                    printf("Circular Linked List is empty\n");

```

```

        traverseListInCLL(first);
    }
    break;
    case 1:printf("Enter a position: ");
    scanf("%d",&pos);
    printf("Enter an element: ");
    scanf("%d", &x);
    if(pos>0 &&pos<=countInCLL(first)+1)
        first=insertAtPos(first,x,pos);
    else
        printf("No such position in CLL so insertion
is not possible\n");

    break;
    case 2:if(first==NULL)
        printf("Circular Linked List is empty so
deletion is not possible\n");

    else
    {
        printf("Enter position : ");
        scanf("%d",&pos);
        if(pos>0 &&pos<=countInCLL(first))
            first=deleteFromPos(first,pos);
        else
            printf("No such position in CLL so deletion
is not possible\n");
    }
    break;
    case 4: exit(0);
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
1
Enter an element:
1
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
2
Enter an element:
2

1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
3
Enter an element:
3
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
4
Enter an element:
4
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
5
Enter an element:
5
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
6
Enter an element:
6
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
3
The elements in CLL are: 1 --> 2 --> 3 --> 4 --> 5 --> 6 -->
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
2
Enter position :
3
The deleted element from CLL : 3
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
2
Enter position :
3
The deleted element from CLL : 4
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
2
Enter position :
3

The deleted element from CLL : 5
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
3
The elements in CLL are: 1 --> 2 --> 6 -->
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
3
Enter an element:
3
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
4
Enter an element:
4
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
5
Enter an element:
5
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
3
The elements in CLL are: 1 --> 2 --> 3 --> 4 --> 5 --> 6 -->
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
4

Test Case - 2
<b>User Output</b>
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
2
Circular Linked List is empty so deletion is not possible
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
3
Circular Linked List is empty
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:

1
Enter an element:
15
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
1
Enter a position:
3
Enter an element:
17
No such position in CLL so insertion is not possible
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
2
Enter position :
3
No such position in CLL so deletion is not possible
1.Insert 2.Delete 3.Print 4.Exit
Enter your option:
4

S.No: 21	Exp. Name: <i>Stack using Arrays</i>	Date: 2024-06-07
----------	--------------------------------------	------------------

**Aim:**

Write a C program to implement stack operations using arrays.

**Input Format**

The program presents a menu with six options. The user inputs a choice corresponding to one of these options:

- 13. **Push Operation:** Input is an integer value to push onto the stack.
- 14. **Pop Operation:** No additional input is required.
- 15. **Display Operation:** No additional input is required.
- 16. **Is Empty Operation:** No additional input is required.
- 17. **Peek Operation:** No additional input is required.
- 18. **Exit Operation:** No additional input is required.

**Output Format**

The output will vary based on the selected option:

- 19. **Push Operation:**
  - iv. If the stack is not full, the output will be: **Successfully pushed**
  - iv. If the stack is full, the output will be: **Stack is overflow**
- 22. **Pop Operation:**
  - iv. If the stack is not empty, it will print: **Popped value: X** where X is the element removed from the stack.
  - iv. If the stack is empty, it will print: **Stack is underflow**
- 25. **Display Operation:**
  - iv. If the stack is not empty, it will print: **Elements: X Y Z ...** where X, Y, Z, etc., are the elements of the stack from top to bottom.
  - iv. If the stack is empty, it will print: **Stack is empty**
- 28. **Is Empty Operation:**
  - iv. If the stack is empty, it will print: **Stack is empty**
  - iv. If the stack is not empty, it will print: **Stack is not empty**
- 31. **Peek Operation:**
  - iv. If the stack is not empty, it will print: **Peek value: X** where X is the top element of the stack.
  - iv. If the stack is empty, it will print: **Stack is underflow**
- 34. **Exit Operation:**
  - iv. The program will terminate with no additional output beyond the program's exit.

**Source Code:**

StackUsingArray.c



```

#include <stdio.h>
#include <stdlib.h>
#define STACK_MAX_SIZE 10
#include "StackOperations.c"

int main() {
    int op, x;
    while(1) {
        printf("1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit\n");
        printf("Option: ");
        scanf("%d", &op);
        switch(op) {
            case 1:
                printf("element: ");
                scanf("%d", &x);
                push(x);
                break;
            case 2:
                pop();
                break;
            case 3:
                display();
                break;
            case 4:
                isEmpty();
                break;
            case 5:
                peek();
                break;
            case 6:
                exit(0);
        }
    }
}

```

StackOperations.c

```

// declare the size of the array
int stack[100];
// define the top to -1

int top=-1;

void push(int element) {
    // write your code here to push an element
    if(top==STACK_MAX_SIZE-1)
        printf("Stack is overflow\n");
    else{
        top++;
        stack[top]=element;
        printf("Successfully pushed\n");
    }
}

void display() {
    // write your code here to display the stack
    if(top== -1)
        printf("Stack is empty\n");
    else
    {
        int i;
        printf("Elements: ");
        for(i=top; i>=0; i--)
            printf("%d ", stack[i]);
        printf("\n");
    }
}

void pop() {
    // write your code here to pop an element
    if(top== -1)
        printf("Stack is underflow\n");
    else{
        printf("Popped value: %d\n", stack[top]);
        top--;
    }
}

void peek(){
    // write your code here to find the peek element
    if(top== -1)
        printf("Stack is underflow\n");
    else{
        printf("Peek value: %d\n", stack[top]);
    }
}

void isEmpty() {
    // write your code here to check whether the stack is empty not
    if(top== -1)
        printf("Stack is empty\n");
    else
        printf("Stack is not empty\n");
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
4
Stack is empty
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
2
Stack is underflow
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
3
Stack is empty
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
5
Stack is underflow
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
25
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
26
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
3
Elements: 26 25
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
2
Popped value: 26
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
4
Stack is not empty
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
5
Peek value: 25
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit

Option:
6

Test Case - 2
<b>User Output</b>
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
1
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
2
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
3
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
4
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
5
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
6
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
7
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit

Option:
1
element:
8
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
9
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
10
Successfully pushed
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
1
element:
11
Stack is overflow
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Option:
6

S.No: 22	Exp. Name: <b>C program to implement different Operations on Stack using Linked Lists</b>	Date: 2024-06-07
----------	---	------------------

**Aim:**

Write a program to implement **stack** using **linked lists**.

**Input Format**

The user is presented with a menu of options and provides input according to the desired operation:

- 36. **Push Operation:**  
nt. Input: Integer value to be pushed onto the stack.
- 38. **Pop Operation:**  
nt. No additional input is required.
- 40. **Display Operation:**  
nt. No additional input is required.
- 42. **Is Empty Operation:**  
nt. No additional input is required.
- 44. **Peek Operation:**  
nt. No additional input is required.
- 46. **Exit Operation:**  
47. No additional input is required.

**Output Format**

The output will vary depending on the selected option:

- 48. **Push Operation:**  
nt. If the stack is not full (no overflow), the output will be: **Successfully pushed**.If memory allocation fails, it will print: **Stack is overflow**.
- 50. **Pop Operation:**  
nt. If the stack is not empty, it will print: **Popped value = X** where X is the value removed from the stack.If the stack is empty, it will print: **Stack is underflow**.
- 52. **Display Operation:**  
nt. If the stack is not empty, it will print: **Elements of the stack are : X Y Z ...** where X, Y, Z, etc., are the elements from top to bottom.If the stack is empty, it will print: **Stack is empty**.
- 54. **Is Empty Operation:**  
nt. If the stack is empty, it will print: **Stack is empty**.If the stack is not empty, it will print: **Stack is not empty**.
- 56. **Peek Operation:**  
nt. If the stack is not empty, it will print: **Peek value = X** where X is the top element of the stack.If the stack is empty, it will print: **Stack is underflow**.
- 58. **Exit Operation:**  
59. The program terminates with no additional output.

**Source Code:**

StackUsingLL.c

```

#include <stdio.h>
#include <stdlib.h>
#include "StackOperationsLL.c"

int main() {
    int op, x;
    while(1) {
        printf("1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit\n");
        printf("Enter your option : ");
        scanf("%d", &op);
        switch(op) {
            case 1:
                printf("Enter element : ");
                scanf("%d", &x);
                push(x);
                break;
            case 2:
                pop();
                break;
            case 3:
                display();
                break;
            case 4:
                isEmpty();
                break;
            case 5:
                peek();
                break;
            case 6:
                exit(0);
        }
    }
}

```

StackOperationsLL.c

```

//write your code here
struct node
{
int data;
struct node *next;
};
typedef struct node * stk;
stk top=NULL;
void push(int x)
{
    stk newnode;
    newnode=(stk)malloc(sizeof(struct node));
    newnode->data=x;
    if(top==NULL)
    {
        newnode->next=NULL;
        top=newnode;
    }
    else
    {
        newnode->next=top;
        top=newnode;
    }
    printf("Successfully pushed.\n");
}
void pop()
{
    if(top==NULL)
        printf("Stack is underflow.\n");
    else
    {
        stk temp=top;
        top=top->next;
        printf("Popped value = %d\n",temp->data);
        free(temp);
    }
}
void display()
{
    stk temp=top;
    if(top==NULL)
        printf("Stack is empty.\n");
    else
    {
        printf("Elements of the stack are : ");
        while(temp!=NULL)
        {
            printf("%d ",temp->data);
            temp=temp->next;
        }
        printf("\n");
    }
}
void isEmpty()
{

```



```

        else
            printf("Stack is not empty.\n");
    }
    void peek()
    {
        if(top==NULL)
            printf("Stack is underflow.\n");
        else
            printf("Peek value = %d\n",top->data);
    }

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
1
Enter element :
33
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
1
Enter element :
22
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
1
Enter element :
55
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
1
Enter element :
66
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
3
Elements of the stack are : 66 55 22 33
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
2
Popped value = 66
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit

Enter your option :
2
Popped value = 55
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
3
Elements of the stack are : 22 33
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
5
Peek value = 22
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
4
Stack is not empty.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
6

Test Case - 2
User Output
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
2
Stack is underflow.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
3
Stack is empty.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
5
Stack is underflow.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
4
Stack is empty.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
1
Enter element :
23
Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
1
Enter element :
24

Successfully pushed.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
3
Elements of the stack are : 24 23
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
5
Peek value = 24
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
2
Popped value = 24
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
2
Popped value = 23
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
2
Stack is underflow.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
4
Stack is empty.
1.Push 2.Pop 3.Display 4.Is Empty 5.Peek 6.Exit
Enter your option :
6

S.No: 23	Exp. Name: <b>C program to evaluate a Postfix expression</b>	Date: 2024-06-07
----------	--	------------------

**Aim:**

C program to evaluate a postfix expression.

Write the code in the functions **isEmpty()**, **push(int x)**, **pop()** and **evaluatePostfix(char \*e)** in the below program according to hints given as comment lines.

**Input Format**

- The user will provide a postfix expression as a single string of characters. The expression can contain digits (0-9) and operators (+, -, \*, /, %).

**Output Format**

- If the postfix expression is valid, the program prints the result of the evaluation in the format:
- If the postfix expression is invalid (e.g., insufficient operands for the operators or extra operands remaining), the program prints: **Invalid postfix expression.**

**Source Code:**

PostfixEvaluation.c

```

#include <ctype.h>
#include <stdio.h>
#include<stdlib.h>
#define STACK_MAX_SIZE 20

void push(int);
int pop();
int is_operator(char);

int stack[STACK_MAX_SIZE];
int top=-1;
int main()
{
    char exp[20];
    char *e,x;
    printf("Enter the postfix expression : ");
    scanf("%s",exp);
    e=exp;

    int op1,op2,result;

    while(*e!='\0')
    {
        if(isalnum(*e))
        {
            int num = *e-'0';
            push(num);
        }
        else if(is_operator(*e))
        {
            op2=pop();
            op1=pop();
            switch(*e)
            {
                case '+': result = op1+op2;
                break;

                case '-': result=op1-op2;
                break;

                case '*': result=op1*op2;
                break;

                case '/': result=op1/op2;
                break;

            }
            push(result);
        }
        e++;
    }
    result=pop();
    if(top== -1)
        printf("Result : %d\n",result);
    else

```

```

int is_operator(char symbol)
{
    if(symbol=='+' || symbol=='-'
        || symbol=='*' || symbol=='/')
    {
        return 1;
    }
    return 0;
}

void push(int x)
{
    if(top==STACK_MAX_SIZE - 1)
    {
        printf("Stack Overflow\n");
        return;
    }
    top++;
    stack[top]=x;
}

int pop()
{
    if(top== -1)
    {
        printf("Invalid postfix expression.\n");
        exit(0);
    }
    else
    {
        int item = stack[top];
        top--;
        return item;
    }
}

```

### Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Enter the postfix expression :
234+-
Result : -5

Test Case - 2
<b>User Output</b>
Enter the postfix expression :
-456+5+
Invalid postfix expression.

<b>S.No: 24</b>	Exp. Name: <b><i>Check for the balanced parenthesis using a stack</i></b>	<b>Date: 2024-06-07</b>
-----------------	---	-------------------------

**Aim:**

Write a C program to check whether an expression consists of balanced parenthesis or not using stack

**Source Code:**

```
BalancedParenthesis.c
```

```

#include<stdio.h>
#include<stdlib.h>
#include<string.h>
#define MAX_SIZE 100
char stack[MAX_SIZE];
int top = -1;
void push(char data) {
    if (top == MAX_SIZE - 1) {
        return;
    }
    top++;
    stack[top] = data;
}
char pop() {
    if (top == -1) {
        return ' ';
    }
    char data = stack[top];
    top--;
    return data;
}
int is_matching_pair(char char1, char char2){
    if (char1 == '(' && char2 == ')') {
        return 1;
    }
    else if (char1 == '[' && char2 == ']') {
        return 1;
    }
    else if (char1 == '{' && char2 == '}') {
        return 1;
    }
    else{
        return 0;
    }
}
int isBalanced(char* text) {
    int i;
    for (i = 0; i < strlen(text); i++){
        if(text[i] == '(' || text[i] == '[' || text[i] == '{'){
            push(text[i]);

        }else if (text[i] == ')' || text[i] == ']' || text[i] == '}') {
            if (top == -1){

                return 0;
            }
            else if(!is_matching_pair(pop(),text[i])) {
                return 0;
            }
        }
    }
    if (top == -1) {
        return 1;
    } else {
        return 0;
    }
}

```



```

int main() {
    char text[MAX_SIZE];
    printf("Enter an expression: ");
    scanf("%s",text);
    if (isBalanced(text))
        printf("balanced\n");
    else
        printf("not balanced\n");
    return 0;
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Enter an expression:
1+2*3+(3+4)
balanced

Test Case - 2
<b>User Output</b>
Enter an expression:
1+2*(3+([4+5]))
not balanced

**Aim:**

Write a program to implement queue operations using static arrays

**Source Code:**

QueueUsingArray.c

```
#include <stdlib.h>
#include <stdio.h>
#include "QueueOperations.c"
int main() {
    int op, x;
    while(1) {
        printf("1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit\n");
        printf("Enter your option : ");
        scanf("%d",&op);
        switch(op) {
            case 1:
                printf("Enter element : ");
                scanf("%d",&x);
                enqueue(x);
                break;
            case 2:
                dequeue();
                break;
            case 3:
                display();
                break;
            case 4:
                isEmpty();
                break;
            case 5:
                size();
                break;
            case 6: exit(0);
        }
    }
    return 0;
}
```

QueueOperations.c

```

#define maxsize 50
int front = -1, rear = -1;
int queue[maxsize];
void enqueue(int item)
{
    if(rear == maxsize-1)
    {
        printf("Queue is overflow.\n");
        return;
    }
    if(front == -1 && rear == -1)
    {
        front = 0;
        rear = 0;
    }
    else
    {
        rear = rear+1;
    }
    queue[rear] = item;
    printf("Successfully inserted.\n");
}
void dequeue()
{
    int item;
    if (front == -1 || front > rear)
    {
        printf("Queue is underflow.\n");
        return;
    }
    else
    {
        item = queue[front];
        if(front == rear)
        {
            front = -1;
            rear = -1;
        }
        else
            front = front + 1;
        printf("Deleted element = %d\n", item);
    }
}
void display()
{
    int i;
    if(rear == -1)
    {
        printf("Queue is empty.\n");
    }
    else
    {
        printf("Elements in the queue : ");
        for(i=front; i<=rear; i++)
            printf("%d ", queue[i]);
    }
}

```

```

}
void isEmpty()
{
    if(front==-1)
printf("Queue is empty.\n");
    else
        printf("Queue is not empty.\n");
}
void size()
{
    int cnt=0;
    if(front!=-1)
        cnt=rear-front+1;
    printf("Queue size : %d\n",cnt);
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
2
Queue is underflow.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
3
Queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
4
Queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
5
Queue size : 0
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
1
Enter element :
14
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
1
Enter element :
78
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit

Enter your option :
1
Enter element :
53
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
3
Elements in the queue : 14 78 53
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
5
Queue size : 3
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
6

Test Case - 2
<b>User Output</b>
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
1
Enter element :
25
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
2
Deleted element = 25
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
2
Queue is underflow.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
3
Queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
1
Enter element :
65
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
3
Elements in the queue : 65
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit

Enter your option :
4
Queue is not empty.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
2
Deleted element = 65
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
4
Queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
5
Queue size : 0
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
1
Enter element :
63
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
5
Queue size : 1
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Enter your option :
6

**Aim:**

Write a C program to implement queue using **linked lists**.

**Source Code:**

QueueUsingLL.c

```
#include <stdlib.h>
#include <stdio.h>
#include "QueueOperationsLL.c"
int main() {
    int op, x;
    while(1) {
        printf("1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit\n");
        printf("Option: ");
        scanf("%d",&op);
        switch(op) {
            case 1:
                printf("element: ");
                scanf("%d",&x);
                enqueue(x);
                break;
            case 2:
                dequeue();
                break;
            case 3:
                display();
                break;
            case 4:
                isEmpty();
                break;
            case 5:
                size();
                break;
            case 6: exit(0);
        }
    }
}
```

QueueOperationsLL.c

```

struct node{
    int data;
    struct node* next;
};
typedef struct node *NODE;
NODE front=NULL,rear=NULL;
void enqueue(int item){
    NODE ptr;
    ptr=(struct node*)malloc(sizeof(struct node));
    ptr->data=item;
    printf("Successfully inserted\n");
    if(front==NULL){
        front=ptr;
        rear=ptr;
        front->next=NULL;
        rear->next=NULL;
    }
    else{
        rear->next=ptr;
        rear=ptr;
        rear->next=NULL;
    }
}
void dequeue(){
    NODE ptr;
    if(front==NULL)
        printf("Queue is underflow\n");
    else{
        ptr=front;
        printf("Deleted value: %d\n",ptr->data);
        front=front->next;
        free(ptr);
    }
}
void display()
{
    NODE ptr;
    ptr=front;
    if(front==NULL)
        printf("Queue is empty\n");
    else{
        printf("Elements: ");
        while(ptr!=NULL){
            printf("%d ",ptr->data);
            ptr=ptr->next;
        }
        printf("\n");
    }
}
void isEmpty()
{
    if(front==NULL)
        printf("Queue is empty\n");
    else

```



```

void size()
{
    int cnt=0;
    NODE ptr=front;
    while(ptr!=NULL){
        cnt++;
        ptr=ptr->next;
    }
    printf("Queue size: %d\n",cnt);
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
2
Queue is underflow
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
3
Queue is empty
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
4
Queue is empty
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
5
Queue size: 0
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
1
element:
44
Successfully inserted
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
1
element:
55
Successfully inserted
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
1
element:
66

Successfully inserted
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
1
element:
67
Successfully inserted
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
3
Elements: 44 55 66 67
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
2
Deleted value: 44
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
2
Deleted value: 55
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
5
Queue size: 2
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
4
Queue is not empty
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
6

<b>Test Case - 2</b>	
<b>User Output</b>	
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit	
Option:	
1	
element:	
23	
Successfully inserted	
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit	
Option:	
1	
element:	
234	
Successfully inserted	
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit	
Option:	
1	

element:
45
Successfully inserted
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
1
element:
456
Successfully inserted
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
2
Deleted value: 23
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
3
Elements: 234 45 456
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
2
Deleted value: 234
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
3
Elements: 45 456
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
4
Queue is not empty
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
5
Queue size: 2
1.Enqueue 2.Dequeue 3.Display 4.Is Empty 5.Size 6.Exit
Option:
6

<b>S.No: 27</b>	Exp. Name: <b><i>Simulation of a simple printer queue system.</i></b>	<b>Date: 2024-06-08</b>
-----------------	---	-------------------------

**Aim:**

Develop a C program to simulate a simple printer queue system.

**Note:** Before exiting the printer system, all the jobs must be done.

**Source Code:**

PrinterQueue.c

```

#include <stdio.h>
#include <stdlib.h>
struct node
{
int data;
struct node *next;
};
typedef struct node *NODE;
NODE front=NULL, rear=NULL;

void enqueue(int item)
{
    NODE ptr;
    ptr = (struct node *)malloc(sizeof(struct node));
    ptr->data=item;
    printf("Job %d added\n",item);
    if(front==NULL) {
        front=ptr;
        rear=ptr;
        front->next=NULL;
        rear->next=NULL;
    }
    else{
        rear->next=ptr;
        rear=ptr;
        rear->next= NULL;
    }
}

void dequeue()
{
    NODE ptr;
    if(front==NULL)
        printf("No job to dequeue\n");
    else
    {
        ptr=front;
        printf("Job %d removed from queue and sent to the printer\n",ptr->data);
        front=front->next;
        free(ptr);
    }
}

int main() {
    int op,x;
    while(1) {
        printf("Printer Queue System\n");
        printf("1. Add a job to queue\n");
        printf("2. Process the next job\n");
        printf("3. Exit\n");
        printf("Choice: ");
        scanf("%d",&op);
        switch(op) {
            case 1:
                printf("Job ID: ");
                scanf("%d",&x);
                enqueue(x);

```

```

        dequeue();
        break;
    case 3:
        printf("Exiting\n");
        while(1) {
            if(front==NULL)
                exit(0);
            else
                dequeue();
        }
        exit(0);
    default:
        printf("Invalid choice\n");
    }
}
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
2
No job to dequeue
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
1
Job ID:
1245
Job 1245 added
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
1
Job ID:
2345
Job 2345 added
Printer Queue System
1. Add a job to queue
2. Process the next job

3. Exit
Choice:
1
Job ID:
2145
Job 2145 added
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
5
Invalid choice
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
2
Job 1245 removed from queue and sent to the printer
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
2
Job 2345 removed from queue and sent to the printer
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
2
Job 2145 removed from queue and sent to the printer
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
2
No job to dequeue
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
3
Exiting

Test Case - 2
<b>User Output</b>
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
1
Job ID:
1245
Job 1245 added
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
1
Job ID:
3654
Job 3654 added
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
1
Job ID:
8569
Job 8569 added
Printer Queue System
1. Add a job to queue
2. Process the next job
3. Exit
Choice:
3
Exiting
Job 1245 removed from queue and sent to the printer
Job 3654 removed from queue and sent to the printer
Job 8569 removed from queue and sent to the printer



<b>S.No: 28</b>	Exp. Name: <b><i>Circular Queues using arrays</i></b>	<b>Date: 2024-06-08</b>
-----------------	---	-------------------------

**Aim:**

Design, Develop and Implement a menu driven Program in C for the following operations on Circular QUEUE of Characters (Array Implementation of Queue with maximum size MAX = 6)

- a) Insert an Element on to Circular QUEUE
- b) Delete an Element from Circular QUEUE
- c) Demonstrate Overflow and Underflow situations on Circular QUEUE
- d) Display the status of Circular QUEUE
- e) Exit

Support the program with appropriate functions for each of the above operations.

**Source Code:**

cQue . c

```

#include<stdio.h>
#include<stdlib.h>
#define max 6
int queue[max];
int front=-1;
int rear=-1;
void enqueue(int element)
{
    if(front==-1 && rear==-1)
    {
        front=0;
        rear=0;
        queue[rear]=element;
    }
    else if((rear+1)%max==front)
    {
        printf("~~~Circular Queue Overflow~~~\n");
    }
    else{
        rear=(rear+1)%max;
        queue[rear]=element;
    }
}
void dequeue()
{
    if((front==-1) &&(rear==-1))
        printf("~~~Circular Queue Underflow~~~\n");
    else if(front==rear)
    {
        printf("Deleted element from the queue is: %d\n",queue[front]);
        front=-1;
        rear=-1;
    }
    else{
        printf("Deleted element from the queue is: %d\n",queue[front]);
        front=(front+1)%max;
    }
}
void display()
{
    int i=front;
    if(front==-1 && rear==-1)
        printf("~~~Circular Queue Empty~~~\n");
    else
    {
        printf("Circular Queue contents are:\n");
        while(i!=rear)
        {
            printf("%d ",queue[i]);
            i=(i+1)%max;
        }
        printf("%d\n",queue[i]);
    }
}
int main()

```

```

while(1) {
    printf("~~Main Menu~~\n");
    printf("=> 1. Insertion and Overflow Demo\n");
    printf("=> 2. Deletion and Underflow Demo\n");
    printf("=> 3. Display\n");
    printf("=> 4. Exit\n");
    printf("Enter Your Choice: ");
    scanf("%d",&choice);
    switch(choice) {
        case 1:
            printf("Enter the element to be inserted: ");
            scanf("%d",&x);
            enqueue(x);
            break;
        case 2:
            dequeue();
            break;
        case 3:
            display();
            break;
        case 4: exit(0);
        default:
            printf("Please enter a valid choice\n");
    }
}
return 0;
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
1
Enter the element to be inserted:
1
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
1
Enter the element to be inserted:
2

~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
1
Enter the element to be inserted:
3
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
1
Enter the element to be inserted:
4
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
1
Enter the element to be inserted:
5
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
3
Circular Queue contents are:
1 2 3 4 5
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
1
Enter the element to be inserted:
6
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit

Enter Your Choice:
3
Circular Queue contents are:
1 2 3 4 5 6
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
1
Enter the element to be inserted:
7
~~~Circular Queue Overflow~~~
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
3
Circular Queue contents are:
1 2 3 4 5 6
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
2
Deleted element from the queue is: 1
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
2
Deleted element from the queue is: 2
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
2
Deleted element from the queue is: 3
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display

=> 4. Exit
Enter Your Choice:
3
Circular Queue contents are:
4 5 6
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
4

Test Case - 2
<b>User Output</b>
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
3
~~~Circular Queue Empty~~~
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
3
~~~Circular Queue Empty~~~
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
2
~~~Circular Queue Underflow~~~
~~Main Menu~~
=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
1
Enter the element to be inserted:
4
~~Main Menu~~

=> 1. Insertion and Overflow Demo
=> 2. Deletion and Underflow Demo
=> 3. Display
=> 4. Exit
Enter Your Choice:
4

Test Case - 3	
User Output	
~~Main Menu~~	
=> 1. Insertion and Overflow Demo	
=> 2. Deletion and Underflow Demo	
=> 3. Display	
=> 4. Exit	
Enter Your Choice:	
5	
Please enter a valid choice	
~~Main Menu~~	
=> 1. Insertion and Overflow Demo	
=> 2. Deletion and Underflow Demo	
=> 3. Display	
=> 4. Exit	
Enter Your Choice:	
4	

S.No: 29	Exp. Name: <b>Implementation of Circular Queue using Linked List</b>	Date: 2024-06-08
----------	--	------------------

**Aim:**

Write a program to implement `circular queue` using **linked lists**.

Sample Input and Output:

```
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 1
Enter element : 15
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 1
Enter element : 16
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 1
Enter element : 17
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 3
Elements in the circular queue : 15 16 17
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 5
Circular queue size : 3
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 2
Deleted value = 15
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 2
Deleted value = 16
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 2
Deleted value = 17
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 3
Circular queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 4
Circular queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 5
Circular queue size : 0
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option : 6
```

**Source Code:**

CQueueLL.c



```

#include <stdlib.h>
#include <stdio.h>
#include "CQueueOperationsLL.c"
int main() {
    int op, x;
    while(1) {
        printf("1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit\n");
        printf("Enter your option : ");
        scanf("%d",&op);
        switch(op) {
            case 1:
                printf("Enter element : ");
                scanf("%d",&x);
                enqueue(x);
                break;
            case 2:
                dequeue();
                break;
            case 3:
                display();
                break;
            case 4:
                isEmpty();
                break;
            case 5:
                size();
                break;
            case 6: exit(0);
        }
    }
}

```

CQueueOperationsLL.c

```

struct queue {
    int data;
    struct queue *next;
};
typedef struct queue *CircularQueue;
CircularQueue front = NULL, rear = NULL;
//complete the below dequeue() and enqueue() functions
void dequeue() {
    CircularQueue temp =front;
    if((front==NULL)&&(rear==NULL))
        printf("Circular queue is underflow.\n");
    else if(front==rear){
        front=rear=NULL;
        printf("Deleted value = %d\n",temp->data);
        free(temp);
    }
    else{
        front=front->next;
        rear->next=front;
        printf("Deleted value = %d\n",temp->data);
        free(temp);
    }

}

void size() {
    int count =0;
    if(front == NULL) {
        printf("Circular queue size : 0\n");
        return;
    }
    CircularQueue temp = front;
    do {
        temp = temp -> next;
        count = count + 1;
    } while(temp != front);
    printf("Circular queue size : %d\n",count);
}

void isEmpty() {
    if(front == NULL ) {
        printf("Circular queue is empty.\n");
    } else {
        printf("Circular queue is not empty.\n");
    }
}

void enqueue(int element) {
    CircularQueue newnode;
    newnode=(CircularQueue)malloc(sizeof(struct queue));
    newnode->data=element;
    newnode->next=NULL;
    if((rear==NULL)&&(front==NULL)) {
        front=rear=newnode;
    }
}

```

```

        else{
            rear->next=newnode;
            rear=newnode;
            newnode->next=front;
        }
        printf("Successfully inserted.\n");
    }

void display() {
    if(front == NULL) {
        printf("Circular queue is empty.\n");
    } else {
        CircularQueue temp = front;
        printf("Elements in the circular queue : ");
        do {
            printf("%d ", temp -> data);
            temp = temp -> next;
        } while(temp != front);
        printf("\n");
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
1
Enter element :
15
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
1
Enter element :
16
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
1
Enter element :
17
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
3

Elements in the circular queue : 15 16 17
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
5
Circular queue size : 3
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
2
Deleted value = 15
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
2
Deleted value = 16
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
2
Deleted value = 17
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
3
Circular queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
4
Circular queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
5
Circular queue size : 0
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
6

Test Case - 2
User Output
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
2
Circular queue is underflow.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
5
Circular queue size : 0
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
4
Circular queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit

Enter your option :
3
Circular queue is empty.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
1
Enter element :
143
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
1
Enter element :
153
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
1
Enter element :
163
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
1
Enter element :
173
Successfully inserted.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
3
Elements in the circular queue : 143 153 163 173
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
2
Deleted value = 143
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
2
Deleted value = 153
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
5
Circular queue size : 2
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
4
Circular queue is not empty.
1.Enqueue 2.Dequeue 3.Display 4.Is empty 5.Size 6.Exit
Enter your option :
6

S.No: 30	Exp. Name: <b><i>Convert an Infix Expression to Postfix and Evaluate it.</i></b>	Date: 2024-06-08
----------	--	------------------

**Aim:**

Write a C program that uses a stack to evaluate an infix expression and convert it to a postfix expression.

**Note:** Only single-digit positive integers and +, -, \*, /, % operators are allowed

**Source Code:**

EvaluateConverted.c

```

#include<stdio.h>
#include<stdlib.h>
#include<ctype.h>
#include<string.h>
int numbers[50],tn=-1,to=-1;
char op[50];
void push_num(int n)
{
    numbers[++tn]=n;}
void push_op(char ch)
{
    op[++to]=ch;
}
int pop_num()
{
    return numbers[tn--];
}
int peek()
{
    return op[to];
}
char pop_op()
{
    return op[to--];
}
int infix_eval(int numbers[50],char op[50])
{
    int x,y;
    char ope;
    x=pop_num();
    y=pop_num();
    ope=pop_op();
    switch(ope)
    {
        case '+':
            return x+y;
        case '-':
            return y-x;
        case '%':
            return y%x;
        case '*':
            return x*y;
        case '/':
            if(x==0) {
                printf("\nCan not divide by 0");
                exit(0);
            }
            else
                return y/x;
    }
    return 0;
}
int is_operator(char ch)
{
    return(ch=='+' || ch=='-' || ch=='*' || ch=='/' || ch=='%');
}

```

```

{
    switch(c)
    {
        case '+':
        case '-': return 1;
        case '*':
        case '/':
        case '%': return 2;
    }
    return -1;
}
int eval(char exp[20])
{
    int i,num,output,r;
    char c;
    for(i=0;exp[i]!='\0';i++)
    {
        c = exp[i];
        if(isdigit(c)!=0)
        {
            num=0;
            while (isdigit(c)) {
                num=num*10+(c-'0');
                i++;
                if(i<strlen(exp))
                    c=exp[i];
                else
                    break;
            }
            i--;
            push_num(num);
        }
        else if(c=='(') {
            push_op(c);
        }
        else if(c==')') {
            while(op[to]!='(') {
                r=infix_eval(numbers,op);
                push_num(r);
            }
            pop_op();
        }
        else if(is_operator(c))
        {
            while(to!=-1 && precedence(c)<=precedence(op[to]))
            {
                output=infix_eval(numbers,op);
                push_num(output);
            }
            push_op(c);
        }
    }
    while(to!=-1)
    {
        output=infix_eval(numbers,op);
    }
}

```



```

        return pop_num();
    }
    void convertInfixToPostfix(char* expression)
    {
        int i, j;
        for(i=0,j= -1; expression[i];++i)
        {
            if(isdigit(expression[i]))
                expression[++j]=expression[i];
            else if(expression[i]=='(')
                push_op(expression[i]);
            else if(expression[i]==')')
            {
                while(to!=-1&&peek()!='(')
                    expression[++j]=pop_op();
                if(to!=-1&&peek()!='(')
                    return;
                else
                    pop_op();
            }
            else
            {
                while(to!=-1&&precedence(expression[i])
<=precedence(peek()))
                    expression[++j]=pop_op();
                push_op(expression[i]);
            }
        }
        while(to!=-1)
            expression[++j]=pop_op();
        expression[++j]='\0';
        printf("Postfix expression: %s\n",expression);
    }
    int main()
    {
        char exp[50];
        int result;
        printf("Infix expression: ");
        scanf("%s",exp);
        result=eval(exp);
        convertInfixToPostfix(exp);
        printf("Result: %d\n",result);
    }

```

## Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Infix expression:
2+3*4
Postfix expression: 234*+
Result: 14

Test Case - 2
<b>User Output</b>
Infix expression:
8%3+6*(2-1)
Postfix expression: 83%621-*+
Result: 8

S.No: 31	Exp. Name: <b><i>Check whether the given string is palindrome or not using stack.</i></b>	Date: 2024-06-08
----------	---	------------------

**Aim:**

Create a C program to determine whether a given string is a palindrome or not using stack.

**Source Code:**

StringPalinUsingStack.c

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

struct Stack {
    int top;
    char items[100];
};
struct Stack *stackPtr;
void initStack(char *inputString);
void push(char);
char pop();
void initStack(char *inputString)
{
    stackPtr=(struct Stack*) malloc(sizeof(struct Stack));
    stackPtr->top=-1;
    for(int i=0;inputString[i]!='\0';i++)
        push(inputString[i]);
}
void push(char ch)
{
    stackPtr->items[++stackPtr->top]=toupper(ch);
}
char pop()
{
    return stackPtr->items[stackPtr->top--];
}
int isPalindrome(char *inputString)
{
    int front=0;
    initStack(inputString);
    for(int i=0;i<(strlen(inputString) / 2);i++) {
        if(stackPtr->items[stackPtr->top]==stackPtr->items[front]) {
            pop();
            front++;
        }
        else
            return 0;
    }
    return 1;
}

int main() {
    char inputString[100];

    printf("String: ");
    scanf("%s", inputString);

    if (isPalindrome(inputString)) {
        printf("%s is a palindrome\n", inputString);
    } else {
        printf("%s is not a palindrome\n", inputString);
    }
}

```

```
return 0;
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
String:
Madam
Madam is a palindrome

Test Case - 2
User Output
String:
Aplha
Aplha is not a palindrome

S.No: 32	Exp. Name: <b><i>Check for Symmetry of a String using Stack</i></b>	Date: 2024-06-08
----------	---	------------------

**Aim:**

Implement a stack using C to perform comparison and check for symmetry of a String.

**Note:** Convert all the characters of the string to lowercase for case-insensitivity before checking for symmetry.

**Source Code:**

StringSymmetry.c

```

#include<stdio.h>
#include<stdlib.h>
#include<string.h>
#include<ctype.h>
struct Stack {
int top;
char items[100];
};
struct Stack *stackPtr;
void initStack(char *inputString);
void isSymmetric(char *inputString);
void push(char);
char pop();
void initStack(char *inputString)
{
    stackPtr=(struct Stack*)malloc(sizeof(struct Stack));
    stackPtr->top=-1;
    for(int i=0;inputString[i]!='\0';i++)
        push(inputString[i]);
}
void push(char ch)
{
    stackPtr->items[++stackPtr->top]=toupper(ch);
}
char pop()
{
    return stackPtr->items[stackPtr->top--];
}
int isSymmetric(char *inputString)
{
    initStack(inputString);
    for(int i=0;i<(strlen(inputString) / 2);i++) {
        if(pop()!=stackPtr->items[i])
            return 0;
    }
    return 1;
}
int main()
{
    char inputString[100];
    printf("String: ");
    scanf("%s", inputString);
    if(isSymmetric(inputString)) {
        printf("%s is symmetric\n", inputString);
    } else {
        printf("%s is not symmetric\n", inputString);
    }
    return 0;
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1

<b>User Output</b>
String:
Emualator
Emualator is not symmetric

<b>Test Case - 2</b>
<b>User Output</b>
String:
Madam
Madam is symmetric



S.No: 33	Exp. Name: <b><i>Check for Symmetry of a String using Queue</i></b>	Date: 2024-06-08
----------	---	------------------

**Aim:**

Implement a queue using C to perform comparison and check for symmetry of a String.

**Note:** Convert all the characters of the string to lowercase for case-insensitivity before checking for symmetry.

**Source Code:**

StringSymmetryUsingQueue.c