

```

import numpy as np

class NeuralNetwork:
    def __init__(self, input_size, hidden_size, output_size):
        self.input_size = input_size
        self.hidden_size = hidden_size
        self.output_size = output_size

        # Initialize weights
        self.weights_input_hidden = np.random.randn(self.input_size,
self.hidden_size)
        self.weights_hidden_output = np.random.randn(self.hidden_size,
self.output_size)

        # Initialize the biases
        self.bias_hidden = np.zeros((1, self.hidden_size))
        self.bias_output = np.zeros((1, self.output_size))

    def sigmoid(self, x):
        return 1 / (1 + np.exp(-x))

    def sigmoid_derivative(self, x):
        return x * (1 - x)

    def feedforward(self, X):
        # Input to hidden
        self.hidden_activation = np.dot(X, self.weights_input_hidden) +
self.bias_hidden
        self.hidden_output = self.sigmoid(self.hidden_activation)

        # Hidden to output
        self.output_activation = np.dot(self.hidden_output,
self.weights_hidden_output) + self.bias_output
        self.predicted_output = self.sigmoid(self.output_activation)

        return self.predicted_output

    def backward(self, X, y, learning_rate):
        # Compute the output layer error
        output_error = y - self.predicted_output
        output_delta = output_error *

```

```

self.sigmoid_derivative(self.predicted_output)

    # Compute the hidden layer error
    hidden_error = np.dot(output_delta, self.weights_hidden_output.T)
    hidden_delta = hidden_error * self.sigmoid_derivative(self.hidden_output)

    # Update weights and biases
    self.weights_hidden_output += np.dot(self.hidden_output.T, output_delta) *
learning_rate
    self.bias_output += np.sum(output_delta, axis=0, keepdims=True) *
learning_rate
    self.weights_input_hidden += np.dot(X.T, hidden_delta) * learning_rate
    self.bias_hidden += np.sum(hidden_delta, axis=0, keepdims=True) *
learning_rate

    def train(self, X, y, epochs, learning_rate):
        for epoch in range(epochs):
            output = self.feedforward(X)
            self.backward(X, y, learning_rate)
            if epoch % 4000 == 0:
                loss = np.mean(np.square(y - output))
                print(f"Epoch {epoch}, Loss:{loss}")

X = np.array([[0, 0], [0, 1], [1, 0], [1, 1]])
y = np.array([[0], [1], [1], [0]])

nn = NeuralNetwork(input_size=2, hidden_size=4, output_size=1)
nn.train(X, y, epochs=10000, learning_rate=0.1)

# Test the trained model
output = nn.feedforward(X)
print("Predictions after training:")
print(output)

```

Output:

```

Epoch 0, Loss:0.26804276270586413
Epoch 4000, Loss:0.012477301332301533
Epoch 8000, Loss:0.0029801470220045504

```

Predictions after training:

```
[[0.02330965]  
 [0.95658721]  
 [0.95049451]  
 [0.05896647]]
```