

UNIT 1



ARTIFICIAL INTELLIGENCE ANDROBOTICS

UNIT I: ROBOT LOCOMOTION

- ❖ INTRODUCTION TO AI AND ROBOTICS
- ❖ ROBOT LOCOMOTION
- ❖ LEGGED MOBILE ROBOTS
- ❖ WHEELED MOBILE ROBOTS
- ❖ AERIAL MOBILE ROBOTS.

Artificial Intelligence (AI):

AI refers to the simulation of human intelligence in machines that are programmed to think and learn like humans. It involves the development of algorithms and models that enable computers to perform tasks traditionally requiring human intelligence, such as visual perception, speech recognition, decision-making, and language translation. AI techniques include machine learning, natural language processing, computer vision, and robotics.

Robotics:

Robotics is the branch of technology that deals with the design, construction, operation, and use of robots. Robots are programmable machines that can carry out tasks autonomously or semi-autonomously. They can be equipped with sensors, actuators, and control systems to interact with their environment and perform specific functions. Robotics combines aspects of mechanical engineering, electrical engineering, computer science, and AI to create machines that can assist humans in various domains, including manufacturing, healthcare, exploration, and entertainment.

INTERCONNECTION:

AI and robotics are closely intertwined fields. AI techniques are essential for enabling robots to perceive their environment, make decisions, and adapt to changing conditions. Robotics, in turn, provides a physical platform for AI algorithms to interact with and manipulate the world. Together, AI and robotics have led to advancements such as autonomous vehicles, **21AD521**

surgical robots, smart assistants, and automated manufacturing systems, revolutionizing industries and impacting daily life.

ROBOT LOCOMOTION

Robot locomotion refers to how robots move from one place to another. There are various methods of locomotion depending on the environment and the tasks the robot needs to perform. Here are some common methods of robot locomotion

Wheeled Locomotion: Robots with wheels are commonly used in indoor environments and on smooth surfaces. They are efficient for fast movement and navigation.

Legged Locomotion: Legged robots, inspired by animals, use legs or limbs to move. This method is useful for navigating rough or uneven terrain where wheels might struggle.

Tracks: Some robots use tracks similar to those on tanks. Tracks provide stability and traction on rough terrain but may be slower than wheeled robots.

Flying: Drones and other aerial robots use propellers or rotors for flying. This enables them to access difficult-to-reach areas and provide aerial surveillance.

Swimming: Underwater robots, or autonomous underwater vehicles (AUVs), use

propellers or fins to navigate underwater environments for tasks such as exploration or oceanography.

Crawling: Some robots crawl using treads or legs that mimic the movement of insects or reptiles. This method is useful for navigating confined spaces or complex terrain.

21AD521

Hybrid Methods: Some robots combine multiple locomotion methods. For example, a robot might have wheels for smooth surfaces but also extend legs or tracks for rough terrain.

Each method of locomotion has its advantages and limitations, and the choice depends on factors such as the environment, tasks to be performed, energy efficiency, and stability requirements.

LEGGED MOBILE ROBOTS

Legged mobile robots, also known as walking robots or quadruped robots, are robots designed to move using legs rather than wheels or tracks. This type of robot mimics the locomotion of animals and humans, allowing them to navigate complex terrains that are challenging for wheeled or aerial robots.

TYPES OF LEGGED MOBILE ROBOTS QUADRUPED ROBOTS

Overview: These robots have four legs, each typically equipped with joints and actuators to simulate animal-like movement.

Mechanism: Quadrupeds can walk, trot, climb, and sometimes even jump or crawl, depending on their design and capabilities.

Advantages: They offer stability and maneuverability on uneven or rough terrain, making them suitable for exploration and search-and-rescue missions.

HEXAPOD ROBOTS

Overview: Hexapods have six legs, which provide greater stability compared to quadrupeds.

Mechanism: Each leg is independently controlled, allowing for a wide range of

movements such as walking, climbing, and turning.

Advantages: Hexapods can navigate more challenging environments and carry heavier payloads compared to quadrupeds.

BIPEDAL ROBOTS

Overview: These robots have two legs, resembling human-like locomotion.

21AD521

Mechanism: Bipedal robots simulate human walking and running motions, requiring advanced balance and coordination algorithms.

Advantages: They can access narrow spaces and perform tasks that require human-like interaction or mobility.

KEY COMPONENTS

LEGS

Typically equipped with joints (such as hip, knee, and ankle joints) and actuators (motors) to facilitate movement.

Designed to mimic the flexibility and range of motion found in animal legs.**Sensors**

IMUs: Measure orientation and acceleration to maintain balance and stability.

Joint Encoders: Provide feedback on joint angles and positions for precise control.

Vision Systems: Cameras and depth sensors for environment perception and navigation.

Force/Torque Sensors: Measure forces exerted by the legs on the ground, aiding in terrain analysis and adaptation.

Control System

Uses algorithms for gait generation, motion planning, and balance control.

Often includes feedback loops to adjust leg movements based on sensor data and environmental feedback.

Power Source

Typically powered by batteries or onboard power systems, depending on the size

and application of the robot.

Applications

Exploration and Mapping: Navigating rough or hazardous terrain where wheeled robots struggle.

21AD521

Search and Rescue: Accessing disaster zones and locating survivors in collapsed buildings or uneven terrain.

Military and Defense: Surveillance, reconnaissance, and logistics in challenging environments.

Assistance and Healthcare: Providing support for elderly or disabled individuals in homes or hospitals.

Entertainment and Research: Used in entertainment shows and research labs to study locomotion and robotics.

Advantages

Terrain Adaptability: Can traverse uneven, rocky, or debris-laden environments that are challenging for wheeled or tracked robots.

Stability: Offer stability on rough terrain and in adverse conditions, enhancing reliability in field operations.

Manipulation: Some legged robots can manipulate objects or perform tasks requiring dexterity, leveraging their limb-like structures.

Challenges

Complexity: Designing and controlling legged robots require advanced mechanical and software engineering skills.

Power Consumption: Operating motors and maintaining stability can consume significant power, limiting operational endurance.

Cost: Higher development and maintenance costs compared to simpler wheeled robots.

Maintenance: Regular upkeep of joints, actuators, and sensors to ensure reliable performance.

Summary

Legged mobile robots represent a significant advancement in robotics, enabling them

to operate in diverse and challenging environments where traditional wheeled or aerial robots may struggle. Their ability to navigate complex terrains, provide stability, and perform tasks that require mobility and manipulation makes them invaluable in fields ranging from exploration and disaster response to healthcare and entertainment. As technology continues to advance, legged robots

21AD521

are expected to play an increasingly vital role in various industries and application

Certainly! Legged mobile robots, also known as walking robots, utilize legs rather than wheels or tracks for locomotion. They are designed to mimic the movement patterns of animals and humans, enabling them to navigate complex terrains that are challenging for other types of robots. Here's a deep dive into the types of legged mobile robots:

1. Quadruped Robots

Overview

Quadruped robots are characterized by having four legs, each typically equipped with multiple joints and actuators. They are inspired by animals such as dogs, horses, and even insects.

Mechanism

Leg Structure: Each leg typically consists of joints that mimic the flexibility of animal limbs (e.g., hip, knee, ankle joints).

Actuation: Actuators, often electric motors, provide the necessary torque and movement to each joint.

Gaits: Quadrupeds can move using various gaits such as walking, trotting, crawling, and sometimes bounding or jumping.

Stability: They offer inherent stability due to their four-legged stance, making them suitable for uneven terrain.

Applications

Exploration: Used in environments like forests, mountains, and disaster zones where wheeled robots may struggle.

Search and Rescue: Navigate debris and uneven surfaces to locate and assist

victims.

Military and Defense: Surveillance, reconnaissance, and logistics in challenging terrain.

21AD521

Examples

Boston Dynamics Spot: One of the most famous quadruped robots, known for its agility, stability, and versatility in various applications.

ANYmal: Designed for autonomous inspection and monitoring in industrial and outdoor environments.

2. Hexapod Robots

Overview

Hexapod robots, as the name suggests, have six legs. This design provides greater stability and load-bearing capacity compared to quadrupeds.

Mechanism

Leg Configuration: Six legs distributed along the body, often with a tripod gait (three legs move while others remain stationary).

Payload Capacity: Can carry heavier loads than quadrupeds due to the additional legs distributing weight.

Movement: Similar to quadrupeds, they can walk, climb, turn, and traverse rough terrain with relative ease.

Applications

Heavy-Duty Tasks: Lifting and transporting heavy equipment in industrial settings.

Exploration: Navigating rugged landscapes and conducting surveys in challenging environments.

Research: Studying locomotion and biomechanics in robotics and biology. **Examples**

Mantis Robot: Known for its large size and robust construction, used in research and development.

TITAN XII: A hexapod robot designed for military applications, offering stability

and maneuverability in harsh conditions.

3. Bipedal Robots

21AD521

Overview

Bipedal robots are designed with two legs, resembling human-like locomotion. They are among the most complex legged robots due to the challenges of balance and coordination.

Mechanism

Humanoid Design: Mimics the skeletal structure and joint movements of humans.

Balance Control: Advanced algorithms and sensors (such as gyroscopes and accelerometers) are used to maintain stability.

Walking Patterns: Can walk, run, climb stairs, and perform tasks requiring precise foot placement.

Applications

Assistance Robotics: Aiding elderly or disabled individuals in daily tasks.

Humanoid Interaction: Interacting with humans in social and service applications.

Research and Development: Advancing understanding of human locomotion and robotics.

Examples

ASIMO: Developed by Honda, ASIMO is one of the most advanced bipedal robots, capable of running, walking on uneven surfaces, and interacting with people.

Atlas: Created by Boston Dynamics, Atlas is used in various research and development projects, demonstrating advanced mobility and dexterity.

Key Components and Challenges

Components

Sensors: IMUs, encoders, cameras, and other sensors for feedback and environmental perception.

Control Systems: Algorithms for gait generation, motion planning, and balance control.
21AD521

Power Systems: Batteries or power sources suitable for the robot's size and operational requirements.

Challenges

Complexity: Designing and controlling legged robots requires sophisticated mechanical engineering, software development, and sensor integration.

Power Consumption: Operating multiple actuators and maintaining stability can drain battery life quickly, limiting operational endurance.

Maintenance: Regular upkeep of joints, actuators, and sensors to ensure reliable performance and durability.

Summary

Legged mobile robots represent a significant advancement in robotics, enabling them to operate in diverse and challenging environments where traditional wheeled or tracked robots may struggle. Each type—quadruped, hexapod, and bipedal—offers unique advantages in terms of stability, maneuverability, and load-bearing capacity, suited to different applications ranging from exploration and search-and-rescue to industrial tasks and research. As technology continues to evolve, legged robots are expected to play an increasingly vital role in various industries and everyday life.

WHEELED MOBILE ROBOTS

Wheeled mobile robots (WMRs) are robots that use wheels for movement. They are widely used in various applications due to their simplicity and efficiency in navigation and control. Here's an overview of the key aspects of wheeled mobile robots:

TYPES OF WHEELED MOBILE ROBOTS

Differential Drive Robots: These robots have two wheels that can be independently driven. They are simple to design and control.

Tricycle Robots: These robots typically have one driving wheel and two passive wheels for balance. They are similar to bicycles in their movement.

Omnidirectional Robots: These robots use specially designed wheels, like omni wheels or mecanum wheels, to move in any direction without changing

orientation.

21AD521

Car-like Robots: These robots have a steering mechanism similar to cars and are used in applications that require high-speed movement.

Differential Drive Robots

Overview

Differential drive robots have two independently driven wheels on either side of the robot. These wheels are controlled separately, allowing the robot to move forward, backward, and rotate in place by varying the speed and direction of each wheel.

Mechanism

Movement: Forward and backward movement is achieved by driving both wheels at the same speed in the same direction. Rotation is achieved by driving the wheels at different speeds or in opposite directions.

Turning: By varying the speeds of the two wheels, the robot can turn. For example, if the left wheel moves faster than the right wheel, the robot will turn right.

Advantages

Simplicity: Simple to design and control.

Maneuverability: Can rotate in place (zero-radius turning).

Disadvantages

Stability: Typically requires additional support (like caster wheels) for balance.

Complex Control: Precise control of wheel speeds is necessary for accurate movement.

Tricycle Robots

Overview

Tricycle robots typically have one driven wheel and two passive wheels for balance. The driven wheel is often also the steering wheel, similar to a bicycle.

Mechanism

21AD521

Movement: The driving wheel provides propulsion, and its orientation determines the direction of movement.

Turning: The driving wheel changes direction through a steering mechanism, similar to turning the handlebars of a bicycle.

Advantages

Stability: More stable than differential drive robots due to the three-point support.

Simple Steering: Steering mechanism is straightforward.

Turning Radius: Has a larger turning radius compared to differential drive robots.

Complexity: More complex mechanical design due to the steering mechanism.

Omnidirectional Robots

Overview

Omnidirectional robots use special wheels, such as omni-wheels or mecanum wheels, to move in any direction without changing orientation. These wheels have multiple rollers that allow for lateral movement.

Mechanism

Movement: Each wheel can be independently driven and controlled to achieve movement in any direction, including sideways and diagonally.

Turning: The robot can move and rotate simultaneously, providing excellent maneuverability.

Advantages

Maneuverability: Can move in any direction instantly, with a high degree of freedom.

Flexibility: Excellent for tight spaces and dynamic environments.

Disadvantages

Complex Control: Requires advanced algorithms for wheel coordination.

Energy Consumption: Typically consumes more energy due to the complexity of wheel movements.

21AD521

Car-like Robots

Overview

Car-like robots mimic the steering mechanism of automobiles, using front-wheel or rear-wheel steering. They are used in applications requiring higher speeds and stability.

Mechanism

Movement: Powered by rear or front wheels, with steering provided by turning the wheels on the opposite axle.

Turning: Achieved by steering the wheels in the desired direction, similar to a car.

Advantages

Stability: High-speed stability and control.

Intuitive Control: Steering mechanism is well-understood and easy to implement.

Disadvantages

Turning Radius: Limited by the steering mechanism, resulting in a larger turning radius.

Complexity: More complex mechanical design and control compared to differential drive robots.

Summary

Differential Drive Robots: Simple, highly maneuverable, but less stable and complex control.

Tricycle Robots: More stable, straightforward steering, but larger turning radius and more complex mechanical design.

Omnidirectional Robots: Highly maneuverable with instant directional changes, but complex control and higher energy consumption.

Car-like Robots: Stable at high speeds with intuitive control, but larger turning radius and more complex mechanical design.

Each type of wheeled mobile robot has its own strengths and weaknesses, making them suitable for different applications depending on the requirements for maneuverability, stability, speed, and complexity.

Car like Robots

Car-like robots, also known as Ackermann steering robots or car-like mobile robots, are designed to mimic the steering mechanism of traditional automobiles. This type of robot is ideal for applications that require high-speed movement and stable control, such as autonomous driving research, delivery services, and various industrial applications. Here is an in-depth look at the key aspects of car like robots:

Mechanical Design

Steering Mechanism

Ackermann Steering Geometry: Car-like robots use Ackermann steering geometry to ensure that all wheels have a common center of rotation during a turn. This reduces tire slippage and improves stability.

Front-Wheel Steering: Most car-like robots use front-wheel steering, where the front wheels are responsible for changing the direction while the rear wheels provide propulsion.

Four-Wheel Steering: Some advanced car-like robots use four-wheel steering, allowing both the front and rear wheels to steer. This improves maneuverability and reduces the turning radius.

Chassis and Suspension

Chassis: The frame that holds all the components together. It needs to be robust to handle the mechanical stresses during movement.

Suspension: Some car-like robots incorporate suspension systems to absorb shocks and provide a smoother ride over uneven terrain.

Control System

Drive System

Electric Motors: Typically powered by electric motors, either DC or brushless DC (BLDC) motors, which provide the necessary torque for propulsion and steering.

Transmission: Gear systems may be used to transmit power from the motors to the wheels, enhancing torque and control.

Sensors and Navigation

GPS: For outdoor navigation, GPS systems provide global positioning data.

Inertial Measurement Units (IMUs): These sensors measure acceleration and rotational rates, helping with balance and orientation.

LiDAR and Cameras: Used for obstacle detection, mapping, and environment perception.

Encoders: Attached to wheels to measure rotation and calculate the robot's position and speed.

Algorithms and Software

Path Planning

Waypoints Navigation: Predefined waypoints are used to guide the robot from start to destination.

Dynamic Path Planning: Algorithms that adjust the path in real-time based on sensor inputs to avoid obstacles.

Control Algorithms

PID Control: Proportional-Integral-Derivative controllers are used to maintain the desired speed and direction by adjusting the motor outputs.

Model Predictive Control (MPC): Advanced control strategy that uses a model of the robot's dynamics to predict future states and optimize control inputs.

Applications

Autonomous Driving

Self-Driving Cars: Used in research and development of autonomous vehicles, simulating real-world driving conditions.

Delivery Robots: Employed in urban environments to deliver goods autonomously.

Industrial Automation

Automated Guided Vehicles (AGVs): Used in warehouses and factories for material handling, following predefined paths or dynamically navigating the environment.

Surveillance and Patrolling

Security Robots: Deployed for surveillance and patrolling in large facilities, parking lots, and campuses.

Advantages

Stability at High Speed: Car-like robots are designed to be stable at higher speeds compared to other types of mobile robots.

Intuitive Control: The steering mechanism is familiar and intuitive, making it easier to control and navigate.

Realistic Simulation: Useful for developing and testing autonomous driving technologies in realistic scenarios.

Challenges

Turning Radius: Larger turning radius compared to differential drive and omnidirectional robots, which can limit maneuverability in tight spaces.

Complexity in Design: Mechanical design is more complex due to the steering mechanism and suspension systems.

Cost: Typically more expensive to build and maintain due to the complexity and number of components involved.

Summary

Car-like robots are sophisticated mobile robots designed to emulate the steering and control mechanisms of traditional automobiles. They are ideal for high-speed applications requiring stability and intuitive control, such as autonomous driving and industrial automation. Despite their complexity and larger turning radius, their ability to simulate real-world driving conditions makes them invaluable in research and practical applications.

Key Components

Chassis: The frame of the robot that holds all the components together.

Wheels: Attached to the motors, they provide movement to the robot. **Motors:** Usually DC or stepper motors that drive the wheels.

Sensors: Used for navigation and obstacle detection. Common sensors include ultrasonic sensors, LiDAR, cameras, and encoders.

Control System: Includes microcontrollers or onboard computers to process sensor data and control motor actions.

Navigation and Control

Odometry: Using data from wheel encoders to estimate the robot's position over time.

SLAM (Simultaneous Localization and Mapping): Algorithms that help the robot map its environment and keep track of its position within that map.

Path Planning: Algorithms to determine the best path from the robot's current location to its destination.

Obstacle Avoidance: Techniques to detect and avoid obstacles in real-time using sensor data.

Applications

Industrial Automation: Used in warehouses and factories for transporting goods and materials.

Service Robots: Used in environments like hospitals and offices for tasks like delivery and cleaning.

Exploration: Used in areas inaccessible to humans, such as underwater or on other planets.

Research and Education: Used for teaching robotics concepts and testing new algorithms.

Advantages

Efficiency: Wheels provide a smooth and efficient mode of transportation. **Simplicity:**

Easier to design and control compared to legged robots. **Cost-Effectiveness:**

Generally cheaper to build and maintain. **Challenges**

Terrain Limitations: Wheeled robots are not suitable for rough or uneven terrain. **Slippage and Skidding:** Can cause errors in odometry and control.

Energy Consumption: Continuous motor operation can lead to high energy consumption.

Wheeled mobile robots continue to evolve with advancements in technology, making them more autonomous, efficient, and capable of handling a wide range of tasks.

AERIAL MOBILE ROBOTS:

Aerial mobile robots, also known as drones or unmanned aerial vehicles (UAVs), are flying robots that can be remotely controlled or autonomously operated. They are designed to perform a variety of tasks while airborne, leveraging their ability to reach places that are difficult, dangerous, or impossible for humans to access.

DEFINITION

Aerial Mobile Robots: Aerial mobile robots are unmanned, often autonomous, flying devices equipped with various sensors, cameras, and communication systems. They are capable of performing tasks such as surveillance, inspection, mapping, and delivery while navigating through the air.

Key Components

Frame:

The structural body of the drone, typically made from lightweight materials like carbon fiber, plastic, or aluminum to minimize weight while maintaining strength.

Propulsion System

Motors: Electric motors, usually brushless DC motors, provide the necessary thrust to keep the drone airborne.

Paired with the motors to generate lift and control movement.

Flight Controller: The central processing unit that integrates sensor data and commands to control the drone's motors, ensuring stable flight and navigation.

21AD521

Power Source: Typically powered by rechargeable batteries, often lithium

polymer (LiPo), though some drones use fuel cells or hybrid systems for longer endurance.

Sensors

IMUs (Inertial Measurement Units): Measure acceleration and rotational rates to maintain stability and orientation.

GPS: Provides location data for navigation and positioning.

Cameras: Capture images and videos for various applications like surveillance, inspection, and mapping.

LiDAR/Radar: Used for obstacle detection and terrain mapping. **Barometers:** Measure altitude to maintain and control flight height.

Communication Systems: Enables remote control and data transmission between the drone and the ground station or operator.

1. Multirotors

Multirotor drones are the most common type of aerial robots and are characterized by multiple rotors that provide lift and thrust.

Types

Quadcopters: Have four rotors and are known for their simplicity and stability. They are widely used in consumer and professional applications.

Hexacopters: Equipped with six rotors, providing greater lift and redundancy (can still fly if one rotor fails). Used for carrying heavier payloads.

Octocopters: Have eight rotors, offering even more lift, stability, and redundancy. Ideal for heavy-lift operations and professional-grade filming.

Key Features

Vertical Take-Off and Landing (VTOL): Can take off and land vertically, making them highly versatile in various environments.

Hovering Capability: Can hover in place, making them suitable for tasks like photography, inspection, and surveillance.

21AD521

Easy Control: Simplified control systems due to their symmetric design.

Applications

Aerial Photography and Videography: Widely used by photographers and filmmakers for capturing aerial shots.

Surveillance and Security: Employed in monitoring and patrolling tasks.

Delivery Services: Used for small parcel delivery in urban and rural areas.

2. Fixed-Wing Drones

Fixed-wing drones are designed like traditional airplanes with wings that generate lift through forward motion.

Key Features

Longer Flight Times: More efficient than multirotors, allowing for longer flights and greater distances.

Higher Speeds: Capable of flying at higher speeds, making them suitable for covering large areas quickly.

Requires Runways: Needs a runway or catapult for takeoff and landing, limiting their operational environments.

Applications

Mapping and Surveying: Ideal for creating detailed maps and conducting surveys over large areas.

Agriculture: Used for monitoring crop health and planning irrigation.

Environmental Monitoring: Employed in tracking wildlife, monitoring forests, and other environmental studies.

3. Hybrid VTOL (Vertical Take-Off and Landing) Drones

Hybrid VTOL drones combine the features of both multirotors and fixed-wing drones.

Key Features

VTOL Capability: Can take off and land vertically like a multirotor.

Fixed-Wing Efficiency: Transitions to fixed-wing flight for efficient long distance travel.

Versatility: Combines the best of both worlds, suitable for a wide range of applications.

Applications

Long-Distance Delivery: Used for delivering goods over longer distances where traditional drones would be inefficient.

Search and Rescue: Employed in missions that require both precise hovering and long-range travel.

Military and Defense: Used in reconnaissance and surveillance missions. 4. Single Rotor Helicopters

Single rotor helicopters have one main rotor and a tail rotor to provide stability and control.

Key Features

Efficient Lift: More efficient than multirotors for longer-duration flights. Higher

Payload Capacity: Can carry heavier payloads compared to multirotors.

Complex Control: Requires more complex control mechanisms due to the single rotor dynamics.

Applications

Heavy-Lift Operations: Suitable for tasks requiring the lifting of heavy equipment.

Agricultural Spraying: Used for spraying crops with fertilizers or pesticides.

Long-Endurance Missions: Employed in missions that require long flight times and heavy payloads.

Summary

Multirotors: Versatile, easy to control, and suitable for short-duration, high precision tasks. Commonly used in photography, surveillance, and delivery services.

Fixed-Wing Drones: Efficient for long-distance, high-speed applications like mapping, surveying, and environmental monitoring. Limited by the need for runways.

Hybrid VTOL Drones: Offer the versatility of both VTOL and fixed-wing flight, making them suitable for a wide range of applications, including long-distance delivery and search and rescue.

Single Rotor Helicopters: Efficient and capable of carrying heavy payloads, ideal for long-endurance and heavy-lift missions, but require more complex control systems.

Each type of aerial mobile robot has its unique strengths and is chosen based on the specific requirements of the task at hand. As technology continues to advance, these drones are becoming increasingly capable and essential in various industries.

*****UNIT1COMPLETED*****