

- 7 (a) State Faraday's law of electromagnetic induction.

.....  
.....  
..... [2]

- (b) Two coils are wound on an iron bar, as shown in Fig. 7.1.




Fig. 7.1

Coil 1 is connected to a potential difference (p.d.)  $V_1$  that gives rise to a magnetic field in the iron bar.

Fig. 7.2 shows the variation with time  $t$  of the magnetic flux density  $B$  in the iron bar.





Fig. 7.2

A voltmeter measures the electromotive force (e.m.f.)  $V_2$  that is induced across coil 2.


On Fig. 7.3, sketch the variation with  $t$  of  $V_2$  between  $t = 0$  and  $t = 0.40\text{s}$ .



**Fig. 7.3**

[4]

- (c) Coil 2 in (b) is now replaced with a copper ring that rests loosely on top of coil 1. The supply to coil 1 is replaced with a cell and a switch that is initially open, as shown in Fig. 7.4.



**Fig. 7.4**

- (i) The switch is now closed. As it is closed, the copper ring is observed to jump upwards.

Explain why this happens.

.....  
.....  
.....  
.....

[3]

- (ii) Suggest, with a reason, what would be the effect of repeating the procedure in (c)(i) with the terminals of the cell reversed.

.....  
.....

[1]