<table>
<tr><td></td><td></td><td></td></tr>
<tr><td>5(a)</td><td><table><tr><td>(0.2 ms)</td><td>8.0 (mV)</td><td>1000</td></tr></table></td><td>B1</td></tr>
<tr><td></td><td><table><tr><td>(0.8 ms)</td><td>5.8 (mV)</td><td>0101</td></tr></table></td><td>B1</td></tr>
<tr><td>5(b)</td><td>series of steps</td><td>B1</td></tr>
<tr><td></td><td>all (step) changes are at 0.2 ms intervals</td><td>B1</td></tr>
<tr><td></td><td>steps with correct levels at correct times
(1 mark if five levels correct; 2 marks if all levels correct)
<table><tr><td>level</td><td>0</td><td>8</td><td>10</td><td>15</td><td>5</td><td>8</td></tr><tr><td>time / ms</td><td>0–0.2</td><td>0.2–0.4</td><td>0.4–0.6</td><td>0.6–0.8</td><td>0.8–1.0</td><td>1.0–1.2</td></tr></table></td><td>B2</td></tr>
<tr><td>5(c)</td><td>smaller step heights (possible)</td><td>B1</td></tr>
<tr><td></td><td>smaller changes (in input signal) can be seen/reproduced/represented
or
(allows) more accurate <u>reproduction</u> (of the input signal)</td><td>B1</td></tr>
</table>

© UCLES 2017