




Solutions. For Life.

PRODUCT PROFILE

Building Services

**Trust of German
Technology**



Welcome to the KSBUILDING World

KSB - A one stop Technology Shop

A systematised solution by KSB involves more than merely designing and building the right pump to meet the exact demands of a variety of customers.

KSB Limited manufactures a wide range of world-class energy efficient pumps and valves from its six facilities in India, each dedicated to a product line. An ISO 9001:2015, ISO14001:2015 & ISO 45001:2018 organisation, KSB in India has systematised concurrent production of dissimilar components. All components, each with different specifications, flow through the computer-controlled manufacturing process.

A systematised solution by KSB involves more than merely designing and building the right pump to meet the exact demands of a variety of customers.

All the pumps and valves are offered to the market through a very wide distribution network comprising of 4 zonal offices, 14 branch offices, over 1000 authorised dealers, 6 service stations, over 350 authorised service centres and 22 godowns...

All this to ensure, that for every KSB pump and valve in use, there is a KSB sales and service outlet around the corner.

KSB not only engineers state-of-the-art pump and valve technology but also strives to provide an air-tight array of service around pumps and valves. KSB stands by its customers all along, through the entire implementation of a project, offers continuous after-sales service and undertakes a variety of service contracts and energy audits to provide optimum and cost effective solutions.

At KSB, the relation with the customer is an ongoing partnership, continuing beyond product commissioning. Regular tailor-made training sessions are held, in-house and at the customers' sites, to acquaint them with selection, operation and maintenance to get the best from KSB pumps and valves.

All this has been made possible by the commitment and dedication of the collective strength of about 2000+ strong team who firmly believe that rewards come through the success of a client's project.

Product Range for Building Services

Hydropneumatic System



MoviBOOST Kt, Vt, VPt

Fully automatic pressure boosting units available in three variants - Kt, Vt & VPt with 2 to 6 vertical In-line high-pressure pumps and fully electronic control of the required supply pressure with standard volt-free contacts for fault indication and status. Suitable for residential & commercial buildings, hospitals, hotels, departmental stores, airports, metro stations, convention centre, sport complex etc.

Capacity	Q	up to 800 m ³ / hr.
Head	H	up to 250 m
Disc. Pressure	P	40 bar
Temperature	t	up to 140° C

Pressure Booster System



MoviBOOST Dual - KHM

The moviBoost Dual system is a pressure booster pump set with two identical horizontal multistage pumps connected in parallel to support the variable flow requirement.

The system consists of 2 nos. KHM pumps including all necessary accessories & piping mounted on common base plate, water tank (optional), pressure sensors and control panel.

Capacity	Q	up to 14 m ³ / hr.
Head	H	up to 54 m
Disc. Pressure	P	10 bar
Temperature	t	up to 70° C

High Pressure In-line Pump



Movitec B

Multi-stage, vertical inline high-pressure centrifugal pumps in ring-section design.

Also available with KSB PumpDrive and IE5 magnetless synchronous reluctance motor*

Suitable for general water supply, sprinkling, irrigation and pressure boosting systems, warm water, hot water and cooling water re-circulation, boiler feed systems, domestic water supply systems and washing plants.

Pump Size	2, 4, 6, 10, 15, 25, 40, 60, 90, 125
Capacity	up to 125 m ³ /hr.
Head	up to 228 mtrs.
Pressure	25 bar
Temperature	-20 to 140°C

End Suction Pump



Etanorm

Horizontal, end suction, centrifugal, radially split volute casing pumps in back-pull-out design fitted with single stage radial impeller.

Suitable for general water supply, sprinkling, irrigation, booster plants, circulation of warm, hot and cooling water, delivery of condensate and boiler-feed water and fire fighting applications.

Pump Size	DN	25 to 150 mm
Capacity	Q	up to 660 m³/hr.
Head	H	up to 160 m
Discharge press.	P	up to 16 bar
Temperature	t	-30 to 140°C
Speed	n	up to 2900 rpm

Closed Coupled Pump



Etabloc

Compact, horizontal, end suction, centrifugal, radially split volute casing pumps in monobloc construction.

Suitable for general water supply, sprinkling, irrigation, booster plants, circulation of warm, hot and cooling water, delivery of condensate and boiler-feed water and fire fighting applications.

Pump Size	25 to 150 mm
Capacity	up to 640 m³/hr.
Head	up to 160 m
Discharge press.	up to 16 bar
Temperature	-30 to 140°C
Speed up to	2900 rpm

Vertical In-line Pump



Etaline


Centrifugal, radially split in-line pumps in monobloc construction.

Can be mounted horizontally or vertically. Flanges are drilled to ASME or EN standard. Suction and delivery sizes are common and hence no need of expander.

Suitable for HVAC, fire fighting, air conditioning, industrial recirculation, etc.

Pump Size	32 to 200 mm
Capacity	up to 700 m³/hr.
Head	up to 95 m
Discharge press.	up to 16 bar
Temperature	-30 to 140°C
Speed	up to 2900 rpm

Horizontal Split Case Pump



Omega / Gamma

Single-stage axially split volute casing pump with double flow radial impeller for horizontal installation.

Suitable for fire fighting, water & waste water, Industry, Irrigation, HVAC etc

Pump Size	80 to 350 mm
Capacity	up to 1000 m³/hr.
Head	up to 150 m
Discharge press.	up to 16 bar
Temperature	0 to 80°C
Speed	up to 2900 rpm

MSMO Pump



WK / WKS

Horizontal, radially split, high pressure, multistage pumps with multi outlet construction.

Suitable for firefighting applications.

Package includes - Pump, base frame, coupling, coupling guard, electric motor / diesel engine, jockey pump along with accessories like control cabinet, fuel tank, batteries, switches etc.

Pump Size	40 to 150 mm
Capacity	up to 210 m³/hr.
Head	up to 400 m
Discharge press.	up to 40 bar
Temperature	-30 to 140°C
Speed	up to 2900 rpm

Listed Pumpsets



UL / FM approved Pumpsets

UL listed and FM approved complete range of fire pumpsets which includes Hydrant, sprinkler, (motor as well as engine driven)

Package includes - Pump, base frame, coupling, coupling guard, electric motor/ diesel engine, jockey pump along with accessories like control cabinet, fuel tank, batteries, switches etc.

Capacity	up to 700 m³/hr.
Head	up to 250 m
Discharge press.	up to 40 bar
Temperature	up to 140°C
Speed	up to 2900 rpm

Submersible Motor Pump



Ama-Drainer

Vertical fully floodable submersible motor with In built swing check valve. Jacket cooled single phase motor with integrated temperature switch. Float switch for automatic operation. Suitable for lowering surface water level, transfer of water, agricultural pits, & sprinklers in gardens, drainage of cellars / basin

Pump Size	DN	35 mm
Capacity	Q	up to 12 m³/hr
Head	H	up to 11 m
Motor		up to 0.60 kW
Temperature	t	up to 40°C
Free passage		up to 10 mm

Sewage/ Drainage Pump



Amarex IN & KRTU

Single stage, submersible centrifugal pumps of closed coupled (monobloc) construction.

Amarex IN pumps are suitable for handling waste water transport, storm water transport, waste water treatment etc.(Also available with cutter option)

KRTU pumps are suitable for handling municipal and industrial waste water. 3 types of impellers available to suit a variety of needs.

Pump Size	DN	50, 65, 100 mm
Capacity	Q	up to 190 m³/hr
Head	H	up to 49 mtrs.
Temperature	t	up to 70°C
Motor power	P	up to 9.5 kW
Speed	n	up to 2900 rpm
Free passage		up to 100 mm

Submersible Drainage Pump



Ama Porter

Vertical, monobloc pumpset, free flow impeller of two sizes, 1Ø and 3Ø motors with IP 68 protection, 1Ø motor with built-in thermal overload protection and float switch, bi-directional mechanical seal

Suitable for pumping surface water, rain water, waste water containing solids, drainage of sumps liable to flood, agricultural pits and canals.

Pump Size	DN	50 mm
Capacity	Q	up to 29 m³/hr
Head	H	up to 16 m
Motor power	P	up to 1.1 kW (1Ø) up to 1.5 kW (3Ø)
Temperature	t	up to 40°C
Free passage		up to 40 mm

Borewell Submersible Pumps




Submersible pump in multi-stage construction with radial or mixed flow impellers coupled with oil or water filled, single or three phase submersible motors.

Suitable for horticulture, irrigation, housing, building services and farm houses, ornamental fountains etc.

Well diameter	D	min. 75 mm
Capacity	Q	up to 800 m³/hr
Head	H	up to 400 m
Motor power	P	up to 110 kW
Speed	n	2900 rpm

Surface Monobloc Pumps



Ultra Plus / Ultra Plus FF

3 Phase Centrifugal pumps in Monobloc design with rigid cast iron body.

Available in 7 models ranging from 3 to 20 HP for agricultural, building, fire fighting and industrial applications. Available with Mechanical Seal and Gland Pack Sealing

Capacity	Q	up to 150 m³/hr
Head	H	up to 76 m
Temperature	t	Ambient
Motor rating	n	upto 15 kW
Speed	n	2900 rpm

HVAC Control Panel



PVAC / SVAC

Fully automatic CL system suitable for driving up to 6 pumps with or without bypass starter. Control panel comprising separate VFDs & controller.

Suitable for handling Primary & secondary pumping in HVAC, warm water/ hot water circulation, cooling water circulation.

Motor	:	up to 110 kW
No. of Pumps	:	up to 08 nos
Display	:	Touch Screen HMI
Enclosure rating	:	IP 55