

200+150 mm Submersible Motor Pumpsets



200+150 mm – Submersible Motor Pumpsets

KSB, a leading manufacturer of pumps, valves and systems offers its clients the latest pumping technology through a variety of pumpsets designed for the future.

KSB Submersible pump with outside diameter of 200 mm and motor of 150 mm can be installed in borewell of size 200 mm and above. The pumps and motors are made using sophisticated and advanced manufacturing processes to ensure top class performance of the pumpsets.

Applications

- Irrigation
- Drinking water supply
- Industrial water supply
- Lift irrigation

Special features

- High efficiency
- Lower power consumption
- Low voltage starting capability
- Special thrust bearing
- Corrosion free motor internals
- Stainless Steel rotor and pump shaft
- Stainless Steel strainer
- Dynamically balanced rotary parts
- Water filled
- Water lubricated
- Noiseless
- Easily re-windable

Selection Table

Pump of 200 mm diameter + motor of 150 mm Suitable for borewells of 200 mm and above.

Pump type	Motor type	Motor rating		Cable size	Starting method	Rated current	Overall length	Weight approx.		Discharge (m ³ /hr.)								
		kW	HP							30	40	50	60	70	80	90	100	110
BPHA	UMA I 150			mm ²		A	mm	kg										
333/2E	6/22	5.50	7.50	2.5	DOL	11.8	1312	81		-	-	27	25	23	19	16	-	-
333/2D	8/22	7.50	10.00	2.5	S/D	15.6	1352	84		-	-	35	33	31	29	25	-	-
333/2C	9/22	9.30	12.50	2.5	S/D	18.5	1392	94		-	-	37	36	34	31	27	-	-
333/3B	9/22	9.30	12.50	2.5	S/D	18.5	1512	102		-	-	49	46	42	38	34	-	-
333/3D	13/22	11.00	15.00	2.5	S/D	22.0	1642	110		-	-	52	49	46	42	38	-	-
BPHA	UMA G 150																	
333/4B	16/21	13.00	17.50	2.5	S/D	27.0	1874	79		-	-	65	61	56	51	45	-	-
333/3C	21/21	15.00	20.00	4.0	S/D	33.0	1854	77		-	60	58	56	52	48	42	35	-
333/4F	21/21	15.00	20.00	4.0	S/D	33.0	1974	85		-	74	70	67	-	-	-	-	-
333/4F	24/21	18.50	25.00	4.0	S/D	40.0	2084	92		-	74	70	67	63	59	54	47	38
BPHA	UMA I 150									50	60	70	80	90	100	110	120	130
384/1D	8/22	7.50	10.00	2.5	S/D	15.6	1242	84		-	-	22	21	20	18	-	-	-
384/2E	9/22	9.30	12.50	2.5	S/D	18.5	1412	99		-	-	35	32	29	26	-	-	-
384/2F	13/22	11.00	15.00	2.5	S/D	22.0	1542	107		-	-	39	37	35	32	-	-	-
BPHA	UMA G 150																	
384/2D	21/21	15.00	20.00	4.0	S/D	33.0	1754	74		48	47	46	44	41	38	35	-	-
384/3H	21/21	15.00	20.00	4.0	S/D	33.0	1884	79		62	60	58	56	-	-	-	-	-
384/3G	24/21	18.50	25.00	4.0	S/D	40.0	1994	86		62	60	58	56	52	48	43	37	30

Pump type	Motor type	Motor rating		Cable size	Starting method	Rated current	Overall length	Weight approx.		Discharge (m ³ /hr.)									
		kW	HP							80	90	100	110	120	130	140	150	160	170
BPHA	UMA I 150			mm ²		A	mm	kg											
373/1A	6/22	5.50	7.50	2.5	DOL	11.8	1229	73		13.5	13.0	12.5	12.0	11.0	10.5	9.5	8.5	7.0	-
373/1B	8/22	7.50	10.00	2.5	S/D	15.6	1269	76		17.5	17.0	16.5	15.5	15.0	14.5	13.5	12.5	11.5	10.0
373/1D	9/22	9.30	12.50	2.5	S/D	18.5	1309	86		18.3	18.0	17.3	17.0	16.7	16.0	15.3	14.7	13.3	12.3
373/2A	13/22	11.00	15.00	2.5	S/D	22.0	1479	109		27	26	25	24	22	21	19	17	14	-
BPHA	UMA H 150																		
373/2C	14/23	13.00	17.50	2.5	S/D	30.0	1606	109		29	28	27	26	25	23	21	19	17	13
373/2B	15/23	15.00	20.00	4.0	S/D	33.0	1666	119		35	34	33	31	30	29	27	25	23	20
373/2D	17/23	15.00	20.00	4.0	S/D	42.0	1736	123		37	36	35	34	33	32	31	29	27	25
373/3C	17/23	18.50	25.00	4.0	S/D	42.0	1876	138		44	42	41	39	37	35	32	29	25	20

Pump type	Motor type	Motor rating		Cable size	Starting method	Rated current	Overall length	Weight approx.		Discharge (m ³ /hr.)						
		kW	HP							80	100	120	140	160	180	200
BPH	UMA I 150			mm ²		A	mm	kg								
383/1A	8/22	7.50	10.00	2.5	S/D	15.6	893	83		18	15	14	13	11	9	5
383/1	9/22	9.30	12.50	2.5	S/D	18.5	913	87		21	19	18	17	15	13	10
BPH	UMA H 150															
383/2A	15/23	15.00	20.00	4.0	S/D	33.0	1272	127		36	30	28	26	22	17	10
383/2	17/23	18.50	25.00	4.0	S/D	42.0	1342	127		42	38	36	34	30	25	20



KSB Pumps Limited
Standard Pumps Division
 Plot No. E3 & E4, MIDC Sinnar, Nashik 422 113.
 Tel.: +91-2551-230252 / 53, 229700 www.ksbindia.co.in

Our toll free no : 1800 233 1299
 (Mon-Fri. 8am-8pm)

Mktg. Serv. / 03-18 / 5000

Subject to technical modification without prior notice.

3402.025