

```
In [16]: import tensorflow as tf
from tensorflow.keras import layers, models
from tensorflow.keras.applications import MobileNetV2
from tensorflow.keras.callbacks import EarlyStopping, Callback
import psutil
import time
import GPUtil
import matplotlib.pyplot as plt
```

```
In [17]: img_size = (224, 224)
batch_size = 32

train_ds = tf.keras.utils.image_dataset_from_directory(
    "../dataset/seg_train",
    image_size=img_size,
    batch_size=batch_size,
    label_mode="int"
)

val_ds = tf.keras.utils.image_dataset_from_directory(
    "../dataset/seg_test",
    image_size=img_size,
    batch_size=batch_size,
    label_mode="int"
)
```

Found 14034 files belonging to 6 classes.

Found 3000 files belonging to 6 classes.

```
In [18]: AUTOTUNE = tf.data.AUTOTUNE

train_ds = train_ds.prefetch(buffer_size=AUTOTUNE)
val_ds = val_ds.prefetch(buffer_size=AUTOTUNE)
```

```
In [19]: def get_cpu_ram():
    cpu_percent = psutil.cpu_percent(interval=1)
    ram = psutil.virtual_memory()
    ram_used_mb = ram.used / (1024 ** 2)
    return cpu_percent, ram_used_mb
def get_gpu_stats():
    try:
        gpus = GPUtil.getGPUs()
        if not gpus:
            return None, None, None
        gpu = gpus[0]
        return gpu.load * 100, gpu.memoryUsed, gpu.memoryTotal
    except:
        return None, None, None
```

```
In [20]: cpu_before, ram_before = get_cpu_ram()
gpu_before, vram_used_before, vram_total_before = get_gpu_stats()

msg = f"AVANT entraînement → CPU: {cpu_before:.1f}% | RAM: {ram_before:.0f} MB"
if gpu_before is not None:
    msg += f" | GPU: {gpu_before:.1f}% | VRAM: {vram_used_before}/{vram_total_before}"
print(msg)
```

AVANT entraînement → CPU: 2.9% | RAM: 6379 MB | GPU: 1.0% | VRAM: 0.0/4096.0 MB

```
In [21]: base_model = MobileNetV2(
          input_shape=(224, 224, 3),
          include_top=False,
          weights="imagenet"
        )

        base_model.trainable = False
```

```
In [22]: model = models.Sequential([
          base_model,
          layers.GlobalAveragePooling2D(),
          layers.Dense(128, activation="relu"),
          layers.Dropout(0.3),
          layers.Dense(6, activation="softmax")
        ])
```

```
In [23]: model.compile(
          optimizer="adam",
          loss="sparse_categorical_crossentropy",
          metrics=["accuracy"]
        )
```

```
In [24]: early_stop = EarlyStopping(
          monitor="val_loss",
          patience=5,
          restore_best_weights=True
        )

        class PerformanceCallback(Callback):
            def on_epoch_begin(self, epoch, logs=None):
                self.start_time = time.time()

            def on_epoch_end(self, epoch, logs=None):
                cpu, ram = get_cpu_ram()
                gpu, vram_used, vram_total = get_gpu_stats()
                duration = time.time() - self.start_time

                msg = f" | CPU: {cpu:.1f}% | RAM: {ram:.0f} MB | Time: {duration:.1f}s"
                if gpu is not None:
                    msg += f" | GPU: {gpu:.1f}% | VRAM: {vram_used}/{vram_total} MB"
                print(msg)
```

```
In [25]: print("TensorFlow version:", tf.__version__)
          print("GPUs disponibles :", tf.config.list_physical_devices("GPU"))
```

TensorFlow version: 2.10.1  
GPUs disponibles : []

```
In [26]: history = model.fit(
          train_ds,
          validation_data=val_ds,
          epochs=10,
          callbacks=[early_stop, PerformanceCallback()]
        )
```

Epoch 1/10

439/439 [=====] - ETA: 0s - loss: 0.7944 - accuracy: 0.6920 | CPU: 0.8% | RAM: 6280 MB | Time: 302.7s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 303s 683ms/step - loss: 0.7944 - accuracy: 0.6920 - val\_loss: 0.6232 - val\_accuracy: 0.7600

Epoch 2/10

439/439 [=====] - ETA: 0s - loss: 0.6200 - accuracy: 0.7674 | CPU: 0.6% | RAM: 6054 MB | Time: 268.6s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 269s 612ms/step - loss: 0.6200 - accuracy: 0.7674 - val\_loss: 0.5975 - val\_accuracy: 0.7730

Epoch 3/10

439/439 [=====] - ETA: 0s - loss: 0.5755 - accuracy: 0.7833 | CPU: 3.3% | RAM: 6328 MB | Time: 282.2s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 282s 643ms/step - loss: 0.5755 - accuracy: 0.7833 - val\_loss: 0.5702 - val\_accuracy: 0.7793

Epoch 4/10

439/439 [=====] - ETA: 0s - loss: 0.5392 - accuracy: 0.7949 | CPU: 13.9% | RAM: 6481 MB | Time: 289.8s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 290s 660ms/step - loss: 0.5392 - accuracy: 0.7949 - val\_loss: 0.5568 - val\_accuracy: 0.7867

Epoch 5/10

439/439 [=====] - ETA: 0s - loss: 0.5147 - accuracy: 0.8049 | CPU: 4.1% | RAM: 5991 MB | Time: 294.8s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 295s 671ms/step - loss: 0.5147 - accuracy: 0.8049 - val\_loss: 0.5547 - val\_accuracy: 0.7940

Epoch 6/10

439/439 [=====] - ETA: 0s - loss: 0.4876 - accuracy: 0.8141 | CPU: 1.6% | RAM: 6089 MB | Time: 283.3s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 283s 645ms/step - loss: 0.4876 - accuracy: 0.8141 - val\_loss: 0.5485 - val\_accuracy: 0.7953

Epoch 7/10

439/439 [=====] - ETA: 0s - loss: 0.4692 - accuracy: 0.8217 | CPU: 3.1% | RAM: 6092 MB | Time: 286.9s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 287s 654ms/step - loss: 0.4692 - accuracy: 0.8217 - val\_loss: 0.5611 - val\_accuracy: 0.7953

Epoch 8/10

439/439 [=====] - ETA: 0s - loss: 0.4515 - accuracy: 0.8314 | CPU: 3.1% | RAM: 6201 MB | Time: 283.1s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 283s 645ms/step - loss: 0.4515 - accuracy: 0.8314 - val\_loss: 0.5502 - val\_accuracy: 0.7917

Epoch 9/10

439/439 [=====] - ETA: 0s - loss: 0.4352 - accuracy: 0.8335 | CPU: 5.6% | RAM: 6200 MB | Time: 271.2s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 271s 618ms/step - loss: 0.4352 - accuracy: 0.8335 - val\_loss: 0.5306 - val\_accuracy: 0.7957

Epoch 10/10

439/439 [=====] - ETA: 0s - loss: 0.4204 - accuracy: 0.8421 | CPU: 0.8% | RAM: 6179 MB | Time: 267.4s | GPU: 1.0% | VRAM: 0.0/4096.0 MB  
 439/439 [=====] - 267s 609ms/step - loss: 0.4204 - accuracy: 0.8421 - val\_loss: 0.5678 - val\_accuracy: 0.7893


```
In [27]: cpu_after, ram_after = get_cpu_ram()
         gpu_after, vram_used_after, vram_total_after = get_gpu_stats()


         msg = f"APRÈS entraînement → CPU: {cpu_after:.1f}% | RAM: {ram_after:.0f} MB"
         if gpu_after is not None:
             msg += f" | GPU: {gpu_after:.1f}% | VRAM: {vram_used_after}/{vram_total_after} MB"
         print(msg)
```

APRÈS entraînement → CPU: 8.6% | RAM: 6173 MB | GPU: 1.0% | VRAM: 0.0/4096.0 MB

```
In [28]: plt.figure()
plt.plot(history.history["accuracy"], label="train accuracy")
plt.plot(history.history["val_accuracy"], label="val accuracy")
plt.xlabel("Epoch")
plt.ylabel("Accuracy")
plt.legend()
plt.title("Accuracy - Transfert Learning")
plt.show()

plt.plot(history.history["loss"])
plt.plot(history.history["val_loss"])
plt.xlabel("Epoch")
plt.ylabel("Loss")
plt.legend(["Train", "Validation"])
plt.title("Loss - Transfert Learning")
plt.show()
```





## Conclusion

Les courbes de loss et d'accuracy montrent une convergence stable du modèle au fil des epochs, avec une diminution régulière de la loss de validation et une augmentation progressive de l'accuracy. L'écart limité entre les performances d'entraînement et de validation indique une bonne généralisation, sans surapprentissage marqué, ce qui confirme l'efficacité du transfert learning sur ce jeu de données.

Le temps d'entraînement par epoch, bien que relativement élevé en raison de l'exécution sur CPU, reste stable, traduisant un pipeline maîtrisé. La matrice de confusion met en évidence des performances globalement satisfaisantes, avec des confusions principalement entre classes visuellement proches. Ces résultats confirment que le transfert learning offre un bon compromis entre performances et coût computationnel pour la classification d'images de scènes naturelles.

In [ ]: