



# What could we improve? (again)

- Avoiding hard-coded parameters
- Processing list of files
- Optimising resource usage

# What could we improve? (again)

- Avoiding hard-coded parameters → config file
- Processing list of files → expand() syntax
- Optimising resource usage → threads directive

# What could we improve? (again)

- Avoiding hard-coded parameters → config file
- Processing list of files → expand() syntax
- Optimising resource usage → threads directive

# Avoiding hard-coded parameters: config file

- Snakemake can use configuration files to render workflows more flexible
  - Change config instead of code!

# Avoiding hard-coded parameters: config file

- Snakemake can use configuration files to render workflows more flexible
  - Change config instead of code!
- 2 possible formats: JSON and YAML
  - Personal opinion: YAML is easier to write, understand and can be commented

```
{  
  "retries": 5,  
  "samples": [  
    "file1",  
    "file2"  
  ],  
  "resources": {  
    "threads": 8,  
    "memory": "500M"  
  }  
}
```

JSON

```
retries: 5 # Single value  
samples: # Multiple values  
- file1  
- file2  
resources: # Nested parameters  
  threads: 8  
  memory: 500M
```

YAML

# Avoiding hard-coded parameters: config file

- Snakemake can use configuration files to render workflows more flexible
  - Change config instead of code!
- 2 possible formats: JSON and YAML
  - Personal opinion: YAML is easier to write, understand and can be commented
- Imported file with `configfile` keyword in Snakefile
  - `configfile: 'path/to/config.yaml'` (relative to working directory)
- Accessed via global variable `config`
  - Imported as a Python dictionary (use keys to access values):  
`config['samples']`

```
configfile: 'config.yaml'
```

Snakefile

# Config file?

- Question 5



# What should appear in a config file?

- Ideally, everything that should not be hard-coded:
  - File locations
  - Sample names and associated information
  - Rule computing resources
  - Etc...

# What should appear in a config file?

- Ideally, everything that should not be hard-coded:
  - File locations
  - Sample names and associated information
  - Rule computing resources
  - Etc...
- But it is preferable to use paths to other smaller config files
  - Same as Snakefile and snakefiles
  - Example:
    - Table containing the sample names and information: `config/samples_info.tsv`
      - Tab-separated format is easy to write, read and parse
    - In the config file: `samples: 'config/samples_info.tsv'`
    - Add a function in a Snakefile to parse the table

# What should **NOT** appear in a config file?

- Credentials: access tokens, passwords...

⇒ Use environment variables (**envvars**)

# What could we improve? (again)

- Avoiding hard-coded parameters → config file
- Processing list of files → expand() syntax
- Optimising resource usage → threads directive

# Processing list of files: the expand syntax

- `expand()`: Snakemake function to expand a wildcard expression to several values
  - Useful to define multiple `inputs` or `outputs` with a common pattern

# Processing list of files: the expand syntax

- **expand()**: Snakemake function to expand a wildcard expression to several values
  - Useful to define multiple **inputs** or **outputs** with a common pattern
  - Syntax: `expand('{wildcard_name}', wildcard_name=<values>)`
    - <values>: iterable (*i.e.* list, tuple, set) containing the wildcard values

```
rule merge_files:
    input:
        'data/test_1.txt',
        'data/test_2.txt',
        'data/test_3.txt'
    output:
        'results/total.txt'
    shell:
        'cat {input} > {output}'
```

```
rule merge_files:
    input:
        expand('data/test_{file}.txt', file=[1, 2, 3])
    output:
        'results/total.txt'
    shell:
        'cat {input} > {output}'
```

- The **rule merge\_files** uses all three **input** files to generate a single **output** file
- **expand()** does not apply the **rule** three times, once per **input**!

# Processing list of files: the expand syntax

- When there are several **wildcards**, `expand()` creates **all possible combinations**

# Processing list of files: the expand syntax

- When there are several **wildcards**, `expand()` creates **all possible combinations**

```
files=['test_A','test_B']
nbs = [1, 2]

rule merge_files:
    input:
        expand('data/{file}_{nb}.txt', file=files, nb=nbs)
    output:
        'results/total.txt'
    shell:
        'cat {input} > {output}'
```



```
input:
    ['data/test_A_1.txt', 'data/test_A_2.txt',
     'data/test_B_1.txt', 'data/test_B_2.txt']
```



# Processing list of files: the expand syntax

- The **wildcards** in `expand()` are **independent** from wildcards in the **rule**

# Processing list of files: the expand syntax

- The **wildcards** in `expand()` are **independent** from wildcards in the **rule**

```
files=['test_A','test_B']
nbs = [1, 2]

rule merge_files:
    input:
        expand('data/{file}_{nb}.txt', file=files, nb=nbs)
    output:
        'results/{file}.txt'
    shell:
        'cat {input} > {output}'
```

➤ Here, **{file}** value will NOT be propagated to the **input**

# What could we improve? (again)

- Avoiding hard-coded parameters → config file
- Processing list of files → expand() syntax
- Optimising resource usage → threads directive

# Optimising resource usage: threads

- 'threads' is a **directive**; its value is the number of threads to allocate to each job spawned by a **rule**
  - New type of value: numeric (integer)
  - When executed locally, '**--cores**' controls the total number of threads allocated to Snakemake; **threads** is automatically decreased if it's lower than '**--cores**'
  - **Check whether software can actually multithread!**

```
rule example:
    input:
        'data/test.txt'
    output:
        'results/modified_test.txt'
    threads: 4
    shell:
        'command --threads {threads} {input} > {output}'
```

# Exercises

- Through the day:
  - Develop a simple RNAseq analysis workflow, from reads (fastq files) to Differentially Expressed Genes (DEG)
- For this session:
  - Use a config file
  - Modularise a workflow
  - Process list of inputs
  - Aggregate outputs in a target rule
  - (Optimise CPU usage)

