

In terraform oidc_githubAction_AWS

=====

```
provider "aws" {  
  region = "us-west-2"  
}
```

Create an IAM OIDC provider

```
resource "aws_iam_openid_connect_provider" "github" {  
  url      = "https://token.actions.githubusercontent.com"  
  client_id_list = ["sts.amazonaws.com"]  
  thumbprint_list = ["6938fd4d98bab03faadb97b34396831e3780aea1"]  
}
```

Create an IAM role for GitHub Actions

```
resource "aws_iam_role" "github_actions_role" {  
  name = "github-actions-role"  
  assume_role_policy = jsonencode({  
  
    "Version" : "2012-10-17",  
    "Statement" : [  
      {  
        "Effect" : "Allow",  
        "Action" : "sts:AssumeRoleWithWebIdentity",  
        "Principal" : {  
          "Federated" : "arn:aws:iam::<Account ID>:oidc-provider/token.actions.githubusercontent.com"  
        },  
        "Condition" : {  
          "StringLike" : {  
            "token.actions.githubusercontent.com:sub" : "repo:sibanando/development_30_12_24:*"
```

```

        "token.actions.githubusercontent.com:sub" : "repo:sibanando:*"
    },
    "StringEquals" : {
        "token.actions.githubusercontent.com:aud" : "sts.amazonaws.com"
    }
}

}

}

]

}))

}

```

```

# Attach the AWS managed policy for full access to the role
resource "aws_iam_role_policy_attachment" "full_access" {
    role      = aws_iam_role.github_actions_role.name
    policy_arn = "arn:aws:iam::aws:policy/AdministratorAccess"
}

```

```

=====

```

```

# This is a basic workflow to help you get started with Actions

```

```

name: CI

```

```

# Controls when the workflow will run

```

on:

Triggers the workflow on push or pull request events but only for the "main" branch

push:

branches: ["main"]

pull_request:

branches: ["main"]

Allows you to run this workflow manually from the Actions tab

workflow_dispatch:

permissions:

id-token: write # This is required for requesting the JWT

A workflow run is made up of one or more jobs that can run sequentially or in parallel

jobs:

This workflow contains a single job called "build"

build:

The type of runner that the job will run on

runs-on: ubuntu-latest

Steps represent a sequence of tasks that will be executed as part of the job

steps:

- name: configure aws credentials

uses: aws-actions/configure-aws-credentials@v2

with:

role-to-assume: \${ secrets.AWS_ASSUME_ROLE }

aws-region: \${ secrets.AWS_REGION }

Runs a single command using the runners shell

- name: Run a one-line script

run: aws s3 ls