Learning When to Escalate on the Edge

Project Deliverable 1.2 · Technical Blueprint · Applied Machine Learning 2 · University of Florida
Sibi Seenivasan · November 11, 2026 · Repository: github.com/sibi-seeni/learning-to-escalate

a. Problem context and project summary

AI agents now act with tools: they send email, move money and run code. When an agent reads poisoned content, such as an email or web page with hidden instructions, it can be hijacked into doing something the user never asked for. Security monitors that check each tool call exist, but they break quietly on tools and domains they weren't trained on. They also stay confident when they're wrong, and the strong ones are too heavy to run next to the agent.

This project builds a **compact monitor** that reads the agent's trace up to each tool call and scores the risk that the call is hijacked. A second small model, the **deferrer**, learns when that monitor is likely to be wrong, and sends those calls to a human within a fixed review budget. Both run on an **Arduino UNO Q** edge board (quad-core ARM, 4 GB RAM). The main question: can a learned error predictor spend a limited review budget better than plain confidence-based escalation, including on unfamiliar tools and domains? Week 1 is done. The data pipeline, leakage controls, baseline monitor and board setup are in the repository.

b. Dataset

Source and type. AgentDrift (arXiv 2609.06972; GitHub `Asif-0209/AgentDrift`, CC BY 4.0). It holds 12,536 synthetic, text-based tool-using agent traces (71,024 steps) across five domains: banking, coding, email, medical and web. There are 103 distinct tools. Each step records the agent's thought, the tool call and arguments, the tool's result, and a label: benign, injection point, hijacked, or failed injection. Besides successful attacks, it has failed attacks (the agent resisted) and hard negatives (legitimate content that looks like an attack).

Format and access. JSON lines, about 32 MB per split, downloaded with `scripts/get_data.sh` at a pinned commit. We use the task-disjoint split (9,081 / 1,733 / 1,722 traces for train / val / test), so no task appears in both training and testing.

Unit of analysis. One *decision point* per tool call (51,507 / 9,721 / 9,796). The model sees only earlier steps plus the proposed call, never that call's result. The target is "this call is hijacked", which is true for 17–18% of calls.

Preprocessing challenges, all solved in week 1:

- **Identity leakage.** Looking up the user's name, company and contacts alone predicts the attack label with 86.4% accuracy. Our anonymizer replaces people, companies and addresses with role placeholders (`<USER>`, `<CONTACT_MANAGER>`, `<EXTERNAL_EMAIL>`). After that, the shortcut drops to 55.4%, the same as always guessing the majority class (55.0%).
- **Repeated attack targets.** 28.9% of injections reuse one fake domain, so we mask domains and money amounts.
- **Shift splits.** Tool-coverage test sets at 100/75/50/25% hold out 20% of each domain's tools, over 3 seeds. Training keeps each trace only up to its first held-out tool, so the model never sees one. A second split leaves one domain out at a time.

- **Class balance.** 44% of traces are attacked, which is far above real life, so the main results will subsample attacks to 1–5%.

Ethics and privacy. The data is fully synthetic, so no real people, patients or accounts are involved. The attack text comes from the published dataset and we write no new attacks.

c. Planned architecture




Figure 1. Data → model → inference → interface. Blue: the monitor path that runs at every tool call. Orange: the deferral path. Dashed: training-time only.

Models to test.

- **Baseline monitor (done).** The AgentDrift paper's six-feature logistic regression, re-fit on prefixes. It reproduces the paper (F1 0.649 against 0.647) and gets AUROC 0.905 at the decision-point level.
- **Compact neural monitor.** An LSTM or a 1–2 layer causal transformer (width 64–128) over the step sequence. Step features use either light hashed tokens or the MiniLM sentence encoder (22.7M parameters). Both are exported to ONNX and quantized to int8. Week 1 found that ONNX Runtime can't quantize GRU layers, so the recurrent option is an LSTM.
- **Stronger reference monitor.** A DriftNet-style trunk on larger embeddings, run on the laptop only, as the "better monitor" baseline.
- **Learned deferrer.** Gradient-boosted trees (LightGBM) on the monitor's calibrated score and verdict, prefix features, and novelty signals (is this tool unseen, how far is the step from the training data). It is trained on the monitor's out-of-fold errors, with missed hijacks weighted 5×.
- **Deferral baselines, same review budget:** no deferral, random, raw confidence, temperature-calibrated confidence, and a stronger monitor with calibrated confidence.

Frameworks. PyTorch for training, scikit-learn and LightGBM, ONNX Runtime on the board, Gradio for the interface. Week 1 timing on the UNO Q: small stand-in models take 0.3–0.45 ms per decision, with 159 MB peak memory and outputs identical to the laptop's.

Role of the interface. It turns the model's numbers into a decision a person can check. It shows what the monitor saw, how sure it was, and why a call went to review, and it collects the reviewer's answer.

d. User interface plan

There are two linked views. A **Gradio trace replay console** on the laptop is used for analysis and the class demo; a working prototype is already in `ui/app.py`. On the **UNO Q**, the board's LED matrix and a push button give a live approve/reject gate.




Figure 2. Working prototype (week 1). Step 3 of a held-out banking trace is a hijacked money transfer. The baseline monitor scores it 0.17 and says SAFE, a dangerous error. Catching exactly these cases is the deferrer's job.

Input. The user picks a held-out trace (or loads their own trace JSON), then steps through it or plays it. On the board, the input is the button: one press approves, a long press rejects.

Output. For each call the interface shows the visible prefix, the monitor score and verdict, and the trust/defer decision with its reason (e.g. "unseen tool", "low confidence"). It also shows a running table of decisions and the reviewer's log. A summary panel adds the risk-versus-review-budget curve and the board's latency.

Why it helps. Reviewers see why they're being asked, not just a score. Showing only the past makes clear the model can't peek ahead, and the ground-truth column, shown in demo mode only, makes errors visible.




Figure 3. Board wireframe. The LED matrix shows the verdict for each call, and deferred calls wait for the button.

e. Innovation and anticipated challenges

What's new. Learned deferral and monitor failure under shift have each been studied separately. What's open is whether an *error-aware* deferrer still helps where monitor rankings flip, below about

50% tool coverage. We test that with a leakage-free, prefix-only protocol, on a model small enough to measure on a low-cost edge board. The deferrer predicts "the monitor is wrong here", not "this is an attack", so it isn't just a second classifier. A careful negative result is still a contribution, and the edge table stands either way.

Risk	Mitigation
Too few monitor errors to train the deferrer, since a good monitor makes few mistakes	Every tool call is a decision point, not just state-changing ones, which also keeps 13% of attacks catchable. Pool out-of-fold errors across folds. Report error counts per split. Fall back to a weaker monitor setting.
Learned deferral is no better than calibrated confidence	Use the same review budget and a calibrated baseline, so any gain is real. Report the full 0–30% curve. A negative result is still reported.
Encoder or quantization doesn't fit the board	Measure on the board in week 2, before building on it. Use hashed features instead of MiniLM, an LSTM instead of a GRU (int8 support), and float as a fallback with the cost reported.

f. Implementation timeline

Week	Focus	Expected outcome
1 · Nov 9–15 D1.2 Nov 11	Data, protocol, baseline, board setup **(done)**	Anonymizer and leakage check (86% → 55%), decision points and error labels, LR baseline, shift splits, board check passing, notebook and UI prototype.
2 · Nov 16–22 D2 Nov 18	Compact neural monitor	LSTM and tiny transformer train end-to-end, int8 ONNX export, one real decision timed on the board, calibration, out-of-fold errors. UI uses the neural monitor.
3 · Nov 23–29 D3 Nov 25	Deferrer and shift experiments	LightGBM deferrer. All policies at 1–5% prevalence, tool coverage 100–25%, five held-out domains, and risk vs. budget curves. UI shows the defer reason and curves.
4 · Nov 30–Dec 6	On-board demo and edge table	Featurizer, monitor and deferrer run on the UNO Q with LED and button. Accuracy × size × latency table. Interface polish.
5 · Dec 7–9 D4 Dec 9	Final report and demo	IEEE-format report, live demo (one trace caught, one deferred, one missed), poster for the UF IoT × AI conference.

g. Responsible AI reflection

- **Transparency.** The interface shows what the model saw, its score and the reason for each deferral. Results state the split protocol, the error counts and every deviation from the published setup.
- **Overstated safety.** The pilot assumes a perfect human reviewer, so the results are an upper bound. A single board is also not a secure boundary, since a compromised process could fake the display. Both limits are stated, and the capstone addresses the second.
- **Fairness across domains.** Results are reported per domain. Banking has fewer attacks and email has the most false alarms, so one average number could hide a domain where the system fails.
- **Human factors.** Too many deferrals cause review fatigue and rubber-stamping. A fixed budget and reporting the false-alarm burden keep that visible.

- **Privacy and dual use.** The data is synthetic and anonymized, and no new attacks are created.
- **Environment.** Small models, CPU training and sub-millisecond inference on a low-power board keep the energy cost low.

Sources: AgentDrift dataset and paper (arXiv 2609.06972); DriftNet (arXiv 2609.10892); What Standard Evaluations Hide About Detectors of Hijacked LLM Agents (arXiv 2610.41803); From Detection to Decision (arXiv 2610.20907).