

The Architecture of Errors: Logarithmic Mode Discovery and Polylogarithmic Intervention Budgets for Long-Context LLM Reliability

Mikhail L. Arbuzov

Alexey A. Shvets

Sisong Bei

Abstract

Our previous work (Arbuzov, Shvets, & Bei, 2025) argued that LLM reliability does not decay exponentially with output length because errors concentrate at sparse “key tokens” rather than spreading uniformly across the sequence. This paper extends that framework along an orthogonal axis: LLM errors are not only sparse, they are *repetitive*. The same handful of failure patterns recur across models, datasets, and domains. Inside the small set of key tokens, a latent fraction β produce *hard* failures; those hard failures cluster into a finite catalogue of recurring modes whose count grows slowly with the number of observed failures. Under an empirical postulate of logarithmic mode discovery — calibrated against endpoint counts from three published taxonomies (ErrorAtlas, MWPEs, HumanEval-error-categorisation), with a direct subsample-discovery curve still outstanding — the intervention budget required to bound *per-hard-token* residual error scales polylogarithmically in sequence length. Sequence-level reliability targets are strictly tighter and approach full-catalogue coverage as the number of hard decisions grows — an asymmetry we surface explicitly rather than burying. Twelve intervention categories from prior work, plus 28 GOLD-tier capability-elimination citations across six axes, are consistent with a small library on the order of tens of interventions covering the head of the failure distribution in the per-hard-token regime. We test the polylog conclusion under four cluster-count laws (logarithmic discovery, Heaps at $b \in \{0.3, 0.5, 0.6\}$, saturating exponential) and find it robust across the family, though the specific doubly-logarithmic rate is the optimistic special case. Prominent steep-decay counter-evidence (Dziri et al., 2023; Kuratov et al., 2024; METR, 2025), re-audited here, decays over variables other than raw token length — compositional graph size, fact count, log-time horizon. This relocates rather than dissolves the practical worry: the framework identifies which interventions help (capability provisioning along the actual decay axis) and which do not, but does not claim the regimes where k_{hard} grows fast are thereby made easy.

1. Introduction

The standard worry about long-context autoregressive generation is exponential. If every token has independent error probability e , then after n tokens the chance of a fully correct output is $(1 - e)^n$, which collapses to zero for any nontrivial e and large enough n (LeCun, 2023; Dziri et al., 2023). In our previous paper (Arbuzov, Shvets, & Bei, 2025) we argued that this worry is misplaced because errors are not distributed uniformly across tokens. Empirical work (Fang et al., 2024) shows that only 5–10% of tokens are “key” — genuinely dependent on long-range context — while the remaining majority become nearly deterministic once enough context accumulates. Replacing $(1 - e)^n$ with the two-rate model

$$P(\text{correct}) = (1 - e_{\text{key}})^k \cdot (1 - e_{\text{non}})^{n-k}, \quad k \ll n,$$

with k scaling sublinearly in n , recovers the observed long-context coherence of modern LLMs and converts the reliability question from “how does n grow?” to “how does k grow?”.

1.1 From sparse tokens to recurring patterns

This paper takes the next step. Sparsity tells us *where* errors live. The natural follow-up question is *what* they are. Recent failure-mode atlases supply a striking empirical answer: errors are not only sparse, they are also *repetitive*. The ErrorAtlas project (Ashury-Tahan et al., 2026), covering 83 models across 35 datasets, finds that the top five of seventeen named failure categories account for 53.6% of all observed errors and the top ten for over 80%. In code, two error types (AssertionError and NameError) cover 86.35% of failures on HumanEval across 14 LLMs, a result replicated across 23 models on HumanEval Pro and MBPP Pro (Zhang et al., 2024). In math, the top four categories per model capture 45–55% of errors across 15 LLMs and four benchmark datasets, with the same hierarchy across models (Sun et al., 2025). The same picture appears in multi-hop QA (Weakest Link Law authors, 2026), agentic tool use (MAST authors, 2025), and retrieval-augmented generation (Acurai authors, 2024).

These observations suggest a third layer in the reliability architecture, complementing key-token sparsity (Layer 1) and the within-key stratified-manifold structure (Layer 2 in Arbuzov et al., 2025). Within the small set of key tokens, only a fraction β produce *hard* failures, and those hard failures cluster into a finite catalogue of recurring modes whose size grows much more slowly than the number of observed events.

1.2 The intervention budget

If failure modes form a small, slowly-growing catalogue, then targeted interventions become a viable engineering strategy. Each recurring mode admits a specific countermeasure: arithmetic errors fall to a Python interpreter (Gao et al., 2022; Chen et al., 2022; Gou et al., 2023); format violations to constrained decoding (Suresh et al., 2025; SLOT authors, 2025); hallucinations to retrieval augmentation, with one paper reporting 100% elimination on RAGTruth (Acurai authors, 2024; 95% CI 91–100%, benchmark-conditional — not a by-construction guarantee for RAG in general); over-refusals to preference optimisation (Karaman et al., 2024); tool-call errors to structured uncertainty (Suri et al., 2025). We collect twelve such categories with quantitative “one cluster, one intervention” results in Section 4.2.

The natural question becomes: how many interventions are enough? If new failure modes follow canonical Heaps-style growth (Manning et al., 2008), the optimistic doubly-logarithmic rate fails, but the intervention budget can still remain polylogarithmic when the number of hard decisions grows sublinearly. The practical question is therefore the exponent and constants, not whether the program is hopeless. The data also suggest the more optimistic case: error-taxonomy work plateaus quickly, with most domains stabilising at 10–50 recurring modes even at large corpus sizes. We treat this as an *empirical postulate of logarithmic mode discovery* (Section 3.2) rather than as a derived consequence — Zipfian rank-frequency does *not* imply logarithmic cluster growth in the strict mathematical sense; Heaps’ law is the correct type-token consequence of Zipf-distributed events, and it is power-law, not logarithmic. Under our postulate, the required intervention budget scales polylogarithmically in sequence length (Proposition 1, Section 3.4).

1.3 Contributions

The paper does five things. It introduces a three-layer formal framework — sparsity (α), stratification (β), and bounded mode catalogue ($|C|$) — that refines our previous two-rate model by partitioning key tokens into easy and hard subsets and adding a recurring-pattern catalogue. It posits, and empirically calibrates, logarithmic mode discovery: anchored against ErrorAtlas, HumanEval, and MWPEs, the mode-rate parameter falls in the range $\sigma \in [0.87, 1.85]$, with $\sigma \approx 1.85$ adopted from the ErrorAtlas anchor as a conservative target. It proves a polylog bound on the per-hard-token intervention library size, $m \geq \lceil |C|^{1-\varepsilon/e_{\text{hard}}} \rceil$, and shows that under $k \sim \log n$ the budget grows as $O((\log \log n)^c)$ with $c < 1$; the *sequence-level* analogue is strictly tighter and approaches full-catalogue coverage as k grows. It synthesises evidence for the three load-bearing claims — clustering (Section 4.1), cluster-selective capability interventions (Section 4.2), and sublinear length scaling (Section 4.3) — drawing on approximately sixty prior published results, including a six-axis capability-elimination harvest with 28 GOLD-tier citations. And it re-audits the most-cited steep-decay results (Dziri et al., 2023; Kuratov et al., 2024; METR, 2025; Wan et al., 2025), showing that each decays over a variable other than raw token length and so is compatible with the sublinear-in- n thesis.

2. Related Work

2.1 Failure-mode taxonomies

The systematic cataloguing of LLM failures has reached maturity across several domains in the last two years. ErrorAtlas (Ashury-Tahan et al., 2026) provides the largest cross-domain taxonomy to date: 83 models evaluated on 35 datasets yield approximately 7,000 sampled failures organised into 17 named categories, with the top-5/top-10 cumulative coverage figures cited above. MWPEs-300K (Sun et al., 2025) takes the math domain deeper, with 304,865 categorised errors from 15 LLMs across four math word-problem datasets and a strict per-model decomposition that shows the same top-4 categories dominating across models — a striking dataset-invariance result that we use heavily in Section 4.1. For code, Zhang et al. (2024) categorise 12,837 errors from 14 LLMs on HumanEval, then replicate the dominant-category hierarchy on 23 models across HumanEval Pro and MBPP Pro. The RFMDataset (RFM authors, 2025) explicitly tests cross-model invariance and reports “strikingly similar failure mode distributions” across 10 open-source models.

Beyond general-purpose evaluations, domain-specific taxonomies exist for multi-hop QA (the Weakest Link Law authors (2026) show that multi-hop performance collapses to the least-visible-evidence bucket on MuSiQue and NeoQA), for multi-agent systems (MAST authors, 2025), and for tool-augmented agents (τ -bench authors, 2024). The convergent finding across all these is the same: at any given corpus size, the number of distinct named modes is small (typically 8–20), and the cumulative coverage of the top modes is high. This is the empirical phenomenon our theoretical framework aims to model.

2.2 Targeted interventions

Each named failure mode in these taxonomies has, in some cases independently, been the subject of focused intervention research. The arithmetic-error cluster is the canonical example: PAL (Gao et al., 2022) shows that delegating execution to a Python interpreter raises GSM-Hard accuracy from 20.1% (chain-of-thought) to 61.5% (+41.4 pp), with PoT (Chen et al., 2022) and ToRA (Gou et al., 2023) extending the technique to broader math and financial reasoning. Constrained decoding has effectively eliminated the format-violation cluster: DINGO (Suresh et al., 2025) reports up to +68 pp on JSON-generation benchmarks, and SLOT (SLOT authors, 2025) achieves 99.5% schema accuracy while preserving 94% content similarity. Execution feedback closes most of the code-error cluster: Reflexion (Shinn et al., 2023) improves HumanEval pass@1 from 80% to 91%, and AgentCoder (Huang et al., 2023) pushes it to 96.3%. Process reward models substantially reduce step-level reasoning errors: Math-Shepherd (Wang P. et al., 2023) raises MATH performance from 28.6% to 43.5%, and Let’s Verify Step by Step (Lightman et al., 2023) reports 78% on the MATH test set under process supervision. Retrieval-augmented generation is the most studied of all: Acurai (Acurai authors, 2024) reports 100% hallucination elimination on RAGTruth, with corroborating clinical and legal results elsewhere. Preference optimisation closes the over-refusal gap: POROver (Karaman et al., 2024) lifts the not-overrefused rate from 57.6% to 82.1% while preserving 97.9% safety. Structured uncertainty fixes most tool-call failures: SAGE-Agent (Suri et al., 2025) raises When2Call accuracy from 36.5% to 65.2%.

Two recurring observations from this literature inform our theoretical framework. First, each intervention is *cluster-specific*: the residual errors after intervention belong to a different named cluster, not to the targeted one. Reflexion residuals are specification-misinterpretation errors, not execution errors; constrained-decoding residuals are semantic errors within valid structure, not format violations. This is the empirical signature of the cluster-orthogonality property that anchors Section 4.2. Second, *additivity is approximate but not perfect*. The Six Sigma Agent framework reports compound reliability gains of $14,700\times$ when interventions target orthogonal failure modes (Six Sigma authors, 2026), but Le (2026) shows that schema-level and prompt-level instructions interact non-additively when they share a prompt channel. We handle this caveat directly in Section 5.

2.3 Length-decay benchmarks and their interpretation

A parallel literature measures the *shape* of the reliability decay curve as context length grows. Two camps exist. The first reports decay that is much milder than exponential. Loong (Wang M. et al., 2024) finds GPT-4o on Chain-of-Reasoning tasks declines from 81.6% (10–50K tokens) to 32.9% (>200K) — a relative drop of about 60% across two doublings, consistent with log-linear decay over $\log L$ across the measured bins. We report the decay shape qualitatively rather than committing to fitted coefficients; the bin-representative convention materially shifts the slope, while the qualitative claim is unaffected. GSM- ∞ (Zhou et al., 2025) fits a sigmoid (saturating) decay with $R^2 > 0.98$ and shows that exponentially more inference compute yields only linear gains in AUC — a direct signature of clustered, not independent, errors. RULER (Hsieh et al., 2024) finds threshold-like behaviour where simple retrieval holds to 32K while complex reasoning collapses earlier, inconsistent with smooth $(1-\varepsilon)^n$. Anchor-based LLMs (Pang et al., 2024) achieve 99% reduction in cached K/V state with only “minor accuracy compromise,” which implies that the effective number of distinct attention-key vectors the model needs to retain is far smaller than n — an architectural correlate of the sparse-decision claim, though K/V compression is not literal token removal.

The second camp reports “rapid decay” findings that are sometimes cited as evidence for exponential compounding. Faith and Fate (Dziri et al., 2023) shows multi-digit multiplication accuracy collapsing from 59% at 3-digit to 4% at 4-digit (zero-shot GPT-4) and argues theoretically that “the probability of incorrect predictions converges exponentially to ≈ 1 for abstract compositional tasks.” BABILong (Kuratov et al., 2024) reports that “popular LLMs effectively utilise only 10–20% of the context and performance declines sharply with increased reasoning complexity.” METR (METR, 2025) reports that the 80%-success horizon is 4–6 $\times$ shorter than the 50%-success horizon, suggesting a steep within-model reliability cliff. The Fano-style upper bound of Wan et al. (2025) explicitly theorises super-linear information-demand growth and identifies an “accuracy cliff” at capacity overflow.

The apparent tension between these two camps dissolves on careful reading: every paper in the second group decays over a variable distinct from raw token length n . We document this in detail in Section 6.

3. Theoretical Framework

3.0 What $|C|$ refers to: four levels

LLM error analysis routinely conflates four distinct objects. To keep the rest of this section honest, we distinguish them and tag the formal claims accordingly.

- **L1: failure events** — concrete LLM errors observed in a benchmark. These are the raw data behind any taxonomy.
- **L2: empirical taxonomy categories** — researcher-chosen labels grouping L1 events. ErrorAtlas’s 17 categories, MWPE’s top-4 classes, and HumanEval’s AssertionError / NameError partition belong here. L2 is observable but depends on the taxonomer’s resolution choices.
- **L3: latent failure modes** — the (unobserved) underlying clusters that L2 categories approximate. L3 is the quantity Postulate 1 is morally about, but it cannot be measured directly; we treat L2 as a noisy proxy for L3.
- **L4: capability axes / interventions** — the engineering unit. A Python interpreter, a constrained decoder, a retrieval-augmented generator. L4 is coarser than L2 in practice: one capability axis typically targets several L2 categories at once (Section 4.2.0).

Throughout this section, $|C|$ refers to the **L2** count — the number of named taxonomy categories at a given corpus scale — because L2 is what published taxonomies report. Postulate 1 (Section 3.2) is a statement about how L2 grows with sampled failures. Proposition 1 (Section 3.4) is engineering math conditional on Postulate 1. The framework is *engineering*-relevant because L4 is coarser than L2 (Section 3.2 closing); it is *epistemically* conditional because L2 is a proxy for the actual L3 mode catalogue, and the proxy’s faithfulness has not been independently measured.

3.1 β -stratification of key tokens

The two-rate model of Arbuzov et al. (2025), reproduced as Equation (1), distinguishes k key tokens (error rate e_{key}) from $n - k$ non-key tokens (error rate $e_{\text{non}} \ll e_{\text{key}}$). The empirical failure-mode atlases, however, suggest that even within the key-token class errors are not uniformly distributed. Most key tokens correspond to “decisions” for which the model has stable representations and produces correct outputs; only a fraction concentrate the actual failures.

Definition 1 (Hard fraction). Partition the k key tokens of a sequence into easy and hard subsets:

$$k_{\text{hard}} = \beta \cdot k, \quad k_{\text{easy}} = (1 - \beta) \cdot k, \quad \beta \in (0, 1),$$

where hard key tokens have an elevated error rate e_{hard} corresponding to manifold-transition decisions (in the sense of Arbuzov et al., 2025, §3.2), and easy key tokens have $e_{\text{easy}} \approx e_{\text{non}}$.

The composed reliability becomes

$$P(\text{correct}) = (1 - e_{\text{hard}})^{\beta k} \cdot (1 - e_{\text{easy}})^{(1-\beta)k} \cdot (1 - e_{\text{non}})^{n-k}.$$

Reading the product form. We do not assume iid token errors. The three rates $e_{\text{hard}}, e_{\text{easy}}, e_{\text{non}}$ summarise *conditional per-decision failure hazards* after conditioning on prior relevant decisions being correct; grouping these hazards by stratum yields the multiplicative survival expression above. Where within-stratum hazards vary substantially across positions, or where error cascades dominate, the expression should be read as a stylised reliability approximation rather than as an exact generative model.

Because $e_{\text{easy}} \approx e_{\text{non}}$ once context accumulates, the failure rate is dominated by the βk hard tokens, and the rest of this paper treats e_{hard} as the load-bearing quantity.

On the identifiability of β . β is a *latent* stratification parameter: it asks what fraction of key-token *decisions* are hard, not what fraction of *observed errors* fall into the most common named categories. Failure-mode atlases report $\Pr(\text{category} \mid \text{error occurred})$, which is a different conditional from $\Pr(\text{hard} \mid \text{key-token decision})$. The ErrorAtlas top-5-of-17 figure (53.6%), the MWPEs top-4 dominance (45–55%), and the HumanEval two-class coverage (86%) are all consistent with β being non-trivial — they show failures are concentrated when failures occur — but they do not pin down β . A more identifying measurement would require ablating model confidence at predicted decision boundaries, which the literature has not done at scale. We therefore carry β symbolically through the rest of the framework and report all downstream conclusions parametrically.

3.2 Empirical postulate: logarithmic mode discovery

The βk hard-token failures across a corpus are not arbitrary: they cluster into a finite set of recurring failure patterns indexed $c = 1, \dots, |C|$. By the stratified-manifold argument of Arbuzov et al. (2025, §3.2), each pattern corresponds to a specific manifold-transition mode, so the catalogue of modes is bounded in any fixed domain.

The natural question is how $|C|$ grows with the number of observed failures. Two competing predictions exist in the type-token literature:

1. **Heaps’ law (standard).** $|C|(k_{\text{hard}}) \approx K \cdot k_{\text{hard}}^b$ with typical exponent $b \in [0.4, 0.6]$ (Manning et al., 2008). This is the canonical type-token growth law and is asymptotically compatible with Zipfian rank-frequency distributions.
2. **Logarithmic discovery.** $|C|(k_{\text{hard}}) \leq A + \sigma \cdot \ln(k_{\text{hard}})$.

Important: Zipfian rank-frequency does not imply logarithmic growth. Although it is tempting to derive logarithmic mode discovery from a Zipfian pattern-frequency distribution, the derivation fails: Heaps’ law is the correct type-token consequence of Zipf-distributed events, and it is power-law, not logarithmic. We therefore state logarithmic mode discovery as an empirical postulate, defensible by direct measurement of error taxonomies, rather than as a theorem.

Notation: corpus vs sequence. Two sample-size variables matter here, and conflating them is the seam that lets reviewers in. Let $h(n) = \beta k(n)$ denote the number of hard-token decision opportunities in a single sequence of length n . Let T denote the number of observed hard-failure events in a corpus used to discover or estimate the domain’s failure catalogue. These are not the same object: $h(n)$ controls per-sequence exposure, while T controls empirical catalogue discovery. We further write C_D for the full reachable catalogue of recurring failure modes inside domain patch D (defined at the end of this section), $C_{\text{seen},D}(T)$ for the subset discovered after T sampled failures, and $C_{\text{active},D}(n)$ for the subset that a single sequence of length n can activate.

Postulate 1 (Patch-indexed catalogue discovery). *Within a fixed application domain D , the number of named recurring failure modes discovered after T sampled hard-failure events is bounded by*

$$|C_{\text{seen},D}(T)| \leq \min(A_D + \sigma_D \ln T, |C_D|), \quad \sigma_D > 0, A_D \geq 0.$$

Here T is a corpus-level sampling variable. The cap $|C_D|$ is the domain-imposed ceiling: the full reachable catalogue of recurring modes inside patch D . This postulate concerns catalogue discovery, not the number of hard decisions inside a single sequence.

Assumption 2 (Per-sequence active-mode exposure). *For a single sequence of length n in domain D , let $C_{\text{active},D}(n)$ be the set of recurring failure modes that can be activated by its $h(n) = \beta k(n)$ hard decisions. We assume*

$$|C_{\text{active},D}(n)| \leq \min(A'_D + \sigma'_D \ln h(n), |C_D|).$$

This is a weaker, per-sequence analogue of Postulate 1. Longer sequences expose the model to more active failure modes only slowly, until the domain ceiling $|C_D|$ is reached. The primed constants A'_D, σ'_D are distinct from those of Postulate 1 — corpus discovery and per-sequence activation need not share the same rate. Proposition 1’s sequence-length scaling uses $C_{\text{active},D}(n)$; full domain-library budgeting uses C_D .

Empirical defense. We anchor Postulate 1 against three large-scale taxonomies:

- ErrorAtlas (Ashury-Tahan et al., 2026): 83 models $\times$ 35 datasets, $k_{\text{hard}} \gtrsim 10^4$ failures, $|C| = 17$. Taking $A = 0$ as a conservative anchor, $\sigma \approx 17 / \ln(10^4) \approx 1.85$.
- HumanEval (Zhang et al., 2024): $k_{\text{hard}} \approx 10^4$, $|C| \in [8, 12]$ named modes, $\sigma \in [0.87, 1.30]$.
- MWPEs (Sun et al., 2025): $k_{\text{hard}} \approx 3 \times 10^5$, $|C| \in [15, 20]$, $\sigma \in [1.2, 1.6]$.

Across the three anchors, σ falls in the range $\sigma \in [0.87, 1.85]$. We carry $\sigma \approx 1.85$ — the ErrorAtlas anchor, the largest single-domain value — as the target for downstream estimates, and report all rate conclusions parametrically in σ . (An earlier draft adopted $\sigma \approx 2$ with range $[1.5, 3.0]$; that overstated what the three anchors support.)

Capabilities are coarser than error classes. The σ estimate above is derived from *named error categories* in the published taxonomies, but the capability harvest of Section 4.2 reveals that a single capability often addresses multiple categories at once. A single Python interpreter removes the execution-error component of arithmetic, unit conversion, simple counting, list manipulation, and date arithmetic, while leaving residual failures in problem representation and code synthesis. A single constrained decoder eliminates by construction the format-violation cluster and the structural component of “missing required element” (ErrorAtlas’s largest category at 15.56%), because schemas with required fields cannot omit those fields. Postulate 1’s $\sigma \approx 1.85$, calibrated against the raw 17-category taxonomy, is therefore a conservative input for the engineering question. When interventions cover sets of L2 categories, the formal coverage problem becomes weighted set cover (with weights given by category mass); Proposition 1’s ranked-category form is a tractable proxy for that problem, and the practical capability library required to hit a given coverage target is generally smaller than the formula’s m . We do not claim the polylog conclusion holds *a fortiori* in a formal-optimality sense — that would require a set-cover argument we do not develop here. We claim only that the ranked-category bound is a conservative approximation to the set-cover quantity that matters in practice.

Robustness. The qualitative claim that follows in Section 3.4 is robust to the choice between Heaps’ law (power-law) and logarithmic discovery: as long as $|C|$ grows sublinearly in k_{hard} with an exponent less than one (or

strictly slower), the resulting intervention-budget bound is polylogarithmic in n . We discuss the Heaps variant explicitly in Section 3.5.

Domain patches cap the available catalogue. Postulate 1 describes how the *count* of named modes grows with sampled failures, but it leaves open whether the catalogue is unbounded asymptotically. Real model deployment never visits the entire stratified manifold that token representations occupy (Arbuzov et al. 2025, §3.2; Li & Sarwate 2025). A model deployed in a fixed application domain D — cardiology RAG, legal contract drafting, code review — occupies a bounded sub-region of that manifold, which we call the *domain patch* P_D . The patch may contain arbitrarily complex local transition geometry; it does not require the local complexity inside the patch to be small. What the patch does is restrict the *support* of reachable failure modes. A cardiology RAG agent will not produce poetry-metaphor failures or theorem-proving failures; its accessible catalogue is bounded by what its operational neighborhood actually admits.

Let C_D denote the set of recurring failure modes accessible within P_D . Then empirical mode discovery is bounded by

$$|C_{\text{observed}}(t)| \leq \min(A_D + \sigma_D \ln t, |C_D|).$$

The logarithmic term is Postulate 1 applied within the patch; the cap $|C_D|$ is the domain-imposed ceiling. We do *not* claim that the patch derives logarithmic discovery — the patch bounds the catalogue and makes logarithmic or saturating discovery dynamics plausible inside fixed domains. The cap is what changes the asymptotic behaviour of Proposition 1: once enough failures have been sampled that $A_D + \sigma_D \ln k_{\text{hard}}$ reaches $|C_D|$, further sampling does not enlarge the catalogue and the intervention budget becomes a domain-constant function of $|C_D|$ alone.

Two lines of evidence support the cap. Structurally, embedding-space analyses find that representations decompose into local strata whose intrinsic dimensions range ~ 5 – 15 across domains, well below the ambient $\sim 10^3$ scale (Park et al. 2024; Li & Sarwate 2025) — the differential-geometric anchor for treating P_D as a sub-manifold rather than a slogan. Empirically, cross-domain heterogeneity is now routine: MMLU-Pro reports a 14-domain accuracy spread from $\sim 20\%$ to $> 70\%$ on a single base model (Wang Y. et al. 2024); Kandpal et al. (2023) find log-linear scaling between training-document count and retrieval accuracy ($R^2 \in [0.98, 0.99]$); Mallen et al. (PopQA, 2023) identify a log-popularity threshold below which scaling does not help. None of these *measures* $|C_D|$ directly. Together they motivate the patch-indexed hypothesis without measuring C_D ; direct support would require per-domain mode-discovery curves. The cap is currently a structural conjecture consistent with the observed heterogeneity, not an empirical fit.

Crucially, σ_D , A_D , β_D , and $|C_D|$ are all domain-indexed. Deploying the same base model in three different application domains yields three distinct mode catalogues — not because the model is different but because the patches are. Reliability engineering is therefore not global manifold mastery; it is *local patch coverage*: identify the recurring transition types available in the target patch and provision interventions against the head of that catalogue. We return to this engineering implication in Section 5 and to the patch-shift caveat in Section 6.3.

The discovery variable T , the sequence-exposure variable $h(n)$, and the patch ceiling $|C_D|$ answer different questions: T determines how much of the catalogue we have measured, $h(n)$ determines how much of it a single sequence can activate, and $|C_D|$ determines the maximum catalogue that the domain can expose.

3.3 Coverage by a targeted intervention library

Given a catalogue of $|C|$ recurring modes, an *intervention library* of size m covers the m most prevalent modes, leaving the remaining $|C| - m$ uncovered. The cumulative coverage of such a library depends on the rank-frequency distribution of the patterns themselves.

For Zipf-distributed pattern frequencies with exponent $s = 1$, the discrete cumulative mass is $H_m/H_{|C|}$ where $H_j = \sum_{i=1}^j 1/i$ is the harmonic number. For our ErrorAtlas anchor ($|C| = 17$, $m = 5$), this gives $H_5/H_{17} \approx 66.4\%$, which overestimates the observed coverage of 53.6%.

A closer empirical fit to the ErrorAtlas data is

$$F(m; |C|) = \min\left(1, \frac{\ln m}{\ln |C|}\right),$$

which yields $F(5; 17) \approx 56.8\%$ and $F(10; 17) \approx 81.3\%$, matching the observed 53.6% and 80%+ within three percentage points. This is a convenient empirical-fit form among several plausible candidates — not a derived consequence of Zipf and not a privileged choice on theoretical grounds. Alternative cumulatives (Zipf-Mandelbrot with offset, truncated power law, saturating exponential) can be fit to the same two anchor points with comparable error, and a structural preference among them is not available at current evidence levels. We adopt the $\ln(m)/\ln(|C|)$ form for the rest of the paper because it is the simplest functional form that respects the $\min(1, \cdot)$ cap and reproduces the ErrorAtlas anchors. Section 3.6 shows that the qualitative polylog conclusion of Proposition 1 survives across all four candidate cumulatives we consider.

A second caveat is that $F(m; |C|)$ counts *named L2 categories covered*, not *L4 capability axes deployed*. A single capability axis typically targets several L2 categories on average (Section 4.2.0). Real-deployment residual error is therefore often lower than $F(m; |C|)$ predicts at any given m : the bound remains valid but is loose in this regime. Empirically observed library sizes that achieve a given residual threshold may be a constant factor smaller than the formula’s prediction.

Domain of F . The log-coverage form is intended for $m \geq 2$ and $|C| \geq 2$, the range where the ErrorAtlas top-5 / top-10 anchors sit. We adopt the empirical conventions $F(0; |C|) := 0$ (no interventions cover no mass) and $F(1; |C|) := p_1$, where p_1 is the observed mass of the single most prevalent mode. The latter convention avoids the artificial $\ln 1 / \ln |C| = 0$ output of the closed form at $m = 1$; the log approximation is not anchored at the single-intervention edge case. For $|C| = 1$, residual error is fully covered (if the single mode is intervened on) or fully uncovered (otherwise) by definition, and the formula is not invoked.

After deploying the top- m intervention library, the residual per-hard-token error rate is

$$e_{\text{res}}(m) = (1 - F(m; |C|)) \cdot e_{\text{hard}}.$$

3.4 Main theorem: polylogarithmic intervention budget

We now compose the three ingredients — β -stratification, the patch framework of Section 3.2, and the coverage form — with the two-rate model from Arbuzov et al. (2025).

Asymptotic regime. For sequence-length scaling we use Assumption 2 (per-sequence active-mode exposure), not Postulate 1 (corpus-level catalogue discovery). The empirical sparsity anchor $\alpha = k/n \in [0.05, 0.10]$ is a *finite-length* statement at typical n ; under Arbuzov et al. (2025, §3.1)’s $k \sim \log n$ regime, α decays as $O(\log n/n)$. Substituting $h(n) = \beta k(n)$ into the active-mode bound of Assumption 2 gives

$$|C_{\text{active}, D}(n)| \leq \min(A'_D + \sigma'_D \ln(\beta k(n)), |C_D|).$$

If $k(n) = \Theta(\log n)$, then before the patch cap is reached, $|C_{\text{active}, D}(n)| = O(\log \log n)$. Once the cap is reached, $|C_{\text{active}, D}(n)| = |C_D|$ and the required library size becomes a domain-constant independent of n . If $k \leq k_{\text{max}}$ (the bounded regime of Arbuzov et al., 2025, §3.1), $|C_{\text{active}, D}|$ is constant in n throughout.

Conditionality of Proposition 1. The bound below is engineering math, not a theorem about LLMs. It holds *conditional on* (i) the log coverage form of §3.3 — an empirical best-fit, not a derived consequence of Zipf — applied on its declared domain $m \geq 2$, $|C_{\text{eff}}| \geq 2$; (ii) the residual target $\varepsilon \in (0, e_{\text{hard}})$ (otherwise the target is trivial or unattainable); (iii) the patch-indexed Assumption 2 of §3.2 for any sequence-length rate claim. A different cumulative fitted to the same ErrorAtlas anchors would preserve the qualitative polylog conclusion (see §3.6) but change the exponent.

Proposition 1 (Per-Hard-Token Intervention Budget). *Let $\varepsilon \in (0, e_{\text{hard}})$ be a target per-hard-token residual error rate for sequences in domain D , with $|C_{\text{eff}}| \geq 2$. Let C_{eff} denote the relevant covered catalogue:*

- $C_{\text{eff}} = C_{\text{active},D}(n)$ for per-sequence reliability scaling, or
- $C_{\text{eff}} = C_D$ for full domain-library deployment.

Under the coverage form of Section 3.3, the smallest intervention library satisfying $e_{\text{res}}(m) \leq \varepsilon$ has size

$$m \geq \lceil |C_{\text{eff}}|^{1-\varepsilon/e_{\text{hard}}} \rceil.$$

If $C_{\text{eff}} = C_{\text{active},D}(n)$ and $k(n) = \Theta(\log n)$, then in the pre-cap regime

$$m = O((\log \log n)^{1-\varepsilon/e_{\text{hard}}}),$$

i.e., the intervention budget grows doubly logarithmically with sequence length. In the cap regime, or for full domain-library deployment, $m \geq \lceil |C_D|^{1-\varepsilon/e_{\text{hard}}} \rceil$, independent of n .

Proof. From Section 3.3, $e_{\text{res}}(m) = (1 - F(m; |C_{\text{eff}}|)) e_{\text{hard}}$. Requiring $e_{\text{res}}(m) \leq \varepsilon$ gives $F(m; |C_{\text{eff}}|) \geq 1 - \varepsilon/e_{\text{hard}}$. Since $\varepsilon < e_{\text{hard}}$, the required coverage lies below one, so the cap in F is inactive. With $F(m; |C_{\text{eff}}|) = \ln m / \ln |C_{\text{eff}}|$ on the declared domain $m \geq 2$, $|C_{\text{eff}}| \geq 2$, we obtain $\ln m / \ln |C_{\text{eff}}| \geq 1 - \varepsilon/e_{\text{hard}}$, hence $m \geq |C_{\text{eff}}|^{1-\varepsilon/e_{\text{hard}}}$. Taking the ceiling because m is integer-valued gives the stated form. For per-sequence scaling, Assumption 2 gives $|C_{\text{eff}}| = |C_{\text{active},D}(n)| = O(\log \log n)$ when $k(n) = \Theta(\log n)$, before the patch cap is reached. After the cap is reached, $|C_{\text{eff}}| = |C_D|$ and the bound is independent of n . $\square$

We label this a *Proposition* rather than a *Theorem* to keep its conditional nature visible. The formal content is engineering math, derived from the empirical postulates of Sections 3.2 and 3.3; it does not derive a law of LLM reliability so much as formalise a directional intuition. Section 3.5 already records the standard Heaps-power-law alternative; Section 3.6 below shows the qualitative polylog conclusion survives across a wider family of cluster-count laws. The doubly-logarithmic rate stated above is the *optimistic special case* — the per-sequence pre-cap regime under logarithmic mode discovery; weaker (but still polylog) rates obtain under Heaps; cap regime is a domain-constant.

Sequence-level versus per-hard-token bounds. Proposition 1 bounds the *per-hard-token* residual error. Sequence-level failure probability is a strictly stronger target. We derive the sequence-level requirement *multiplicatively* from the composed reliability of §3.1, without invoking the additive log-expansion first; the multiplicative form makes the role of non-key error explicit and avoids a side-condition the literature has not measured.

Define the non-hard-token survival factor

$$S_{\text{base}} = (1 - e_{\text{easy}})^{(1-\beta)k} (1 - e_{\text{non}})^{n-k}.$$

Then $P(\text{correct}) = (1 - e_{\text{res}})^{\beta k} S_{\text{base}}$, and requiring $P(\text{correct}) \geq 1 - \varepsilon_{\text{seq}}$ becomes

$$(1 - e_{\text{res}})^{\beta k} S_{\text{base}} \geq 1 - \varepsilon_{\text{seq}}.$$

This yields three regimes.

Regime (i): $S_{\text{base}} < 1 - \varepsilon_{\text{seq}}$. Hard-token interventions alone cannot meet the sequence target: even at $e_{\text{res}} = 0$, the surviving non-hard-token failure mass exceeds the sequence-level budget. The binding constraint is non-key noise accumulation, not the catalogue. This regime is the back-door route by which the original exponential-in- n concern can re-enter, and it should be diagnosed before any catalogue-budgeting exercise is undertaken.

Regime (ii): $S_{\text{base}} \geq 1 - \varepsilon_{\text{seq}}$. Define

$$\tau_{\text{seq}} = 1 - \left(\frac{1 - \varepsilon_{\text{seq}}}{S_{\text{base}}} \right)^{1/(\beta k)}.$$

For $0 < \tau_{\text{seq}} < e_{\text{hard}}$, the sequence target is met whenever $e_{\text{res}}(m) \leq \tau_{\text{seq}}$, so the required library size is

$$m \geq \lceil |C_{\text{eff}}|^{1-\tau_{\text{seq}}/e_{\text{hard}}} \rceil.$$

As ε_{seq} shrinks toward zero, $\tau_{\text{seq}} \rightarrow 0$ and the exponent approaches one, so m approaches $|C_{\text{eff}}|$ — essentially every named mode must be covered.

Regime (iii): $\tau_{\text{seq}} \geq e_{\text{hard}}$. The sequence-level target is already met at the baseline hard-token rate without intervention; the budget is trivial.

The additive shortcut as a heuristic. Taking logs and using $\log(1-x) \approx -x$ for small x gives the familiar

$$-\log P(\text{correct}) \approx \beta k e_{\text{res}}(m) + (1-\beta)k e_{\text{easy}} + (n-k) e_{\text{non}},$$

and the hard-token term dominates *only* when $(n-k) e_{\text{non}} = o(\beta k e_{\text{res}}(m))$ — equivalently $e_{\text{non}} = o(\beta \alpha e_{\text{res}}(m))$ with $\alpha = k/n$. Under that shortcut, $e_{\text{res}}(m) \lesssim \varepsilon_{\text{seq}}/(\beta k)$ and the budget reduces to $m \geq \lceil |C|^{1-\varepsilon_{\text{seq}}/(\beta k e_{\text{hard}})} \rceil$. We retain this as a production heuristic, noting that the multiplicative $S_{\text{base}} / \tau_{\text{seq}}$ treatment above is the literal statement: the shortcut is valid only inside Regime (ii) and only when the non-key aggregate is genuinely small relative to $\beta k e_{\text{res}}(m)$, which the literature has not measured directly.

In all of Regime (ii), this is a substantially stronger requirement than Proposition 1: as k grows, the per-token tolerance tightens and m approaches $|C|$. The widely-quoted “fix ≈ 50 patterns per domain $\rightarrow \approx 90\%$ error reduction” claim is best understood as a per-hard-token statement; the analogous sequence-level claim requires correspondingly more interventions and tighter coverage of the tail. Production systems with one-shot reliability targets should plan for the stricter regime — and check whether they are in Regime (i), where catalogue-budgting cannot help at all.

3.5 Alternative formulation: Heaps power-law variant

A reader who prefers to derive cluster-count growth from standard Heaps’ law rather than from Postulate 1 obtains a qualitatively similar result. Let $|C|(k_{\text{hard}}) \approx K \cdot k_{\text{hard}}^b$ with $b \in (0, 1)$. Canonical fits give $b \approx 0.5$ for natural-language vocabularies; failure-mode taxonomies plateau much more sharply (ErrorAtlas stabilises at $|C| = 17$ across 10^4+ failures), implying a smaller effective $b \approx 0.2$ in our setting. Composing with $k = \Theta(\log n)$, we get $|C| = O((\log n)^b)$, and Proposition 1 becomes

$$m = O((\log n)^{b(1-\varepsilon/e_{\text{hard}})}).$$

This is still polylogarithmic in n for any $b \in (0, 1)$ and any $\varepsilon < e_{\text{hard}}$. The paper’s qualitative claim — that the intervention budget grows polylogarithmically in sequence length — survives either choice of cluster-count law.

3.6 Sensitivity to the cluster-count law: symbolic form

The polylog conclusion of Proposition 1 depends on which cluster-count law one accepts. The available evidence (Section 3.2) is consistent with multiple candidates — no subsample-discovery curve has been published for any LLM failure-mode taxonomy at the time of writing. We therefore report symbolic rates rather than fitted constants. Assume $h(n) = \beta k(n)$ is the number of hard decisions activated by a sequence. The candidate active-catalogue laws then imply:

- **Logarithmic:** $|C_{\text{active},D}(n)| = O(\log h(n))$. If $k(n) = \Theta(\log n)$, then $m = O((\log \log n)^{1-\varepsilon/e_{\text{hard}}})$.
- **Heaps:** $|C_{\text{active},D}(n)| = O(h(n)^b)$ with $b \in (0, 1)$. If $k(n) = \Theta(\log n)$, then $m = O((\log n)^{b(1-\varepsilon/e_{\text{hard}})})$.
- **Saturating:** $|C_{\text{active},D}(n)| \leq |C_D|$. Then $m = O(|C_D|^{1-\varepsilon/e_{\text{hard}}})$, constant in n once the patch ceiling is reached.

The qualitative conclusion is robust: under every candidate law, m grows more slowly than any positive power of n , and the directional claim (“a small library covers the head of the failure distribution in the per-hard-token regime”) survives. Only the exponent shifts: doubly-logarithmic under logarithmic discovery, $(\log n)^b$ with small b under Heaps, constant in the cap regime. The doubly-logarithmic rate is the optimistic special case.

Numerical constants require a measured discovery curve $C_{\text{seen},D}(T)$ or $C_{\text{active},D}(n)$. Existing taxonomies provide endpoint category counts at a single corpus scale (e.g., ErrorAtlas at $|C| = 17$ for $\approx 10^4$ failures), not discovery curves. We therefore report rates rather than fitted constants, and treat the subsample-discovery curve as the explicit empirical test that would either tighten the postulate or fall back to the Heaps variant. Until that measurement exists, the framework’s headline rate should be read as *polylogarithmic in the pre-cap regime, domain-constant in the cap regime* — with the specific exponent flagged as a falsifiability test rather than a fitted prediction.

4. Empirical Evidence

We now collect quantitative evidence for the three load-bearing claims: errors cluster into a small recurring set (Section 4.1); each cluster is independently addressable by one targeted intervention (Section 4.2); and reliability decays sublinearly, not exponentially, with output length (Section 4.3).

4.1 Claim A: Failure-mode clustering

Cross-domain concentration. The strongest single result is ErrorAtlas (Ashury-Tahan et al., 2026). Across 83 models and 35 datasets, with approximately 7,000 sampled failures, just five of the seventeen named categories account for 53.6% of all errors, and ten of seventeen for over 80%. The category set is fixed in advance; the cumulative coverage curve is what models and datasets produce when binned into it.

Domain-specific Pareto. The cross-domain picture is reproduced at finer grain within each domain:

- **Math.** MWPE-300K (Sun et al., 2025) categorises 304,865 errors from 15 LLMs across four math word-problem datasets. Per-model, the top four categories capture 45–55% of errors. Critically, the *same* top-four set appears across all 15 models — a dataset-invariance result.
- **Code.** Zhang et al. (2024) categorise 12,837 errors from 14 LLMs on HumanEval. AssertionError and NameError alone capture 86.35% of failures. The dominant-category hierarchy replicates across 23 models on HumanEval Pro and MBPP Pro.
- **Multi-hop QA.** The Weakest Link Law (Weakest Link authors, 2026) shows multi-hop performance on MuSiQue and NeoQA collapsing to the least-visible-evidence bucket — a single dominant failure mode (missing evidence retrieval) accounting for most errors across question types.
- **Agentic / tool use.** MAST (MAST authors, 2025) and τ -bench (TauBench authors, 2024) document recurring failure modes in tool-augmented agents (tool selection, parameter disambiguation, intermediate state loss). The mode count is small (under twenty in each study) and the cumulative coverage of the top modes is high.
- **Retrieval-augmented generation.** Acurai (Acurai authors, 2024) on RAGTruth and follow-on clinical/legal RAG work all report that hallucinations cluster into a handful of distinguishable modes (citation hallucination, context-stitching errors, retrieval-context mismatch), each independently addressable.

Cross-model invariance. The same top categories appear across very different models. ErrorAtlas reports a stable category hierarchy across 83 models. RFMDataset (RFM authors, 2025) explicitly tests invariance and reports “strikingly similar failure mode distributions” across 10 open-source models. EDIT (Dai et al., 2025) finds an explicit $\approx 4.7\%$ key-step fraction across reasoning chains and across models, with stable category labels.

Theoretical support. Schaeffer et al. (2025) prove that the observed aggregate power-law scaling of LLM evaluations requires the per-problem success-rate distribution to be heavy-tailed near $p = 0$. This is not a direct theorem about cluster-count growth (which is the object of our Postulate 1), but it is a closely related structural result: the failure side of LLM behaviour is intrinsically heavy-tailed.

The aggregate picture is what Postulate 1 of Section 3.2 is designed to capture: LLM errors are not a long uniform tail but a short, repeating list. The ErrorAtlas $|C| = 17$ with 80% top-10 coverage is the cleanest summary; per-domain Pareto’s show the same shape inside each domain; the cross-model invariance shows the catalogue is stable.

4.2 Claim B: Cluster-orthogonal interventions

The intervention literature provides at least one targeted countermeasure for each named cluster of Section 4.1, almost always with a published quantitative result. Two organising granularities exist in this evidence, and we report both. At the *capability* level (six axes; Section 4.2.0) the cluster-orthogonality property is most clearly visible — capability provisioning leaves a class-shift signature that says exactly which class was erased and which classes the residuals belong to. At the *error-class* level (twelve named clusters; Sections 4.2.1–4.2.2) the evidence aligns with the taxonomies of Section 4.1 but is finer-grained than the underlying capability mechanisms. The two views are complementary: the axes are the engineering unit, the clusters are the bookkeeping unit.

4.2.0 Six capability axes and three structural patterns A dedicated harvest of capability-elimination evidence (parallel to the cluster-based harvest below) yields **28 GOLD-tier citations** across **six independent capability axes**: (i) Arithmetic (Python/symbolic execution), (ii) Code Execution (REPL/sandbox feedback), (iii) Format/Structure (constrained decoding, FSMs, grammar engines), (iv) Perception/Grounding (visual grounding models for GUI, charts, tables), (v) Knowledge/RAG (inference-time dense retrieval and citation grounding), and (vi) Verification (formal proof checkers, learned verifiers, classifier rerouting, process supervision). Each axis is independently confirmed by 3–9 GOLD citations. The 28 citations exhibit three structural patterns of capability-elimination that strengthen — and refine — the cluster-orthogonality claim.

We stratify these into three tiers by the *kind* of evidence each provides, taking care not to inflate empirical reductions into mathematical guarantees.

Pattern A — Hard guarantees (by-construction). Seven citations achieve residual error rate equal to zero *by construction*, restricted strictly to structural / verifiable error classes: constrained decoders set $P(\text{invalid token}) = 0$ at every generation step (DINGO, ToolDec, XGrammar, XGrammar-2, OpenAI Structured Outputs); a static syntax check rejects any program with a `SyntaxError` before execution (LlmFix’s `SyntaxError` repair, 5.76% $\rightarrow$ 0.01%); proof kernels reject any output that fails type-checking (Lean / DeepSeek-Prover-V2). The class of “outputs that violate the grammar” is mathematically empty under these mechanisms. We restrict Pattern A to this narrow sense: format, syntax, schema, formal-proof validity. (LlmFix’s `NameError` row, by contrast, is a Pattern-C statistical reduction — 22.7% $\rightarrow$ 2.3%, not zero — and is tabulated as such.)

Pattern B — Strong empirical reductions with class-shift signature. Roughly fourteen citations report empirical reductions of 80–100% in a named error class, with the post-intervention failure log dominated by structurally different residual classes. The cleanest example is Program-of-Thoughts on GSM8K (Chen et al., 2022): manual taxonomy of 50 PoT failures shows calculation errors drop from 30% of CoT failures to **0%**, while residuals are 62% reasoning + 36% misunderstanding. In the OpenMedCalc arm of Goodell et al. (2025), “*only interpretation errors were identified*” — the calculation-error class is empirically absent from the post-tool failure log. Acurai (2024) reports 100% hallucination elimination on RAGTruth (95% CI 91–100%) for GPT-4 and GPT-3.5 — a strong empirical result on that benchmark, not a by-construction property of RAG in general. The class-shift signature is the structural observation: post-intervention residuals belong to different classes, consistent with cluster orthogonality, though formally the framework only requires this in expectation rather than identically.

Pattern C — Moderate reductions (60–80%) with residuals shifting outside the target class. Several citations: Legal RAG (Dantart, 2026) reduces fabricated citations from >30% to <0.2%; SimpleQA web search (OpenAI, 2025) cuts factual errors from 47% to 9.6%; CRITIC toxicity (Gou et al., 2024) reduces toxic generation by 79.2%. Residuals shift toward reasoning / planning errors rather than inflating the targeted class. This is the regime where the framework’s “selectivity” claim is supported but does not rise to elimination.

The tier boundaries matter for what the paper claims. Pattern A admits the strongest rhetoric (“by construction”, “mathematically empty”). Pattern B admits “strong empirical reduction” and “class-shift signature” but not “by construction” — Acurai’s 100% on RAGTruth is a benchmark-conditional empirical fact, not a mathematical guarantee. Pattern C supports “selective reduction” without claiming class elimination. The earlier framing in this section’s first draft blurred these boundaries; the revised version keeps them sharp.

The 28 GOLD citations, organised by axis and pattern, are summarised below.

Axis	Citation	Targeted class	Pre → Post	Pattern
Verification	DeepSeek-Prover-V2 (2025)	Invalid Lean proof	any → 0% by construction	A
Format	OpenAI Structured Outputs (2024)	JSON schema violation	>60% → 0% by construction	A
Format	ToolDec (Zhang et al., 2023)	Tool-call syntax error	21–100% → 0%	A
Format	DINGO (Suresh et al., 2025)	JSON parse failure	13–82% → 0%	A
Format	XGrammar (Dong et al., 2024)	Multi-format errors	20–38% → 0%	A
Format	XGrammar-2 (Dong et al., 2026)	Malformed tool calls	33–78% → 0%	A
Arithmetic	Program of Thoughts (Chen et al., 2022)	Calculation errors on GSM8K	30% of failures → 0%	B
Arithmetic	OpenMedCalc (Goodell et al., 2025)	Clinical arithmetic	“only interpretation errors remained”	B
Knowledge/RAG	Radiology RAG (Wada et al., 2025)	RAG hallucinations	8% → 0% (p=0.012)	B
Knowledge/RAG	Acurai (2024)	Context-conflict hallucinations	100% → 0% on conflict subset	B
Knowledge/RAG	Rigorous Archivist (Dantart, 2026)	Fabricated legal citations	>30% → <0.2%	C
Code Exec	LlmFix (Zhang et al., 2024)	SyntaxError (HumanEval)	5.76% → 0.01%	A
Code Exec	AlphaCode (Li et al., 2022)	False-positive submissions	62% → 4%	B
Code Exec	MGDebugger (Shi et al., 2024)	5 code-bug classes	100% repair (5/6 classes)	B
Knowledge/RAG	ALCE (Gao et al., 2023)	Citation grounding errors	73% ungrounded → 15%	C
Knowledge/RAG	GPT-5 SimpleQA (OpenAI, 2025)	Factual errors (web QA)	47% → 9.6%	C
Knowledge/RAG	Almanac (NEJM AI 2024)	Clinical citation errors	44% → 9%	C
Arithmetic	MedRaC (Wang Z. et al., 2025)	Arithmetic in medical reasoning	426 → 74 errors	B
Code Exec	LlmFix NameError (Zhang et al., 2024)	NameError repair	22.7% → 2.3%	C
Perception	UGround (Gou et al., 2025)	GUI grounding errors	16.2% → 73.3% accuracy	B
Perception	Jedi / OSWorld (Xie et al., 2025)	GUI task failures	5% → 27% SR (5.4×)	B
Perception	SeeClick (Cheng et al., 2024)	Element mis-location	5.2% → 53.4% (10.3×)	B
Perception	DePlot (Liu et al., 2023)	Chart-reading errors	38.2% → 67.6% (+29.4 pp)	B
Verification	CRITIC toxicity (Gou et al., 2024)	Toxic generation	79.2% reduction	C

Axis	Citation	Targeted class	Pre → Post	Pattern
Verification	Math-Shepherd (Wang P. et al., 2023)	Reasoning step errors on MATH	28.6% → 43.5%	B
Knowledge/RAG	Self-RAG (Asai et al., 2024)	Unsupported facts	55.5% → 22% error	B
Perception	OmniParser (Lu et al., 2024)	Icon / element errors	70.5% → 93.8% (79% error reduction)	B
Knowledge/RAG	PopQA (Mallen et al., 2023)	Long-tail entity errors	~80% → ~50% failure (~75% on tail)	B

Capabilities are coarser than error classes. Several GOLD citations reveal “two-for-one” reductions where one capability addresses multiple named clusters. A single Python interpreter removes the execution-error component of arithmetic (cluster A), unit conversion (B), simple counting (C), list manipulation, and date arithmetic — five named classes under one provisioning, with residual failures shifting to problem representation and code synthesis. Constrained decoding eliminates by construction both format violations (D) and the structural component of “missing required elements” (the largest single ErrorAtlas category at 15.56%, our Category I), because schemas with `required: [ . . . ]` fields cannot omit those fields. Code execution feedback strongly reduces `SyntaxError`, `NameError`, and most `TypeError` (three subclasses of cluster E) together. RAG strongly reduces factual hallucinations (J), fabricated citations, and outdated information jointly when the relevant evidence is retrieved and grounded, while leaving residual failures in retrieval coverage, context selection, and reasoning over retrieved material. The practical capability library required to address a given fraction of failures is therefore smaller than the count of named error categories — the empirical phenomenon noted in Section 3.2 as a conservative-bound tightening of Postulate 1.

A negative-control result confirms the framework’s selectivity: DebugBench (Tian et al., 2024) finds that execution feedback works well for syntax/reference errors but is “*unhelpful for logic errors... may even cause disruptions.*” Capability provisioning addresses what it can detect or constrain, and the prediction of where it fails (semantic / open-ended classes) is correct. We return to this point in Section 6.

Summary of the twelve categories

Cluster	Covering axis	Intervention	Before → After	Δ	Strength	Citation
A. Arithmetic / computation	Arithmetic	Python interpreter (PAL)	20.1% → 61.5%	+41.4 pp	Strong	Gao et al., 2022
B. Unit conversion	Arithmetic	Folded into A (Python handles units natively)	—	—	(Folded)	—
C. Counting / enumeration	Arithmetic	Explicit counter (research gap)	—	—	Gap	Mechanistic interp. work
D. Format / schema violation	Format/Structure	Constrained decoding (DINGO, SLOT)	baseline → +68 pp; 99.5% schema acc.	+68 pp	Strong	Suresh et al., 2025; SLOT authors, 2025

Cluster	Covering axis	Intervention	Before → After	Δ	Strength	Citation
E. Code logic / type / null	Code Exec	REPL feedback (Reflexion, AgentCoder)	80% → 96.3% pass@1	+16.3 pp	Strong	Shinn et al., 2023
F. Multi-hop decomposition drift	Knowledge/RAG	Entity-grounded rewriter (ChainRAG)	consistent gains across 3 benchmarks	\$~\$5–10 pp	Medium	Zhu et al., 2025
G. Reasoning step errors	Verification	Process reward model (Math-Shepherd)	28.6% → 43.5%	+14.9 pp	Strong	Wang P. et al., 2023
H. Specification misinterpretation	(semantic residual)	Clarification loops (AmbigNLG)	ROUGE-L +15; compliance 86% → 94% (subsumed)	+8 pp	Medium	Niwa & Iso, 2024
I. Missing required elements	Format/Structure	Reframed as Category D for structural, G/H for semantic		—	Reframed	This work
J. Hallucination / factual errors	Knowledge/RAG	RAG query reformatting (Acurai)	non-zero → 0%	−100%	Strong	Acurai authors, 2024
K. Inappropriate refusal	Verification	Preference optimisation (POROver)	57.6% → 82.1%	+24.5 pp	Strong	Karaman et al., 2024
L. Tool / API usage errors	Format/Structure + Verification	Structured uncertainty (SAGE-Agent)	36.5% → 65.2%	+28.7 pp	Strong	Suri et al., 2025

Eight of twelve categories have a strong citation with double-digit percentage-point improvement; three (B, C, I) lack a clean single-cluster ablation in the literature and are addressed below; one (F) has consistent medium-strength evidence.

Detailed evidence on the strongest categories The arithmetic category is the cleanest example of cluster orthogonality. Delegating execution to a Python interpreter, PAL (Gao et al., 2022) lifts GSM-Hard accuracy from 20.1% to 61.5% — a 41.4-point gain on the benchmark configuration where large numbers stress LLM tokenisation. What matters more than the gain is the composition of the residual: PAL’s remaining failures are problem-comprehension errors, mis-translations from word problem to code. Arithmetic execution errors have left the failure log. Toolformer (Schick et al., 2023) self-teaches the same shift and lands a 97.9% calculator-call rate on arithmetic queries; and on clinical calculations Goodell et al. (2025) report a 5–13× error reduction (LLaMA: 16% → 88%; GPT-4: 4.8% → 64%) once the appropriate domain tool is in the loop.

Format violations admit something stronger still: a mathematical guarantee. DINGO (Suresh et al., 2025) reports up to +68 percentage points on JSON-generation tasks. SLOT (SLOT authors, 2025) reaches 99.5% schema accuracy with 94% content similarity — the cluster is essentially gone. A systematic evaluation of four production frameworks (Guidance, Outlines, Llamacpp, XGrammar) by JSONSchemaBench (Geng et al., 2025) reports coverage up to 0.96 on real-world schemas. The mechanism is uniform across the family: zero out the logits of

grammar-violating tokens at each decoding step and the violations cannot occur.

The hallucination result is the most striking single number in the harvest. Acurai (Acurai authors, 2024) — query reformatting applied to RAG — reports 100% hallucination elimination on RAGTruth for both GPT-4 and GPT-3.5, with a 95% CI of 91–100%. This is a benchmark-specific empirical result, not a general by-construction guarantee: Acurai does not prove that hallucinations cannot occur, only that none were observed on RAGTruth’s test set under their specific query-reformatting setup. Domain-specific variants (legal, clinical) report 60–90% reduction with magnitudes depending on the baseline. The mechanism is austere but not mathematical: hallucinations require the model to generate factual claims absent from context, and citation-grounded retrieval tightens — without eliminating in general — that failure path.

Code generation shows a clean staircase. Reflexion (Shinn et al., 2023) lifts HumanEval pass@1 from 80% to 91% by reflecting on execution feedback; AgentCoder (Huang et al., 2023) extends the loop to multi-agent test-driven generation and reaches 96.3% — approaching ceiling. At 96.3% the residual is dominated by spec-misinterpretation (Category H). The execution-feedback capability has erased what it can erase.

The Category-I reframing Of the three apparent gaps (B, C, I), Category I — “missing required elements” — is the most significant because it is the largest single category in ErrorAtlas at 15.56% of all errors. Originally we expected to find a dedicated “checklist verifier” intervention in the literature; we did not. The cleanest resolution is mechanistic equivalence with Category D. A “missing required element” error is structurally a schema-violation where the schema’s required: [...] field list is not satisfied. Constrained decoders (DINGO, SLOT, Outlines, Guidance, XGrammar) enforce schema constraints during decoding; with a properly specified schema, they mathematically *cannot* produce output that omits a required field. SLOT’s 99.5% schema accuracy directly includes required enforcement.

We therefore split Category I into two mechanistically distinct sub-clusters: (I.a) structural missing elements — omitted JSON field, missing function argument, missing required citation — which are absorbed by Category D’s constrained-decoding interventions; and (I.b) semantic missing elements — incomplete reasoning step, missing edge case in code, omitted assumption in proof — which fall under Category G (process supervision) or Category H (clarification loops). No new intervention category is required, and two of the highest-volume clusters (D format + I.a structural missing, jointly $\approx 25\%$ of ErrorAtlas) share a single mechanism — which strengthens rather than weakens the cluster-orthogonality argument.

Categories B (unit conversion) and C (counting) remain technical gaps. Unit conversion is naturally folded into Category A: any Python interpreter handles dimensional analysis, and PAL/PoT/ToRA results already encompass it. Counting is the smallest residual gap; a focused literature pass or a one-day inference-only ablation would close it.

Additivity and its limits Six Sigma Agent results (Six Sigma authors, 2026) demonstrate that stacking interventions targeting orthogonal failure modes can produce large compound reliability gains. In their parallel-consensus framework, atomic task decomposition combined with five-way majority voting yields a $14,700\times$ improvement over a single-pass baseline on the authors’ internal benchmark — we read this as evidence for compound gains from decomposition plus consensus aggregation under their specific parallel-voting regime, not as a direct demonstration that heterogeneous cluster-targeted interventions compose additively in the absence of voting. AgentSquare (AgentSquare authors, 2024) similarly shows supra-additive gains when modules target distinct failure modes. These are encouraging but benchmark- and aggregation-specific.

There is a caveat. Le (2026) reports that schema-level and prompt-level instructions interact *non-additively* for some model families: stacking constrained decoding (Category D) with prompt-level specification clarifications (Category H) produces less than the sum of individual gains, sometimes substantially so. The interaction is concentrated in cases where both interventions share a common prompt channel. We treat this as evidence not against additivity in general but for a refinement: interventions that operate on orthogonal processing layers (decoding constraint vs. retrieval vs. training-signal vs. inference-time tool call) compose near-additively, while those that share a channel may interfere. This refinement is itself testable and we leave it as future work.

4.3 Claim C: Sublinear length scaling

We now compile direct evidence that LLM reliability decays sublinearly — typically logarithmically, sigmoidally, or in a plateau-then-cliff pattern — rather than exponentially with output or context length. This is the headline conclusion of Arbuzov et al. (2025); we extend it here with newly available benchmark results and reconcile it with the steeper-decay reports re-examined in Section 6.

Log-linear decay on multi-document reasoning. Loong (Wang M. et al., 2024) evaluates 4 task types on 4 context-length sets (10K–50K, 50K–100K, 100K–200K, >200K). GPT-4o on Chain-of-Reasoning declines 81.6% → 62.1% → 45.1% → 32.9% across the four sets — consistent with log-linear decay across the measured bins. Exponential per-token decay would predict near-zero accuracy by 200K and is decisively ruled out by the 32.9% endpoint. We do not commit to a specific log-linear fit constant because the bin-representative convention (lower bound, midpoint, mean) materially shifts the slope; the qualitative claim — mild, much-slower-than-exponential decay over $\log L$ — is robust to that choice.

Sigmoid decay on synthetic math. GSM- ∞ (Zhou et al., 2025) fits a sigmoid (saturating) shape with $R^2 > 0.98$ on the Medium subtask. Two further results from the same paper directly attack the independent-error model. First, exponentially more inference compute yields only *linear* AUC gains ($R^2 > 0.99$ for the linear fit) — under independent per-step Bernoulli errors, more trials should give exponential improvement. Second, DeepSeek-R1 maintains 10%+ accuracy at 130 reasoning operations; $(1 - \varepsilon)^{130}$ with any reasonable ε would predict near-zero. Both are consistent with errors concentrated at semantic decision points, not distributed uniformly.

Compositionality gap is bounded, not growing. Press et al. (2023) measure the gap between models’ ability to answer two-hop questions and the product of their one-hop accuracies. Under independent per-step compounding, the gap should grow with chain length; under clustered errors, it should be bounded. Press et al. find a $\sim 40\%$ gap that is approximately *constant* across the GPT-3 family of models they evaluate (spanning sub-billion to 175B-parameter variants). This is direct empirical evidence against per-step independent compounding.

Self-consistency is consistent with — but does not prove — clustered structure. Wang X. et al. (2023) report +17.9 pp on GSM8K from majority voting over 40 sampled chains. A common reading interprets the magnitude as incompatible with independent sampled paths, but this is not quite right: Condorcet aggregation of iid Bernoulli(p) chains with $p > 0.5$ can move accuracy substantially as the sample count grows, so gain magnitude alone is not diagnostic. The clustered-attractor interpretation remains *consistent* with the observed gain — sampled chains converge on a small number of recurring reasoning paths, exactly the structural prediction of Section 3 — but is not established by it. We therefore retain self-consistency as suggestive evidence pointing in the same direction as Section 4.1’s concentration result, not as an independent proof of cluster structure.

Bounded effective decision count via K/V compression. Pang et al. (2024)’s Anchor LLMs achieve $\approx 99\%$ reduction in cached K/V state per layer with only minor accuracy compromise, plus a $3.5\times$ inference speedup. The mechanism operates on internal K/V vectors, not on the input token stream — so the observation does not directly imply input-token redundancy. What it does imply is that the *effective number of distinct attention-key vectors* a long-context model needs to retain to produce coherent output is far smaller than n — exactly the architectural form of the sparse-decision claim. LongLLMLingua (Jiang et al., 2024) and Recurrent Context Compression (Huang et al., 2024) report similar prompt- and context-compression bounds along the same theme.

Staircase / plateau-and-cliff patterns. Think-Prune-Train (Costello et al., 2025) reports that successive self-training rounds raise Pass@1 (Gemma-2B: 41.9% → 57.6%; LLaMA-70B: 78% → 91.5%) while Pass@20 *plateaus* after the first round. This is the manifold-transition signature: the model is finding the correct cluster more reliably (Pass@1 rises) but is not finding new correct solutions (Pass@20 unchanged). RULER (Hsieh et al., 2024) reports threshold behaviour: simple retrieval holds to 32K; complex reasoning collapses earlier. Neither pattern is consistent with smooth $(1 - \varepsilon)^n$ decay.

METR’s logistic-in-log-length. METR (METR, 2025) fits per-model success as a logistic function of $\log(\text{human-time})$: $S(t) = \sigma(\beta \cdot (\log t - \log h))$. Logistic-in-log is mathematically sublinear in length itself. The famous METR exponential — capability doubling every seven months — is an *inter-model* claim about how the horizon h grows over generations, not an *intra-model* claim about within-model decay shape. We address the common misreading in Section 6.

Counter-evidence. Several prominent papers report what reads as rapid or “exponential” decay — Dziri et al. (2023), Kuratov et al. (2024), METR (2025), Wan et al. (2025). Read carefully, each decays over a variable other than raw token length: compositional graph size, number of supporting facts, log-time horizon, capacity threshold. Section 6 walks through each one.

5. Practical Implications

Reliability engineering is local patch coverage. Within a fixed domain patch, Proposition 1’s polylog bound makes reliability a small-catalogue engineering problem rather than an asymptotic scaling problem. A team building a reliable LLM system in a measured domain should initially budget for a library on the order of tens of interventions, then refine that estimate from the local mode-discovery curve $C_{\text{seen},D}(T)$ and the empirical rank-frequency distribution. Current evidence is consistent with ≈ 50 named interventions covering the head of the per-hard-token failure distribution in many measured domains — but this number is a planning prior, not a universal constant. The same base model in three different patches (cardiology RAG, legal contract drafting, code review) yields three different intervention libraries: C_D , A_D , and σ_D all change with the deployment domain. The engineering goal is not global manifold mastery; it is identifying the recurring transition types available in the target patch and provisioning interventions against the head of that local catalogue.

Domain transfer is mild but non-trivial. The mode-rate constant σ shifts between domains (math ≈ 1.2 – 1.6 ; code ≈ 0.87 – 1.30 ; general ≈ 1.85), and higher- σ domains carry larger catalogues at any given corpus size — so they need proportionally more interventions for matched coverage. The dependence is linear in σ at fixed coverage: a domain with twice the mode-discovery rate needs roughly twice the catalogue size. Across the domains measured here, σ does not vary by orders of magnitude.

Per-hard-token vs. sequence-level targets matter for SLA design. The result in Section 3.4 separates two cases that are often conflated. Per-hard-token residual error rate — the right metric for systems that surface or correct errors continuously — has a polylog intervention budget. Sequence-level failure probability — the right metric for systems where a single error invalidates the output — is strictly stricter and requires nearly full-catalogue coverage as k grows. Production deployments should design their reliability SLA to match the actual cost structure: continuous-correction systems can lean on the polylog result, while one-shot systems should plan for tighter coverage.

Library design as engineering, not asymptotic theory. A practical implication of the cluster-selectivity finding (Section 4.2) is that an intervention library can be assembled module-by-module, in any order, as long as the modules target distinct failure classes. The Le (2026) caveat applies only to interventions sharing a prompt channel; layer-separated interventions (constrained decoding + retrieval + process supervision + tool call) compose approximately additively in our data, though the additivity is empirical rather than derived. Library construction is therefore highly parallelisable: different teams can ship independent interventions and combine them with minimal integration risk, modulo the prompt-channel caveat.

Capability libraries are coarser than error-class libraries. Five named error classes in the math domain (arithmetic, units, counting, list manipulation, date arithmetic) are all addressed by a single Python interpreter; three code-error classes (SyntaxError, NameError, most TypeError) collapse under one execution-feedback loop; format violations and the structural component of “missing required element” — together more than 20% of ErrorAtlas — collapse under one constrained-decoder deployment. The practical reliability library is therefore smaller than the count of named error clusters. A team budgeting for “ ≈ 50 interventions per domain” can expect to need fewer than 50 capability-axis interventions while still covering ≈ 50 named clusters. The six axes of Section 4.2.0 are likely closer to the right unit of engineering accounting than the twelve clusters of Section 4.2.

6. Discussion

6.1 By-construction elimination as a boundary case

Seven of the 28 GOLD citations in Section 4.2.0 — DeepSeek-Prover-V2’s Lean proof checker, OpenAI Structured Outputs, ToolDec, DINGO, XGrammar, XGrammar-2, and LlmFix’s static syntax check — achieve residual error rate equal to zero *by mathematical construction*, not statistically. Constrained decoders set $P(\text{invalid token}) = 0$ at every generation step, so no invalid token can be emitted. Proof kernels reject any output that fails type-checking. Schema validators reject any output missing a required field. (Acurai’s RAG result is excluded from Pattern A here, despite its 100% RAGTruth number; it is a benchmark-conditional empirical observation, not a by-construction property of citation-grounded retrieval in general — see Section 4.2.0 Pattern B. LlmFix’s NameError repair is also excluded, since its residual is 2.3% rather than zero — Pattern C.)

In this regime, the polylog bound of Proposition 1 — $m \geq \lceil |C|^{1-\varepsilon/e_{\text{hard}}} \rceil$ — is loose. The cluster covered by a by-construction intervention contributes zero to the residual error, not a small positive quantity. The formal statement is that for any cluster $c \in \{1, \dots, m\}$ covered by a Pattern-A intervention, $\Pr(\text{failure} \mid \text{cluster } c) = 0$ identically, regardless of how many hard-token decisions the model makes inside that cluster. The Proposition 1 budget formula treats coverage as a $[0, 1]$ fractional quantity; Pattern A pushes a subset of clusters to coverage exactly 1.

This is a strengthening result, not a counter-example. The framework’s qualitative claim — that capability provisioning can erase an error class — admits a sharp boundary case where the implication is mathematical certainty rather than statistical reduction. Crucially, Pattern A applies precisely to the *structural / verifiable* classes (format, syntax, schema, invalid proofs), which are also the head of the heavy-tailed cluster frequency distribution. Capability provisioning therefore exerts its strongest effect exactly where the failure-mode catalogue is densest, which compounds the polylog conclusion of Section 3.4.

6.2 Re-audit of counter-evidence: relocation, not dissolution

Four prominent papers are routinely cited as evidence that LLM reliability decays steeply with length, in apparent tension with our framework: Dziri et al. (2023), Kuratov et al. (2024), METR (2025), and Wan et al. (2025). To these we add NoCha (Karpinska et al., 2024) for completeness. A careful re-reading shows that *every one* of these papers decays over a variable distinct from raw token length n .

Identifying the decay axis is not the same as dissolving the practical concern. In real tasks where compositional graph size, fact count, or evidence scope grow with problem length, the framework predicts steep failure curves; the contribution is to identify which interventions help (capability provisioning along the actual decay axis) and which do not (longer context windows, more compute on the n -axis). The papers below are not refuted by the framework. Each correctly identifies a regime in which the framework expects difficulty — sometimes severe — and our analysis below acknowledges those regimes explicitly rather than relabelling them away.

Dziri et al. (2023), Faith and Fate. GPT-4 multi-digit multiplication accuracy drops from 59% (3-digit) to 4% (4-digit) in zero-shot. The authors theorise that “the probability of incorrect predictions converges exponentially to ≈ 1 for abstract compositional tasks.” The decay variable, however, is *compositional graph size* N , not raw token length n . The 3×3 multiplication graph has on the order of d^2 partial products plus carries — call the resulting node count N_3 ; the 4×4 graph similarly has node count N_4 , with $N_4 > N_3$ (Dziri et al. report the graph-size grouping but exact node counts depend on the carry convention, so we read off the order-of-magnitude rather than commit to specific integers). Multi-digit multiplication is engineered so that $k_{\text{hard}} \approx N$ — every node in the computation graph is a hard decision. For natural-language tasks, where the harvest evidence in Section 4.1 gives $k_{\text{hard}} \ll n$, the Dziri regime is the *boundary case* in which our framework reduces to their result. We agree with their empirical decay; we disagree with the interpretation that it extends to natural-language n .

A complementary observation: a clean $(1 - \varepsilon)^N$ exponential cannot simultaneously reproduce 59% at the 3-digit graph size and 4% at the 4-digit graph size for any single per-node ε — the observed drop is locally steeper than per-node-iid exponential. This is consistent with a finite catalogue of failure modes that gets exhausted as N grows, not a smooth uniform per-node failure rate. **Where the framework concedes:** in adversarial compositional tasks engineered so that $k_{\text{hard}} \approx N$, the framework reduces to Dziri’s regime and does not relieve

it; the relocation is informational, not magical.

Kuratov et al. (2024), BABILong. The abstract reports “performance declines sharply with increased reasoning complexity” and that models “effectively utilise only 10–20% of the context.” Read in detail, BABILong varies *two* axes: context length n (from 0K to 10M tokens) and number of supporting facts k (from QA1 = 1 fact to QA3 = 3 facts, etc.). The sharp decline is in k , not in n . For QA1 (single-fact), most models “perform well up to 4,000 tokens” — a plateau, not exponential decay. The famous RAG-flat-across-length result (60% on single-fact QA *independent of context length*) is the cleanest possible demonstration that when the relevant evidence is in window, length does not matter. Recurrent Memory Transformers maintaining performance to 50M tokens further confirms that effective k is determined by architecture, not by raw n . **Where the framework concedes:** for multi-hop tasks whose required fact count grows with task complexity, BABILong’s sharp k -axis decay is the framework’s *predicted* trouble, not a counter-example to it.

METR (2025). Per-model success fits a logistic curve in $\log(\text{human-task-duration})$: $S(t) = \sigma(\beta \cdot (\log t - \log h))$. Logistic-in-log-length is *mathematically sublinear* in length itself. The 80%-horizon being 4–6 $\times$ shorter than the 50%-horizon is a steep within-model cliff but is by construction compatible with the polylog result of Section 3.4 — a cliff at a specific capacity threshold is a manifold-transition signature, exactly the structure of Arbuzov et al. (2025, §3.2). The famous exponential — capability doubling every seven months — is an *inter-model* claim about how the horizon h moves across generations, orthogonal to within-model decay shape. When a model improves, its h shifts right; the curve does not steepen. **Where the framework concedes:** the within-model logistic-in-log cliff is steep on a practical scale; calling it “sublinear in length” is technically correct but engineering-useful only for systems that can be designed to operate well below the 50% horizon.

Wan et al. (2025), Fano-style upper bound. This paper theorises super-linear information-demand growth and identifies an “accuracy cliff” at capacity overflow: “when the task’s information demand surpasses the model’s output capacity, performance does not degrade gracefully but instead collapses sharply.” The behavioural prediction is a *threshold*, not smooth $(1 - \varepsilon)^n$. A cliff at a specific capacity threshold is exactly the manifold-transition behaviour our Section 3 framework predicts at the boundary between covered and uncovered modes; Wan et al.’s mechanism (capacity overflow) is one specific cause of the boundary, complementary to ours. **Where the framework concedes:** Wan documents a mechanism by which $|C|$ effectively exceeds the model’s coverage in a single forward pass; Pattern A interventions (constrained decoding, formal verification) are the kind of response the framework expects but does not automatically supply.

Karpinska et al. (2024), NoCha. GPT-4o achieves 55.8% pair accuracy across 1,001 minimally-different true/false claim pairs about long fictional books (mean length 127K tokens). The paper reports performance by *evidence scope*, not by context length: 59.8% on sentence-level retrieval, 47.6% on passage-level, 41.6% on global reasoning. No per-context-length curve is reported. The decay axis is the number of evidence pieces that must be integrated — i.e., a k -axis quantity, not an n -axis one. NoCha is therefore not counter-evidence to a sublinear-in- n claim. **Where the framework concedes:** evidence-scope decay is a k -axis observation that the framework predicts cannot be addressed by scaling raw context length; it requires retrieval or process supervision along the actual decay axis.

Unifying observation. Every counter-paper decays over a variable that is not n : compositional graph size, fact count, log-time horizon, capacity threshold, or evidence scope. The apparent rapid decay is, in each case, in a quantity that our framework already concentrates the action in (k_{hard} and $|C|$), not in raw sequence length. This is a relocation, not a dissolution. These papers are not counter-evidence to the sublinear-in- n thesis, but they identify regimes where the framework predicts steep k_{hard} -axis decay in practice. Identifying the correct intervention axis is the contribution of this re-audit; promising that those regimes are easy is not. Where k_{hard} grows with task length — adversarial compositional structure, multi-hop fact chains, long horizons that force more decisions — reliability remains hard; the framework’s value is in directing intervention toward capability provisioning along the actual decay axis rather than toward context-window or compute-budget expansion that does not help.

6.3 Limitations, residual budget, and falsifiability

Mathematical limitations. Three are worth flagging. First, Postulate 1 is empirical, not derived. While it is consistent with ErrorAtlas, HumanEval, and MWPEs at corpus scale, a domain with genuinely Heaps-power-

law mode discovery (canonical $b \approx 0.5$) would invalidate the doubly-logarithmic special case of Proposition 1, although the qualitative polylog result of Section 3.5 would still hold. Second, the coverage form in Section 3.3 is an empirical best-fit choice among several plausible candidates; readers should not interpret the close numerical match against two anchor points as theoretical confirmation. Third, the cluster-orthogonality assumption that underwrites Proposition 1’s composition step is only approximate; the Le (2026) caveat on prompt-channel interference is real and would tighten the bound in shared-channel settings.

Domain narrowness. Postulate 1’s empirical anchor rests on three taxonomies (ErrorAtlas, HumanEval categorisation, MWPEs-300K) all published in 2025–2026 and covering general, code, and math domains. The framework is untested on agentic workflows, long-running scientific reasoning, multi-turn tool use over millions of tokens, and production codebases. Those are precisely the regimes where $|C|$ may grow faster than logarithmically — and where the practical reliability question matters most. The polylog conclusion of Section 3.4 should be read as a domain-conditional claim until subsample-discovery measurements (Section 3.6 lists the falsifiability test) are available in those regimes.

Single-point calibration of σ . The estimate $\sigma \approx 1.85$ is a calibration against the ErrorAtlas category count at one corpus scale, not a fit to a discovery curve. A subsample-vs-distinct-modes plot has not been published for ErrorAtlas (or for any other LLM error taxonomy at the time of writing); Section 3.6 lists this as the explicit empirical test that would either tighten the postulate or move the analysis to the Heaps variant of Section 3.5.

Identifiability of β . β is a latent stratification parameter; we report no empirical range because failure-mode atlases measure $\Pr(\text{category} \mid \text{error occurred})$, which does not identify $\Pr(\text{hard} \mid \text{key-token})$. Future work measuring hard-token opportunities directly — e.g., by ablation of model confidence at predicted decision boundaries, or by comparing confidence distributions over sampled key-token positions — would close this gap.

Taxonomy granularity and the L2–L3 gap. The framework operates on L2 (taxonomy categories) as a proxy for L3 (latent modes). $|C|$ depends on the taxonomer’s resolution choices: splitting “reasoning error” into 200 subtypes inflates $|C|$ without changing the underlying mode catalogue. We have no independent measurement of how faithful current taxonomies are as L3 proxies, and we treat this as a residual epistemic risk rather than a solved problem.

Goalpost-relocation caveat. By concentrating the practical action in k_{hard} and $|C|$ rather than raw n , the framework *relocates* the difficulty of long-context reliability rather than resolving it. Domains where k_{hard} grows with task length — adversarial compositional structure, multi-hop chains, long agent horizons — remain hard. The framework’s claim is to identify the axis of intervention (capability provisioning along the actual decay variable), not to dissolve the underlying engineering problem. Practical reliability work in those regimes still requires the hard interventions; the framework’s value is in saying which interventions are on-axis and which are off.

Patch-shift between deployments. When a model moves from one application domain to another — say, from general-purpose chat to clinical decision support — the four domain-indexed quantities A_D , σ_D , β_D , and $|C_D|$ all change. A library calibrated against one patch will under-cover the next patch’s mode catalogue. The framework predicts this transfer failure structurally (heavy-tailed and bounded per patch) but says nothing about the *content* of C_D in advance. The operationally useful response is to re-measure inside the new patch and re-fit the head of the local distribution. The cleanest follow-up evidence would be per-domain mode-discovery measurement — subsamples of size t versus distinct discovered modes, the falsifiability test of §3.6 — but no such curve has been published at the time of writing. The framework’s prediction is that such curves should rise log- or Heaps-style inside the patch and asymptote to a domain-specific $|C_D|$.

The irreducible-semantic residual. Of the 17 ErrorAtlas categories, 13 are addressed under Patterns A, B, or C by one of the six capability axes of Section 4.2.0; four are not. The mapping below makes this audit-able through the paper’s own 12-cluster scheme of Section 4.2 (with Category I split into its structural and semantic sub-clusters per §4.2’s reframing, yielding 13 distinct addressable sub-classes):

Cluster (this paper)	Covering axis	Pattern	Notes
A. Arithmetic / computation	Arithmetic	B	PAL, PoT, ToRA

Cluster (this paper)	Covering axis	Pattern	Notes
B. Unit conversion	Arithmetic	B	folded into A — Python handles units
C. Counting / enumeration	Arithmetic	(gap $\rightarrow$ C)	smallest residual gap
D. Format / schema violation	Format/Structure	A	constrained decoding
E. Code logic / type / null	Code Exec	A/B	REPL feedback; SyntaxError is Pattern A
F. Multi-hop decomposition drift	Knowledge/RAG	C	entity-grounded rewriter
G. Reasoning step errors	Verification	B	process reward
H. Specification misinterpretation	Verification (weak)	C	clarification loops; weakest fit
I.a Structural missing element	Format/Structure	A	subsumed by D's constrained decoders
I.b Semantic missing element	Verification + clarification	C	subsumed by G/H
J. Hallucination / factual	Knowledge/RAG	B/C	RAG, citation grounding
K. Inappropriate refusal	Verification	C	preference optimisation
L. Tool / API usage	Format/Structure + Verification	B	structured uncertainty

That accounts for 13 sub-classes mapped to one of the six axes. The remaining four ErrorAtlas categories — (1) a residual of inappropriate refusal beyond what preference optimisation reaches, (2) specification misinterpretation not closed by clarification loops, (3) reasoning bottlenecks at the level of problem decomposition, and (4) a small “user wanted something different” semantic remainder — admit no clean capability-provisioning fix in the current literature. These are *irreducible-semantic residuals*: classes where the failure is in choosing what to do, not in executing it. Proposition 1’s prediction of $O(\log)$ rather than $O(0)$ residual reliability reflects exactly this irreducible core. The framework does not claim 100% coverage of all failures; it claims polylog-bounded *capability-eliminable* failures, with the named semantic residual as the floor.

A falsifiability test the framework passes. DebugBench (Tian et al., 2024) explicitly catalogues which error classes execution-feedback can and cannot repair. It works well for syntax and reference errors — quoted: “*SyntaxError can be fixed: 99.74% on HumanEval, 100.00% on MBPP.*” It does not work for logic errors — quoted: “*the feedback information is unhelpful for logic errors... may even cause disruptions.*” This is the framework’s predicted failure mode (execution feedback is a Pattern-A/B capability for structural-class errors and a Pattern-C-at-best for semantic-class errors) and a falsifiability test it passes. If capability provisioning bled into the semantic residual — if execution feedback claimed to fix logic errors — the framework’s selectivity claim would be wrong. The empirical result is that capability provisioning correctly identifies both what it can erase and what it cannot.

Net assessment. The framework correctly characterises both the success regime and the failure regime; the residuals are honest limitations, not silent failures. A future extension addressing the irreducible-semantic residual — through richer process supervision, ensemble-based verification, or higher-order capability layers — would tighten the bound but is not required for the polylog conclusion to hold over the capability-eliminable fraction.

7. Conclusion

LLM reliability is often framed as an asymptotic scaling problem: as outputs get longer, do errors compound to inevitable failure? In our previous work (Arbuzov et al., 2025) we argued that this framing rests on a false uniformity assumption — errors concentrate at $\sim 5\text{--}10\%$ of tokens, not all of them. This paper takes the next step:

within that sparse set, errors are not only concentrated but also *repetitive*. They cluster into a finite catalogue of recurring failure modes whose size, under the empirical postulate of Section 3.2, grows logarithmically — and under the more conservative Heaps alternative, as a small power — of the number of observed failures.

The conditional consequence (Proposition 1) is that the intervention budget required to bound per-hard-token residual error scales polylogarithmically in sequence length within a fixed domain patch, and becomes a domain-constant once the patch ceiling $|C_D|$ is reached. The optimistic special case (Postulate 1, $k \sim \log n$) gives a doubly-logarithmic rate; the conservative Heaps variant of Section 3.5 gives $(\log n)^b$ with small b ; the symbolic-rates form of Section 3.6 shows the polylog conclusion is stable across this family. Available evidence is consistent with libraries on the order of tens of interventions covering the head of the per-hard-token failure distribution in many fixed domains. The exact number is patch-indexed and should be estimated from local discovery and rank-coverage curves, not assumed from cross-domain priors. Sequence-level reliability targets are strictly tighter and approach full-catalogue coverage as k grows; practitioners should pick the regime that matches their cost structure rather than reading the per-token result as the production SLA.

This reframes the long-context reliability question from “can we bound the growth of n -token error?” to “have we catalogued enough failure modes?” The latter question is finite and addressable. Whether it generalises to agentic, scientific, and long-horizon regimes where the published taxonomies do not yet reach is the open empirical question this paper invites. In the domains where taxonomies have been measured — general, code, math — the architecture of LLM errors is compact and the engineering problem is small. Whether the same holds elsewhere is a falsifiable empirical test, and we have named it.

Several extensions stand out. Direct empirical measurement of the mode-rate constant σ on new domains — agentic, scientific, code-in-production — would test the cross-domain generality of Postulate 1 and surface outlier domains where the catalogue may grow faster than logarithmically. A sequence-level analogue of Proposition 1, replacing the per-hard-token bound with a probabilistic bound on sequence failure, would close the gap between Section 3.4’s two regimes and give one-shot systems a cleaner SLA target. The deepest question is structural: why does mode discovery look logarithmic in the first place? Integration with the attention-mechanism bounds and stratified-manifold geometry flagged as future work in Arbuzov et al. (2025, §6) would replace our empirical postulate with a derived result — closing the loop between the two papers.

References

- Acurai authors. (2024). Acurai: Query reformatting for hallucination-free retrieval-augmented generation. *arXiv preprint arXiv:2412.05223*.
- AgentSquare authors. (2024). AgentSquare: Modular composition for LLM agents. *arXiv preprint arXiv:2410.06153*.
- Almanac authors. (2024). Almanac: Retrieval-augmented large language models for clinical question answering. *NEJM AI*.
- Arbuzov, M. L., Shvets, A. A., & Bei, S. (2025). Beyond exponential decay: Rethinking error accumulation in large language models. *arXiv preprint arXiv:2505.24187*.
- Asai, A., et al. (2024). Self-RAG: Learning to retrieve, generate, and critique through self-reflection. *International Conference on Learning Representations (ICLR) 2024*. arXiv:2310.11511.
- Ashury-Tahan, Y., et al. (2026). ErrorAtlas: A large-scale empirical atlas of LLM failure patterns across models and benchmarks. *arXiv preprint arXiv:2601.15812*.
- Chen, W., Ma, X., Wang, X., & Cohen, W. W. (2022). Program of thoughts prompting: Disentangling computation from reasoning for numerical reasoning tasks. *arXiv preprint arXiv:2211.12588*.
- Cheng, K., et al. (2024). SeeClick: Harnessing GUI grounding for advanced visual GUI agents. *Proceedings of ACL 2024*. arXiv:2401.10935.

Costello, C., Wells, C., Grefenstette, E., & Glaese, A. (2025). Think, prune, train, improve: Scaling reasoning without scaling models. *arXiv preprint arXiv:2504.18116*.

Dai, X., et al. (2025). EDIT: Identifying key reasoning steps in chain-of-thought. *Proceedings of ACL 2025*. arXiv:2405.19737.

Dantart, J. (2026). The rigorous archivist: Source-restricted retrieval for fabrication-free legal citation. *arXiv preprint arXiv:2601.15476*.

DeepSeek-Prover team. (2025). DeepSeek-Prover-V2: Advancing formal mathematical reasoning via large-scale reinforcement learning with verifier feedback. *arXiv preprint arXiv:2504.21801*.

Dong, Y., et al. (2024). XGrammar: Efficient grammar-constrained decoding for large language models. *arXiv preprint arXiv:2411.15100*.

Dong, Y., et al. (2026). XGrammar-2: Scaling schema-constrained tool calls. *arXiv preprint arXiv:2601.04426*.

Dziri, N., Lu, X., Sclar, M., Li, X. L., Jiang, L., Lin, B. Y., West, P., Bhagavatula, C., Le Bras, R., Hwang, J. D., et al. (2023). Faith and fate: Limits of transformers on compositionality. *Advances in Neural Information Processing Systems* 36. arXiv:2305.18654.

Fang, L., Wang, Y., Liu, Z., Zhang, C., Jegelka, S., Gao, J., Ding, B., & Wang, Y. (2024). What is wrong with perplexity for long-context language modeling? *International Conference on Learning Representations (ICLR) 2025*. arXiv:2410.23771.

Gao, L., Madaan, A., Zhou, S., Alon, U., Liu, P., Yang, Y., Callan, J., & Neubig, G. (2022). PAL: Program-aided language models. *Proceedings of ICML 2023*. arXiv:2211.10435.

Gao, T., et al. (2023). ALCE: Enabling large language models to generate text with citations. *Proceedings of EMNLP 2023*. arXiv:2305.14627.

Geng, S., et al. (2025). JSONSchemaBench: Evaluating constrained decoding. *arXiv preprint arXiv:2501.10868*.

Goodell, A., et al. (2025). Task-specific tools for clinical calculations: A large language model evaluation. *Nature npj Digital Medicine*.

Gou, B., et al. (2025). UGround: Navigating the digital world as humans do. *International Conference on Learning Representations (ICLR) 2025*. arXiv:2410.05243.

Gou, Z., et al. (2023). ToRA: A tool-integrated reasoning agent for mathematical problem solving. *arXiv preprint arXiv:2309.17452*.

Gou, Z., et al. (2024). CRITIC: Large language models can self-correct with tool-interactive critiquing. *International Conference on Learning Representations (ICLR) 2024*. arXiv:2305.11738.

Hsieh, C.-P., Sun, S., Krizan, S., Acharya, S., Rekesh, D., Jia, F., Zhang, Y., & Ginsburg, B. (2024). RULER: What's the real context size of your long-context language models? *arXiv preprint arXiv:2404.06654*.

Huang, C., Zhu, G., Wang, X., Luo, Y., Ge, G., Chen, H., Yi, D., & Wang, J. (2024). Recurrent context compression: Efficiently expanding the context window of LLM. *arXiv preprint arXiv:2406.06110*.

Huang, D., et al. (2023). AgentCoder: Multi-agent-based code generation with iterative testing and optimisation. *arXiv preprint arXiv:2312.13010*.

Jiang, H., Wu, Q., Luo, X., Li, D., Lin, C.-Y., Yang, Y., & Qiu, L. (2024). LongLLMLingua: Accelerating and enhancing LLMs in long context scenarios via prompt compression. *arXiv preprint arXiv:2310.06839*.

Karaman, O. M., et al. (2024). POROver: Improving safety and reducing over-refusal in large language models with over-refusal-aware preference optimization. *arXiv preprint arXiv:2410.12999*.

Kandpal, N., Deng, H., Roberts, A., Wallace, E., & Raffel, C. (2023). Large language models struggle to learn long-tail knowledge. *Proceedings of ACL 2023*. arXiv:2211.08411.

Karpinska, M., et al. (2024). One thousand and one pairs: A “novel” challenge for long-context language models. *Proceedings of EMNLP 2024*. arXiv:2406.16264.

Kuraton, Y., Bulatov, A., Anokhin, P., Rodkin, I., Sorokin, D., Sorokin, A., & Burtsev, M. (2024). BABILong: Testing the limits of LLMs with long context reasoning-in-a-haystack. *NeurIPS 2024 Datasets and Benchmarks Track*. arXiv:2406.10149.

Le, T. (2026). Schema-level and prompt-level instructions interact non-additively in structured generation. *arXiv preprint*.

LeCun, Y. (2023). Why autoregressive language models are exponentially diverging and doomed. *Public commentary*.

Li, X., & Sarwate, A. D. (2025). Unraveling the localized latents: Learning stratified manifold structures in LLM embedding space with sparse mixture-of-experts. *arXiv preprint arXiv:2502.13577*.

Li, Y., et al. (2022). Competition-level code generation with AlphaCode. *Science*, 378(6624), 1092–1097.

Lightman, H., et al. (2023). Let’s verify step by step. *arXiv preprint arXiv:2305.20050*.

Liu, F., et al. (2023). DePlot: One-shot visual language reasoning by plot-to-table translation. *Findings of ACL 2023*. arXiv:2212.10505.

Lu, Y., et al. (2024). OmniParser for pure vision based GUI agent. *arXiv preprint arXiv:2408.00203*.

Mallen, A., et al. (2023). When not to trust language models: Investigating effectiveness of parametric and non-parametric memories (PopQA). *Proceedings of ACL 2023*. arXiv:2212.10511.

Manning, C. D., Raghavan, P., & Schütze, H. (2008). *Introduction to information retrieval*. Cambridge University Press. (Section on Heaps’ law: <https://nlp.stanford.edu/IR-book/html/htmledition/heaps-law-estimating-the-number-of-terms-1.html>.)

MAST authors. (2025). MAST: Failure-mode analysis of multi-agent LLM systems. *arXiv preprint arXiv:2503.13657*.

METR. (2025). Measuring AI ability to complete long software tasks. *arXiv preprint arXiv:2503.14499*.

Niwa, S., & Iso, H. (2024). AmbigNLG: Addressing task ambiguity in open-domain NLG. *Proceedings of EMNLP 2024*. arXiv:2402.17717.

OpenAI. (2024). Introducing structured outputs in the API. *OpenAI Engineering Blog*. <https://openai.com/index/introducing-structured-outputs-in-the-api/>.

OpenAI. (2025). GPT-5 system card. *OpenAI*. <https://openai.com/index/gpt-5-system-card/>.

Pang, J., Ye, F., Wong, D. F., He, X., Chen, W., & Wang, L. (2024). Anchor-based large language models. *Findings of ACL 2024*. arXiv:2402.07616.

Park, K., Choe, Y. J., & Veitch, V. (2024). The linear representation hypothesis and the geometry of large language models. *Proceedings of ICML 2024*. arXiv:2311.03658.

Press, O., Zhang, M., Min, S., Schmidt, L., Smith, N. A., & Lewis, M. (2023). Measuring and narrowing the compositionality gap in language models. *Findings of EMNLP 2023*. arXiv:2210.03350.

RFM authors. (2025). RFMDataset: Recurring failure modes across open-source LLMs. *arXiv preprint arXiv:2506.17114*.

Schaeffer, R., et al. (2025). Why are large language models’ scaling laws power laws? *International Conference on Machine Learning (ICML) 2025*. arXiv:2502.17578.

Schick, T., et al. (2023). Toolformer: Language models can teach themselves to use tools. *Advances in Neural Information Processing Systems* 36. arXiv:2302.04761.

Shi, F., et al. (2024). MGDebugger: From syntax to semantics — multi-granularity LLM-driven code debugging. *arXiv preprint arXiv:2410.01215*.

Shinn, N., Cassano, F., Berman, E., Gopinath, A., Narasimhan, K., & Yao, S. (2023). Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems* 36. arXiv:2303.11366.

Six Sigma authors. (2026). Six Sigma agent framework: Compound reliability through orthogonal interventions. *arXiv preprint*.

SLOT authors. (2025). SLOT: Schema-level output transformation for reliable structured generation. *arXiv preprint arXiv:2505.04016*.

Sun, J., et al. (2025). MWPEs-300K: A large-scale math word problem error set with per-category failure distributions. *Findings of ACL 2025*. arXiv:2501.15581.

Suresh, S., et al. (2025). DINGO: Constrained decoding for diffusion language models. *arXiv preprint arXiv:2505.23061*.

Suri, K., et al. (2025). SAGE-Agent: Structured uncertainty in agentic AI. *arXiv preprint arXiv:2511.08798*.

TauBench authors. (2024). τ -bench: A benchmark for tool-augmented LLM agents. *arXiv preprint arXiv:2406.12045*.

Tian, R., et al. (2024). DebugBench: Evaluating debugging capability of large language models. *arXiv preprint arXiv:2401.04621*.

Wada, S., et al. (2025). Domain retrieval-augmented generation eliminates radiology report hallucinations. *Nature npj Digital Medicine*.

Wan, K., et al. (2025). A Fano-style accuracy upper bound for LLM single-pass reasoning in multi-hop QA. *arXiv preprint arXiv:2509.21199*.

Wang, M., et al. (2024). Leave no document behind: Benchmarking long-context LLMs with extended multi-doc QA. *Proceedings of EMNLP 2024*. arXiv:2406.17419.

Wang, P., et al. (2023). Math-Shepherd: Verify and reinforce LLMs step-by-step without human annotations. *arXiv preprint arXiv:2312.08935*.

Wang, X., Wei, J., Schuurmans, D., Le, Q., Chi, E., Narang, S., Chowdhery, A., & Zhou, D. (2023). Self-consistency improves chain of thought reasoning in language models. *International Conference on Learning Representations (ICLR) 2023*. arXiv:2203.11171.

Wang, Y., et al. (2024). MMLU-Pro: A more robust and challenging multi-task language understanding benchmark. *arXiv preprint arXiv:2406.01574*.

Wang, Z., et al. (2025). From scores to steps: Diagnosing and improving LLM performance on medical calculation tasks (MedRaC). *Proceedings of EMNLP 2025*. arXiv:2509.16584.

Weakest Link authors. (2026). The weakest link law: Multi-hop QA performance collapses to the least-visible-evidence bucket. *arXiv preprint arXiv:2601.12499*.

Xie, T., et al. (2025). Jedi: A grounding-dataset-driven approach to OSWorld and GUI agent tasks. *NeurIPS 2025*. arXiv:2509.13644.

Zhang, J., et al. (2024). Categorizing code-generation errors of large language models on HumanEval (LlmFix). *arXiv preprint arXiv:2409.00676*.

Zhang, K., et al. (2023). ToolDec: Syntax error-free and generalisable tool use via finite-state-machine constrained decoding. *arXiv preprint arXiv:2310.07075*.

Zhou, Y., Liu, H., Chen, Z., Tian, Y., & Chen, B. (2025). GSM-Infinite: How do your LLMs behave over infinitely increasing context length and reasoning complexity? *arXiv preprint arXiv:2502.05252*.

Zhu, H., et al. (2025). Lost-in-retrieval: Decomposition failures in multi-hop retrieval-augmented generation. *arXiv preprint arXiv:2502.14245*.