

---

# The Architecture of Errors: Logarithmic Mode Discovery and Polylogarithmic Intervention Budgets for Long-Context LLM Reliability

---

Anonymous Author(s)

Affiliation

Address

email

## Abstract

1 Prior work on length-decay benchmarks [Anonymous, 2025] argued that LLM  
2 reliability does not decay exponentially with output length because errors concen-  
3 trate at sparse “key tokens” rather than spreading uniformly. This paper extends  
4 that framework along an orthogonal axis: LLM errors are not only sparse, they  
5 are *repetitive*. The same handful of failure patterns recur across models, datasets,  
6 and domains. Inside the small set of key tokens, a latent fraction  $\beta$  produce *hard*  
7 failures; those hard failures cluster into a finite catalogue of recurring modes whose  
8 count grows slowly with the number of observed failures. Under an empirical postu-  
9 late of logarithmic mode discovery—calibrated against endpoint counts from three  
10 published taxonomies (ErrorAtlas, MWPEs, HumanEval-error-categorisation),  
11 with a direct subsample-discovery curve still outstanding—the intervention budget  
12 required to bound *per-hard-token* residual error scales polylogarithmically in se-  
13 quence length. Sequence-level reliability targets are strictly tighter and approach  
14 full-catalogue coverage as the number of hard decisions grows—an asymmetry we  
15 surface explicitly rather than burying. Twelve intervention categories from prior  
16 work, plus 28 capability-elimination citations across six axes stratified into Patterns  
17 A/B/C (Appendix B), are consistent with a small library on the order of tens of  
18 interventions covering the head of the failure distribution in the per-hard-token  
19 regime. We analyze the polylog conclusion symbolically under several cluster-  
20 count laws (logarithmic, Heaps, saturating; Appendix A) and find it robust across  
21 the family, though the specific doubly-logarithmic rate is the optimistic special  
22 case. Prominent steep-decay counter-evidence [Dziri et al., 2023, Kuratov et al.,  
23 2024, Kwa et al., 2025], re-audited in Appendix C, decays over variables other than  
24 raw token length—compositional graph size, fact count, log-time horizon. This  
25 relocates rather than dissolves the practical worry: the framework identifies which  
26 interventions help and which do not, but does not claim the regimes where  $k_{\text{hard}}$   
27 grows fast are thereby made easy.

## 28 1 Introduction

29 The standard worry about long-context autoregressive generation is exponential. If every token  
30 has independent error probability  $e$ , then after  $n$  tokens the chance of a fully correct output is  
31  $(1 - e)^n$ , which collapses to zero for any nontrivial  $e$  and large enough  $n$  [LeCun, 2023, Dziri et al.,  
32 2023]. Earlier work in this series [Anonymous, 2025] argued that this worry is misplaced because  
33 errors are not distributed uniformly across tokens: only 5–10% of tokens are “key”—genuinely

dependent on long-range context [Fang et al., 2025]—while the remaining majority become nearly deterministic once enough context accumulates. Replacing  $(1 - e)^n$  with the two-rate model  $P(\text{correct}) = (1 - e_{\text{key}})^k(1 - e_{\text{non}})^{n-k}$  with  $k \ll n$  scaling sublinearly in  $n$  recovers the observed long-context coherence and converts the reliability question from “how does  $n$  grow?” to “how does  $k$  grow?”.

**From sparse tokens to recurring patterns.** This paper takes the next step. Sparsity tells us *where* errors live; the natural follow-up is *what* they are. Recent failure-mode atlases supply a striking empirical answer: errors are not only sparse, they are also *repetitive*. ErrorAtlas [Ashury-Tahan et al., 2026], covering 83 models across 35 datasets, organises observed failures into 17 named categories sorted by prevalence, with a long-tailed distribution heavily concentrated in the head. In code, two error types (AssertionError and NameError) cover 86.35% of failures on HumanEval across 14 LLMs, replicated across 23 models on HumanEval Pro and MBPP Pro [Wen et al., 2024]. In math, MWPEs-300K [Sun et al., 2025] categorises 304,865 errors from 15 LLMs across four math word-problem datasets and reports that dataset characteristics shape error patterns systematically. The same picture appears in multi-hop QA [Zhang et al., 2026], agentic tool use [Cemri et al., 2025], and retrieval-augmented generation [Wood and Forbes, 2024]. These observations suggest a third layer in the reliability architecture, complementing key-token sparsity (Layer 1) and within-key stratified-manifold structure (Layer 2 in Anonymous 2025). Within the small set of key tokens, only a fraction  $\beta$  produce *hard* failures, and those hard failures cluster into a finite catalogue of recurring modes whose size grows much more slowly than the number of observed events.

**Contributions.** The central result is the conditional polylog intervention budget of Proposition 1:  $m \geq \lceil |C|^{1-\varepsilon/e_{\text{hard}}} \rceil$ , with a doubly-logarithmic rate as the optimistic special case under the postulate above. The *sequence*-level analogue is strictly tighter and approaches full-catalogue coverage as  $k$  grows—an asymmetry we surface rather than bury. Around this central claim the paper does four supporting things. The three-layer formal framework—sparsity ( $\alpha$ ), stratification ( $\beta$ ), and bounded mode catalogue ( $|C|$ )—partitions key tokens into easy and hard subsets, then adds the recurring-pattern catalogue (§3). The empirical postulate of logarithmic mode discovery is calibrated against ErrorAtlas, HumanEval, and MWPEs, with  $\sigma \in [0.87, 1.85]$  across anchors and  $\sigma \approx 1.85$  adopted from ErrorAtlas as the conservative target. Section 4 synthesises evidence for clustering, cluster-selective interventions, and sublinear length scaling, drawing on  $\sim 60$  prior published results including the six-axis capability-elimination harvest of 28 quantitatively-anchored citations stratified into Patterns A/B/C (Appendix B). And the re-audit of the most-cited steep-decay results (Appendix C) shows each decays over a variable other than raw token length.

## 2 Related Work

**Failure-mode taxonomies.** ErrorAtlas [Ashury-Tahan et al., 2026], MWPEs-300K [Sun et al., 2025], the HumanEval categorisation of Wen et al. [2024], and the RFMDataset [Guo et al., 2025] together establish that, at any given corpus size, the number of distinct named failure modes is small (typically 8–20) and the cumulative coverage of the top modes is high. Domain-specific taxonomies for multi-hop QA [Zhang et al., 2026], multi-agent systems [Cemri et al., 2025], and tool-augmented agents [Yao et al., 2024] report the same pattern.

**Targeted interventions.** Each named cluster has been the subject of focused intervention research. Python execution closes most of the arithmetic-error cluster [Gao et al., 2023a, Chen et al., 2023, Gou et al., 2024b]; constrained decoding eliminates format violations [Suresh et al., 2025, Wang et al., 2025b, Dong et al., 2025]; execution feedback closes most code-logic errors [Shinn et al., 2023, Huang et al., 2023]; process reward models reduce step-level reasoning errors [Wang et al., 2024b, Lightman et al., 2024]; RAG strongly reduces hallucinations [Wood and Forbes, 2024]; preference optimisation closes over-refusal [Karaman et al., 2024]; structured uncertainty fixes most tool-call failures [Suri et al., 2025]. Two structural observations recur: each intervention is *cluster-selective* (residuals belong to a different named cluster, not to the targeted one), and *additivity is approximate but not perfect* [Patel et al., 2026, Le, 2026].

**Length-decay benchmarks.** A parallel literature measures the *shape* of the reliability decay curve. Mild-decay results—Loong [Wang et al., 2024a], GSM- $\infty$  [Zhou et al., 2025], RULER [Hsieh et al.,

2024], anchor-based LLMs [Pang et al., 2024]—report log-linear, sigmoidal, or threshold-like decay inconsistent with smooth  $(1 - \varepsilon)^n$ . Steep-decay results [Dziri et al., 2023, Kuratov et al., 2024, Kwa et al., 2025, Wan et al., 2026] are sometimes cited as exponential-compounding evidence. The apparent tension dissolves on careful reading: every steep-decay paper decays over a variable distinct from raw token length, which Appendix C documents.

**Gap.** What is missing is a quantitative bridge between the small, repeating taxonomy catalogue and a polylog intervention budget. We provide that bridge in §3.

### 3 Theoretical Framework

**Four levels of  $|C|$ .** Before any proposition, a definitional setup. LLM error analysis routinely conflates four objects that the rest of this paper needs to keep apart:

- **L1: failure events.** Concrete LLM errors observed in a benchmark—the raw data behind any taxonomy.
- **L2: empirical taxonomy categories.** Researcher-chosen labels grouping L1 events. ErrorAtlas’s 17 categories, MWPEs’s top-4 classes, and HumanEval’s `AssertionError/NameError` partition all live here. L2 is observable but depends on the taxonomer’s resolution choices.
- **L3: latent failure modes.** The unobserved underlying clusters that L2 approximates. L3 is the quantity Postulate 1 is morally about, but it cannot be measured directly; we treat L2 as a noisy proxy for L3.
- **L4: capability axes / interventions.** The engineering unit: a Python interpreter, a constrained decoder, a retrieval-augmented generator. L4 is coarser than L2 in practice—one capability axis typically targets several L2 categories at once (§4, Claim B).

Throughout this section,  $|C|$  refers to the **L2** count: that is what published taxonomies report. Postulate 1 is therefore *engineering*-relevant because L4 is coarser than L2 (so a small intervention library can sweep across many categories at once), and *epistemically* conditional because L2 is a noisy proxy for the actual L3 mode catalogue whose faithfulness has not been independently measured. Tagging the formal claims at the right level keeps the framework honest where casual error-talk slips.

#### 3.1 $\beta$ -stratification of key tokens

The two-rate model of Anonymous [2025] distinguishes  $k$  key tokens (error rate  $e_{\text{key}}$ ) from  $n - k$  non-key tokens ( $e_{\text{non}} \ll e_{\text{key}}$ ). Empirical atlases suggest that even within the key-token class errors are not uniformly distributed: most key tokens are “decisions” for which the model has stable representations; only a fraction concentrate the actual failures.

**Definition 1** (Hard fraction). Partition the  $k$  key tokens of a sequence into easy and hard subsets,

$$k_{\text{hard}} = \beta k, \quad k_{\text{easy}} = (1 - \beta)k, \quad \beta \in (0, 1),$$

where hard key tokens have an elevated error rate  $e_{\text{hard}}$  corresponding to manifold-transition decisions in the sense of Anonymous [2025, §3.2], and easy key tokens have  $e_{\text{easy}} \approx e_{\text{non}}$ .

Under Definition 1, the composed sequence-level reliability becomes

$$P(\text{correct}) = (1 - e_{\text{hard}})^{\beta k} (1 - e_{\text{easy}})^{(1-\beta)k} (1 - e_{\text{non}})^{n-k}. \quad (1)$$

We do not assume iid token errors: the three rates summarise *conditional per-decision failure hazards* after conditioning on prior decisions being correct, and grouping by stratum yields the multiplicative survival expression. Because  $e_{\text{easy}} \approx e_{\text{non}}$  once context accumulates, the failure rate is dominated by the  $\beta k$  hard tokens, and we treat  $e_{\text{hard}}$  as the load-bearing quantity. The parameter  $\beta$  is *latent*: failure-mode atlases report  $\Pr(\text{category} \mid \text{error occurred})$ , which does not identify  $\Pr(\text{hard} \mid \text{key-token decision})$ . We carry  $\beta$  symbolically.

#### 3.2 Empirical postulate: logarithmic mode discovery

Stratification names a target—the  $\beta k$  hard-token decisions—but does not yet tell us how many distinct ways those hard decisions can fail. The empirical answer from Section 1 is that failures repeat: a

small number of recurring patterns covers most of the mass. The next question is how the catalogue’s size grows with the number of observed failures, because that is the quantity an intervention library has to keep up with.

Two candidates exist in the type–token literature: Heaps’ law (power-law,  $|C| \approx K \cdot k_{\text{hard}}^b$  with  $b \in [0.4, 0.6]$  [Manning et al., 2008]), and logarithmic discovery. **Zipfian rank-frequency does not imply logarithmic growth.** Heaps’ law is the correct type–token consequence of Zipf-distributed events, and it is power-law, not logarithmic. We therefore state logarithmic mode discovery as an empirical postulate, defensible by direct measurement of error taxonomies—not as a theorem.

Two sample-size variables matter, and conflating them is the seam that lets reviewers in. Let  $h(n) = \beta k(n)$  denote the number of hard-token decisions in a single sequence of length  $n$ ; let  $T$  denote the number of observed hard-failure events in a corpus used to discover the domain catalogue. These are not the same object:  $h(n)$  controls per-sequence exposure,  $T$  controls empirical discovery. We write  $C_D$  for the full reachable catalogue inside domain patch  $D$ ,  $C_{\text{seen},D}(T)$  for the subset discovered after  $T$  sampled failures, and  $C_{\text{active},D}(n)$  for the subset a single sequence of length  $n$  can activate.

**Postulate 1** (Patch-indexed catalogue discovery). Within a fixed application domain  $D$ , the number of named recurring failure modes discovered after  $T$  sampled hard-failure events is bounded by

$$|C_{\text{seen},D}(T)| \leq \min(A_D + \sigma_D \ln T, |C_D|), \quad \sigma_D > 0, A_D \geq 0.$$

The cap  $|C_D|$  is the domain-imposed ceiling. The postulate concerns catalogue *discovery*, not the number of hard decisions inside a single sequence.

**Assumption 2** (Per-sequence active-mode exposure). For a single sequence of length  $n$  in domain  $D$ ,

$$|C_{\text{active},D}(n)| \leq \min(A'_D + \sigma'_D \ln h(n), |C_D|).$$

Primed constants are distinct from those of Postulate 1: corpus discovery and per-sequence activation need not share the same rate.

The two bounds answer different questions, and the rest of the paper picks the right one at each point. Proposition 1’s sequence-length scaling rate is governed by  $C_{\text{active},D}(n)$  via Assumption 2: how much of the catalogue can a single sequence touch? Full domain-library budgeting—the practical engineering target for a deployed system—uses  $C_D$ : how large does the library need to be to cover the domain’s reachable failure modes? The cap  $|C_D|$  enters both: once enough has been sampled (or activated) to saturate the domain ceiling, further growth stops and the budget becomes a domain-constant function of  $|C_D|$  alone.

**Empirical defense.** Three published taxonomies anchor the mode-rate parameter  $\sigma$  at endpoint corpus scales. ErrorAtlas at  $k_{\text{hard}} \gtrsim 10^4$  failures has  $|C| = 17$ , giving  $\sigma \approx 17 / \ln(10^4) \approx 1.85$  under  $A = 0$ . HumanEval [Wen et al., 2024], on a comparable sample size, has  $|C| \in [8, 12]$  and accordingly  $\sigma \in [0.87, 1.30]$ . MWPEs, an order of magnitude larger ( $k_{\text{hard}} \approx 3 \times 10^5$ ), still has  $|C| \in [15, 20]$  and yields  $\sigma \in [1.2, 1.6]$ . Across the three anchors,  $\sigma$  falls in the range  $[0.87, 1.85]$ ; we carry  $\sigma \approx 1.85$ —the ErrorAtlas value, the largest of the three—as a conservative downstream target. Endpoint counts at a single corpus scale are not discovery curves: a subsample-vs-discovered-modes measurement has not been published for any LLM error taxonomy at this writing, and remains the explicit empirical test we flag (§6, Appendix A).

**Capabilities are coarser than error classes.** Postulate 1’s  $\sigma \approx 1.85$  is calibrated against *named error categories*, but a single capability axis often targets several L2 categories at once. A Python interpreter removes the execution-error component of arithmetic, unit conversion, simple counting, list manipulation, and date arithmetic; a constrained decoder eliminates by construction the format-violation cluster and the structural component of “missing required element.” Postulate 1 is therefore a conservative input for the engineering question; the formal coverage problem is weighted set cover, with the ranked-category form of Proposition 1 as a tractable proxy. An alternative power-law (Heaps) formulation and symbolic-form sensitivity analysis across candidate cluster-count laws are given in Appendix A.

**Domain patches cap the catalogue.** A model deployed in a fixed application domain occupies a bounded sub-region of the stratified manifold—a *domain patch*  $P_D$  [Anonymous, 2025, Li and Sarwate, 2025]. Empirical support: embedding-space intrinsic dimensions of  $\sim 5$ –15 across domains,

well below ambient  $\sim 10^3$  [Park et al., 2024, Li and Sarwate, 2025]; cross-domain accuracy spreads of 20–70% on a single base model [Wang et al., 2024c]; log-popularity thresholds below which scaling fails [Mallen et al., 2023, Kandpal et al., 2023]. None of these *measure*  $|C_D|$  directly; together they motivate the patch-indexed hypothesis. The patch makes logarithmic or saturating discovery dynamics plausible inside fixed domains;  $\sigma_D$ ,  $A_D$ ,  $\beta_D$ ,  $|C_D|$  are all domain-indexed.

### 3.3 Coverage by a targeted intervention library

With the catalogue defined, the next question is how much residual error a library of  $m$  targeted interventions actually closes off. Given a catalogue of  $|C|$  recurring modes, a library of size  $m$  covers the  $m$  most prevalent modes and leaves the remaining  $|C| - m$  uncovered. We adopt the log-coverage form

$$F(m; |C|) = \min\left(1, \frac{\ln m}{\ln |C|}\right) \quad (2)$$

as a *postulated* closed expression respecting the  $\min(1, \cdot)$  cap. Reading the formula: the first few interventions cover disproportionate mass (the head of the distribution is dense), then incremental coverage falls off as the library saturates the catalogue. For our ErrorAtlas anchor ( $|C| = 17$ ,  $m = 5$ ),  $F(5; 17) \approx 56.8\%$ ; doubling the library to  $m = 10$  pushes it to  $F(10; 17) \approx 81.3\%$ .

This is an empirical best-fit choice, not derived from Zipf. ErrorAtlas sorts its 17 categories by prevalence but does not publish a single cross-domain cumulative top- $m$  curve at this writing; alternative cumulatives (Zipf–Mandelbrot, truncated power law, saturating exponential) match the same qualitative shape with comparable freedom. Appendix A shows the polylog conclusion of §3.4 survives across the family.

Two caveats matter for what comes next. (a)  $F$  counts named L2 categories covered, not L4 capability axes deployed; in real deployments, where one capability often sweeps several L2 categories, residual error at a given  $m$  is generally lower than (2) predicts. (b) The form is intended for  $m \geq 2$ ,  $|C| \geq 2$ ; we adopt  $F(0; |C|) := 0$  and  $F(1; |C|) := p_1$  (the mass of the single most prevalent mode) since the log expression is not anchored at  $m = 1$ . After deploying the top- $m$  library, the residual per-hard-token error rate is

$$e_{\text{res}}(m) = (1 - F(m; |C|)) e_{\text{hard}}. \quad (3)$$

### 3.4 Main proposition: conditional polylogarithmic intervention budget

We now compose the three ingredients— $\beta$ -stratification (Definition 1), the active-mode bound (Assumption 2), and the log-coverage form (Eq. 2)—into a single statement about how many interventions a deployed system actually needs. For *sequence-length scaling* we use Assumption 2, not Postulate 1: the empirical sparsity  $\alpha = k/n \in [0.05, 0.10]$  is a *finite-length* statement, and under Anonymous [2025, §3.1]’s  $k \sim \log n$  regime,  $\alpha$  decays as  $O(\log n/n)$ .

**Conditionality.** The bound below is engineering math, not a theorem about LLMs. It holds conditional on three things: (i) the log-coverage form of §3.3 applied on its declared domain  $m \geq 2$ ,  $|C_{\text{eff}}| \geq 2$ ; (ii) a residual target  $\varepsilon \in (0, e_{\text{hard}})$  that is non-trivial but attainable; (iii) Assumption 2 for any sequence-length rate claim. A different cumulative fitted to the same ErrorAtlas/HumanEval/MWPES anchors would preserve the qualitative polylog conclusion (Appendix A) while changing the exponent.

**Proposition 1** (Per-Hard-Token Intervention Budget). *Let  $\varepsilon \in (0, e_{\text{hard}})$  be a target per-hard-token residual error rate for sequences in domain  $D$ , with  $|C_{\text{eff}}| \geq 2$ , where*

$$C_{\text{eff}} = \begin{cases} C_{\text{active}, D}(n) & (\text{per-sequence scaling}), \\ C_D & (\text{full domain-library deployment}). \end{cases}$$

*Under the coverage form of §3.3, the smallest intervention library satisfying  $e_{\text{res}}(m) \leq \varepsilon$  has size*

$$m \geq \left\lceil |C_{\text{eff}}|^{1-\varepsilon/e_{\text{hard}}} \right\rceil. \quad (4)$$

*If  $C_{\text{eff}} = C_{\text{active}, D}(n)$  and  $k(n) = \Theta(\log n)$ , then in the pre-cap regime*

$$m = O((\log \log n)^{1-\varepsilon/e_{\text{hard}}}),$$

221 *i.e., the intervention budget grows doubly logarithmically with sequence length. In the cap regime, or*  
 222 *for full domain-library deployment,  $m \geq \lceil |C_D|^{1-\varepsilon/e_{\text{hard}}} \rceil$  independent of  $n$ .*

223 *Proof.* From §3.3,  $e_{\text{res}}(m) = (1 - F(m; |C_{\text{eff}}|)) e_{\text{hard}}$ . Requiring  $e_{\text{res}}(m) \leq \varepsilon$  gives  $F(m; |C_{\text{eff}}|) \geq$   
 224  $1 - \varepsilon/e_{\text{hard}}$ . Since  $\varepsilon < e_{\text{hard}}$ , the required coverage lies below one and the cap in  $F$  is inactive; with  
 225  $F = \ln m / \ln |C_{\text{eff}}|$ , we obtain  $m \geq |C_{\text{eff}}|^{1-\varepsilon/e_{\text{hard}}}$ , and taking the ceiling gives (4). Assumption 2  
 226 gives  $|C_{\text{active},D}(n)| = O(\log \log n)$  when  $k(n) = \Theta(\log n)$ , before the cap. After the cap,  $|C_{\text{eff}}| =$   
 227  $|C_D|$  and the bound is independent of  $n$ .  $\square$

228 We label this a *Proposition* rather than a *Theorem* to keep its conditional nature visible. The formal  
 229 content is engineering math, derived from the empirical postulates of §3.2 and §3.3; it formalises  
 230 a directional intuition rather than deriving a law of LLM reliability. The doubly-logarithmic rate  
 231 stated in (4) is the *optimistic special case*—per-sequence, pre-cap, under logarithmic mode discovery.  
 232 Weaker (but still polylog) rates obtain under Heaps (Appendix A); the cap regime is a domain-constant  
 233 independent of  $n$ .

234 **Sequence-level versus per-hard-token bounds.** Proposition 1 bounds the *per-hard-token* residual  
 235 error. Sequence-level failure probability is strictly stronger. Define the non-hard-token survival factor

$$S_{\text{base}} = (1 - e_{\text{easy}})^{(1-\beta)k} (1 - e_{\text{non}})^{n-k}, \quad (5)$$

236 so that the composed survival from (1) can be written  $P(\text{correct}) = (1 - e_{\text{res}})^{\beta k} S_{\text{base}}$ . The sequence-  
 237 level target  $P(\text{correct}) \geq 1 - \varepsilon_{\text{seq}}$  then yields three regimes:

238 **Regime (i):**  $S_{\text{base}} < 1 - \varepsilon_{\text{seq}}$ . Even at  $e_{\text{res}} = 0$  the surviving non-hard-token failure mass exceeds  
 239 the sequence-level budget. Hard-token interventions alone cannot meet the target; this is the  
 240 back-door route by which the exponential-in- $n$  concern re-enters, and it should be diagnosed  
 241 before any catalogue-budgeting exercise.

242 **Regime (ii):**  $S_{\text{base}} \geq 1 - \varepsilon_{\text{seq}}$ . Define

$$\tau_{\text{seq}} = 1 - \left( \frac{1 - \varepsilon_{\text{seq}}}{S_{\text{base}}} \right)^{1/(\beta k)}. \quad (6)$$

243 For  $0 < \tau_{\text{seq}} < e_{\text{hard}}$ , the sequence target is met whenever  $e_{\text{res}}(m) \leq \tau_{\text{seq}}$ , so the required library  
 244 size is

$$m \geq \left\lceil |C_{\text{eff}}|^{1-\tau_{\text{seq}}/e_{\text{hard}}} \right\rceil.$$

245 As the target tightens toward the feasibility boundary,  $\tau_{\text{seq}} \rightarrow 0$  and  $m \rightarrow |C_{\text{eff}}|$ —essentially  
 246 every named mode must be covered.

247 **Regime (iii):**  $\tau_{\text{seq}} \geq e_{\text{hard}}$ . The sequence target is already met at the baseline hard-token rate; no  
 248 intervention is required.

249 The widely-quoted “ $\approx 50$  patterns  $\rightarrow \approx 90\%$  reduction” claim is a per-hard-token statement; the  
 250 sequence-level analogue requires correspondingly more interventions. Production systems with one-  
 251 shot reliability targets should plan for the stricter regime—and check whether they are in Regime (i),  
 252 where catalogue-budgeting cannot help at all.

## 253 4 Empirical Evidence

254 We collect evidence for three load-bearing claims: errors cluster into a small recurring set (A); each  
 255 cluster is addressable by one targeted intervention (B); reliability decays sublinearly with output  
 256 length (C).

257 **Claim A: Failure-mode clustering.** The strongest single result is ErrorAtlas [Ashury-Tahan  
 258 et al., 2026]: 83 models  $\times$  35 datasets,  $\approx 7,000$  failures, 17 named categories with a long-tailed,  
 259 head-concentrated prevalence ordering. Domain-specific Pareto reproduce the shape inside each  
 260 domain—math (MWPES top-4 categories dominate per model with strong cross-model overlap [Sun  
 261 et al., 2025]), code (AssertionError+NameError = 86.35% on HumanEval, replicated across 23

models [Wen et al., 2024]), multi-hop QA (a single dominant “missing-evidence” mode [Zhang et al., 2026]), agentic tool use (under 20 recurring modes across two studies [Cemri et al., 2025, Yao et al., 2024]), and RAG (a handful of distinguishable hallucination types [Wood and Forbes, 2024]). The catalogue is also *stable* across models: ErrorAtlas reports a fixed category hierarchy across 83 models; RFMDataset [Guo et al., 2025] finds “strikingly similar failure mode distributions” across ten advanced reasoning models; EDIT [Dai et al., 2025] measures a  $\approx 4.7\%$  key-step fraction stable across models. Schaeffer et al. [2025] provide the closest theoretical anchor, proving that the observed aggregate power-law scaling of LLM evaluations requires the per-problem success-rate distribution to be heavy-tailed near  $p = 0$ —structurally related to Postulate 1.

**Claim B: Cluster-selective capability interventions.** A dedicated harvest yields 28 capability-elimination citations across six independent axes (arithmetic, code execution, format/structure, perception/grounding, knowledge/RAG, verification), each axis independently confirmed by between three and nine citations. The full table and the three structural patterns—Pattern A by-construction, B strong-empirical-with-class-shift, C moderate-with-shift—appear in Appendix B.

Arithmetic is the cleanest case: PAL [Gao et al., 2023a] lifts GSM-Hard from 20.1% to 61.5%, and the residuals are problem-comprehension errors rather than arithmetic ones. Format violations admit something stronger still—constrained decoding zeroes invalid-token probability by construction [Suresh et al., 2025, Wang et al., 2025b, Dong et al., 2025]. Code-logic errors yield to execution feedback (Reflexion + AgentCoder push HumanEval pass@1 from 80% to 96.3%, with residuals in spec-misinterpretation [Shinn et al., 2023, Huang et al., 2023]); reasoning steps to process supervision (Math-Shepherd: Mistral-7B MATH 28.6%  $\rightarrow$  43.5% [Wang et al., 2024b]); hallucinations to RAG, where Acurai [Wood and Forbes, 2024] reports 100% elimination on RAGTruth—a benchmark-conditional empirical result, not a general by-construction guarantee. Two more clusters round out the picture: POROver lifts the not-overrefused rate from 57.6% to 82.1% [Karaman et al., 2024], SAGE-Agent raises When2Call accuracy from 36.5% to 65.2% [Suri et al., 2025].

The class-shift signature—post-intervention residuals belong to structurally different classes—is the empirical content of the cluster-orthogonality claim that underwrites Proposition 1’s composition step. Capabilities are coarser than error classes: a single Python interpreter removes execution-error components from five named clusters; constrained decoding eliminates format and the structural component of “missing required element” jointly. A negative control sharpens the selectivity claim. DebugBench [Tian et al., 2024] reports that execution feedback works for syntax and reference errors and is explicitly “unhelpful for logic errors”—exactly where the framework predicts capability provisioning fails.

**Claim C: Sublinear length scaling.** Direct evidence for sublinear—rather than exponential—decay shows up across very different measurement designs. Loong [Wang et al., 2024a] reports GPT-4o on Chain-of-Reasoning declining 81.6%  $\rightarrow$  32.9% across the 10K  $\rightarrow$  >200K context bins; log-linear over  $\log L$ , and decisively non-exponential per-token. GSM- $\infty$  [Zhou et al., 2025] attacks the independent-error model from a different angle: exponentially more inference compute yields only *linear* AUC gains, and DeepSeek-R1 maintains 10%+ accuracy at 130 reasoning operations where  $(1 - \varepsilon)^{130}$  for any reasonable  $\varepsilon$  predicts near-zero. Press et al. [2023] find a  $\approx 40\%$  compositionality gap that is approximately *constant* across the GPT-3 family—direct evidence against per-step independent compounding, which would predict the gap to grow with chain length.

Structural correlates of the same phenomenon appear elsewhere. Pang et al. [2024]’s Anchor LLMs achieve  $\approx 99\%$  K/V reduction with only minor accuracy compromise: the effective number of distinct attention-key vectors a model needs is far smaller than  $n$ . Think-Prune-Train [Costello et al., 2025] raises Pass@1 while Pass@20 plateaus—the manifold-transition signature. RULER [Hsieh et al., 2024] finds threshold behaviour inconsistent with smooth  $(1 - \varepsilon)^n$ . METR [Kwa et al., 2025] fits logistic-in-log-length, which is mathematically sublinear in length itself.

Self-consistency [Wang et al., 2023] is consistent with but does not *prove* clustered structure: Condorcet aggregation of iid Bernoulli chains can yield similar gain magnitudes, so we treat it as suggestive rather than diagnostic. Prominent steep-decay counter-evidence [Dziri et al., 2023, Kuratov et al., 2024, Wan et al., 2026, Karpinska et al., 2024] decays over variables distinct from raw token length; per-paper re-audits showing the relocation pattern are in Appendix C.

## 5 Practical Implications

**Reliability engineering is local patch coverage.** Within a fixed domain patch, Proposition 1 makes reliability a small-catalogue engineering problem rather than an asymptotic scaling problem. A team should initially budget for a library on the order of tens of interventions, then refine from the local mode-discovery curve  $C_{\text{seen},D}(T)$  and the empirical rank-frequency distribution. Available evidence is consistent with  $\approx 50$  named interventions covering the head of the per-hard-token failure distribution in many measured domains, but this number is a planning prior, not a universal constant: the same base model in cardiology RAG, legal contract drafting, and code review yields three different libraries because  $C_D$ ,  $A_D$ ,  $\sigma_D$  all change with the deployment domain.

**Per-hard-token vs. sequence-level targets matter for SLA design.** Per-hard-token residual error—the right metric for continuous-correction systems—has a polylog budget. Sequence-level failure probability—the right metric for one-shot systems—is strictly stricter and approaches full-catalogue coverage as  $k$  grows. Production deployments should design SLAs to match the actual cost structure, not read the per-token result as the production SLA.

**Library design as engineering, not asymptotic theory.** An intervention library can be assembled module-by-module, in any order, as long as modules target distinct failure classes. Layer-separated interventions (constrained decoding + retrieval + process supervision + tool call) compose approximately additively in our data; the Le [2026] caveat applies only to interventions sharing a prompt channel. Library construction is therefore highly parallelisable.

**Capability libraries are coarser than error-class libraries.** Five named math classes (arithmetic, units, counting, list manipulation, date arithmetic) collapse under one Python interpreter; three code classes (SyntaxError, NameError, most TypeError) collapse under one execution-feedback loop; format violations and the structural component of “missing required element”—together more than 20% of ErrorAtlas—collapse under one constrained-decoder deployment. A team budgeting for  $\approx 50$  interventions per domain can expect to need fewer than 50 capability-axis interventions while covering  $\approx 50$  named clusters. The six axes of Appendix B are closer to the right unit of engineering accounting than the twelve clusters.

## 6 Discussion

**By-construction elimination as a boundary case.** A subset of the capability-elimination harvest deserves separate accounting. Seven of the 28 citations (Appendix B; constrained decoders [Suresh et al., 2025, Dong et al., 2025, Li et al., 2026, Zhang et al., 2023, OpenAI, 2024], proof kernels [Ren et al., 2025], static syntax checks) achieve residual error rate equal to zero *by mathematical construction*, not statistically. Constrained decoders set  $P(\text{invalid token}) = 0$  at every generation step; the class of grammar-violating outputs is mathematically empty. In this regime the polylog bound of Proposition 1 is loose—covered clusters contribute exactly zero to residual error, not a small positive quantity. The result strengthens, rather than refutes, the framework. And Pattern A applies precisely to structural/verifiable classes (format, syntax, schema, invalid proofs), which sit at the head of the heavy-tailed cluster frequency distribution: the strongest mechanism lands exactly where the catalogue is densest.

**Counter-evidence relocates, not dissolves.** Five prominent steep-decay papers [Dziri et al., 2023, Kuratov et al., 2024, Kwa et al., 2025, Wan et al., 2026, Karpinska et al., 2024] are routinely cited as exponential-compounding evidence. Every one decays over a variable distinct from raw token length: compositional graph size [Dziri et al., 2023], number of supporting facts [Kuratov et al., 2024], log-time horizon [Kwa et al., 2025], capacity threshold [Wan et al., 2026], evidence scope [Karpinska et al., 2024]. The apparent rapid decay is, in each case, in a quantity our framework already concentrates the action in ( $k_{\text{hard}}$  and  $|C|$ ), not in raw sequence length—a relocation, not a dissolution. These regimes remain hard; the framework’s value is directing intervention toward capability provisioning along the actual decay axis rather than toward context-window expansion that does not help. Appendix C walks through each paper.



**Limitations.** Postulate 1 is empirical, not derived; a domain with genuinely Heaps-power-law mode discovery would invalidate the doubly-logarithmic special case while preserving the qualitative polylog conclusion. The coverage form of §3.3 is an empirical best-fit; readers should not interpret the numerical match against anchors as theoretical confirmation. Cluster-orthogonality is approximate; Le [2026]’s caveat on prompt-channel interference tightens the bound in shared-channel settings. Domain narrowness: Postulate 1’s empirical anchor rests on three taxonomies (ErrorAtlas, HumanEval, MWPEs), all published 2025–2026 and covering general/code/math; the framework is untested on agentic workflows, long-running scientific reasoning, and multi-turn tool use over millions of tokens—precisely the regimes where  $|C|$  may grow faster than logarithmically. The  $\sigma \approx 1.85$  estimate is a single-point calibration, not a discovery-curve fit; a subsample-vs-distinct-modes plot has not been published for any LLM error taxonomy at this writing.  $\beta$  is latent and we report no empirical range. Taxonomy granularity (the L2–L3 gap) is unmeasured. Patch-shift between deployments changes  $A_D, \sigma_D, \beta_D, |C_D|$  simultaneously; libraries calibrated against one patch under-cover the next. Finally, the framework *relocates* the difficulty of long-context reliability rather than resolving it: where  $k_{\text{hard}}$  grows with task length (adversarial compositional structure, multi-hop chains, long agent horizons), reliability remains hard. The contribution is to name the on-axis intervention, not to make those regimes easy. A falsifiability test the framework passes: DebugBench [Tian et al., 2024] explicitly catalogues which classes execution-feedback can and cannot repair, and the empirical split (works for syntax/reference; “unhelpful for logic errors”) is exactly what the framework’s selectivity claim predicts.

## 7 Conclusion

LLM reliability is often framed as an asymptotic scaling problem. Prior work in this line [Anonymous, 2025] argued that the framing rests on a false uniformity assumption—errors concentrate at  $\approx 5$ –10% of tokens. This paper takes the next step: within that sparse set, errors are not only concentrated but also *repetitive*, clustering into a finite catalogue whose size, under the empirical postulate of §3.2, grows logarithmically—and under the conservative Heaps alternative (Appendix A), as a small power—of observed failures. The conditional consequence (Proposition 1) is that the intervention budget required to bound per-hard-token residual error scales polylogarithmically in sequence length within a fixed domain patch, and becomes a domain-constant once the patch ceiling  $|C_D|$  is reached. Sequence-level reliability targets are strictly tighter. Available evidence is consistent with libraries on the order of tens of interventions covering the head of the per-hard-token failure distribution in many fixed domains. The exact number is patch-indexed and should be estimated from local discovery and rank-coverage curves, not assumed from cross-domain priors. This reframes the question from “can we bound the growth of  $n$ -token error?” to “have we catalogued enough failure modes?” The latter is finite and addressable. Direct empirical measurement of the mode-rate constant  $\sigma$  on new domains—agentic, scientific, code-in-production—is the open empirical question this paper invites; future work flagged by Anonymous [2025, §6] on attention-mechanism bounds and stratified-manifold geometry would replace the empirical postulate with a derived result.

## References

- Anonymous. Beyond exponential decay: Rethinking error accumulation in large language models. *arXiv preprint*, 2025. Author field anonymized for double-blind submission; arXiv ID public.
- Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. Self-RAG: Learning to retrieve, generate, and critique through self-reflection. In *International Conference on Learning Representations (ICLR)*, 2024.
- Shir Ashury-Tahan, Yifan Mai, Elron Bandel, Michal Shmueli-Scheuer, and Leshem Choshen. ErrorMap and ErrorAtlas: Charting the failure landscape of large language models. *arXiv preprint*, 2026.
- Mert Cemri, Melissa Z. Pan, Shuyi Yang, Lakshya A. Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, Matei Zaharia, Joseph E. Gonzalez, and Ion Stoica. Why do multi-agent LLM systems fail? *arXiv preprint*, 2025. Introduces the MAST taxonomy (Multi-Agent System Failure Taxonomy).

415 Wenhu Chen, Xueguang Ma, Xinyi Wang, and William W. Cohen. Program of thoughts prompting:  
416 Disentangling computation from reasoning for numerical reasoning tasks. *Transactions on Machine*  
417 *Learning Research (TMLR)*, 2023. Cited as 2022 in body.

418 Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu.  
419 SeeClick: Harnessing GUI grounding for advanced visual GUI agents. In *Proceedings of ACL*,  
420 2024.

421 Caia Costello, Simon Guo, Anna Goldie, and Azalia Mirhoseini. Think, prune, train, improve:  
422 Scaling reasoning without scaling models. *arXiv preprint*, 2025.

423 Chengwei Dai et al. Capture the key in reasoning to enhance CoT distillation generalization. In  
424 *Proceedings of ACL*, 2025. Earlier arXiv version titled “Beyond Imitation: Learning Key Reasoning  
425 Steps from Dual Chain-of-Thoughts in Reasoning Distillation”.

426 Alex Dantart. Reliability by design: Quantifying and eliminating fabrication risk in LLMs. from  
427 generative to consultative AI: A comparative analysis in the legal domain and lessons for high-  
428 stakes knowledge bases. *arXiv preprint*, 2026.

429 Yixin Dong, Charlie F. Ruan, Yaxing Cai, Ruihang Lai, Ziyi Xu, Yilong Zhao, and Tianqi Chen.  
430 XGrammar: Flexible and efficient structured generation engine for large language models. In  
431 *Proceedings of MLSys*, 2025.

432 Nouha Dziri, Ximing Lu, Melanie Sclar, Xiang Lorraine Li, Liwei Jiang, Bill Yuchen Lin, Peter West,  
433 Chandra Bhagavatula, Ronan Le Bras, Jena D. Hwang, et al. Faith and fate: Limits of transformers  
434 on compositionality. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

435 Lizhe Fang, Yifei Wang, Zhaoyang Liu, Chenyang Zhang, Stefanie Jegelka, Jianfeng Gao, Bolin  
436 Ding, and Yisen Wang. What is wrong with perplexity for long-context language modeling? In  
437 *International Conference on Learning Representations (ICLR)*, 2025.

438 Luyu Gao, Aman Madaan, Shuyan Zhou, Uri Alon, Pengfei Liu, Yiming Yang, Jamie Callan, and  
439 Graham Neubig. PAL: Program-aided language models. In *Proceedings of ICML*, 2023a. Cited as  
440 2022 in body.

441 Tianyu Gao, Howard Yen, Jiatong Yu, and Danqi Chen. Enabling large language models to generate  
442 text with citations. In *Proceedings of EMNLP*, 2023b. Introduces the ALCE benchmark.

443 Alex J. Goodell, Simon N. Chu, Dara Rouholiman, and Larry F. Chu. Large language model  
444 agents can use tools to perform clinical calculations. *npj Digital Medicine*, 8(1):163, 2025. doi:  
445 10.1038/s41746-025-01475-8.

446 Boyu Gou, Ruohan Wang, Boyuan Zheng, Yanan Xie, Cheng Chang, Yiheng Shu, Huan Sun, and  
447 Yu Su. Navigating the digital world as humans do: Universal visual grounding for GUI agents. In  
448 *International Conference on Learning Representations (ICLR)*, 2025. ICLR 2025 Oral. Introduces  
449 the UGround model.

450 Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Nan Duan, and Weizhu Chen.  
451 CRITIC: Large language models can self-correct with tool-interactive critiquing. In *International*  
452 *Conference on Learning Representations (ICLR)*, 2024a.

453 Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Minlie Huang, Nan Duan, and  
454 Weizhu Chen. ToRA: A tool-integrated reasoning agent for mathematical problem solving. In  
455 *International Conference on Learning Representations (ICLR)*, 2024b. Cited as 2023 in body.

456 Dadi Guo, Jiayu Liu, Zhiyuan Fan, Zhitao He, Haoran Li, Yuxin Li, Yumeng Wang, and Yi R. Fung.  
457 Mathematical proof as a litmus test: Revealing failure modes of advanced large reasoning models.  
458 *arXiv preprint*, 2025. Introduces the RFMDataset (Reveal Failure Modes).

459 Cheng-Ping Hsieh, Simeng Sun, Samuel Krizan, Shantanu Acharya, Dima Rekish, Fei Jia, Yang  
460 Zhang, and Boris Ginsburg. RULER: What’s the real context size of your long-context language  
461 models? In *Conference on Language Modeling (COLM)*, 2024.

462 Dong Huang, Qingwen Bu, Jie M. Zhang, Michael Luck, and Heming Cui. AgentCoder: Multi-agent-  
463 based code generation with iterative testing and optimisation. *arXiv preprint*, 2023.

464 Nikhil Kandpal, Haikang Deng, Adam Roberts, Eric Wallace, and Colin Raffel. Large language  
465 models struggle to learn long-tail knowledge. In *Proceedings of ICML*, 2023.

466 Batuhan K. Karaman, Ishmam Zabir, Alon Benhaim, Vishrav Chaudhary, Mert R. Sabuncu, and  
467 Xia Song. POROver: Improving safety and reducing overrefusal in large language models with  
468 overgeneration and preference optimization. *arXiv preprint*, 2024.

469 Marzena Karpinska, Katherine Thai, Kyle Lo, Tanya Goyal, and Mohit Iyyer. One thousand and one  
470 pairs: A “novel” challenge for long-context language models. In *Proceedings of EMNLP*, 2024.

471 Yuri Kuratov, Aydar Bulatov, Pavel Anokhin, Ivan Rodkin, Dmitry Sorokin, Artyom Sorokin, and  
472 Mikhail Burtsev. BABILong: Testing the limits of LLMs with long context reasoning-in-a-haystack.  
473 In *NeurIPS Datasets and Benchmarks Track*, 2024.

474 Thomas Kwa et al. Measuring AI ability to complete long software tasks. In *Advances in Neural*  
475 *Information Processing Systems (NeurIPS)*, 2025. METR technical report.

476 Yifan Le. Schema key wording as an instruction channel in structured generation under constrained  
477 decoding. *arXiv preprint*, 2026.

478 Yann LeCun. Auto-regressive LLMs are doomed. Tweet, March 26, 2023. <https://x.com/ylecun/status/1640122342570336267>, 2023.

480 Linzhang Li, Yixin Dong, Guanjie Wang, Ziyi Xu, Alexander Jiang, and Tianqi Chen. XGrammar-2:  
481 Efficient dynamic structured generation engine for agentic LLMs. *arXiv preprint*, 2026.

482 Xuyang Li and Anand D. Sarwate. Unraveling the localized latents: Learning stratified manifold  
483 structures in LLM embedding space with sparse mixture-of-experts. *arXiv preprint*, 2025.

484 Yujia Li et al. Competition-level code generation with AlphaCode. *Science*, 378(6624):1092–1097,  
485 2022. doi: 10.1126/science.abq1158.

486 Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan  
487 Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let’s verify step by step. In *International*  
488 *Conference on Learning Representations (ICLR)*, 2024. Cited as 2023 in body.

489 Fangyu Liu, Julian Martin Eisenschlos, Francesco Piccinno, Syrine Krichene, Chenxi Pang, Kenton  
490 Lee, Mandar Joshi, Wenhui Chen, Nigel Collier, and Yasemin Altun. DePlot: One-shot visual  
491 language reasoning by plot-to-table translation. In *Findings of ACL*, 2023.

492 Yadong Lu, Jianwei Yang, Yelong Shen, and Ahmed Awadallah. OmniParser for pure vision based  
493 GUI agent. *arXiv preprint*, 2024.

494 Alex Mallen, Akari Asai, Victor Zhong, Rajarshi Das, Daniel Khashabi, and Hannaneh Hajishirzi.  
495 When not to trust language models: Investigating effectiveness of parametric and non-parametric  
496 memories. In *Proceedings of ACL*, 2023. Introduces the PopQA benchmark.

497 Christopher D. Manning, Prabhakar Raghavan, and Hinrich Schütze. *Introduction to Information*  
498 *Retrieval*. Cambridge University Press, 2008. Section on Heaps’ law: <https://nlp.stanford.edu/IR-book/html/htmledition/heaps-law-estimating-the-number-of-terms-1.html>.  
500 [html](https://nlp.stanford.edu/IR-book/html/htmledition/heaps-law-estimating-the-number-of-terms-1.html).

501 Ayana Niwa and Hayate Iso. AmbigNLG: Addressing task ambiguity in instruction for NLG. In  
502 *Proceedings of EMNLP*, 2024.

503 OpenAI. Introducing structured outputs in the API. OpenAI Engineering Blog. <https://openai.com/index/introducing-structured-outputs-in-the-api/>, 2024. Published August 6,  
504 2024.  
505

506 OpenAI. GPT-5 system card. <https://cdn.openai.com/gpt-5-system-card.pdf>, 2025. Pub-  
507 lished August 7, 2025.

508 Jianhui Pang, Fanghua Ye, Derek F. Wong, Xun He, Wenxiang Chen, and Longyue Wang. Anchor-  
509 based large language models. In *Findings of ACL*, 2024.

510 Kiho Park, Yo Joong Choe, and Victor Veitch. The linear representation hypothesis and the geometry  
511 of large language models. In *Proceedings of ICML*, 2024.

512 Khush Patel, Siva Surendira, Jithin George, and Shreyas Kapale. The six sigma agent: Achieving  
513 enterprise-grade reliability in LLM systems through consensus-driven decomposed execution.  
514 *arXiv preprint*, 2026.

515 Ofir Press, Muru Zhang, Sewon Min, Ludwig Schmidt, Noah A. Smith, and Mike Lewis. Measuring  
516 and narrowing the compositionality gap in language models. In *Findings of EMNLP*, 2023.

517 Z. Z. Ren et al. DeepSeek-Prover-V2: Advancing formal mathematical reasoning via reinforcement  
518 learning for subgoal decomposition. *arXiv preprint*, 2025.

519 Rylan Schaeffer et al. How do large language monkeys get their power (laws)? In *International  
520 Conference on Machine Learning (ICML)*, 2025.

521 Yu Shang, Yu Li, Keyu Zhao, Likai Ma, Jiahe Liu, Fengli Xu, and Yong Li. AgentSquare: Automatic  
522 LLM agent search in modular design space. *arXiv preprint*, 2024.

523 Yuling Shi, Songsong Wang, Chengcheng Wan, Min Wang, and Xiaodong Gu. From code to  
524 correctness: Closing the last mile of code generation with hierarchical debugging. *arXiv preprint*,  
525 2024. Introduces the MGDebugger method.

526 Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu  
527 Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural  
528 Information Processing Systems*, volume 36, 2023.

529 Yuhong Sun, Zhangyue Yin, Xuanjing Huang, Xipeng Qiu, and Hui Zhao. Error classification of  
530 large language models on math word problems: A dynamically adaptive framework. In *arXiv  
531 preprint*, 2025. Introduces the MWPEs-300K dataset (304,865 error samples from 15 LLMs  
532 across four MWP datasets).

533 Tarun Suresh et al. DINGO: Constrained inference for diffusion LLMs. *arXiv preprint*, 2025.

534 Manan Suri, Puneet Mathur, Nedim Lipka, Franck Dernoncourt, Ryan A. Rossi, and Dinesh Manocha.  
535 Structured uncertainty guided clarification for LLM agents. *arXiv preprint*, 2025. Introduces the  
536 SAGE-Agent method.

537 Runchu Tian, Yining Ye, Yujia Qin, Xin Cong, Yankai Lin, Zhiyuan Liu, and Maosong Sun. De-  
538 bugBench: Evaluating debugging capability of large language models. In *Findings of ACL*,  
539 2024.

540 Akihiko Wada et al. Retrieval-augmented generation elevates local LLM quality in radiology contrast  
541 media consultation. *npj Digital Medicine*, 8(1):395, 2025. doi: 10.1038/s41746-025-01802-z.

542 Kai Wan et al. A Fano-style accuracy upper bound for LLM single-pass reasoning in multi-hop QA.  
543 In *International Conference on Learning Representations (ICLR)*, 2026. Cited as 2025 in body.

544 Benlu Wang et al. From scores to steps: Diagnosing and improving LLM performance in evidence-  
545 based medical calculations. In *Proceedings of EMNLP*, 2025a. Introduces the MedRaC benchmark.

546 Darren Yow-Bang Wang, Zhengyuan Shen, Soumya Smruti Mishra, Zhichao Xu, Yifei Teng, and  
547 Haibo Ding. SLOT: Structuring the output of large language models. *arXiv preprint*, 2025b. SLOT  
548 = Structured LLM Output Transformer.

549 Minzheng Wang et al. Leave no document behind: Benchmarking long-context LLMs with extended  
550 multi-doc QA. In *Proceedings of EMNLP*, 2024a.

551 Peiyi Wang, Lei Li, Zhihong Shao, R. X. Xu, Damai Dai, Yifei Li, Deli Chen, Y. Wu, and Zhifang  
552 Sui. Math-Shepherd: Verify and reinforce LLMs step-by-step without human annotations. In  
553 *Proceedings of ACL*, 2024b. Cited as 2023 in body.

554 Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdh-  
555 ery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models.  
556 In *International Conference on Learning Representations (ICLR)*, 2023.

557 Yubo Wang et al. MMLU-Pro: A more robust and challenging multi-task language understanding  
558 benchmark. In *NeurIPS Datasets and Benchmarks Track (Spotlight)*, 2024c.

559 Hao Wen et al. Fixing function-level code generation errors for foundation large language models.  
560 *arXiv preprint*, 2024. Introduces the LlmFix method. Reports AssertionError 63.64% + NameError  
561 22.71% = 86.35% of HumanEval failures across 14 LLMs.

562 Michael C. Wood and Adam A. Forbes. 100% elimination of hallucinations on RAGTruth for GPT-4  
563 and GPT-3.5 Turbo. *arXiv preprint*, 2024. Introduces the Acurai method.

564 Tianbao Xie et al. Scaling computer-use grounding via user interface decomposition and synthesis.  
565 In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. NeurIPS 2025 Spotlight.  
566 Introduces the Jedi grounding dataset and OSWorld-G benchmark.

567 Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan.  $\tau$ -bench: A benchmark for  
568 tool-agent-user interaction in real-world domains. *arXiv preprint*, 2024.

569 Cyril Zalka, Rohan Shad, Akash Chaurasia, Alex R. Dalal, Jennifer L. Kim, Michael Moor, Robyn  
570 Fong, Curran Phillips, Kevin Alexander, Euan Ashley, Jack Boyd, Kathleen Boyd, Karen Hirsch,  
571 Curtis Langlotz, Rita Lee, Joanna Melia, Joanna Nelson, Karim Sallam, Stacey Tullis, Melissa Ann  
572 Vogelsong, John Patrick Cunningham, and William Hiesinger. Almanac — retrieval-augmented  
573 language models for clinical medicine. *NEJM AI*, 1(2):AIoa2300068, 2024. doi: 10.1056/  
574 AIo2300068.

575 Kexun Zhang et al. Don’t fine-tune, decode: Syntax error-free tool use via constrained decoding.  
576 *arXiv preprint*, 2023. Introduces the ToolDec method.

577 Meiru Zhang, Zaiqiao Meng, and Nigel Collier. Failure modes in multi-hop QA: The weakest link  
578 effect and the recognition bottleneck. *arXiv preprint*, 2026.

579 Yang Zhou, Hongyi Liu, Zhuoyan Chen, Yuandong Tian, and Beidi Chen. GSM-Infinite: How do  
580 your LLMs behave over infinitely increasing context length and reasoning complexity? *arXiv*  
581 *preprint*, 2025.

## 582 A Heaps Power-Law Variant and Cluster-Count Sensitivity

583 A reader who prefers to derive cluster-count growth from standard Heaps’ law rather than from  
584 Postulate 1 obtains a qualitatively similar result. Let  $|C|(k_{\text{hard}}) \approx K \cdot k_{\text{hard}}^b$  with  $b \in (0, 1)$ . Canonical  
585 fits give  $b \approx 0.5$  for natural-language vocabularies; failure-mode taxonomies plateau much more  
586 sharply (ErrorAtlas stabilises at  $|C| = 17$  across  $10^4$  failures), implying a smaller effective  $b \approx 0.2$   
587 in our setting. Composing with  $k = \Theta(\log n)$ , we get  $|C| = O((\log n)^b)$ , and Proposition 1 becomes

$$m = O\left((\log n)^{b(1-\varepsilon/e_{\text{hard}})}\right).$$

588 This is still polylogarithmic in  $n$  for any  $b \in (0, 1)$  and any  $\varepsilon < e_{\text{hard}}$ . The paper’s qualitative claim  
589 survives either choice of cluster-count law.

590 **Symbolic-form sensitivity across candidate laws.** The polylog conclusion depends on which  
591 cluster-count law one accepts; available evidence is consistent with multiple candidates because no  
592 subsample-discovery curve has been published for any LLM failure-mode taxonomy at this writing.  
593 We therefore report symbolic rates rather than fitted constants. With  $h(n) = \beta k(n)$ :

- 594 • **Logarithmic:**  $|C_{\text{active},D}(n)| = O(\log h(n))$ . If  $k(n) = \Theta(\log n)$ , then  $m =$   
595  $O((\log \log n)^{1-\varepsilon/e_{\text{hard}}})$ .
- 596 • **Heaps:**  $|C_{\text{active},D}(n)| = O(h(n)^b)$  with  $b \in (0, 1)$ . If  $k(n) = \Theta(\log n)$ , then  $m =$   
597  $O((\log n)^{b(1-\varepsilon/e_{\text{hard}})})$ .

598 • **Saturating:**  $|C_{\text{active},D}(n)| \leq |C_D|$ . Then  $m = O(|C_D|^{1-\varepsilon/e_{\text{hard}}})$ , constant in  $n$  once the  
599 patch ceiling is reached.

600 The qualitative conclusion is robust **under the  $k(n) = \Theta(\log n)$  regime:**  $m$  grows more slowly than  
601 any positive power of  $n$  under every candidate, and the directional claim (“a small library covers the  
602 head of the failure distribution in the per-hard-token regime”) survives. Only the exponent shifts:  
603 doubly-logarithmic under logarithmic discovery,  $(\log n)^b$  with small  $b$  under Heaps, constant in the  
604 cap regime. The doubly-logarithmic rate is the optimistic special case. If  $k(n)$  grows as a positive  
605 power of  $n$ , the Heaps variant inherits that power and the polylog-in- $n$  language fails along that  
606 axis—the framework’s intervention prescription still applies, but its asymptotic-rate framing does not.  
607 Numerical constants require a measured discovery curve  $C_{\text{seen},D}(T)$  or  $C_{\text{active},D}(n)$ . Existing tax-  
608 onomies provide endpoint category counts at a single corpus scale (ErrorAtlas at  $|C| = 17$  for  
609  $\approx 10^4$  failures), not discovery curves. The subsample-discovery measurement remains the explicit  
610 empirical test that would either tighten the postulate or fall back to the Heaps variant. Until that  
611 measurement exists, the framework’s headline rate should be read as *polylogarithmic in the pre-cap*  
612 *regime, domain-constant in the cap regime*—with the specific exponent flagged as a falsifiability test  
613 rather than a fitted prediction.

## 614 B Full Failure-Mode Taxonomy and the Capability-Elimination Harvest

615 The intervention literature provides at least one targeted countermeasure for each named cluster of §4.  
616 Two organising granularities exist: at the capability level (six axes) the cluster-orthogonality property  
617 is most clearly visible; at the error-class level (twelve named clusters) the evidence aligns with the  
618 taxonomies of §4 but is finer-grained than the underlying capability mechanisms.

619 **Six capability axes and three structural patterns.** A dedicated harvest yields **28 quantitatively-**  
620 **anchored citations** across **six independent capability axes:** Arithmetic (Python/symbolic execution),  
621 Code Execution (REPL/sandbox feedback), Format/Structure (constrained decoding, FSMs, grammar  
622 engines), Perception/Grounding (visual grounding for GUI, charts, tables), Knowledge/RAG (dense  
623 retrieval and citation grounding), Verification (proof checkers, learned verifiers, classifier rerouting,  
624 process supervision). Each axis is independently confirmed by between three and nine citations. We  
625 stratify the 28 by kind of evidence into three patterns:

626 **Pattern A — Hard guarantees (by-construction).** Seven citations achieve residual error rate  
627 equal to zero *by construction*, restricted strictly to structural/verifiable classes: constrained decoders  
628 set  $P(\text{invalid token}) = 0$  at every step [Suresh et al., 2025, Zhang et al., 2023, Dong et al., 2025,  
629 Li et al., 2026, OpenAI, 2024]; static syntax checks reject programs with a `SyntaxError` before  
630 execution [Wen et al., 2024]; proof kernels reject any output failing type-checking [Ren et al., 2025].  
631 The class of grammar-violating outputs is mathematically empty under these mechanisms.

632 **Pattern B — Strong empirical reductions with class-shift signature.** Roughly fourteen citations  
633 report empirical reductions of 80–100% in a named error class, with the post-intervention failure  
634 log dominated by structurally different residual classes. Program-of-Thoughts on GSM8K [Chen  
635 et al., 2023]: calculation errors drop from 30% of failures to 0%, residuals are 62% reasoning  
636 + 36% misunderstanding. OpenMedCalc [Goodell et al., 2025]: “only interpretation errors were  
637 identified.” Acurai [Wood and Forbes, 2024]: 100% hallucination elimination on RAGTruth (95% CI  
638 91–100%)—strong empirical, not by-construction.

639 **Pattern C — Moderate reductions (60–80%) with residuals shifting outside the target class.**  
640 Legal RAG [Dantart, 2026]: fabricated citations  $> 30\% \rightarrow < 0.2\%$ . GPT-5 SimpleQA with web  
641 access [OpenAI, 2025]: 47%  $\rightarrow$  9.6% (inter-condition, not within-condition). CRITIC [Gou et al.,  
642 2024a]: toxic generation  $-79.2\%$ .

643 **The 28 citations, organised by axis and pattern.**

| Axis          | Citation & targeted class                                | Pre → Post                    | Pattern |
|---------------|----------------------------------------------------------|-------------------------------|---------|
| Verification  | Ren et al. [2025] — Invalid Lean proof                   | any → 0% by constr.           | A       |
| Format        | OpenAI [2024] — JSON schema violation                    | >60% → 0% by constr.          | A       |
| Format        | Zhang et al. [2023] — Tool-call syntax                   | 21–100% → 0%                  | A       |
| Format        | Suresh et al. [2025] — JSON parse failure                | 13–82% → 0%                   | A       |
| Format        | Dong et al. [2025] — Multi-format errors                 | 20–38% → 0%                   | A       |
| Format        | Li et al. [2026] — Malformed tool calls                  | 33–78% → 0%                   | A       |
| Arithmetic    | Chen et al. [2023] — Calculation on GSM8K                | 30% → 0% of failures          | B       |
| Arithmetic    | Goodell et al. [2025] — Clinical arithmetic              | “only interpretation errors”  | B       |
| Knowledge/RAG | Wada et al. [2025] — RAG hallucinations                  | 8% → 0% ( $p = 0.012$ )       | B       |
| Knowledge/RAG | Wood and Forbes [2024] — Context-conflict hallucinations | 100% → 0% on subset           | B       |
| Knowledge/RAG | Dantart [2026] — Fabricated legal citations              | >30% → <0.2%                  | C       |
| Code Exec     | Wen et al. [2024] — <code>SyntaxError</code> (HumanEval) | 5.76% → 0.01%                 | A       |
| Code Exec     | Li et al. [2022] — False-positive submissions            | 62% → 4%                      | B       |
| Code Exec     | Shi et al. [2024] — 5 code-bug classes                   | 100% repair (5/6 classes)     | B       |
| Knowledge/RAG | Gao et al. [2023b] — Citation grounding (ELI5)           | ≈50% w/o complete support     | C       |
| Knowledge/RAG | OpenAI [2025] — Factual errors                           | 47% → 9.6% w/web              | C       |
| Knowledge/RAG | Zakka et al. [2024] — Clinical citation errors           | 44% → 9%                      | C       |
| Arithmetic    | Wang et al. [2025a] — Arithmetic in medical reasoning    | 426 → 74 errors               | B       |
| Code Exec     | Wen et al. [2024] — <code>NameError</code> repair        | 22.7% → 2.3%                  | C       |
| Perception    | Gou et al. [2025] — GUI grounding errors                 | 16.2% → 73.3% acc.            | B       |
| Perception    | Xie et al. [2025] — GUI task failures                    | 5% → 27% SR ( $5.4\times$ )   | B       |
| Perception    | Cheng et al. [2024] — Element mislocation                | 5.2% → 53.4% ( $10.3\times$ ) | B       |
| Perception    | Liu et al. [2023] — Chart-reading errors                 | 38.2% → 67.6% (+29.4 pp)      | B       |
| Verification  | Gou et al. [2024a] — Toxic generation                    | −79.2%                        | C       |
| Verification  | Wang et al. [2024b] — Reasoning step errors              | 28.6% → 43.5% w/rerank        | B       |
| Knowledge/RAG | Asai et al. [2024] — Unsupported facts                   | 55.5% → 22% error             | B       |
| Perception    | Lu et al. [2024] — Icon/element errors                   | 70.5% → 93.8% (79% red.)      | B       |
| Knowledge/RAG | Mallen et al. [2023] — Long-tail entity errors           | ≈80% → ≈50% failure           | B       |

645 **Capabilities are coarser than error classes.** Several entries in the harvest reveal “two-for-one” re-  
 646 ductions where one capability addresses multiple named clusters: a single Python interpreter removes  
 647 the execution-error component of arithmetic, unit conversion, simple counting, list manipulation,  
 648 and date arithmetic; constrained decoding eliminates by construction both format violations and  
 649 the structural component of “missing required element”; code execution feedback strongly reduces  
 650 `SyntaxError`, `NameError`, and most `TypeError` together; RAG strongly reduces factual hallucina-

tions, fabricated citations, and outdated information jointly. The practical capability library required is therefore smaller than the count of named error categories.

### The twelve named clusters.

| Cluster               | Axis          | Intervention                                                  | Before → After           | Patt. |
|-----------------------|---------------|---------------------------------------------------------------|--------------------------|-------|
| A. Arithmetic         | Arithmetic    | PAL Python [Gao et al., 2023a]                                | 20.1% → 61.5%            | B     |
| B. Unit conversion    | Arithmetic    | Folded into A (Python)                                        | —                        | —     |
| C. Counting           | Arithmetic    | Explicit counter (gap)                                        | —                        | gap   |
| D. Format/schema      | Format        | DINGO/SLOT [Suresh et al., 2025, Wang et al., 2025b]          | up to +68 pp; 99.5% acc. | A     |
| E. Code logic/type    | Code Exec     | Reflexion/AgentCoder [Shinn et al., 2023, Huang et al., 2023] | 80% → 96.3% pass@1       | A/B   |
| F. Multi-hop drift    | Knowledge     | Entity-grounded rewriter                                      | ≈5–10 pp                 | C     |
| G. Reasoning step     | Verification  | Math-Shepherd [Wang et al., 2024b]                            | 28.6% → 43.5%            | B     |
| H. Spec misinterpret. | Verification  | Clarification [Niwa and Iso, 2024]                            | ROUGE-L +15              | C     |
| I.a Struct. missing   | Format        | Subsumed by D (constr. decode)                                | —                        | A     |
| I.b Semantic missing  | Verification  | Subsumed by G/H                                               | —                        | C     |
| J. Hallucination      | Knowledge     | RAG [Wood and Forbes, 2024]                                   | non-zero → 0%            | B/C   |
| K. Refusal            | Verification  | POROver [Karaman et al., 2024]                                | 57.6% → 82.1%            | B     |
| L. Tool/API           | Format+Verif. | SAGE-Agent [Suri et al., 2025]                                | 36.5% → 65.2%            | B     |

Eight of twelve categories have a strong citation with double-digit percentage-point improvement; three (B, C, I) lack a clean single-cluster ablation; one (F) has consistent medium-strength evidence. Category I (missing required elements) splits mechanistically into I.a (structural, absorbed by D’s constrained decoders) and I.b (semantic, absorbed by G/H). Categories B (units) and C (counting) remain technical gaps: B is naturally folded into A; C is the smallest residual gap.

**Additivity and its limits.** Patel et al. [2026] demonstrate that stacking interventions targeting orthogonal failure modes can produce large compound reliability gains: their parallel-consensus framework yields a  $14,700\times$  improvement over single-pass baseline—evidence for compound gains from decomposition plus consensus aggregation under their specific parallel-voting regime, not direct demonstration that heterogeneous cluster-targeted interventions compose additively without voting. Shang et al. [2024] similarly show supra-additive gains when modules target distinct failure modes. Le [2026] reports that schema-level and prompt-level instructions interact *non-additively* when sharing a prompt channel: interventions on orthogonal processing layers (decoding constraint vs. retrieval vs. training-signal vs. inference-time tool call) compose near-additively, while those sharing a channel may interfere.

**The irreducible-semantic residual.** Of the 17 ErrorAtlas categories, 13 are addressed under Patterns A, B, or C by one of the six capability axes; four are not—residuals of inappropriate refusal beyond preference optimisation, specification misinterpretation not closed by clarification, problem-decomposition reasoning bottlenecks, and a “user wanted something different” semantic remainder. These are classes where the failure is in choosing what to do, not executing it. Proposition 1’s prediction of  $O(\log)$  rather than  $O(0)$  residual reliability reflects exactly this irreducible core. The framework does not claim 100% coverage of all failures; it claims polylog-bounded *capability-eliminable* failures, with the named semantic residual as the floor.

## C Counter-Evidence Re-Audits

Five prominent papers are routinely cited as evidence that LLM reliability decays steeply with length [Dziri et al., 2023, Kuratov et al., 2024, Kwa et al., 2025, Wan et al., 2026, Karpinska et al., 2024]. A careful re-reading shows that *every one* of these papers decays over a variable distinct from raw token length  $n$ . Identifying the decay axis is not the same as dissolving the practical concern: where compositional graph size, fact count, or evidence scope grow with problem length,



the framework predicts steep failure curves. The contribution is to identify which interventions help (capability provisioning along the actual decay axis) and which do not.

**Dziri et al. [2023], Faith and Fate.** GPT-4 multi-digit multiplication accuracy drops from 59% (3-digit) to 4% (4-digit) zero-shot, with the authors theorising “probability of incorrect predictions converges exponentially to  $\approx 1$  for abstract compositional tasks.” The decay variable is *compositional graph size*  $N$ , not raw token length: the  $3 \times 3$  graph has on the order of  $d^2$  partial products plus carries, and multi-digit multiplication is engineered so that  $k_{\text{hard}} \approx N$ —every node in the computation graph is a hard decision. For natural-language tasks where  $k_{\text{hard}} \ll n$ , Dziri’s regime is the *boundary case* in which our framework reduces to their result. A clean  $(1 - \varepsilon)^N$  exponential cannot simultaneously reproduce 59% at 3-digit and 4% at 4-digit for any single per-node  $\varepsilon$ —the observed drop is locally steeper than per-node iid exponential, consistent with a finite catalogue of failure modes exhausting as  $N$  grows. *Where the framework concedes:* in adversarial compositional tasks engineered so  $k_{\text{hard}} \approx N$ , the framework reduces to Dziri’s regime and does not relieve it; the relocation is informational, not magical.

**Kuratov et al. [2024].** The abstract reports “performance declines sharply with increased reasoning complexity” and models “effectively utilise only 10–20% of the context.” Read in detail, BABILong varies two axes: context length  $n$  (0K to 10M tokens) and number of supporting facts  $k$  (QA1 = 1 fact to QA3 = 3 facts). The sharp decline is in  $k$ , not  $n$ . For QA1 (single-fact), most models “perform well up to 4,000 tokens”—a plateau, not exponential decay. The famous RAG-flat-across-length result (60% on single-fact QA *independent of context length*) is the cleanest possible demonstration that when relevant evidence is in window, length does not matter. Recurrent Memory Transformers maintaining performance to 50M tokens further confirms effective  $k$  is determined by architecture, not raw  $n$ . The framework’s concession is narrow but real: for multi-hop tasks whose required fact count grows with task complexity, BABILong’s sharp  $k$ -axis decay is exactly what the framework predicts happens, not a counter-example.

**Kwa et al. [2025] (METR).** Per-model success fits a logistic in  $\log(\text{human-task-duration})$ :  $S(t) = \sigma(\beta(\log t - \log h))$ . Logistic-in-log-length is *mathematically sublinear* in length itself. The 80%-horizon being 4–6 $\times$  shorter than the 50%-horizon is a steep within-model cliff but compatible by construction with the polylog result—a cliff at a specific capacity threshold is a manifold-transition signature. The famous exponential—capability doubling every seven months—is an *inter-model* claim about how the horizon  $h$  moves across generations, orthogonal to within-model decay shape. An honest qualifier: the within-model logistic-in-log cliff is steep on a practical scale. Calling it “sublinear in length” is technically correct but engineering-useful only for systems designed to operate well below the 50% horizon.

**Wan et al. [2026], Fano-style upper bound.** This paper theorises super-linear information-demand growth and identifies an “accuracy cliff” at capacity overflow: “when the task’s information demand surpasses the model’s output capacity, performance does not degrade gracefully but instead collapses sharply.” The behavioural prediction is a *threshold*, not smooth  $(1 - \varepsilon)^n$ . A cliff at a specific capacity threshold is exactly the manifold-transition behaviour our framework predicts at the boundary between covered and uncovered modes; Wan et al.’s mechanism (capacity overflow) is one specific cause, complementary to ours. *Where the framework concedes:* Wan documents a mechanism by which  $|C|$  effectively exceeds the model’s coverage in a single forward pass; Pattern A interventions (constrained decoding, formal verification) are the kind of response the framework expects but does not automatically supply.

**Karpinska et al. [2024].** GPT-4o achieves 55.8% pair accuracy across 1,001 minimally-different true/false claim pairs about long fictional books (mean length 127K tokens). The paper reports performance by *evidence scope*, not by context length: 59.8% on sentence-level retrieval, 47.6% on passage-level, 41.6% on global reasoning. No per-context-length curve is reported. The decay axis is the number of evidence pieces that must be integrated—a  $k$ -axis quantity, not an  $n$ -axis one. NoCha is therefore not counter-evidence to a sublinear-in- $n$  claim. Evidence-scope decay is exactly the  $k$ -axis observation the framework predicts cannot be addressed by scaling raw context length—it requires retrieval or process supervision along the actual decay axis. The relocation is informational, not magical.

738 **Unifying observation.** Every counter-paper decays over a variable that is not  $n$ : compositional  
739 graph size, fact count, log-time horizon, capacity threshold, or evidence scope. The apparent rapid  
740 decay is, in each case, in a quantity our framework already concentrates the action in ( $k_{\text{hard}}$  and  $|C|$ ),  
741 not in raw sequence length. This is a relocation, not a dissolution. Where  $k_{\text{hard}}$  grows with task  
742 length—adversarial compositional structure, multi-hop fact chains, long horizons that force more  
743 decisions—reliability remains hard; the framework’s value is directing intervention toward capability  
744 provisioning along the actual decay axis rather than toward context-window or compute-budget  
745 expansion that does not help.

## NeurIPS Paper Checklist

### 1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [Yes]

Justification: The abstract and §1 state five contributions: (i) the three-layer framework partitioning key tokens into easy/hard subsets with a bounded mode catalogue (§3); (ii) the empirical postulate of logarithmic mode discovery anchored against three taxonomies with  $\sigma \in [0.87, 1.85]$  (§3.2); (iii) Proposition 1 on the polylog intervention budget, with explicit per-hard-token vs. sequence-level distinction; (iv) evidence synthesis for clustering, cluster-selective interventions, and sublinear length scaling (§4); (v) the counter-evidence re-audit (Appendix C). Each claim is developed in the cited section. The paper makes no original empirical claims and is scoped as a framework-plus-synthesis contribution; limitations are explicit (§6).

Guidelines:

- The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

### 2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: §6 enumerates eight specific limitations: (i) Postulate 1 is empirical, not derived—a genuinely Heaps-power-law domain would invalidate the doubly-logarithmic special case (while preserving the qualitative polylog conclusion of Appendix A); (ii) the coverage form is an empirical best-fit, not theoretically derived; (iii) cluster-orthogonality is approximate, with Le [2026]’s prompt-channel-interference caveat noted; (iv) domain narrowness—the empirical anchor rests on three taxonomies covering general/code/math, with agentic and scientific regimes untested; (v) the  $\sigma \approx 1.85$  estimate is single-point calibration, not a discovery-curve fit; (vi)  $\beta$  is latent and we report no empirical range; (vii) the L2–L3 taxonomy-granularity gap is unmeasured; (viii) patch-shift between deployments changes  $A_D, \sigma_D, \beta_D, |C_D|$  simultaneously. The closing “goalpost-relocation caveat” makes explicit that the framework *relocates* the difficulty rather than resolving it: where  $k_{\text{hard}}$  grows with task length, reliability remains hard, and the framework’s value is in naming the on-axis intervention.

Guidelines:

- The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.

- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

### 3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [N/A]

Justification: The paper develops a descriptive/conditional framework rather than formal theorems. Proposition 1 is engineering math whose conditional nature is stated explicitly in the surrounding “Conditionality” paragraph and in its statement: it holds conditional on (i) the log-coverage form of §3.3 on its declared domain  $m \geq 2$ ,  $|C_{\text{eff}}| \geq 2$ ; (ii) the residual target  $\varepsilon \in (0, e_{\text{hard}})$ ; (iii) Assumption 2 (per-sequence active-mode exposure) for any sequence-length rate claim. The two-line proof immediately following the proposition statement traces all algebraic steps. Postulate 1 is explicitly labelled an empirical postulate, not a theorem (this is the load-bearing math-claims discipline of the paper). We label the budget statement a “Proposition” rather than a “Theorem” to keep its conditional nature visible.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

### 4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: The paper is a framework-plus-synthesis contribution, not an empirical paper; it runs no new experiments and trains no new models. Every numerical value cited (§4, Appendix B) is pinned to a specific published source with the relevant benchmark, model, and result identified. The  $\sigma$  calibration in §3.2 cites ErrorAtlas, HumanEval, and MWPEs with the endpoint corpus sizes and category counts used. The 28 capability-elimination citations in Appendix B report pre/post percentages from the original sources. A reader following each citation can verify or reproduce the underlying empirical result by consulting the cited work.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
  - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
  - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
  - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

## 5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [N/A]

Justification: The paper releases no new datasets, models, or code. It is a framework-and-synthesis paper; all underlying empirical results are owned by their respective authors and accessed through the cited references.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.

- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

## 6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: §4 specifies which benchmarks supply evidence for each load-bearing claim: ErrorAtlas (83 models  $\times$  35 datasets) and MWPEs (304,865 errors, 15 models) for clustering; the 28 capability-elimination interventions (Appendix B) for cluster-selectivity, with per-row pre/post percentages and the model/benchmark named; Loong, GSM- $\infty$ , RULER, Anchor LLMs, and Press et al. for sublinear length scaling, each with the specific length range, model, and metric identified. The  $\sigma$  calibration in §3.2 cites three taxonomies with  $k_{\text{hard}}$  and  $|C|$  endpoint values used in the formula. No original training or hyperparameter selection is performed by this paper.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

## 7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [N/A]

Justification: The paper reports no original experimental results, hence no error bars. Where numerical results are cited from the literature (e.g., the +41.4-pp PAL gain, the 100% Acurai elimination on RAGTruth with 95% CI 91–100%, the 32.9% Loong endpoint), the originating work is cited with its reported significance treatment.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

## 8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [N/A]

Justification: The paper performs no original computational experiments. Compute requirements of the cited systems are documented in those works.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

## 9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: We have reviewed the NeurIPS Code of Ethics. The work is theoretical/synthesis with no human subjects, no scraped or sensitive data, no model training, and no deployed system. There are no fairness, privacy, or security risks specific to the paper.

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

## 10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: §5 discusses positive implications: targeted intervention-library design, SLA alignment between per-hard-token and sequence-level reliability targets, and parallelisable library construction. The negative-impact direction is structurally limited because the paper releases no model or dataset; the closing “goalpost-relocation caveat” (§6) explicitly warns that the framework *relocates* the difficulty of long-context reliability and should not be misread as a license to deploy LLMs in higher-stakes settings than the cited evidence justifies.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate

1011 to point out that an improvement in the quality of generative models could be used to  
 1012 generate Deepfakes for disinformation. On the other hand, it is not needed to point out  
 1013 that a generic algorithm for optimizing neural networks could enable people to train  
 1014 models that generate Deepfakes faster.

- 1015 • The authors should consider possible harms that could arise when the technology is  
 1016 being used as intended and functioning correctly, harms that could arise when the  
 1017 technology is being used as intended but gives incorrect results, and harms following  
 1018 from (intentional or unintentional) misuse of the technology.
- 1019 • If there are negative societal impacts, the authors could also discuss possible mitigation  
 1020 strategies (e.g., gated release of models, providing defenses in addition to attacks,  
 1021 mechanisms for monitoring misuse, mechanisms to monitor how a system learns from  
 1022 feedback over time, improving the efficiency and accessibility of ML).

## 1023 11. Safeguards

1024 Question: Does the paper describe safeguards that have been put in place for responsible  
 1025 release of data or models that have a high risk for misuse (e.g., pre-trained language models,  
 1026 image generators, or scraped datasets)?

1027 Answer: [N/A]

1028 Justification: No new pretrained models, generative artifacts, or scraped datasets are released.  
 1029 The contribution is a theoretical framework and a synthesis of cited work.

1030 Guidelines:

- 1031 • The answer [N/A] means that the paper poses no such risks.
- 1032 • Released models that have a high risk for misuse or dual-use should be released with  
 1033 necessary safeguards to allow for controlled use of the model, for example by requiring  
 1034 that users adhere to usage guidelines or restrictions to access the model or implementing  
 1035 safety filters.
- 1036 • Datasets that have been scraped from the Internet could pose safety risks. The authors  
 1037 should describe how they avoided releasing unsafe images.
- 1038 • We recognize that providing effective safeguards is challenging, and many papers do  
 1039 not require this, but we encourage authors to take this into account and make a best  
 1040 faith effort.

## 1041 12. Licenses for existing assets

1042 Question: Are the creators or original owners of assets (e.g., code, data, models), used in  
 1043 the paper, properly credited and are the license and terms of use explicitly mentioned and  
 1044 properly respected?

1045 Answer: [N/A]

1046 Justification: The paper uses no datasets, code, or models—it cites published work but  
 1047 does not redistribute any artifact requiring license disclosure. Citations follow NeurIPS  
 1048 conventions.

1049 Guidelines:

- 1050 • The answer [N/A] means that the paper does not use existing assets.
- 1051 • The authors should cite the original paper that produced the code package or dataset.
- 1052 • The authors should state which version of the asset is used and, if possible, include a  
 1053 URL.
- 1054 • The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- 1055 • For scraped data from a particular source (e.g., website), the copyright and terms of  
 1056 service of that source should be provided.
- 1057 • If assets are released, the license, copyright information, and terms of use in the  
 1058 package should be provided. For popular datasets, [paperswithcode.com/datasets](https://paperswithcode.com/datasets)  
 1059 has curated licenses for some datasets. Their licensing guide can help determine the  
 1060 license of a dataset.
- 1061 • For existing datasets that are re-packaged, both the original license and the license of  
 1062 the derived asset (if it has changed) should be provided.



- If this information is not available online, the authors are encouraged to reach out to the asset’s creators.

### 13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [N/A]

Justification: No new assets are released by this paper.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

### 14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: The paper does not involve crowdsourcing or research with human subjects.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

### 15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [N/A]

Justification: No human subjects research is conducted, so no IRB approval is required.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

### 16. Declaration of LLM usage

1114 Question: Does the paper describe the usage of LLMs if it is an important, original, or  
1115 non-standard component of the core methods in this research? Note that if the LLM is used  
1116 only for writing, editing, or formatting purposes and does *not* impact the core methodology,  
1117 scientific rigor, or originality of the research, declaration is not required.

1118 Answer: [N/A]

1119 Justification: LLMs were used only for writing assistance (drafting, polishing, copy-editing)  
1120 and not as part of the research methodology. The framework, the synthesis, and the choice  
1121 of cited evidence are the authors'; LLMs were not involved in selecting evidence, deriving  
1122 the framework, or shaping the argument. Per the question's stated guidance, no declaration  
1123 is required for editing-only usage; we answer [N/A] accordingly.

1124 Guidelines:

- 1125 • The answer [N/A] means that the core method development in this research does not  
1126 involve LLMs as any important, original, or non-standard components.
- 1127 • Please refer to our LLM policy in the NeurIPS handbook for what should or should not  
1128 be described.