IEEE Access
Multidisciplinary | Rapid Review | Open Access Journal

Date of publication xxxx 00, 0000, date of current version xxxx 00, 0000.

Digital Object Identifier 10.1109/ACCESS.2026.0000000

Frontier and Localhost: A Survey of How Production AI Learns Outside the Weights

MIKHAIL L. ARBUZOV[1], LEE MOSBACKER[2], SISONG BEI[3], ZIWEI DONG[4], DMITRI KALAEV[5], AND ALEXEY SHVETS[6]

[1]Independent Researcher, CITY, COUNTRY (e-mail: mike.arbuzov54@gmail.com)
[2]Independent Researcher, CITY, COUNTRY (e-mail: lee.mosbacker@gmail.com)
[3]Independent Researcher, CITY, COUNTRY (e-mail: qurining@gmail.com)
[4]Independent Researcher, CITY, COUNTRY (e-mail: ziwei.dong@alumni.emory.edu)
[5]Independent Researcher, CITY, COUNTRY (e-mail: kalaevdr@gmail.com)
[6]Palo Alto Networks, CITY, COUNTRY (e-mail: ashvets@paloaltonetworks.com)

Corresponding author: Mikhail L. Arbuzov (e-mail: mike.arbuzov54@gmail.com).

TODO(authors): funding statement, e.g., "This work received no external funding." A. Shvets is employed by Palo Alto Networks; the views expressed are the authors' own.

ABSTRACT Every serious AI deployment now improves itself outside the model weights. After a failure, a team edits instructions, skills, memories, tools, orchestration, or evaluation suites, and the system changes within the hour; the weights change on a cycle of months. This survey of 256 production and research systems asks what discipline that layer needs and finds the industry has built most of its optimizer and never assembled it. The optimizer is one loop with two halves: trace a recurring failure to the artifact responsible, make one edit, keep it only if the deployment's failure rate falls, then decide how far it may travel, to a team, an organization, or every customer. Its first half is routine. The second exists in parts that no surveyed system assembles into promotion across organizations with lineage, access control, and rollback, so every customer relearns the same fixes and nobody can say which rule helped. The reason is structural. What a deployment can automate is fixed by the feedback that decides whether an edit is kept: an exact check, an observed outcome, a judgment, or a reward months late. An accepted edit improves only what that feedback measured, so no lift travels on its own. The survey turns that finding into tools: five conditions that separate an optimizer from a pile, four feedback classes that say which half of the loop a deployment can automate, and, for the half still unassembled, four properties to audit against and the piece each class should build first.

INDEX TERMS AI governance, agent memory, agent skills, evaluation, large language models, LLM agents, prompt optimization, self-improving systems, survey

I. INTRODUCTION

The standard mental model of a system built on a large language model (LLM) is the model. Pre-training fixes the weights, fine-tuning nudges them, and deployment wraps a thin layer of prompts and tools around the result. Production in 2025 and 2026 has stopped behaving this way. Frontier weights change on a cycle of months; the systems built on them change daily, in instruction files checked into repositories, memories that persist across sessions, skills loaded on demand, registered tools, evaluation suites that block a merge, agent topologies, and pull-request gates on shared rule repositories. We call that fast-changing layer around a slow-changing model the scaffold, and a growing share of the adaptation that makes a deployed system reliable now happens there, outside the weights.

Read one at a time, these artifacts look like unrelated engineering. A skill file is a procedure the model did not have; a repository rule is a convention for one project; a retrieval connector is memory access for one workflow; a tool registry provisions a capability the base model cannot reach; a pull-request review against a shared rule repository is a promotion gate. Read together, they are one adaptation surface, the non-model part of what Zaharia et al. call a compound AI system [1], and most deployments maintain it as patchwork. A failure happens, someone adds a rule, the pile grows, nobody knows which addition helped, a fix validated in one place leaks into another that never tested it, and every customer relearns the same lesson. This survey asks what optimization discipline that surface needs. Its answer is that the industry has built most of the optimizer, piece by piece, and has never assembled it.

The optimizer is one loop with two halves. A coding agent

keeps misnaming a class in one repository; the first half traces that recurring failure to the rule file responsible, proposes one edit, and keeps it only if the repository's own failure rate falls. The second half decides how far the edit may travel, to a team template, to the company's core instructions, or to a registry shared across companies, and lets it travel only as far as evidence supports. Five conditions make the loop an optimizer rather than good intentions. The decisive one, a measurable loss, carries two consequences the paper returns to throughout: an accepted edit improves only what its gate measured, and the loop descends to that measure's ceiling rather than evolving toward some better goal.

Set side by side, the 256 systems in this survey tell one story about that loop. Its first half is routine: in most research systems and a growing number of production ones it closes under an automatic gate. The second half exists in parts. The newer systems wait for several pieces of evidence before keeping an edit, remove stale skills through the same check that admitted them, keep a history of every change to memory, have settled on one artifact format and one tool protocol, and in a few cases carry edits between deployments of one operator. None of the 256 assembles those parts into promotion across organizations under versioned lineage, access control, and rollback. The reason is structural rather than a matter of effort. What a deployment can automate is fixed by the feedback its gate receives: a test or an observed outcome can gate an edit by program, a judgment only once the judge is calibrated against people, and a reward that arrives months later cannot gate edits one at a time. Because the lift an edit earns is bounded by what its gate measured, that lift reaches another deployment only if the receiver measures the same thing or measures again.

What follows turns that finding into things a reader can use. Section III states the loop in plain language and as an update rule, with the five conditions against which a team can check whether its own maintenance is an optimizer or a pile. The rule that decides, from the feedback a deployment can get, which half of the loop it may automate today and which failure it should expect is the subject of Section IV. The rest of the survey tests that rule against the corpus: Sections V to VIII find the field converged on the first half and sorted on the second exactly as the rule predicts, with five research lines arriving at the same loop from five different starting problems. For the half nobody has built, Sections IX to XI give the four properties any future system must show, the failures the literature has already measured in their absence, and, for each feedback class, the piece to build next. The survey runs no experiments; its evidence is the published behavior of 256 systems, scored on a released table.

II. WHY ADAPTATION LIVES OUTSIDE THE WEIGHTS

A. BREADTH IN THE WEIGHTS, DEPTH IN THE SCAFFOLD

Frontier training optimizes for breadth. The weights are tuned to generalize across millions of unseen deployments, and the objective smooths over exactly what one deployment cares about: local naming conventions, contradictory preferences between customers, rare workflow-specific failures. Reinforcement learning from human feedback reduces output diversity and homogenizes preferred style across users [2], [3], and instruction-tuning data rewards patterns that generalize across the annotator pool, so the frontier model is trained to disfavor one customer's idiosyncrasies. Tiwari et al. [4] reach the same place from the optimization side: in-context adaptation is cheap but capacity-bounded, in-weights adaptation is expressive but induces forgetting and loss of plasticity [5], so a system that learns slowly in the weights needs a cheap outer layer that learns fast outside them.

Production reliability is won in depth, inside one deployment, and it turns on what global training had to smooth away. Encoding every deployment in the weights is ruled out three times over: fine-tuning per customer multiplies the training, evaluation, and serving lifecycle by the number of deployments; weights ship quarterly at best, while the deployment wants daily updates; and overfitting the weights to one customer degrades the neighbors whose preferences contradict. In principle, per-customer adapters [6], distilled models, and learned routing could absorb some of the residual, the failures that remain after training. In practice they are rare. Adaptation lands in the scaffold, the one substrate that is cheap, inspectable, reversible, scoped to one customer, and updatable daily.

B. WHY THE SCAFFOLD IS THE RIGHT ARCHITECTURE: THE TWO EARLIER RESULTS

The case for learning outside the weights does not rest on cost alone. The two papers that precede this one in the series supply the hypothesis that explains the pattern the corpus shows, and each states the scope on which it rests. *Beyond Exponential Decay* [7] argues that long outputs do not fail at the rate a uniform per-token error model predicts, because reliability hinges on a sparse set of key decisions. Its evidence is twofold: a direct measurement of long-range dependence on one natural-text corpus, where under a tenth of tokens depend on distant context, and the accuracy that majority voting recovers on reasoning benchmarks. The argument stops where the number of decisions grows with the task, as in long-horizon agentic work. For a deployment that operates inside a bounded slice of recurring tasks, tools, and evaluator expectations, *The Architecture of Errors* [8] argues that those decisions fail in a small recurring catalogue of modes whose size grows only slowly with the number of observed failures. A targeted intervention budget that grows polylogarithmically in sequence length, and becomes constant once the catalogue saturates, then covers the residual. The paper's own negative result marks the limit: no finite catalogue covers an unbounded domain.

If those results hold in general, a deployment's errors are few enough to fix one at a time, and a small catalogue of fixable modes is exactly what a cheap, inspectable, reversible artifact layer is for. This article asks where the fixes live, and the corpus answers: in persistent artifacts outside the weights, one recurring mode at a time, which is the pattern the

hypothesis predicts. On that hypothesis the gated and scoped layer is not a workaround for an inadequate model. It is the architecture the error structure calls for: a frontier model that generalizes, a local scaffold that specializes, and reliability that comes from governing the specialization. The survey's own findings, in Sections VI to IX, stand without it.

C. RELATION TO EXISTING SURVEYS

The neighboring surveys explain how agents evolve, what their memories store, how context is engineered, how skills are evaluated, and how harnesses are built. None asks the question this one is organized around: who decides that an edit is good, and how far may the edit travel. That question has four parts: whether a feedback loop closes at all, whether its gate is a program or a person, what the gate can observe, and whether promotion beyond one deployment is governed. Table 1 says, for each neighbor, what it classifies by and where this survey departs from it. Two neighbors come close on the governance part. Ding et al.'s survey of persistent-state agents finds the literature concentrated on accumulating and retrieving state rather than on governing, recovering, or relinquishing it [9], and the memory-security survey of Lin et al. scopes and rolls back memory for safety [10]; neither asks who gates an edit, and neither covers promotion across organizations.

A reader will also expect the prompt-optimization lineage: OPRO, EvoPrompt, Promptbreeder, DSPy, and TextGrad [18]–[22]. That lineage optimizes a prompt or program once against a development set and is not a deployed loop; agentic context engineering [23] does persist its artifact, an evolving playbook, but never promotes it. The closest precedents optimize the scaffold itself under a benchmark score: agent symbolic learning updates prompts, tools, and pipeline as symbolic parameters from textual feedback [24], STOP's scaffolding program improves its own improvement code [25], and a coding agent edits its own harness to raise its score [26]. What changes here is that the edited artifact persists in a deployment and must clear a second gate before it earns any scope beyond it (Supplementary Material S7).

III. THE LOOP: ARTIFACT-LAYER DESCENT

A. THE LOOP IN PLAIN LANGUAGE

We call the disciplined version of scaffold maintenance artifact-layer descent. It is one loop with two halves, run again and again over the life of a deployment: Loop 1 fixes a recurring failure inside one deployment, and Loop 2 decides how far the fix may travel. Fig. 1 draws the first half. The deployment runs and logs what goes wrong: failed outputs, user corrections, rejected answers, evaluation regressions, tool-call errors. The loop does not react to single failures. It clusters the log into recurring modes and takes up the ones that matter most, ranked by how often each recurs and how badly it fails. For such a mode it locates the scaffold coordinate responsible, which may be a stale memory entry, an under-specified instruction, a missing tool argument, a brittle retrieval rule, or a misrouted agent edge, and it proposes one candidate edit to that coordinate.

Then it measures. A deployment serves one **patch**: the slice of users, tasks, and conventions it handles. The failure rate on that patch's recurring tasks is the **patch loss**. A gate accepts the edit if the patch loss falls and rejects it otherwise. An accepted edit stays in the scaffold, versioned; one that a later check shows made things worse is rolled back. That is the whole of Loop 1, and it is what most research systems and a growing number of production systems now do.

Loop 2 is the step most systems skip. An engineer notices that a coding agent keeps misnaming a class in one repository. The fix is a one-line rule in that repository's instruction file. That same rule could be promoted to a team-wide template, to the company's core instructions, or to a skill registry shared across companies. The edit did not change; its scope did. And the gate that should let it through gets stricter at each step, because the loss it is tested against is now an average over more deployments, and a fix that helps one repository can hurt another.

The scopes nest (Fig. 2). USER is one person's account or fork; PROJECT is one repository, workflow, or product workspace; STACK is a curated bundle of projects under one team; a **tenant** is one organization or customer; CORE is the scope every tenant shares. Each level's loss is the average failure rate over the deployments it contains. Promotion that reaches CORE crosses tenants, which is what cross-tenant promotion means here. Loop 2 promotes an edit upward only as far as the evidence reaches; we call that limit the edit's **evidence radius**. The check that belongs at each rung is **receiving-side evaluation**: a check run where the edit arrives, not where it was made. In optimizer terms, Loop 1 sets the step (how much one accepted edit changes the local scaffold) and Loop 2 sets the target (which average failure rate the scaffold is tuned to reduce). Governance is therefore not administrative overhead. It is the regularization that keeps a small fix from being aimed at the wrong target.

B. WHEN THE LOOP IS AN OPTIMIZER

The loop is an optimization process, rather than a description of good practice, when five conditions hold:

1. a measurable patch loss, such as a failure rate, a correction rate, or an evaluation score;
2. captured residuals, so that failures are logged rather than lost;
3. credit assignment, so that a failure can be traced, at least sometimes, to the scaffold coordinate that caused it;
4. a synthesized candidate edit to that coordinate; and
5. a gate that checks whether the edit lowers the loss before the edit is kept or promoted.

The conditions presuppose frozen frontier weights, edits that persist as inspectable artifacts rather than transient prompts, and promotion that widens an artifact's scope under a gate rather than averaging comparable updates as weight-space federated learning does.

TABLE 1. Neighboring surveys and where this one departs from each. This survey classifies by loop closure, gate type, signal class, and governance, and is the only one to cover promotion across organizations.

Survey	Scope	How this survey differs
Gao et al. [11]	self-evolving agents	organizes by what, when, how, and where an agent evolves; the gate that accepts an edit, and the edit's scope, are mentioned but not classified
Fang et al. [12]	self-evolving agents	organizes by inputs, agent system, environment, and optimizer; loop closure appears in passing, gates and promotion do not
Zhou et al. [13]	self-evolving coding agents (108 methods)	organizes by evolution target, timing, and code signal; closest on reversibility, with no gate or promotion axis
Ding et al. [9]	persistent-state agents (435 works)	organizes by authority, scope, mutability, provenance, and recoverability of state; governance is an axis, the gate on an edit is not
Lin et al. [10]	memory security (~90 works)	organizes by lifecycle phase and security objective; principal scoping and rollback are axes, feedback and promotion are not
Guo et al. [14]	agent system and harness design	organizes by six runtime responsibilities; touches all four questions without classifying by any
Xia et al. [15]	skill-mediated agents (8 systems)	organizes by four responsibility layers and ten patterns; loop closure and governance appear as patterns, not as axes
Ding et al. [16]	skill evaluation and evolution	organizes by four evolution paradigms and six benchmark classes; evaluation is the subject, the gate it feeds is not
Mei et al. [17]	context engineering (1,411 papers)	organizes by components and system implementations; adaptation loops lie outside its scope




FIGURE 1. Loop 1, the local half of artifact-layer descent. A recurring failure is traced to one scaffold coordinate, one edit is proposed, and a gate keeps the edit only if the deployment's patch loss falls. An accepted edit then enters Loop 2 (Fig. 2).

Written out, the patch loss of deployment D is

$$L_D(\theta_s) = \mathbb{E}_{x\sim D}[\ell(\pi(\theta_M, \theta_s, x))]\,,$$

where θ_M are the frontier weights, fixed during deployment, θ_s is the scaffold, a structured object over the six substrate coordinates of Section V, and ℓ is an operational loss. A failure yields no analytic gradient. It yields a candidate edit z_t, proposed by reflecting over the accumulated failure history. The gate accepts the edit when its noisy estimate of the change in loss clears a margin,

$$G_t(z_t) = 1 \iff \widehat{\Delta}_{z_t} L_D(\theta_s^t) + \lambda\,\Omega(z_t) \le -\tau_t,$$

where $\Omega \ge 0$ penalizes the complexity of the edit and the breadth of its promotion, and $\tau_t \ge 0$ is the required margin. Production systems implement this inequality without ever writing it down: an evaluation blocks a merge on regression, a reviewer rejects a vague rule, a governance system holds an artifact back until evidence accumulates. Under a bounded-bias assumption on the gate, the update satisfies a one-step descent inequality. When that bias is summable over the run, the loss converges and improving edits stop clearing the gate; the scaffold is then gate-stable, which is a statement about the gate, not about optimality (Appendix XII). Where a condition fails, the picture is an analogy, and the survey marks which systems meet which conditions.

Each half of the loop has a gate, and we name three kinds by who decides. A gate is **Auto** when a program applies a check before the edit goes through: an evaluation score, a verifier, a reinforcement-learning threshold, or a language-model judge [27] with a quantified agreement rate. It is **Human** when




FIGURE 2. Loop 2, the promotion half. Scopes nest from USER to CORE, each rung's loss averages the deployments it contains, and an edit rises one rung at a time, only while a check at the receiving side shows the wider loss falling and only as far as its evidence radius. Promotion into CORE crosses tenants.

a person decides. It is **None** when nothing decides, either because that half of the loop is absent or because the step runs unchecked, as when a system pushes every edit to its neighbors without a test. Who writes the candidate is recorded separately and is not a gate: the author may be an agent reflecting over failures, an engineer at a desk, or a contributor registering an artifact. We write a system's two gates as a pair, Loop 1 first: [Auto × Human] means an algorithmic local gate and a human promotion gate. These pairs index the design space of Section VII.

Condition 1 says the loss must be measurable. It does not say what measures it, and that turns out to be the question that sorts the corpus.

C. FROM PATCHWORK TO DESCENT

Three stages of scaffold maintenance recur across the corpus, and the five conditions separate them. Take the coding agent above that keeps misnaming a class. At the first stage, patchwork, an engineer adds a rule to the instruction file after noticing the failure; nobody measures whether it helped, nothing is promoted on evidence, and the file sprawls with every incident until nobody knows which rule does what. At the second stage, random artifact search, the system tries many variants of the file under the test suite and keeps the best. The suite is the only signal and no failure is traced to the rule that caused it; the winning variant has learned the suite as much as the task. At the third stage, artifact-layer descent, the recurring failure is traced to the one rule responsible, one edit is proposed, the gate checks that the patch loss falls, and promotion stops at the evidence radius and can be reversed. A loop reaches the third stage once the five conditions hold, and its dominant failure becomes evaluation fragility, because the suite that gates the edits is itself a scaffold artifact that drifts and can be gamed (Section X). Production deployments that reach it on Loop 1 then promote in one of two ways: behind a human gate, as Spotify does [28], or, in Letta's Context Repositories alone, by an ungated push that carries lineage but no evaluation.

Two consequences of condition 1 follow the loop everywhere, and the survey keeps returning to them. The first is that the measure bounds the lift. An accepted edit is an improvement in what the gate measured, on the tasks the gate sampled, and nothing more; a rule that lowers the failure rate on one repository's suite has earned nothing about another repository's. Every loss has a scope. That is why Loop 2 cannot carry Loop 1's evidence: the receiving scope measures a different mix of tasks, so a promoted edit either travels under a measure the scopes share or re-establishes its lift where it arrives, which is what receiving-side evaluation is for. Where tenants measure different things, a lift does not transfer at all without it.

The second is that the loop optimizes and does not evolve. It needs a defined measure before it can start and descends toward that measure's ceiling; at the ceiling no edit clears the gate, which is what gate stability means. It does not discover a better goal than the one its measure encodes. Two scaffolds optimized for the same goal under the same measure need not converge to one version; each stops at the ceiling by its own route. A system that edits its own measure, the reflexive gate of Section IV, moves the destination rather than evolving toward an unknown truth. The distinction matters because the corpus is often described in the vocabulary of evolution; what the gated systems in it actually do is descent.

IV. WHERE THE SIGNAL COMES FROM: FOUR CLASSES OF FEEDBACK

Four scaffolds all run the loop of Section III. A coding agent changes one line in its repository rule file; the test suite runs and reports pass or fail within seconds. A scheduling assistant changes how it phrases a booking request; the appointment either appears on the calendar or it does not, and the system learns which an hour later. A marketing assistant changes the tone rule in its instructions; nobody can say whether the next draft is better, only whether a reviewer prefers it. A research assistant changes how it chooses which direction to pursue; whether the choice was good becomes visible months later, after many other edits have landed. All four produce a candidate edit. They differ in what the gate can know about it.

That difference is the whole of this section. The gate needs an estimate of one quantity: whether the edit lowered the patch loss. That estimate comes from a feedback signal. Signals differ in three ways: how soon they arrive, how exact they are, and whether there is a fact of the matter at all. Those three differences sort every surveyed system into four classes (Table 2), and the class fixes what the gate can be, which

half of the loop can close automatically, and which failure dominates.

The classes are a partition, not three independent axes: a system is assigned by the property that binds its gate first. Delay binds before anything else, so an outcome that arrives months later is C4 even when it is objective; the absence of ground truth binds next, so an immediate judgment is C3; and among signals that are prompt and objective, exactness separates C1 from C2.

C1, exact. A deterministic checker returns pass or fail, or an exact score, immediately and repeatably: unit tests, compilers, type checkers, exact-match answer keys, proof checkers, schema validators. DGM runs every self-modification in a sandbox and keeps every one that still compiles and can edit code, a functionality check on ten benchmark tasks; the benchmark score then weights which archive members are chosen as parents rather than deciding which are kept [29]; AlphaEvolve scores candidate programs with a cascade of exact evaluators [30]; SkillOpt gates a skill edit on a held-out exact-match split of a math benchmark [31]. Because the check is exact for the artifact and the test it runs, and repeating it returns the same answer, one run settles the checked case. What the check does not settle is the patch loss: the suite is a sample of the patch's task mix, and the agent that runs under the edited scaffold is stochastic, so the gate's estimate of the loss change still carries sampling error. The gate can be a program and its margin can be small, but the margin absorbs sampling error, not error in the check. The improvement the check certifies is also bounded and specific: an improvement in what the check measures, on the cases it ran, not an improvement in general. Two things stay hard. A failing test localizes the output, not the scaffold coordinate that caused it, so credit assignment remains open; and a checker that is also the training target can be gamed. The dominant failures are test overfitting and scaffold bloat, because cheap acceptances accumulate.

C2, observable outcome. The environment or the user emits an outcome after an episode: a booked appointment, a closed ticket, a merged pull request, a tool call that returns without error, a retrieved document that contains the answer. The signal is real but one episode late, noisy, and confounded, since a user can accept a wrong answer and reject a right one. Gates of this class include Devin's merged pull requests [32], SAGE's task success on AppWorld [33], and PACE's failure signals from a deployed small model [34]; SkillRL reads the same signal only as a trigger, a success rate that decides when new skills are proposed but not whether they stay [35]. The gate can still be a program (a reinforcement-learning threshold or a held-out task suite), but it needs a positive margin, and it absorbs the noise by batching episodes or by requiring agreement across samples (Appendix XIII). Credit assignment takes its most stubborn form here: the outcome says *that* the episode failed, not *why*. Most production deployments live in this class, and its signal arrives through a channel an attacker can control, which is why poisoned memory and tool-output injection dominate.

C3, judged. There is no fact of the matter. An essay, a marketing page, a design, a pitch deck, or a code review for style can be scored only by a judge: a human rater, a language-model judge, a rubric, or a comparison against references. In SkillForge a judge that agrees with people more than nine times in ten flags the failed replies that drive each skill rewrite, and the rewritten skill is committed without an acceptance test [36]; CASCADE consolidates memory under a human-and-agent gate [37]; Anthropic's skills repository promotes a skill when a reviewer approves the pull request. The gate can be a program only after the judge has been calibrated against people, because the judge's bias is now the estimator's bias. Residuals, meanwhile, are captured only when someone objects, so condition 2 depends on complaint channels rather than instrumentation. The dominant failure is Goodhart's law in the form measured for reward models: optimizing a proxy past a point lowers the true score [38]. Once the judge is the target, the scaffold learns the judge. Nor is a human judge stable: Shankar et al. find that evaluators' criteria drift as they grade more outputs [39].

C4, delayed and sparse. The outcome arrives after weeks or months, once per many edits, in a world that has moved on. Research programs, product strategy, and open-ended discovery are of this kind; the clearest instances are automated research pipelines such as the AI Scientist, which generates ideas, runs experiments, and writes the paper [40]. NanoResearch merges candidate skills by semantic compatibility rather than by a measured loss change [41], and CORAL promotes findings into shared memory on a heartbeat rather than on an evaluation [42]. AlphaEvolve's evolutionary database can look like an instance, and is not one: it balances improving the best programs against diversity only after every candidate has been scored by its exact evaluators, so it is a search strategy inside the exact class, not a gate for a delayed signal [30]. With no per-edit estimate to gate on, the gate degenerates to proposal pruning plus proxy milestones, and the descent argument covers only the composition of pruning and whatever gate exists at the horizon (Appendix XIII). Temporal credit assignment across many edits is open. The dominant failure is drift: the scaffold ages faster than the signal that would correct it. An optimizer in this class also cannot be told from random search by its outcomes alone; Ong et al. [43] report the same indistinguishability for harness optimizers.

The judge is part of the scaffold. The judged class has one feature the other three lack: the rubric that sets the loss is itself a scaffold coordinate, and it returns in the findings and in the open problems. Suppose a pitch-review system keeps overrating decks that claim a large market without numbers. It traces the failure to its rubric and edits ''evaluate market size'' into ''require a numeric estimate and a source''. That edit changes the gate that will judge the next edit. We call this the *reflexive gate*, and nothing in the corpus calibrates one: three scaffold systems report judge calibration [36], [44], [45], and none calibrates a judge that is itself being edited. The weight side faces the same question. Reinforcement learning from verifiable rewards lies outside the scored corpus, but

TABLE 2. The four feedback-signal classes. Reading across a row: what the gate receives, what it can therefore be, and what it cannot fix.

Class	The signal the gate receives	What the gate can be	What stays hard	Corpus examples
C1 exact	A check that returns pass or fail, or an exact score, at once and repeatably: tests, compilers, answer keys	An automatic check; one run per case, repeated only to sample the task mix	The lift is bounded and specific, an improvement in what the check measures on the cases it ran; the check names the failed output, not the coordinate that caused it; a check that is also the target can be gamed	DGM, AlphaEvolve, SkillOpt
C2 observable outcome	A real result one episode later: a booked slot, a merged pull request, a closed ticket; noisy and confounded	An automatic threshold over batched episodes; a person at promotion	The outcome says *that* the episode failed, not *why*; the channel can be poisoned	Devin, Sierra, SAGE, SkillRL, PACE, Voyager
C3 judged	A rater, a rubric, or a model judge; no ground truth	A judge calibrated against people; a person at promotion	The rubric is itself a scaffold coordinate, so the gate judges edits to itself; the proxy gets optimized past the point where it tracks quality	SkillForge, CASCADE, skills-repository review
C4 delayed	An outcome weeks or months later, once per many edits	No per-edit gate; proposals are pruned and milestones stand in	Credit across many edits; drift; the loop cannot be told from random search	NanoResearch, CORAL, the AI Scientist

pushing it into writing and other open-ended tasks has forced researchers to build judged gates. One group holds the gate fixed while the policy learns, as a checklist, a pairwise judge, a reference-anchored judge, or a fixed rubric [46]–[49]; a second group lets the gate move with the policy, scoring by the policy's own probability of a reference or updating the rubric or judge during training [50]–[54]. Fixed versus co-evolved is exactly the reflexive-gate question, and of the co-evolving methods only RLPR, whose reward is a probability rather than a rubric, reports agreement with human labels (Supplementary Material S6).

What the class decides. Read down the table and three consequences follow, each a prediction about the corpus that Section VII checks. First, which half of the loop can close automatically. An exact check or an observed outcome can gate a local edit by program. A judgment can do so only once the judge is calibrated, and a delayed reward cannot gate edits one at a time. Promotion is stricter. Only the exact class carries its own measure to the receiver, and only when the receiving side runs the same check: that is the one case in which the sending side's evidence means the same thing on arrival. In every other case the receiving-side evaluation of Section III is still owed. Second, which gate pairings a deployment can reach. [Auto × Auto] belongs to exact signals and simulated outcomes; [Auto × Human] belongs to observed outcomes and judgments, where the person on Loop 2 does the work the missing exact signal cannot; and the delayed class has no per-edit gate on either half. Third, which failure dominates, as the last column of the table records and Section X develops.

V. THE CORPUS, AND HOW IT WAS READ AGAINST THE LOOP

Every placement in Sections VI to X is a reading of one system's own text in the vocabulary of Section III: which scaffold coordinate the system edits, whether a measure gates the edit, who decides, and how far the edit travels. The reading was done from each system's method section or documentation, and it is released row by row with a one-line justification, so that any placement below can be checked against the system rather than against this survey.

A. HOW THE CORPUS WAS ASSEMBLED

A system enters the corpus if it wraps a foundation model with at least one persistent artifact updated from deployment signal, or if it is described in public as self-improving, scaffolded, or agentic; systems whose only update mechanism is weight-level training, and systems with no public evidence of deployment or release, are excluded (Supplementary Material S2). The systems were found in public sources in two passes (130 by May 2026 and 126 more by the October 2026 cutoff), and the second pass records, for each system it added, the gate on each half of the loop, the signal class, and the governance properties as columns of the released table, so the counts that follow by gate and by class are counts over the systems it added.

Two filters sort the systems (Fig. 3), and both are stricter than the field's own labels. The first keeps a system in the core corpus only when some artifact of it persists across scope or is updated from feedback, which is a score of at least 3 on at least one substrate on the ruler below; systems that carry the labels but fail it form a contrast corpus, kept so that the boundary can be audited rather than asserted. Of the 256 systems, 204 form the core corpus and 52 the contrast corpus. Every system




FIGURE 3. Corpus flow. Every system is scored on the substrates it adapts, with an integrated row for systems that adapt several, giving 269 substrate-level rows for 256 systems; the discriminator splits core from contrast; the composite two-loop audit selects the systems placed in the design space of Section VII.

is scored on each substrate it adapts, and a system that adapts several gets one composite row as well, which is why 256 systems give 269 rows.

The second filter is the two-loop audit, which asks each core system the two questions of the loop's two halves: does Loop 1 modify a persisted artifact from session signal, and does Loop 2 promote the artifact beyond the deployment that produced it, with versioning or lineage? Applied to the 204 core systems, and to ten more classified from their papers alone (they are not rows of the released table), it admits 11 research systems (10 table rows and SkillOpt) and 3 industry exemplars (Sierra Agent OS 2.0, Cognition Devin, and Letta's Context Repositories). These are the systems the gate grid of Section VII places by who decides on each half; the grid's lighter cells also show curation and, for comparison, the systems with no failure-driven loop, and the systems that promote without lineage join cells already occupied. Passing the audit is a weaker thing than having the governed second loop of the thesis: every passing system promotes across users, teams, or repositories inside one operator, none reaches another organization, and one of them, Letta, promotes with no gate at all (Section IX).

B. SIX COORDINATES AND ONE RULER

Condition 3 of Section III asks that a failure be traced to the scaffold coordinate that caused it, and the corpus locates that coordinate on one of six substrates (Table 3); they are the coordinates of θ_s, each editable independently of the others, and the three kinds of memory on the memory substrate follow the cognitive-architecture taxonomy of Sumers et al. [55].

The ruler is the same on every substrate, 0 to 5, and it measures distance along the loop. At 0 the artifact is ephemeral; at 1 it is persistent and local; at 2 it is persistent with tool attachment but no feedback; up to that point an artifact persists and nothing measures it, which is the patchwork stage of Section III. At 3 the artifact either spans scopes with no gate on the way or is updated from feedback by a person; at 4 a program updates it from feedback, so Loop 1 closes. The top mark, 5, is each substrate's own in Table 3: both halves of the loop on the substrates that hold adaptable content (S1, S2, S5), and the machinery a second loop would need on those that hold governance (S3, S4, S6), which is why a registry or a prompt platform can score 5 with no Loop 1 at all.

C. WHAT WAS GATHERED, BY SUBSTRATE

No system matures all six substrates at once (Table 4). Research systems learn fast and lack enterprise governance; production systems govern well and learn slowly; open standards solve artifact portability but not adaptation. Each kind was built to satisfy one constraint (fast learning, safe change, or portability) and matured only the substrates that constraint touches, so the top marks fall on different substrates for different kinds of system: research systems on skills and memory and in the composite row, products and standards on tools and governance, and no system at all on instructions or orchestration.

D. EVIDENCE AND SCORING DISCIPLINE

Every classification rests on public evidence of uneven strength and on one rater. Each system carries one or more evidence tiers (T1 to T5 in the released table: peer-reviewed publication, arXiv preprint, production claim with metrics, open-source artifact, industry blog or interview); peer-reviewed papers and open-source artifacts weigh most in corpus-level statements, a production claim counts when it names a benchmark or integration target, a blog post or interview counts only when a higher tier corroborates it, and production claims are never pooled with peer-reviewed evidence in a corpus-level statistic. Industry systems evaluated from vendor documentation rather than a paper are flagged wherever they appear. One author scored every system, used half-scores only when one criterion was clearly met and another partially, and rounded ambiguous cases down; the scores have not been independently re-rated, and that check is future work. The complete score table, with a one-line justification per row, is released so that every scored classification can be re-derived (Supplementary Material S1); the counts move under natural relaxations of the audit (counting rollback alone as Loop-2 governance, asking for a promotion mechanism with no governance at all, admitting a Loop 1 that persists only optimizer state) while the qualitative findings survive every one of them (Supplementary Material S2).

VI. LOOP 1 IN THE INDUSTRY: A FAILURE, ONE EDIT, A GATE

The local half of the loop is built, and it is built from the gate backward. In nine of ten of the most recently added

TABLE 3. The six scaffold substrates, what each holds, and what a system must do on it to score 5.

Substrate	What persists	A score of 5 requires
S1 Instructions	Project, team, or organization rules attached to a workspace	Versioned rules promoted under an automatic gate
S2 Skills	Procedures, as code or text, loaded on demand	A skill bank that edits itself on failure, test-gated, versioned, and promoted
S3 Memory	Experience kept across sessions: episodic, semantic, procedural	Provenance, versions, and a correction path for every entry
S4 Tools	The vetted action surface and its schemas	Evaluation-gated tool versions; a curated bundle as the product
S5 Orchestration	The multi-role graph and its routing	Topology updated from an outer-loop signal
S6 Governance	Versioning, promotion, audit, rollback	Staged promotion with evaluation thresholds, an audit log, and rollback

TABLE 4. Substrate maturity across the 256-system corpus. Column n counts scored rows on each substrate, Mean is the average score, and Score-5 systems reach the substrate's top mark; the composite row counts systems scored across several substrates as one row. Of the 126 most recently added systems, 102 are core and 31 are skill systems; 92 of those core systems close Loop 1 under a program, and none of the 126 scores 5 on any substrate.

Substrate	*n*	Mean	Score-5 systems	What the corpus holds on it
S1 Instructions	15	3.07	(none)	Rules persist across IDEs and agents and nothing measures them; no system closes both loops; ceiling 4
S2 Skills	50	3.34	SAGE, COSPLAY	Loop 1 closes under a program in the research systems; the production repositories merge by hand
S3 Memory	50	3.06	Cuadros et al.	The ledger ships in products; the correction a gate would enforce is absent
S4 Tools	20	3.65	MCP, Harvey, Hippocratic AI	The most mature production substrate; registries govern admission, not evaluation
S5 Orchestration	37	3.08	(none)	Topologies change under an evaluation gate; one structurally gated instance; no two-loop system
S6 Governance	45	3.02	Braintrust, Vellum, LangSmith Hub, AGENTS.md/AAIF	Prompts-as-code mature; registries add lineage and rollback; no Loop 1 generates a candidate
Integrated	52	3.81	NanoResearch, AutoAgent, SkillRL	High-water mark; reached only by research systems without enterprise governance

core systems a program keeps or discards each local edit on a measured loss, and the pattern holds on every substrate that has a failure-driven loop at all (Table 4). What stands before the gate is far less built: production deployments log preferences and successes rather than failures, so there is little to cluster, and no general method traces a failed output to the coordinate that caused it. What stands after the gate is half built: the memory products keep every entry's history and still return facts that were revoked. Walked in the order it runs, from the logged failure to the kept edit, Loop 1 is a gate the field has made well, fed by a trace it has hardly made at all.

A. THE FAILURE AND ITS TRACE

Condition 2 asks that failures be logged rather than lost, and in production they are mostly lost. Deployed memory systems record preferences and successful facts, not residuals, so the loop has little to cluster. The one field report of a store that records dead ends so they are not repeated describes a single, self-reported deployment [56]; everywhere else the log that Loop 1 would cluster is never written. The gap sits in the observable-outcome class (C2), where an episode is recorded as a success or a preference and the failure that would have been the residual leaves no entry.

Which sessions inform the next edit is left to chance. The loop of Section III ranks recurring modes by how often they recur and how badly they fail before it takes one up; nearly every system in the corpus takes failures in the order they arrive instead. Task-CoEvolve's variance-weighted task sampling and AutoSaddler's mini-batch failure signals are the exceptions [57], [58], and both weight the sessions the loop learns from by how much they disagree (C2). A loop that learns from whatever arrived last is descending on a sample nobody chose.

Condition 3, tracing a failure to the coordinate that caused it, is the step the field itself names as the bottleneck: the harness-optimization line and the evaluation of harness optimizers by Ong et al. agree that attributing a system-level failure to one scaffold coordinate is what separates descent from trial and error [43], [59]–[63]. Where it is solved, it is solved one substrate at a time. Meta-Harness keeps a

filesystem of candidate harnesses that records which edit helped, and that record is the history the loop reflects over [61]; SkillsVote attributes each outcome to skill, exploration, or environment before an update is admitted [63]; SkillOpt-Lite's consensus filter across rollouts is the form of credit assignment its ablation finds load-bearing [64]. In the general case, where a failed output may come from a stale memory entry, an under-specified rule, or a misrouted edge, the trace remains unsolved. A gate can keep only the edit it is given, and the step that would say which coordinate to edit is the one the field has hardly built.

B. THE EDIT AND THE POOL

Three kinds of author write the candidate of condition 4, and who writes it decides how often the loop can start. In the research systems an agent writes it by reflecting over the failure history, which is the author the loop of Section III assumes. In the prompts-as-code platforms an engineer writes it at a desk, and session feedback never triggers a candidate (Section VII). A contributor writes it in the public skill repositories, where every substantive edit is human-authored and human-merged [65]. Who writes the candidate is not a gate, but where the author is a person Loop 1 runs only as often as a person notices.

The pool the candidate enters is governed as carefully as the candidate. Eleven skill systems treat removing an artifact as an operation that must pass a check, the same as adding one [66]–[69]. The reason is in Ratchet's result: skills written by a language model gain nothing over a no-skill baseline until lifecycle hygiene is applied, while human-curated ones show a double-digit gain [70]. A pool nobody prunes starves the gate of signal, because failures caused by stale artifacts cannot be told from failures the edit under test would fix (Section X). Hygiene is not an alternative to descent; it is what makes the gate readable.

C. THE GATE: WHAT IT MEASURES, WHO DECIDES, HOW LONG IT WAITS

Wherever a failure-driven loop runs on skills or orchestration, the local gate is now a program, with one exception, and the research activity is concentrated there. On skills, SAGE and COSPLAY close both halves of the loop inside one research environment [33], [71]; the exception is SkillChain, which puts a person after the judge, a human reflection gate before an edit reaches the skill bank [44]. On orchestration, topology changes are evaluation-gated or evaluation-informed, and no system closes both loops: GPTSwarm's optimizable graphs [72] and AFlow's tree search over code-represented workflows [73] searched for a topology under a score; AgentGrad and HarnessForge keep a change only under an evaluation [74], [75], and TOCOMAS keeps it only when it also satisfies a structural invariant [76]. OptiMAS evolves the topology continuously instead: an LLM optimizer reads the training trajectories and a scalar validation score and writes the next configuration, with no per-edit accept-or-reject step, and an edit is reverted only when the optimizer's own analysis refutes the hypothesis behind it [77].

The counter-example is the most widespread artifact of all. Instruction files persist across IDEs and agents (Claude Code, Cursor, AGENTS.md [78], Windsurf, Continue.dev) and appear in a fifth to a quarter of coding-agent projects [79], [80], yet two controlled studies disagree on cost, and neither shows a gain in task success. In one, context files raise inference cost by about a fifth and buy nothing in task success [81]; in the other, a paired run on 124 pull requests that toggles only the root AGENTS.md, the file cuts median wall-clock time by about 29% and median output tokens by about 17%, leaves total tokens flat, and does not measure correctness [82]. That is the patchwork stage of Section III on the most widely deployed substrate: a rule is added after a failure, nothing measures whether it helped, and the file grows. A rule file that nobody measures is patchwork at scale.

Read by who decides, the three gate kinds of Section III fall on Loop 1 in a fixed pattern. A program decides nearly everywhere a failure-driven loop runs. A person decides only in curation, where an agent drafts and a person chooses what is kept, as in VerificAgent's fact-checked and frozen memories [83] and SkillChain's final reflection gate. Where no local loop exists, in the prompts-as-code platforms and the registries of Section VII, nothing decides on Loop 1 at all; what those systems gate is admission to a shared pool, which is a Loop 2 decision. The pattern is the one Section IV predicts for the local half: a program wherever the loop has a check or an outcome to read, or a judge calibrated against people.

How long the gate waits is where the newer systems differ from the earlier ones. The earlier systems accepted an edit on one evaluation and absorbed the estimator's noise through the margin alone; the newer ones wait. SAGE-gate commits an edit only when a paired per-item test says its wins are reliable [84]; in VaG, three heterogeneous critics must pass [85]; AutoSaddler feeds mini-batch failure signals into validation-based selection [58]. Waiting hides two different operations: if each of k independent proposals is wrongly accepted with probability p, requiring all k to agree drives the false-accept rate to p^k, while averaging k noisy scores shrinks the variance of the estimate only by $1/k$ (Appendix XIII). A gate that waits for a batch is condition 5 taking the noise in condition 1 seriously, and in the corpus that care arrived after the gate itself.

D. THE LEDGER: VERSIONED, NOT CORRECTED

Versioning and rollback are the last step of Loop 1: an accepted edit stays in the scaffold and is reversed if a later check shows it made things worse. They are also the record a second loop would read, and the memory products have built the record and not the correction. Letta's git-backed Context Repositories [86], Mem0's per-memory history [87], and Zep's bitemporal facts [88] all record how an entry came to be, so a user who asks what the system remembers and why can be answered. Research memory splits into write-gating and provenance on one side [89]–[91] and verifier-

gated failure loops on the other [92], [93]. VerMem [94] belongs to the first group: its verifiers shape the memory policy only during training, at run time the whole gate is a validity check on each write, and every Update keeps the prior version and every Delete keeps its record. Only the governed collaborative memory of Cuadros et al. does both [95], which is why it alone reaches the top mark.

What lineage does not give is correction. Five production backends still return facts that were revoked [96]: the ledger exists, the gate that would act on it does not, and the gap sits in the observable-outcome and judged classes (C2, C3), where a revocation arrives as a user's objection rather than as a failed check. Rollback of a single edit inside one deployment exists, as edit-level reversal [67], [97] and as an admission test that rejects edits which cannot be undone [98], and the one negative result on it cuts deep: once a contaminated skill has descendants, rolling it back recovers little, so gating must happen before commit [85]. No system rolls back a promotion that has crossed an organization, because none makes one (Section IX). A memory that remembers its own history and cannot forget on request has the record a second loop would read, without the gate that would act on it.

VII. LOOP 2 IN THE INDUSTRY: HOW FAR AN EDIT TRAVELS, AND WHO LETS IT

The second half of the loop exists in parts, and the parts sort by what they cross. Below the tenant boundary every kind of crossing is occupied inside one operator, from one user to another and one repository to another up to teams, and across the clients of a federated run. Who lets an edit climb is set by the feedback the crossing can get, as Section IV predicted: a program where a check travels with the edit, a person where the signal is an observed outcome or a judgment, and in one production system nothing at all. Above the tenant boundary the scope exists and the promotion does not: CORE is settled across vendors as a format and a protocol, and what fills it is admitted by hand. On the gate grid the industry has converged on the local gate and is sorted on the promotion gate by its signal, and no system carries a promotion out of its operator under lineage, access control, and rollback.

A. INSIDE ONE OPERATOR: WHAT CROSSES, AND THE CHECK WHERE IT ARRIVES

Each crossing below the tenant boundary is occupied by a system of one operator, and a promotion differs from a push in having a check at all; the check that counts is the one where the edit arrives. The crossings run up the ladder of Section III. Between users, ShareMem consolidates one user's memories for another and evaluates them there [99]. Between repositories, a rule in XRepoSkill survives only if it is verified in at least two of them [100]. Evo2Team promotes routing skills between teams (the STACK rung) and confirms them at the target [101]. Across the data-local clients of a federated run (partitions, not deployments of a tenant, so they sit on no rung), EvolveNet evolves a shared harness and accepts a merge only when it fixes at least as many held-out items as it breaks [102], and FederatedSkill's server agent applies, adapts, or rejects each client's patch and logs the decision [103]. VACE is not a crossing: it checks each candidate harness against the freshly trained checkpoint that will use it, held fixed, on the run's own validation set, so the edit is made and kept inside one training run, a Loop-1 gate that sits on no rung [104]. RASO adapts skills retrieved from a public corpus, which is inbound retrieval rather than promotion [105].

Where the check sits is the next difference. ShareMem, XRepoSkill, and Evo2Team check where the edit arrives; EvolveNet checks at the aggregator and nowhere else; FederatedSkill records a decision taken at the server. The receiving-side evaluation that Section III places at every rung is therefore present in the corpus and rare, and where it is present it is necessary rather than sufficient: nearly a fifth of Evo2Team's confirmed transfers still fail on graphs the confirmation never saw.

None of these leaves its operator: no system promotes across customers or organizations with evidence. That is the thesis of this article, and because the failure log and the trace of Section VI are hardly built, a system that tried would have little to promote and no way to check what it promoted.

B. WHO LETS IT CLIMB: A PROGRAM, A PERSON, OR NOTHING

A program lets an edit climb where a check travels with it. In AlphaEvolve, and in FunSearch before it, the evaluator cascade that scores every candidate is also the only thing that admits a program to the archive every later generation draws from, and the programs admitted that way went on to production gains at Google [30], [106]. It is a research loop run in production rather than a product, so it does not count against the two production routes of Section III, behind a person or not at all.

A person lets an edit climb where the signal is an observed outcome or a judgment. CASCADE consolidates memory under a human-and-agent gate [37]. Sierra routes agent-generated insights through human-authored expert answers [107]. In Devin one event serves both halves: the merge of a pull request is the outcome Loop 1 reads, and the reviewer's decision to merge is also what lets the edit stand in the repository every later session uses [32]. Spotify's automatically optimized prompts and plans go live only after an online A/B test and a launch decision [28]. In every one of them the person on Loop 2 stands in for the exact signal production lacks, which makes the pairing the production-viable one rather than a compromise.

Nothing lets an edit climb in one production system. Letta's Context Repositories push every edit to shared memory with lineage and no check; the ledger records what crossed, and nothing asks whether it should have.

C. THE TOP RUNG: CORE EXISTS, AND EVERYTHING IN IT IS ADMITTED BY HAND

CORE, the scope every tenant shares, exists today in two forms, and an edit promoted into it on evidence is not one of them. The first form is a format: Claude Agent Skills, Cursor Rules, GitHub Copilot instructions, Windsurf, Continue.dev, Zed, and Replit all keep a git-tracked markdown artifact attached to a workspace, with an MCP-style tool layer beside it [80], [108], so an artifact written for one deployment can be carried to any other. The second form is a registry that admits artifacts for everyone, and admission is by hand: in the five public skill repositories of one field study, every substantive edit is written and merged by a person, with one deprecation in 254 edits [65]; the MCP registries split into catalogues (namespaces and version records, no scanning) and control planes (scanning, access control, quarantine) [109]–[111]; and the governance registries bring lineage and rollback [112]–[114], one of them, EDDOps, gating promotion on evaluation thresholds before a human sign-off [112], but none generates the candidate from a failure. The prompts-as-code platforms hold the rest of the machinery a second loop would need, and nothing feeds it: Braintrust, Vellum, and LangSmith Hub [115]–[117] keep immutable versions, evaluation thresholds, and rollback. But engineers author the candidates at a desk, an evaluation blocks a release on regression, and session feedback never triggers either, which makes them MLOps for scaffolds rather than for weights. Even where a repository runs an autonomous loop, the runtime state of that loop sits outside version control [118], so what the format versions is the artifact and not the process that edits it. Registries govern what may be used and the platforms gate releases on evaluation, but neither generates a candidate from a failure, which is how tools and governance reach the top mark of Section V with no Loop 1 at all.

D. THE TWO HALVES TOGETHER: THE GATE GRID

The loop makes exactly two decisions, whether a local edit enters the scaffold and whether an accepted edit leaves the deployment, and the grid of Fig. 4 puts one on each axis, the gate on Loop 1 in the rows and the gate on Loop 2 in the columns, with the three gate kinds of Section III. One thing jumps out of it: the field varies almost only along one axis. Every system whose local gate is a program sits in the top row, and what tells them apart is the column: a program, a person, or nothing. The column is not a free choice; it follows the signal as Section IV predicted, with one qualification the data adds for two systems. Every [Auto × Auto] system whose promotion gate estimates the loss change runs on an exact signal or a simulated outcome, as EvolveNet's held-out merge and XRepoSkill's second repository do. The two on delayed or judged signals, NanoResearch and ShareMem, decide by program on both halves but by pruning or a judged merge rather than by estimating a loss change, which is the degenerate gate Section IV describes for a loop without a per-edit estimate. [Auto × Human] holds observed outcomes and judgments and no exact-signal system. Nor does any system




FIGURE 4. The two-loop design space. Rows give the Loop 1 gate and columns the Loop 2 gate, with None for a step that is absent or runs unchecked; a cell [Loop 1 × Loop 2] such as [Auto × Human] pairs an algorithmic local gate with a human promotion gate. Darker cells mark the three populated kinds of system; lighter cells hold curation, the registries, and the systems whose promotion is ungated or absent.

calibrate a judge under edit. The industry has converged on the local gate and is sorted on the promotion gate by the feedback it can get (Table 5).

The top row holds the learning. A program keeps the local edit and a program lets it climb in NanoResearch, FunSearch and AlphaEvolve, DGM, ADAS, Voyager, and SAGE [29], [30], [33], [41], [106], [119], [120] and in the systems that carry edits between deployments of one operator; what they promote into is a bank or archive shared beyond the run that produced the edit, which is as far as any of them travels, and none of them has access control, audited promotion, or a gate at a receiving organization. A program keeps it and a person lets it climb in CASCADE, Sierra, and Devin; the six systems that promote without lineage on the promoted artifact, Spotify among them, join cells already occupied and open no new one (Supplementary Material S2). In Letta's Context Repositories and in the systems whose accepted edits never leave the deployment that made them, such as AutoAgent, whose analyzer revises one agent's own tool and peer descriptions [121], a program keeps it and nothing lets it climb.

The rest of the grid holds the governance and the curation. A person keeps the local edit and nothing lets it climb only in curation, where an agent drafts and a person decides what is kept (VerificAgent, SkillChain's reflection gate); [Human × Auto] and [Human × Human] are empty, since no surveyed system puts a person on the local gate of a failure-driven loop and then promotes the result. The bottom row holds the systems with no failure-driven loop at all, which enter the grid for comparison rather than through the audit (Supplementary Material S4): the prompt-management platforms, which gate promotion on evaluation but generate no candidates, and the registries and community hubs in which a person registers an artifact and a person, or an admission scan, approves its use [109]–[111], [122]. No system has both the learning of

TABLE 5. The gate grid read cell by cell: who keeps a local edit and who lets it climb, which systems sit in the cell, and the feedback signal they gate on. [Human × Auto] and [Human × Human] hold no surveyed system.

Cell	Who keeps the local edit, who lets it climb	Who is there	Signal found there
[Auto × Auto]	A program keeps it; a program lets it climb	Research systems that close both halves inside one environment or one operator	Exact and simulated outcomes; delayed and judged only under pruning or merging
[Auto × Human]	A program keeps it; a person lets it climb	Production systems with a reviewer on promotion	Observed outcomes and judgments
[Auto × None]	A program keeps it; nothing lets it climb	Letta's ungated push; systems that promote nothing	As on the local gate
[Human × None]	A person keeps it; nothing lets it climb	Curation	Judged
[None × Auto]	Nothing generates candidates; a threshold gates release	Prompt-management platforms and governance registries	No failure-driven loop
[None × Human]	Nothing generates candidates; a person admits	Open standards, MCP registries, community hubs	No failure-driven loop

the top row and the governance of the bottom, and what no cell contains is governed cross-tenant promotion, which Section IX specifies.

VIII. FIVE RESEARCH LINES ARRIVE AT THE SAME LOOP

Nobody designed the loop of Section III. Five research lines, each started from a different problem, built a different part of it, though the parts do not map one to a condition: the candidate (condition 4), the penalty in the gate (condition 5), the trace (condition 3), the gate applied to removal, and the check where a promoted edit arrives (Loop 2). A single research system, SkillOpt, holds all five conditions at once, and the ablation in its follow-up says which of them carry the weight.

A. WHERE EACH LINE STARTED, AND THE PART IT BUILT

Reflective evolution came from prompt optimization and continual learning: GEPA proposes edits by reflecting over trajectories, and Tiwari et al. argue on two timescales for keeping those edits outside the weights [4], [123]. Reflective context learning (RCL), the most direct independent formalization of the loop, came from the observation that credit assignment, overfitting, forgetting, and high-variance signals persist whether the learned object lies in parameter space or context space. Its generalization penalty is the complexity term Ω of the gate [124]. Starting from orchestration rather than skills, harness optimization works on the trace, which it names as its bottleneck: Meta-Harness keeps a filesystem of candidate harnesses that records which edit helped, and that record is the accumulated history the loop reflects over; roughly two hundred papers cite the line's founding entries, and a dozen are scored here [59]–[62], [75], [125], [126]. The lifecycle line came from skill pools that bloat under platform limits and built the gate on the way out: retirement is a gated operation in eleven systems, each outcome is attributed to skill, exploration, or environment before an update is admitted, and the complexity penalty becomes a hard frontier once platform limits bind, so the gate trades gain against size rather than weighting it [63], [66]–[70], [127]. The transfer line came from how far an edit travels and built the check on arrival, from measuring how far one edit's lift carries, one task at a time, to federating skill patches across clients or deployments, with FederatedSkill's server agent applying, adapting, or rejecting each client's patch [34], [42], [102], [103], [128], [129]. Table 6 sets the five side by side with what each leaves open.

B. ONE SYSTEM HOLDS ALL FIVE CONDITIONS

SkillOpt [31] treats one markdown skill document as the trainable external state of a frozen agent, and read condition by condition it holds all five: a held-out exact-match split is the measurable loss (condition 1, an exact signal in the terms of Section IV); rollout and reflection batches are the captured residuals (condition 2); a consensus filter across rollouts is the credit assignment (condition 3); add, delete, and replace edits under a bounded step are the candidate (condition 4); and a held-out gate that accepts only a strictly better score is the gate (condition 5). Across six benchmarks, seven target models, and three harnesses it is best or tied on every cell its authors evaluate. Its transfer across models, harnesses, and benchmarks measures how far one edit's lift carries, which is the evidence radius of Section III, and governs nothing about how far the edit may go. Its follow-up SkillOpt-Lite [64] strips the stabilizers (a rejected-edit buffer and a slow update schedule), keeps the held-out gate and the consensus filter, and matches or beats it; so the gate and a consensus form of credit assignment are load-bearing and the rest are stabilizers (Supplementary Material S5).

C. WHAT THE CONVERGENCE SHOWS, AND WHAT IT DOES NOT

Two things follow, and one does not. The scaffold-versus-weights decomposition is confirmed independently: GEPA, Meta-Harness, MOSS, RCL, PACE, and the harness-

TABLE 6. Five research lines converging on artifact-layer descent: the problem each started from, the part of the loop it built, and what it leaves open.

Research line	Started from	The part of the loop it built	What it leaves open
Reflective evolution	Prompt optimization and continual learning	Condition 4, the candidate: proposal by reflection over trajectory evidence; the two-timescale case for editing outside the weights	A persistent artifact; a bounded step; a held-out gate
Reflective context	Learning in context as a setting of its own	Condition 5, the penalty: the learned object in context space; a generalization penalty, the Ω of the gate	A cross-deployment Loop 2
Harness optimization	Orchestration and harness engineering	Condition 3, the trace: attribution of a failure to one slot of the orchestration graph; source-level edits	A governed Loop 2; access control; rollback
Lifecycle and multi-objective	Skill pools that bloat under platform limits	The gate on removal: gated retirement; hygiene as a precondition; a hard frontier as the shape of Ω	Closing the loop as descent; retiring a promoted artifact's descendants
Transfer and federation	How far an edit travels	Loop 2, the check on arrival: evidence radius measured one task at a time; cross-client aggregation; receiving-side confirmation	A cross-organization gate, lineage, and rollback

optimization papers all begin from the observation that weights and the external artifact layer are distinct adaptation surfaces with different cost, reversibility, and scope, and a system that updates both keeps them as separate levers [130]. No line documents the governed second loop: FederatedSkill and EvolveNet each narrow the gap on different properties, and neither meets the four that Section IX sets out. What does not follow is that the shape is the best one. The vendors' convergence on one artifact format and one tool layer is the same kind of evidence from the production side (Section VII), reached by groups that were not looking for it; convergence shows only that the same constraints keep producing the same shape.

IX. THE MISSING ARCHITECTURE: GOVERNED CROSS-TENANT SCAFFOLD OPTIMIZATION

What is missing is the rung that crosses a tenant boundary under a gate, and it is specific enough to audit for. Four properties define it, and no surveyed system holds all four. Which of them a deployment should expect to meet follows from the feedback it has rather than from its domain. The four are:

- (a) **auto-gated Loop 1**: the commit criterion is an algorithmic threshold;
- (b) **cross-organization promotion**: Loop 2 routes artifacts between organizations (we use *cross-tenant* and *cross-organizational* interchangeably);
- (c) **versioned lineage with access control**: promoted artifacts carry versions, audit trails, and role-based access policies;
- (d) **rollback**: a bad promotion can be reverted without redeploy.

The closest approaches split these properties among them, and no row of Table 7 is full on promotion across organizations.

Row by row, the partition is tidy: the two federated systems carry the automatic gate and part of the promotion, SkillForge carries the gate and part of the lineage but keeps every skill version in the deployment that wrote it, the registries carry lineage and rollback without an inner loop, and the control planes carry access control alone. Rollback exists inside one federated round and, as Section VI records, inside single deployments; no system rolls back a promotion that has crossed an organization boundary, because none makes such a promotion (Supplementary Material S4).

In machine-learning terms, what is missing is a cross-tenant aggregator with an automated evaluation gate at the scaffold layer. It would carry five parts: per-tenant artifact pools, each tagged with provenance; an aggregation step across tenants that respects tenant isolation; a held-out evaluation at the receiving tenant that blocks a promotion whenever it does not lower that tenant's patch loss; versioned lineage with access control; and a rollback envelope on every promoted artifact. The federated-learning analogy [131]–[133] is useful only in the limit where artifacts are mergeable update representations; federated prompt tuning, in which participants learn a shared prompt rather than shared weights [134], is the weight-side precedent closest to that limit. In surveyed practice Loop 2 is selection and merge: the nearest systems aggregate program edits with a language model, not by averaging.

Whether the architecture *should* be built depends on the feedback-signal class, not on the application domain (Section IV). Where the signal is exact, automatically gated cross-tenant promotion of a test-validated skill would be low-risk, and receiving-side evaluation is cheap to add. Where it is an observable outcome, the sending side's outcome does not transfer, so promotion should be automated only behind receiving-side evaluation, the check that re-establishes the lift under the receiver's own measure and would catch a scaffold over-fitted to one deployment before it propagates to another. Even that check is necessary rather than sufficient: some of

TABLE 7. The closest approaches to governed cross-organization scaffold optimization, scored against the four properties.

System	(a) auto-gated Loop 1	(b) cross-organization promotion	(c) versioned lineage with access control	(d) rollback
FederatedSkill [103]	full	partial: privacy-preserving aggregation of skill patches across heterogeneous clients that sit under one operator	partial: auditable per-modification decision log	none
EvolveNet [102]	full	partial: held-out merge gate at the aggregator, but clients are benchmark partitions, not organizations	none: no lineage, no access control	full: rollback to the previous shared harness after a failed round
SkillForge [36]	full	none: skill versions stay in the scenario deployment	partial	not documented
Governance-first registries [112]–[114]	none: no inner loop	none	partial: lineage without access control	full, with evidence
MCP control planes [109]	none: no inner loop	none	partial: access control without evaluation-gated promotion	not reported

Evo2Team's transfers still fail on new graphs after target-side confirmation [101]. Where it is judged, a human gate on Loop 2 is a design feature, and governance means lineage and rollback around a human decision. With a delayed signal, property (a) cannot be met; what remains is lineage and rollback without an automatic gate. Safety-critical domains, the usual case for human gates, are judged or delayed domains with high stakes. Whatever the class, the measure bound of Section III holds: where tenants measure different things, as they usually do across organizations, no lift transfers without the receiving-side check.

X. THE FAILURE SURFACE

While the second loop is missing, deployments pay for its absence in failures that weight-only systems do not have. They are the scaffold-layer entries in the technical-debt ledger that Sculley et al. opened for machine-learning systems a decade ago [135]. There are seven, each shown below in a measured case and paired with the piece of the optimizer that would close it (Table 8). Each dominates in the feedback-signal class that the third prediction of Section IV assigns it, bloat and test overfitting to the exact class, poisoning to the observed-outcome class, a gamed judge to the judged class, drift to the delayed class, which is why the open problems of Section XI come one per class. The entries are documented attacks and degradations, not a new threat model.

Bloat is not only slow; it is a signal-quality problem. Instruction-following accuracy falls and latency grows sharply as the instruction count scales [136]. Ratchet's result, that model-written skills gain nothing until lifecycle hygiene is applied, is the loop-level symptom [70]: in the vocabulary of Section III, failures cannot be captured and clustered on a messy artifact pool, which is why gated retirement comes before descent, not after it.

Poisoning and injection are the two ways an adversary reaches the scaffold, and both arrive through the channel the observable-outcome class depends on. Memory is reached by writing: attacks against standard retrieval-augmented generation succeed at high rates [137], AgentPoison shows that backdoors can be planted in long-term memory or knowledge bases [138], and memory control-flow attacks work across the major agent frameworks [139]. Tools are reached by output: a tool's result or a connected server can smuggle instructions into context [140], [141], and one approved MCP configuration could later be modified without re-approval (CVE-2025-54136) [142]. The responses are the ledger of Section VI and the governance of Section IX turned inward: provenance and write gating with a rollback envelope on memory [143], [144], and a privilege hierarchy over instructions [145] with tool bindings that pass the same promotion gate as every other coordinate.

Evaluation fragility compounds because the evaluation suite is itself a patch-local artifact rather than a fixed instrument. It is optimized against: once a metric becomes the target it is gamed, optimizing a proxy reward past a point lowers the true score [38], and access asymmetries alone produce large relative gains that reflect exposure to the test [146]. It is read non-independently, because the gate scores path-dependent agent trajectories whose readings do not compose like ordinary test-set statistics. It goes stale, because the suite adapts on the same cadence as the scaffold it gates; and because failures concentrate in a finite catalogue of recurring modes, a suite that samples tasks at random under-weights exactly the families that drive the failure rate. The consequence has been measured: harness optimizers cannot be told from trial-and-error by downstream score alone [43]. From those facts the response follows: held-out and scoped, mode-weighted, re-read, and checked against attribution rather than only against score.

The remaining three are failures of structure rather than of signal. Multi-agent systems fail in fourteen measured modes, dominated by role confusion and context lost between agents [147], and the response is to treat the topology as one more scaffold coordinate under the same gate and rollback. A

TABLE 8. The failure surface of patchwork scaffold maintenance: what goes wrong, the piece of the loop that answers it, and the feedback-signal class in which it dominates.

Failure	What goes wrong	The loop piece that answers it	Dominant class
Scaffold bloat	Rules and skills accumulate until the model follows them worse and the gate has no clean signal	Complexity penalty Ω in the gate; pruning and expiry as first-class gated operations	C1, C3
Poisoned memory	An attacker writes an entry that later retrieval trusts	Provenance on every entry; write gating; a rollback envelope	C2
Injection via tools and MCP	A tool's output or a connected server carries instructions into context	Narrow tool permissions; a privilege hierarchy over instructions; tool bindings pass the same promotion gate as any other coordinate	C2
Evaluation fragility	The suite that gates edits is itself edited, gamed, and read non-independently	Held-out evaluations scoped within evidence radius, weighted toward recurring modes, re-read as the target drifts, checked against attribution	C3 (primary), C1
Coordination failures	Multi-agent roles blur and context is lost between agents	Orchestration topology treated as a scaffold coordinate under the same gate and rollback discipline	C2
Patch overfitting	A scaffold tuned to one deployment degrades another	Evidence-radius discipline at promotion; receiving-side held-out evaluation	C2
Plasticity loss	Old rules, polluted memory, and drifting tool versions crowd out adaptation	Expiry and rollback as explicit loop operations rather than retrospective hygiene	C4

scaffold tuned to one deployment over-fits it by construction (Supplementary Material S3). Because the measure bounds the lift, the answer at promotion is evidence-radius discipline, with a held-out evaluation at the receiving side. And a scaffold that only grows loses plasticity the way a long context does: context rot [148], instruction conflict, memory pollution, and tool-version drift accumulate until expiry and rollback, run as loop operations rather than as retrospective hygiene, are the only way to recover it.

None of the seven needs a new mechanism. Every response in the table is a piece of the second loop or of the governance around it. The surface stays largely unmitigated in production because no surveyed system runs those pieces together, so what the table itemizes is the cost of the missing half, already measured.

XI. OPEN PROBLEMS AND CONCLUSION

Each feedback-signal class leaves one problem open, and the architecture a fifth. None is a general agenda; each is the specific step its class is blocked on.

1. **Exact signals: credit assignment from a failing check to a scaffold coordinate.** A test tells the loop that an output failed, not which instruction, skill, or tool binding caused it. Slot attribution [62], intervention-based attribution [74], and contrastive multi-agent attribution [60] each solve one substrate's case; a general method is the bottleneck the harness-optimization family names.
2. **Observable outcomes: receiving-side evaluation before promotion.** The outcome that justified an edit on the sending side does not transfer, and even where a promoted edit is checked on arrival, some transfers still fail (Section VII). The gate a federated scaffold optimizer needs, a held-out test at the receiving tenant, has been proposed but not built [149].
3. **Judged signals: calibrating a gate that is itself being edited.** When the rubric is a scaffold coordinate, each accepted edit to it moves the instrument that judges the next edit. No method that co-evolves a rubric or judge reports agreement with human judgment, and no scaffold system calibrates a judge under edit (Section IV); the nearest measurement is on the human side, where evaluators' criteria drift as they grade [39].
4. **Delayed signals: telling descent from search.** Where the outcome arrives after many edits, an optimizer's gains cannot be distinguished from trial-and-error by outcome alone [43]; evaluating harness optimizers against their attribution claims rather than their scores is the open method.
5. **The governed cross-organization loop.** The architecture of Section IX, properties (a) through (d), is documented by no surveyed system; the receiving-side gate of problem 2 is the piece that would make cross-organization promotion safe in the two classes where it should be automatic.

The field has built an external adaptation layer for language models but not, as far as public evidence shows, the optimizer that should govern it. Both earlier papers of this series supply the hypothesis for why the layer belongs where it is: errors concentrate in a few key decisions; inside a bounded deployment, those decisions fail in a small and recurring catalogue of modes; and such a catalogue can be fixed one mode at a time in a persistent, inspectable, reversible artifact outside the weights. The corpus is consistent with that hypothesis. If it holds, the gated and scoped artifact layer is not a workaround but the architecture the error structure calls for.

Seen whole, the corpus says the industry has built most of that optimizer piecemeal. The local loop closes automatically in most research systems and in a growing number of production ones; evidence is batched before acceptance; retirement is gated; memory ships with its lineage; formats and registries have converged; and the first federations promote edits across deployments inside one operator. What nobody has done is assemble the pieces. No surveyed system promotes a validated edit across an organization boundary under an automatic gate with lineage, access control, and rollback. Read by signal class, this is not one gap but four, each with its own reachable answer. Under every class the same rule holds: a lift travels only as far as its measure does.

The frontier model generalizes. The local scaffold specializes. Reliability comes from governing that specialization. Because the instruments that judge each edit are themselves part of the moving scaffold, the same evidence-radius and lifecycle discipline the optimizer needs must extend to the gates that judge it.

XII. APPENDIX: FORMAL STATEMENT OF ARTIFACT-LAYER DESCENT

This appendix states the setup behind Section III, a one-step descent inequality under a noisy gate, an informal convergence proposition, the optimization-analogy correspondence, and four worked cases. No new theorem is claimed; the proposition is the ordinary target of local stochastic optimization under noisy estimators, restated for a discrete, versioned parameter.

A. SETUP

Let the frontier model have fixed parameters θ_M and let the scaffold be a structured object $\theta_s \in \Theta_s = \Theta_1 \times \cdots \times \Theta_6$ over the six substrate coordinates of Section V; Θ_s is discrete, symbolic, and versioned. For a deployment D, $L_D(\theta_s) = \mathbb{E}_{x\sim D}[\ell(\pi(\theta_M, \theta_s, x))]$. A candidate edit $z_t \sim Q_t(z \mid H_t, \theta_s^t)$ is drawn from a proposal process conditioned on the accumulated history H_t of failures, corrections, rejected outputs, evaluation regressions, and prior accepted edits. Q_t is not uniform: for a mode m that recurs with frequency f_m and carries per-occurrence loss s_m, its expected contribution to the failure rate is $f_m s_m$, so high-frequency or high-severity modes are proposed first. The finite directional difference is $\Delta_z L_D(\theta_s) = L_D(\theta_s \oplus z) - L_D(\theta_s)$; the gate sees only a noisy estimate $\widehat{\Delta}_z L_D$. The update is

$$\theta_s^{t+1} = \theta_s^t \oplus z_t \text{ if } G_t(z_t) = 1, \quad \theta_s^{t+1} = \theta_s^t \text{ otherwise.}$$

B. DESCENT INEQUALITY

Assume (A1) positive descent bias on accepted edits, $\mathbb{E}[\widehat{\Delta}_{z_t} L_D \mid G_t = 1, \theta_s^t] \le -\gamma_t - \tau_t$ for some $\gamma_t > 0$, and (A2) bounded estimator bias on accepted edits, $|\mathbb{E}[\Delta_{z_t} L_D - \widehat{\Delta}_{z_t} L_D \mid G_t = 1, \theta_s^t]| \le \varepsilon_t$. With $p_t = \Pr(G_t = 1 \mid \theta_s^t)$,

$$\mathbb{E}[L_D(\theta_s^{t+1}) \mid \theta_s^t] \le L_D(\theta_s^t) - p_t(\gamma_t + \tau_t) + p_t\,\varepsilon_t.$$

Per-step expected improvement is the gate's margin minus its estimator bias, weighted by acceptance probability. In the feedback-signal classes of Section IV, ε_t is near zero for the check itself in C1, with the sampling error of a finite suite over the patch remaining, bounded by batching for an observable outcome (C2), equal to the judge's bias and bounded only by calibration for a judged signal (C3), and unavailable per edit for a delayed signal (C4).

C. CONVERGENCE (INFORMAL)

Add (A3) proposal coverage with acceptance: at every non-gate-stable scaffold, Q_t places probability at least $q > 0$ on an admissible edit with $\mathbb{E}[\Delta_z L_D] \le -\delta$, and the gate accepts such an edit with probability at least $q' > 0$, so that $p_t(\gamma_t + \tau_t) \ge qq'\delta$ there; (A4) effective compactness of the reachable orbit; and (A5) summable bias, $\sum_t p_t \varepsilon_t < \infty$; and let $0 \le L_D \le B$. The one-step inequality is then of the Robbins–Siegmund form, a non-negative process that decreases in expectation up to a summable perturbation $p_t\varepsilon_t$, so $L_D(\theta_s^t)$ converges almost surely and $\sum_t p_t(\gamma_t + \tau_t) < \infty$ almost surely [150]. The finite sum carries the content: a bounded loss cannot pay for infinitely many accepted edits with a positive expected margin, so under (A3) the process visits non-gate-stable scaffolds only finitely often, and with (A4) the limit set of $\{\theta_s^t\}$ is gate-stable: no admissible edit clears the gate with negative expected directional loss in the limit. This is convergence of the loss and stability of the gate decision, not convergence to an optimum; a globally suboptimal gate-stable scaffold is consistent with the result, because Q_t may never propose the improving edit or $\widehat{\Delta}$ may be biased to reject it. In a non-stationary deployment ($D = D_t$) the same mechanism tracks a moving optimum rather than converging once, which is why recency weighting, pruning, expiry, and rollback are the scaffold-level analogues of continual-learning machinery rather than optional hygiene.

D. CORRESPONDENCE

Table 9 pairs each optimization concept with its scaffold analogue. Credit assignment here is attribution, not backpropagation. Scaffold systems do not differentiate through instruction files. They trace an output error to an upstream coordinate, manually or with a judge or verifier. The descent argument needs only that this attribution succeeds with nonzero probability per failure, which is the credit-assignment condition of Section III.

E. WORKED CASES

Retrieval. Failures recur because retrieved context omits the decisive clause. Attribution traces the error to the retrieval coordinate: chunking, query rewriting, metadata filter, embedding model, reranker, or context-packing rule. The candidate edit tightens chunk boundaries or adds a metadata constraint, and the gate checks that recall and answer accuracy improve on the patch evaluation without degrading adjacent cases. Signal class C1 or C2.

Pitch review. The system repeatedly overrates decks that claim a large market without numbers, and the failure cluster points at an under-specified rubric coordinate. The edit

TABLE 9. Optimization concepts and their scaffold analogues.

Optimization concept	Scaffold analogue
Parameter vector	Instructions, skills, memories, tools, routing graphs, evaluation gates, governance rules
Loss	Failure, user correction, evaluation regression, retrieval miss, tool error, schema violation
Gradient estimate	Credit assignment identifying the coordinate responsible for a failure
Step	Accepted scaffold edit; step size is edit magnitude under $\oplus$
Aggregated update	Several recurring failures combined before an update, by averaging or by agreement across k proposals
Update radius	Promotion scope: which loss is descended (USER, PROJECT, STACK, TENANT, CORE)
Validation loss	Held-out patch evaluation before merge
Regularization	Complexity penalty $\Omega(z)$, bloat control, cross-patch regression checks
Overfitting	Scaffold improves on this deployment and degrades elsewhere
Rollback	Reverting a harmful accepted update

changes ''evaluate market size'' into ''require a numeric estimate and a source; if absent, cap the score''; the gate runs the revised rubric against held-out decks with human scores. What the edit changed was the gate that will judge the next edit: the reflexive gate of Section IV, class C3.

Tool use. Calls fail because optional parameters are underspecified. The responsible coordinate may be the tool schema, the call policy, or the clarification rule. The edit adds required fields or a pre-call uncertainty check; the gate checks that tool-call failures fall without raising refusals or latency. Class C2.

Memory. A stale customer preference is repeatedly retrieved and causes bad decisions. The responsible coordinate is a memory entry together with its provenance, priority, and expiry policy. The edit corrects, expires, or version-tags the entry; the gate checks that future behavior improves without erasing useful history. Class C2, with the correction itself observable only when a later outcome reveals it.

XIII. APPENDIX: GATE FAMILIES AND FEEDBACK-SIGNAL CLASSES

Section III collapses every production gate into one per-edit test G_t on an estimate of the loss change. Surveyed systems instantiate that test in several distinct ways, and some of them are better read as proposal pruning that precedes the per-edit gate than as estimators of $\widehat{\Delta}L_D$. Table 10 lists the families, the slot each occupies, representative systems, and the feedback-signal class (Section IV) each family serves.

The first five families populate G_t directly and, under the assumptions of Appendix XII, inherit its descent guarantee. Semantic merge and archive selection are not estimators of $\widehat{\Delta}L_D$; they constrain the proposal distribution, and the descent argument applies to the composition of pruning and gate. Multi-sample agreement is listed because it is the correct analogue of ''wait for k pieces of evidence before accepting an edit'', a different operation from mini-batch averaging and one that should not be conflated with it. Read down the signal-class column. The only families available to a judged (C3) deployment are the two whose estimator is a judge, and a delayed (C4) deployment has no family that estimates the loss change per edit at all: what it has is semantic merge before the gate and whatever proxy milestone stands at the horizon. That is the structural content of Section IV.

ACKNOWLEDGMENT

The authors used an AI assistant (Claude, Anthropic) to help search the literature, check citations, and edit prose; all claims, scores, and classifications were reviewed and approved by the authors. Earlier versions of this argument appeared as an arXiv preprint and as a non-archival workshop submission; this article extends them with the feedback-signal classification of Section IV and a corpus scored through October 2026.

REFERENCES

[1] M. Zaharia, O. Khattab, L. Chen, J. Q. Davis, H. Miller, C. Potts, J. Zou, M. Carbin, J. Frankle, N. Rao, and A. Ghodsi, ''The shift from models to compound AI systems,'' Berkeley Artificial Intelligence Research (BAIR) Blog, https://bair.berkeley.edu/blog/2024/02/18/compound-ai-systems/, 2024.

[2] R. Kirk, I. Mediratta, C. Nalmpantis *et al.*, ''Understanding the effects of RLHF on LLM generalisation and diversity,'' in *ICLR 2024*, 2024.

[3] V. Padmakumar and H. He, ''Does writing with language models reduce content diversity?'' *arXiv preprint*, 2023.

[4] R. Tiwari, K. Sareen, L. A. Agrawal, J. E. Gonzalez, M. Zaharia, K. Keutzer, I. S. Dhillon, R. Agarwal, and D. Khatri, ''Learning, fast and slow: Towards LLMs that adapt continually,'' *arXiv preprint*, 2026.

[5] S. Dohare *et al.*, ''Loss of plasticity in deep continual learning,'' *Nature*, vol. 632, no. 8026, pp. 768–774, 2024.

[6] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, ''LoRA: Low-rank adaptation of large language models,'' *arXiv preprint arXiv:2106.09685*, 2021.

[7] M. L. Arbuzov, S. Bei, Z. Dong, D. Kalaev, and A. A. Shvets, ''Beyond exponential decay: Rethinking error accumulation in large language models,'' *arXiv preprint*, 2025.

[8] M. L. Arbuzov, L. Mosbacker, S. Bei, Z. Dong, D. Kalaev, and A. Shvets, ''The architecture of errors: From universal impossibility to patch-local LLM reliability,'' *arXiv preprint arXiv:2605.30628*, 2026.

[9] T. Ding, A. Nannapaneni, B. Liu, and L. Zhang, ''Always-on agents: A survey of persistent memory, state, and governance in LLM agents,'' *arXiv preprint arXiv:2606.30306*, 2026.

[10] Z. Lin, X. Hao, R. Fu, S. Cui, K. Chen, C. Li, Z. Li, and F. Xiong, ''A survey on long-term memory security in LLM agents: Attacks, defenses, and governance across the memory lifecycle,'' in *Proceedings of EMNLP 2026*, 2026, arXiv:2604.16548v3, 22 Sep 2026.

[11] H.-a. Gao, J. Geng, W. Hua, M. Hu, X. Juan *et al.*, ''A survey of self-evolving agents: What, when, how, and where to evolve on the path to ar-

TABLE 10. Gate families, their slot in the formalism, and the feedback-signal class each serves.

Gate family	What it estimates	Slot in Section III	Signal class	Representative systems
Surrogate verifier	Pass or fail from tests, a symbolic checker, or an exact match	Per-edit gate G_t	C1	DGM (sandboxed compile-and-edit check; score weights selection, not retention), SkillOpt (held-out exact match), Voyager (game-state check: C2)
Evaluation cascade	$\widehat{\Delta}L_D$ on a held-out task suite, cheap-to-expensive evaluators	Per-edit gate G_t	C1 when the suite is exact; C2 when it is a task suite	AlphaEvolve, Braintrust, Vellum, LangSmith Hub
RL threshold	Reward improvement against a deployment threshold	Per-edit gate G_t	C2	SAGE, PACE
LLM judge with calibration	Pairwise or rubric score, calibrated against human agreement	Per-edit gate G_t	C3	SkillChain (judge stage, before its human reflection gate)
Reviewer judgment	Human credit assignment by pull-request review, expert sign-off, or a user's acceptance	Per-edit gate G_t, human-instantiated	C3 (and C2 when the reviewer has outcome data)	Sierra Agent OS 2.0, Anthropic skills repository, CASCADE (the user's satisfaction click gates the memory write)
Semantic merge	Whether a candidate duplicates or conflicts with existing artifacts	Proposal pruning before G_t	C4 (also a pre-filter in C2, C3)	NanoResearch orchestrator, FederatedSkill server agent, EvolveR (admission: cosine pre-filter plus LLM equivalence judgment on each distilled principle; retention: periodic pruning on per-principle success rate)
Archive selection	Whether a candidate improves on, or diversifies, an archive of already-scored programs	Proposal pruning before G_t	Any; inherits the class of the evaluator that scored the archive (C1 in AlphaEvolve)	AlphaEvolve (MAP-Elites-style database), ADAS
Multi-sample agreement	Whether k independent proposals or evaluations agree; false-accept rate decays as p^k rather than variance as $1/k$	Aggregation filter on the estimate	C2, C3 noise absorption	VaG (three heterogeneous critics must all pass); SkillOpt-Lite (consensus filter across rollouts)

tificial super intelligence," *Transactions on Machine Learning Research*, 2026, arXiv:2507.21046v4, 16 Jan 2026.

[12] J. Fang, Y. Peng, X. Zhang, Y. Wang, X. Yi, G. Zhang, Y. Xu, B. Wu, S. Liu, Z. Li, Z. Ren, N. Aletras, X. Wang, H. Zhou, and Z. Meng, "A comprehensive survey of self-evolving AI agents: A new paradigm bridging foundation models and lifelong agentic systems," *arXiv preprint arXiv:2508.07407*, Aug. 2025.

[13] H. Zhou, H. Hu, T. Luo, Y. Shang, C. Fang, Z. Chen, L. Xiao, and Q. Zhang, "Self-evolving coding agents," *arXiv preprint arXiv:2608.03392*, Aug. 2026.

[14] J. Guo, Z. Hao, C. Wang, C. Fan, T. Luo, H. Li, Y. Gao, H. Mei, J. Peng, R. Xu, M. Dong, H. Wu, M. Zheng, K. Han, S. Wang, C. Xu, and Y. Wang, "From question answering to task completion: A survey on agent system and harness design," *arXiv preprint arXiv:2606.20683*, Jun. 2026.

[15] B. Xia, L. Zhu, Z. Xing, Q. Lu, D. Sejdinovic, and X. Xu, "Harnessing agent skills: Architectural patterns and a reference architecture for skill-mediated LLM agents," *arXiv preprint arXiv:2606.20631*, May 2026.

[16] K. Ding, Y. Zhou, C. Jin, F. Tong, M. Zhou, and D. N. Metaxas, "Agent skill evaluation and evolution: Frameworks and benchmarks," *arXiv preprint arXiv:2606.11435*, Jun. 2026.

[17] L. Mei, J. Yao, Y. Ge, Y. Wang, B. Bi, Y. Cai, J. Liu, M. Li, Z.-Z. Li, D. Zhang, C. Zhou, J. Mao, T. Xia, J. Guo, and S. Liu, "A survey of context engineering for large language models," *arXiv preprint arXiv:2507.13334*, Jul. 2025.

[18] C. Yang, X. Wang, Y. Lu, H. Liu, Q. V. Le, D. Zhou, and X. Chen, "Large language models as optimizers," in *International Conference on Learning Representations (ICLR)*, 2024, arXiv:2309.03409.

[19] Q. Guo, R. Wang, J. Guo, B. Li, K. Song, X. Tan, G. Liu, J. Bian, and Y. Yang, "EvoPrompt: Connecting LLMs with evolutionary algorithms yields powerful prompt optimizers," in *International Conference on Learning Representations (ICLR)*, 2024, arXiv:2309.08532.

[20] C. Fernando, D. Banarse, H. Michalewski, S. Osindero, and T. Rocktäschel, "Promptbreeder: Self-referential self-improvement via prompt evolution," *arXiv preprint arXiv:2309.16797*, 2023.

[21] O. Khattab, A. Singhvi, P. Maheshwari, Z. Zhang, K. Santhanam, S. Vardhamanan, S. Haq, A. Sharma, T. T. Joshi, H. Moazam, H. Miller, M. Zaharia, and C. Potts, "DSPy: Compiling declarative language model calls into self-improving pipelines," *arXiv preprint arXiv:2310.03714*, 2023.

[22] M. Yuksekgonul, F. Bianchi, J. Boen, S. Liu, Z. Huang, C. Guestrin, and J. Zou, "TextGrad: Automatic "differentiation" via text," *arXiv preprint*, 2024.

[23] Q. Zhang, C. Hu, S. Upasani *et al.*, "Agentic context engineering: Evolving contexts for self-improving language models," arXiv preprint arXiv:2510.04618, 2025.

[24] W. Zhou, Y. Ou, S. Ding, L. Li, J. Wu, T. Wang, J. Chen, S. Wang, X. Xu, N. Zhang, H. Chen, and Y. E. Jiang, "Symbolic learning enables self-evolving agents," *arXiv preprint arXiv:2406.18532*, 2024.

[25] E. Zelikman, E. Lorch, L. Mackey, and A. T. Kalai, "Self-taught optimizer

(STOP): Recursively self-improving code generation," in *First Conference on Language Modeling (COLM 2024)*, 2024, arXiv:2310.02304.

[26] M. Robeyns, M. Szummer, and L. Aitchison, "A self-improving coding agent," *arXiv preprint arXiv:2504.15228*, 2025.

[27] L. Zheng, W.-L. Chiang, Y. Sheng, S. Zhuang, Z. Wu, Y. Zhuang, Z. Lin, Z. Li, D. Li, E. P. Xing, H. Zhang, J. E. Gonzalez, and I. Stoica, "Judging LLM-as-a-judge with MT-Bench and Chatbot Arena," in *Advances in Neural Information Processing Systems (NeurIPS 2023), Datasets and Benchmarks Track*, 2023, arXiv:2306.05685.

[28] E. Palumbo, A. Tamborrino, V. Ode, B. Lacker, A. Casas Escoda, J. Hopple, M. Better, J. Leoni, H. Galvão, H. Bouchard, M. Lalmas, J. L. Redondo García, A. Abebe, A. Clifton, A. Blomberg, H. Lindström, D. Doro, and C. Doig Cardet, "Bootstrapping conversational recommendation agents at spotify: Synthetic data generation and self-improvement loops," *arXiv preprint arXiv:2609.30297*, 2026.

[29] J. Zhang *et al.*, "Darwin Gödel machine: Open-ended evolution of self-improving agents," *arXiv preprint*, 2025.

[30] A. Novikov *et al.*, "AlphaEvolve: A coding agent for scientific and algorithmic discovery," arXiv preprint arXiv:2506.13131, 2025.

[31] Y. Yang, Z. Gong, W. Huang, Q. Yang, Z. Zhou, Z. Huang, Y. Li, X. Gao, Q. Dai, B. Liu, K. Qiu, Y. Yang, D. Chen, X. Yang, and C. Luo, "SkillOpt: Executive strategy for self-evolving agent skills," arXiv preprint arXiv:2605.23904, 2026. [Online]. Available: https://microsoft.github.io/SkillOpt

[32] Cognition, "Devin's 2025 performance review: Learnings from 18 months of agents at work," https://cognition.com/blog/devin-annual-performance-review-2025, 2025.

[33] J. Wang *et al.*, "Reinforcement learning for self-improving agent with skill library," *arXiv preprint*, 2025.

[34] C. Ling, P. Chen, A. Guan, J. Qu, S. A. Akbar, M. Gopinathan, and E. Cornejo, "PACE: Two-timescale self-evolution for small language model agents," *arXiv preprint*, 2026.

[35] P. Xia *et al.*, "SkillRL: Evolving agents via recursive skill-augmented reinforcement learning," *arXiv preprint*, 2026.

[36] X. Liu *et al.*, "SkillForge: Forging domain-specific, self-evolving agent skills in cloud technical support," *arXiv preprint*, 2026, accepted at ACM SIGIR 2026 Industry Track.

[37] X. Huang *et al.*, "CASCADE: Cumulative agentic skill creation through autonomous development and evolution," *arXiv preprint*, 2025.

[38] L. Gao, J. Schulman, and J. Hilton, "Scaling laws for reward model overoptimization," *arXiv preprint arXiv:2210.10760*, 2022.

[39] S. Shankar, J. Zamfirescu-Pereira, B. Hartmann, A. G. Parameswaran, and I. Arawjo, "Who validates the validators? aligning LLM-assisted evaluation of LLM outputs with human preferences," *arXiv preprint arXiv:2404.12272*, 2024.

[40] C. Lu, C. Lu, R. T. Lange, J. Foerster, J. Clune, and D. Ha, "The AI scientist: Towards fully automated open-ended scientific discovery," *arXiv preprint arXiv:2408.06292*, 2024.

[41] J. Xu *et al.*, "NanoResearch: Co-evolving skills, memory, and policy for personalized research automation," *arXiv preprint*, 2026.

[42] A. Qu, H. Zheng, Z. Zhou, Y. Yan, Y. Tang, S. Y. Ong, F. Hong, K. Zhou, C. Jiang, M. Kong, J. Zhu, X. Jiang, S. Li, C. Wu, B. K. H. Low, J. Zhao, and P. P. Liang, "CORAL: Towards autonomous multi-agent evolution for open-ended discovery," *arXiv preprint*, 2026.

[43] K. T.-i. Ong, M. Kang, D. Choi, J. Cho, S. Kim, S. Lim, G. Jang, M. Oh, B. Jeong, S. Kim, T. Kwon, and J. Yeo, "Towards direct evaluation of harness optimizers via priority ranking," *arXiv preprint*, 2026.

[44] Y. Hu, M. Xu, H. Guo, Y. Song, X. Zhu, and B. Zheng, "Skillchain: Closing the loop on skill evolution for image-based e-commerce ai assistants," *arXiv preprint arXiv:2606.12984*, 2026.

[45] J. Zhu, K. Mao, Y. Guo, D. He, S. Xu, S. Gu, and Y. Yue, "Skillcoach: Self-evolving rubrics for evaluating and enhancing agentic skill-use," *arXiv preprint arXiv:2607.01874*, 2026.

[46] A. Gunjal, A. Wang, E. Lau, V. Nath, Y. He, B. Liu, and S. Hendryx, "Rubrics as rewards: Reinforcement learning beyond verifiable domains," *arXiv preprint arXiv:2507.17746*, 2025.

[47] R. Jia, Y. Yang, Y. Gai, K. Luo, S. Huang, J. Lin, X. Jiang, and G. Jiang, "Writing-zero: Bridge the gap between non-verifiable tasks and verifiable rewards," *arXiv preprint arXiv:2506.00103*, 2025.

[48] K. Shi, Y. Liu, P. Wang, A. R. Fabbri, S. Joty, and A. Cohan, "References improve LLM alignment in non-verifiable domains," *arXiv preprint arXiv:2602.16802*, Feb. 2026.

[49] X. Jin, J. Zhang, T. Cao, and B. Yang, "Beyond score prediction: LLM-based essay scoring and feedback generation via reinforcement learning with rubric rewards," *arXiv preprint arXiv:2607.19219*, Jul. 2026.

[50] T. Yu, B. Ji, S. Wang, S. Yao, Z. Wang, G. Cui, L. Yuan, N. Ding, Y. Yao, Z. Liu, M. Sun, and T.-S. Chua, "RLPR: Extrapolating RLVR to general domains without verifiers," *arXiv preprint arXiv:2506.18254*, Jun. 2025.

[51] R. Xu, T. Liu, Z. Dong, T. Yu, I. Hong, C. Yang, L. Zhang, T. Zhao, and H. Wang, "Alternating reinforcement learning for rubric-based reward modeling in non-verifiable LLM post-training," *arXiv preprint arXiv:2602.01511*, 2026.

[52] H. Ding, B. Huang, Y. Fang, W. Liao, Z. Li, J. Zhang, Z. Wu, J. Zhao, and Y. Wang, "EvoRubrics: Dynamic rubrics as rewards via adversarial co-evolution for LLM reinforcement learning," *arXiv preprint arXiv:2606.23038*, Jun. 2026.

[53] H. Zhu, C. Cai, Y. Song, X. Chen, S. Han, and Y. Guo, "Self-evolving deep research via joint generation and evaluation," *arXiv preprint arXiv:2606.04507*, Jun. 2026.

[54] G. Li, B. Dalvi Mishra, Z. Wang, J. Yan, Y. Chen, C.-L. Li, L. T. Le, R. Han, G. Lee, H. Tong, C.-Y. Lee, and T. Pfister, "RubricEM: Meta-RL with rubric-guided policy decomposition beyond verifiable rewards," *arXiv preprint arXiv:2605.10899*, May 2026.

[55] T. R. Sumers, S. Yao, K. Narasimhan, and T. L. Griffiths, "Cognitive architectures for language agents (CoALA)," *Transactions on Machine Learning Research (TMLR)*, 2023.

[56] M. Helwig, "Memory as infrastructure: Reliability engineering for persistent agent memory in months-long LLM-assisted development," *arXiv preprint arXiv:2609.05510*, Aug. 2026.

[57] A. Miyai, K. Aizawa, and T. Yamasaki, "Task-coevolve: Efficient harness optimization via adaptive validation task selection," *arXiv preprint arXiv:2608.20169*, 2026.

[58] S. Park, W. Kim, R. Tan, J. Zhang, W.-S. Han, P. Gao, C. Park, Y. Yao, R. Fu, E. Nallipogu, Q. Lin, S. Rajmohan, and D. Zhang, "Autosaddler: Automatic harness optimization with durable updates from agent execution traces," *arXiv preprint arXiv:2608.23041*, 2026.

[59] J. Lin, S. Liu, C. Pan, L. Lin, S. Dou, Z. Xi, X. Huang, H. Yan, Z. Han, T. Gui, and Y.-G. Jiang, "Agentic harness engineering: Observability-driven automatic evolution of coding-agent harnesses," *arXiv preprint*, 2026.

[60] T. Zehle, "CANTANTE: Optimizing agentic systems via contrastive credit attribution," *arXiv preprint*, 2026.

[61] Y. Lee, R. Nair, Q. Zhang, K. Lee, O. Khattab, and C. Finn, "Meta-Harness: End-to-end optimization of model harnesses," *arXiv preprint*, 2026.

[62] M. Nguyen, W. C. Tan, N. A. Hassan, A. Raman, L. H. Lim, and A. F. Razak, "Where does harness-optimization value live? Localized gains and the budget-splitting trap in self-evolving LLM agents," *arXiv preprint arXiv:2609.02889*, 2026.

[63] H. Liu, H. Yang, T. Jiang, B. Tang, F. Xiong, Y. Luo, and Z. Li, "SkillsVote: Lifecycle governance of agent skills from collection, recommendation to evolution," *arXiv preprint arXiv:2605.18401*, 2026.

[64] Y. Shen, B. Li, and X. Zhang, "SkillOpt-Lite: Better and faster agent self-evolution via one line of vibe," *arXiv preprint arXiv:2607.03451*, 2026.

[65] C. Shen and E. Hruschka, "Who maintains agent skills? A longitudinal study of human-governed, AI-assisted skill maintenance," *arXiv preprint arXiv:2609.05677*, 2026.

[66] X. Zhang, Y. Cui, G. Wang, Z. Li, W. Qiu, B. Zhu, and P. He, "Library drift: Diagnosing and fixing a silent failure mode in self-evolving llm skill libraries," *arXiv preprint arXiv:2605.19576*, 2026.

[67] Y. Wei, Z. Huang, S. Lu, J. Qian, Q. Wang, C. Wu, and L. He, "Skillsmith: Co-evolving skills and tools for self-improving agent systems," *arXiv preprint arXiv:2606.01314*, 2026.

[68] H. Pu, X. Song, and L. Zhao, "Skillops: Managing llm agent skill libraries as self-maintaining software ecosystems," *arXiv preprint arXiv:2605.13716*, 2026.

[69] Y. Wang, Y. Zhou, Y. Liang, C. Zhang, F. Liu, J. Zhou, and H. Yao, "Not all skills help: Measuring and repairing agent knowledge," *arXiv preprint arXiv:2606.15390*, 2026.

[70] X. Zhang, Y. Cui, G. Wang, Z. Li, W. Qiu, B. Zhu, and P. He, "Ratchet: A minimal hygiene recipe for self-evolving LLM agents," *arXiv preprint*, 2026.

[71] X. Wu *et al.*, "Co-evolving LLM decision and skill bank agents for long-horizon tasks," *arXiv preprint*, 2026.

[72] M. Zhuge, W. Wang, L. Kirsch, F. Faccio, D. Khizbullin, and J. Schmidhuber, "Language agents as optimizable graphs," in *Forty-first International Conference on Machine Learning (ICML 2024)*, 2024, arXiv:2402.16823.

[73] J. Zhang, J. Xiang, Z. Yu, F. Teng, X. Chen, J. Chen, M. Zhuge, X. Cheng, S. Hong, J. Wang, B. Zheng, B. Liu, Y. Luo, and C. Wu, "AFlow: Automating agentic workflow generation," *arXiv preprint arXiv:2410.10762*, 2024.

[74] J. Chu, J. Seo, J. Cho, J. Na, Y. Xiong, Y. Kim, and H. J. Kim, "Agentgrad: Intervention-guided prompt optimization for multi agent systems," *arXiv preprint arXiv:2609.08572*, 2026.

[75] M. Chen, C. Lv, G. Zhang, H. Chang, and S. Zhou, "Harnessforge: Joint harness and policy evolution for adaptive agent systems," *arXiv preprint arXiv:2606.01779*, 2026.

[76] S. Zhao, R. Kong, Z. Zhang, L. Shen, X. He, X. Zhang, and Q. Zhang, "Topological coherence for self-evolving multi-agent systems," *arXiv preprint arXiv:2609.37953*, 2026.

[77] Y. Cheng, C. Liu, H. Yu, H. Tan, T. Wu, W. Jin, J. Ran, K. Wang, X. Li, H. Bai, G. Chesi, and N. Wong, "Optimas: Automatically optimize multi-agent system," *arXiv preprint arXiv:2608.21918*, 2026.

[78] AGENTS.md, "AGENTS.md: A cross-vendor open standard for agent instructions," 2025. [Online]. Available: https://agents.md

[79] R. Robbes, T. Matricon, T. Degueule, A. Hora, and S. Zacchiroli, "Agentic much? adoption of coding agents on github," *arXiv preprint arXiv:2601.18341*, 2026.

[80] M. Galster, S. Mohsenimofidi, J. L. Lulla, M. A. Abubakar, C. Treude, and S. Baltes, "Harness engineering for agentic ai coding tools: An exploratory study," *arXiv preprint arXiv:2602.14690*, 2026.

[81] T. Gloaguen, N. Mündler-Sasahara, M. N. Müller, V. Raychev, and M. Vechev, "Evaluating agents.md: Are repository-level context files helpful for coding agents?" *arXiv preprint arXiv:2602.11988*, 2026.

[82] J. L. Lulla *et al.*, "On the impact of AGENTS.md files on the efficiency of AI coding agents," *arXiv preprint*, 2026.

[83] T. Q. Nguyen, S. Desai, R. H. Anwar, F. Shaik, V. Suryanarayanan, and V. Chowdhary, "VerificAgent: Domain-specific memory verification for scalable oversight of aligned computer-use agents," *arXiv preprint arXiv:2506.02539*, Jun. 2025.

[84] Y. Wang, L. Xia, R. Liu, Z. Zhang, H. Wu, Y. Yang, J. He, Y. Guo, and K. Lei, "Sage: A statistical acceptance gate for self-evolving agents," *arXiv preprint arXiv:2609.36043*, 2026.

[85] L. Shang, M. Xu, Y. Sun, T. Xia, L. Hu, L. Xu, and N. Zheng, "When self-evolution backfires: Pre-commit gating against skill contamination in llm agents," *arXiv preprint arXiv:2608.05810*, 2026.

[86] Letta, "MemFS; memory & dreaming; introducing context repositories: Git-based memory for coding agents," https://docs.letta.com/letta-code/memfs, https://docs.letta.com/letta-agent/memory, https://www.letta.com/blog/context-repositories/, 2026.

[87] Mem0, "Mem0 platform: Memory history, feedback, and changelog," https://docs.mem0.ai/api-reference/memory/history-memory, https://docs.mem0.ai/api-reference/memory/feedback, https://docs.mem0.ai/changelog, 2026.

[88] Zep, "Zep documentation: Facts; february 2026 deprecation wave; changelog," https://help.getzep.com/facts, https://help.getzep.com/february-2026-deprecation-wave, https://help.getzep.com/changelog/2026/9/24, 2026.

[89] Z. Wang, "TOKI: A bitemporal operator algebra for contradiction resolution in LLM-agent persistent memory," *arXiv preprint arXiv:2606.06240*, Jun. 2026.

[90] J. Xu, Y. Xiao, W. Shao, H. Liu, and X. Li, "Memory provenance laundering in LLM agents: A non-amplification firewall for persistent memory," *arXiv preprint arXiv:2607.29167*, Jul. 2026.

[91] Y. Margalit, N. Cohen-Inger, E. Avram, R. Taig, and O. Margalit, "Governed shared memory for multi-agent LLM systems," *arXiv preprint arXiv:2606.24535*, Jun. 2026.

[92] Z. Yu, Y. Wu, Z. Yin, K. Chen, Z. Zhao, M. Wang, S. Yan, and L. Yang, "Recursive experiential–working memory evolution for long-horizon agent harnesses," *arXiv preprint arXiv:2608.24876*, Aug. 2026.

[93] H. Wang, G. Dong, H. Liang, Z. Zhang, J. Luo, C. Liu, C. Xue, and H. Tang, "MemGuard: Persisting verifier signals for LLM-agent memory governance," *arXiv preprint arXiv:2608.21867*, Aug. 2026.

[94] X. Sun, Q. Wang, H. Li, and L. Chen, "Verifiable memory: Learning unified memory management with local and global verifiers for large language model agents," *arXiv preprint arXiv:2608.03137*, Aug. 2026.

[95] D. F. Cuadros, A.-A. Maiga, H. Meskhidze, and A. Curtis-Trudel, "Governed collaborative memory as artificial selection in LLM-based multi-agent systems," *arXiv preprint*, 2026.

[96] Y. T. Shen, K. Toyoda, and A. Leung, "Revoked but still authoritative: An empirical study of revocation enforcement in agent-memory systems," *arXiv preprint arXiv:2609.08258*, Sep. 2026.

[97] H. Gao, H. Chen, C. Wang, S. Guo, L. Pang, Z. Liu, H. Shen, and X. Cheng, "Skillaudit: Ground-truth-free skill evolution via paired trajectory auditing," *arXiv preprint arXiv:2606.14239*, 2026.

[98] T. Sah, D. Sah, H. Jain, and T. Sah, "Evoundo: Recoverability-constrained self-evolution for llm agent harnesses," *arXiv preprint arXiv:2608.28363*, 2026.

[99] J. Hu, H. Zhao, Q. Jia, D. Chen, T. Zhao, S. Duan, and G. Liu, "Learning from others, acting for you: Cross-user memory sharing for llm agents," *arXiv preprint arXiv:2609.32511*, 2026.

[100] Y. Guo, H. Zhou, J. Zhang, Y. Zhang, Y. Liu, Q. Chen, Q. Lin, H. Dong, J. M. Zhang, and Z. Chen, "Xreposkill: Learning transferable skills for software engineering agents," *arXiv preprint arXiv:2609.36807*, 2026.

[101] R. Wang and J. Cui, "Evo2team: When do evolved skills transfer? from selection to deployment," *arXiv preprint arXiv:2609.34135*, 2026.

[102] J. Nie, Y. Zhang, Q. Cai, Y.-m. Cheung, X. Tian, and B. Han, "Evolvenet: Collaborative harness evolution for agent self-improvement," *arXiv preprint arXiv:2608.04968*, 2026.

[103] J. Yang, G. Yao, Y. Zhang, R. R. Kompella, G. Liu, and S. Chang, "FederatedSkill: Federated learning for agentic skill evolution," *arXiv preprint arXiv:2606.03143*, 2026.

[104] J. Qi, Y. He, J. Liu, Q. Huang, S. Hu, Z. Dang, G. Chen, R. Yang, W. Jiang, Y. Liu, T. Lyu, and F. Li, "Vace: Validation-gated alternating co-evolution of agent models and harnesses," *arXiv preprint arXiv:2609.37105*, 2026.

[105] J. Chu, J. S. Lee, J. Park, D. Ko, J. Na, S. Lee, T. Lee, M. Yoon, M. Joo, Y. Xiong, and H. J. Kim, "Retrieval-augmented skill optimization via cross-harness adaptation," *arXiv preprint arXiv:2609.38024*, 2026.

[106] B. Romera-Paredes, M. Barekatain, A. Novikov, M. Balog, M. P. Kumar, E. Dupont, F. J. R. Ruiz, J. S. Ellenberg, P. Wang, O. Fawzi, P. Kohli, and A. Fawzi, "Mathematical discoveries from program search with large language models," *Nature*, vol. 625, pp. 468–475, 2024.

[107] Sierra, "Agent OS 2.0: From answers to memory and action," 2025. [Online]. Available: https://sierra.ai/blog/agent-os-2-0

[108] P. Barbaste, T. Darrigol, G. Vu, and T. Wiltberger, "Harness engineering: Anatomy, architecture, and evolution of coding agents – a source-code study of eleven systems," *arXiv preprint arXiv:2609.00006*, 2026.

[109] agentic-community, "Mcp gateway & registry," https://github.com/agentic-community/mcp-gateway-registry, 2026.

[110] Microsoft, "Inventory and discover mcp servers in your api center," https://learn.microsoft.com/en-us/azure/api-center/register-discover-mcp-server, 2026.

[111] TrueFoundry, "Mcp gateway authentication and security," https://www.truefoundry.com/docs/ai-gateway/mcp-gateway-auth-security, 2026.

[112] R. Kang and V. Wang, "Registry-governed agent lifecycle: Completing EDDOps with evaluation-driven registration, promotion, and retirement on AWS AgentCore," *arXiv preprint arXiv:2607.00345*, Jul. 2026.

[113] A. Quessada-Vial, "Agentic configuration management (ACM): A reference configuration model for governed agentic systems," *arXiv preprint arXiv:2608.11166*, Aug. 2026.

[114] X. Qin, S. Luan, J. See, Z. Boukhers, C. Yang, and Z. Li, "Governed capability evolution: Lifecycle-time compatibility checking and rollback for AI-component-based systems, with a proof-of-concept evaluation on embodied agents," *arXiv preprint arXiv:2604.08059*, Apr. 2026.

[115] Braintrust, "Use prompts in code," Braintrust documentation, https://www.braintrust.dev/docs/guides/prompts, 2026, accessed 2026-10-03.

[116] Vellum, "Release tags," Vellum documentation, https://docs.vellum.ai/product/deployments/release-tags, 2026, accessed 2026-10-03.

[117] LangChain, "Prompt engineering concepts," LangSmith documentation, https://docs.langchain.com/langsmith/prompt-engineering-concepts, 2026, accessed 2026-10-03.

[118] J. L. Lulla, V. Nersesyan, S. Mohsenimofidi, C. Treude, and S. Baltes, "Loop engineering: Building blocks, adoption, and impact," *arXiv preprint arXiv:2608.21884*, 2026.

[119] S. Hu, C. Lu, and J. Clune, "Automated design of agentic systems (ADAS)," *arXiv preprint*, 2024.

[120] G. Wang *et al.*, "Voyager: An open-ended embodied agent with large language models," *arXiv preprint*, 2023.

[121] X. Wang *et al.*, "AutoAgent: Evolving cognition and elastic memory orchestration for adaptive agents," *arXiv preprint*, 2026.

[122] Z. Jiang and B. Dong, "Buildrix: An open platform for sharing and benchmarking agentic ai skills in building engineering," *arXiv preprint arXiv:2606.25139*, 2026.
[123] L. A. Agrawal, S. Tan, D. Soylu, N. Ziems, R. Khare, K. Opsahl-Ong, A. Singhvi, H. Shandilya, M. J. Ryan, M. Jiang, C. Potts, K. Sen, A. G. Dimakis, I. Stoica, D. Klein, M. Zaharia, and O. Khattab, "GEPA: Reflective prompt evolution can outperform reinforcement learning," *arXiv preprint*, 2025.
[124] N. Vassilyev, W. Berrios, R. Zhang, B. Han, D. Kiela, and S. Mehri, "Reflective context learning: Studying the optimization primitives of context space," *arXiv preprint*, 2026.
[125] Q. Cai, Y. Zhang, X. Jia, H. Zheng, W. Xue, J. Song, X. Tian, and Y. Guo, "MOSS: Self-evolution through source-level rewriting in autonomous agent systems," *arXiv preprint*, 2026.
[126] L. Li, J. Li, J. Zhao, K. Ye, Y. Li, C.-z. Xu, and X. Gao, "Grow the harness, not the context: From strategy-free scaffolds to reusable specialist agents," *arXiv preprint arXiv:2609.26760*, 2026.
[127] M. M. Tanjim, J. Subramanian, X. Chen, B. Kveton, S. Mukherjee, A. Zhang, S. Kim, S. Sarkhel, and S. Choudhury, "MOCHA: Multi-objective chebyshev annealing for agent skill optimization," *arXiv preprint*, 2026.
[128] Y. Shalev, Z. Ding, and M. Jamnik, "Training language agents to learn from experience," *arXiv preprint*, 2026.
[129] H. Li, R. He, Q. Zhang, C. Ji, Q. Mang, X. Chen, L. A. Agrawal, W.-L. Liao, E. Yang, A. Cheung, J. Zou, K. Olukotun, I. Stoica, and J. E. Gonzalez, "Combee: Scaling prompt learning for self-improving language model agents," *arXiv preprint*, 2026.
[130] P. Hebbar, Y. Manawat, S. Verboomen, A. Ivanova, S. Palanimalai, K. Bhatia, and V. Baskaran, "Sia: Self improving ai with harness & weight updates," *arXiv preprint arXiv:2605.27276*, 2026.
[131] H. B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. Agüera y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS)*, ser. Proceedings of Machine Learning Research, vol. 54, 2017, pp. 1273–1282.
[132] H. B. McMahan, D. Ramage, K. Talwar, and L. Zhang, "Learning differentially private recurrent language models," in *International Conference on Learning Representations (ICLR)*, 2018, arXiv:1710.06963.
[133] P. Kairouz, H. B. McMahan, B. Avent, A. Bellet, M. Bennis *et al.*, "Advances and open problems in federated learning," *arXiv preprint arXiv:1912.04977*, 2019, published in Foundations and Trends in Machine Learning, vol. 14, no. 1–2, 2021.
[134] T. Guo, S. Guo, J. Wang, and W. Xu, "PromptFL: Let federated participants cooperatively learn prompts instead of models – federated learning in age of foundation model," *arXiv preprint arXiv:2208.11625*, 2022.
[135] D. Sculley, G. Holt, D. Golovin, E. Davydov, T. Phillips, D. Ebner, V. Chaudhary, M. Young, J.-F. Crespo, and D. Dennison, "Hidden technical debt in machine learning systems," in *Advances in Neural Information Processing Systems 28 (NIPS 2015)*, 2015.
[136] D. Jaroslawicz *et al.*, "How many instructions can LLMs follow at once?" *arXiv preprint*, 2025.
[137] W. Zou *et al.*, "PoisonedRAG: Knowledge corruption attacks to retrieval-augmented generation of large language models," *arXiv preprint*, 2024, accepted at USENIX Security 2025.
[138] Z. Chen, Z. Xiang, C. Xiao, D. Song, and B. Li, "AgentPoison: Red-teaming LLM agents via poisoning memory or knowledge bases," *arXiv preprint arXiv:2407.12784*, 2024.
[139] Z. Xu *et al.*, "From storage to steering: Memory control flow attacks on LLM agents," *arXiv preprint*, 2026.
[140] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," *arXiv preprint arXiv:2302.12173*, 2023.
[141] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr, "AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents," *arXiv preprint arXiv:2406.13352*, 2024.
[142] Check Point Research, "MCPoison: Cursor IDE's MCP vulnerability (CVE-2025-54136)," https://research.checkpoint.com/2025/cursor-vulnerability-mcpoison/, 2025.
[143] Y. Su, W. Xu, C. Zuo, and E. Bertino, "ChronoMem: Version control and semantic rollback for large language model agent memory," *arXiv preprint arXiv:2607.27773*, 2026.
[144] C. Yu, Y. Wang, J. Zhang, Y. Duan, M. Zheng, Z. Wu, K. Shi, and T. Cai, "From faulty memories to corrected actions: Dependency-guided rollback repair for memory-augmented agents," *arXiv preprint arXiv:2608.10502*, 2026.
[145] E. Wallace, K. Xiao, R. Leike, L. Weng, J. Heidecke, and A. Beutel, "The instruction hierarchy: Training LLMs to prioritize privileged instructions," *arXiv preprint arXiv:2404.13208*, 2024.
[146] S. Singh *et al.*, "The leaderboard illusion," *arXiv preprint*, 2025.
[147] M. Cemri *et al.*, "Why do multi-agent LLM systems fail?" *arXiv preprint*, 2025.
[148] N. F. Liu *et al.*, "Lost in the middle: How language models use long contexts," *Transactions of the Association for Computational Linguistics (TACL)*, 2023.
[149] Q. Yang, Z. Kou, X. Zhang, D.-D. Wu, H. Gu, J. Guo, Y. Liu, D. Jiang, and Q. Xu, "Federated agent optimization," *arXiv preprint arXiv:2610.01195*, 2026.
[150] H. Robbins and D. Siegmund, "A convergence theorem for non negative almost supermartingales and some applications," in *Optimizing Methods in Statistics*. Academic Press, 1971, pp. 233–257.

MIKHAIL L. ARBUZOV TODO(bio).

LEE MOSBACKER TODO(bio).

SISONG BEI TODO(bio).

ZIWEI DONG TODO(bio).

DMITRI KALAEV TODO(bio).

ALEXEY SHVETS TODO(bio).