




Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

Equal interval:



Difference table:

x	y	Δy	$\Delta^2 y$	$\Delta^3 y$
x_0	y_0	$(y_1 - y_0) = \Delta y_0$	$\Delta y_1 - \Delta y_0 = \Delta^2 y_0$	$\Delta^2 y_1 - \Delta^2 y_0 = \Delta^3 y_0$
x_1	y_1	$(y_2 - y_1) = \Delta y_1$	$\Delta y_2 - \Delta y_1 = \Delta^2 y_1$	
x_2	y_2	$(y_3 - y_2) = \Delta y_2$		
x_3	y_3			

Newton's forward (indicated by a red arrow from y_0 to $\Delta^3 y_0$)

Newton's backward (indicated by a green arrow from y_3 to $\Delta^3 y_0$)



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

Newton's forward:

Δ (Delta)

$$x = x_o + Sh$$

$$S = \frac{x - x_o}{h}, \quad 0 < S < 1$$

$$y = f(x) = y_o + S \Delta y_o + \frac{S(S-1)}{2!} \Delta^2 y_o + \frac{S(S-1)(S-2)}{3!} \Delta^3 y_o + \dots + \frac{S(S-1)(S-2)\dots(S-n+1)}{n!} \Delta^n y_o$$

Newton's backward:

(interval delta ∇) معكوس

$$S = \frac{x - x_n}{h}, \quad S < 0$$

$$y = f(x) = y_n + S \nabla y_n + \frac{S(S+1)}{2!} \nabla^2 y_n + \frac{S(S+1)(S+2)}{3!} \nabla^3 y_o + \dots + \frac{S(S+1)(S+2)\dots(S+n-1)}{n!} \nabla^n y_o$$

Example (10):

From the following data given $f(x) = \sin(x)$ estimate the value of $\sin(30.2^\circ)$, $\sin(31.3^\circ)$

X	30.0	30.5	31.0	31.5
Y	0.50000	0.50754	0.51504	0.52250



Department of Physics and Engineering Mathematics
Numerical analysis (BAS12)
Mechatronics Engineering
Lecture (1)



Tanta University

Faculty of Engineering

Solution:

Difference is given by table

x	$F(x_i)$	$\Delta F(x_i)$	$\Delta^2 F(x_i)$	$\Delta^3 F(x_i)$
30.0	0.50000	0.00754	-0.00004	0.00000
30.5	0.50754			
31.0	0.51504		-0.00004	
31.5	0.52250	0.00746		

$$h = 0.5 \text{ At } x = 30.2^\circ$$

Newton's forward

$$y = p_3(x) = y_o + S \Delta y_o + \frac{S(S-1)}{2!} \Delta^2 y_o + \dots$$

$$S = \frac{x - x_o}{h} = \frac{30.2 - 30}{0.5} = 0.4$$

عدد موجب 0.4

$$p_3(x) = p_3(30.2) = 0.5 + 0.4(0.00754) + \frac{0.4(0.4-1)}{2!}(-0.00004) + 0$$

$$p_3(x) = p_3(30.2) = 0.50302$$

$$h = 0.5 \text{ At } x = 31.3^\circ$$

Newton's backward



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

$$S = \frac{-x_n + x}{h} = \frac{-31.5 + 31.3}{0.5} = -0.4$$

عدد سالب -0.4

$$P_3(x) = P_3(31.3) = y_n + S \nabla y_n + \frac{S(S+1)}{2!} \nabla^2 y_n + \dots$$

$$P_3(31.3) = 0.5225 - 0.4(0.00746) - 0.4 \frac{(-0.4+1)}{2!} (-0.00004) + 0$$

$$P_3(31.3) = 0.5195$$



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS1)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

Interpolation with Spline function:

هنا الفكرة تختلف عن الطرق السابقة في أنه نكون بين كل نقطتين في الجدول بدالة كثيرة حدود $S_i(x)$ أما في الطرق

الأخرى هناك دالة كثيرة حدود واحدة تصل بين جميع النقاط $P_n(x)$

Linear Interpolation (First Degree Spline) :

نصل بين كل النقاط بخط مستقيم

$$S_i(x) = y_i + \frac{y_{i+1} - y_i}{x_{i+1} - x_i} (x - x_i)$$

$$S_i(x) = y_i + \delta_i (x - x_i) \rightarrow i = 0, 1, 2, 3, \dots$$

Example (11):

Find a spline of degree one to interpolate the following data and use the resulting spline to approximate $f(2.2)$

X	1	1.5	2	2.5	3
$y = F(x)$	1	3	7	10	15

Solution:

$$S_i(x) = y_i + \delta_i (x - x_i)$$



Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Tanta University

Faculty of Engineering

At $i = 0$

$$S_0(x) = y_0 + \delta_0(x - x_0)$$

$$S_0(x) = 1 + 4(x - 1) \rightarrow S_0(x) = 4x - 3$$

At $i = 1$

$$S_1(x) = y_1 + \delta_1(x - x_1)$$

$$S_1(x) = 3 + 8(x - 1.5) \rightarrow S_1(x) = 8x - 9$$

At $i = 2$

$$S_2(x) = y_2 + \delta_2(x - x_2)$$

$$S_2(x) = 7 + 6(x - 2) \rightarrow S_2(x) = 6x - 5$$

At $i = 3$

$$S_3(x) = y_3 + \delta_3(x - x_3)$$

$$S_3(x) = 10 + 10(x - 2.5) \rightarrow S_3(x) = 10x - 15$$

x	$y = F(x)$	δ_i
1	1	$\frac{3-1}{1.5-1} = 4 \rightarrow \delta_0$
1.5	3	
2	7	$\frac{7-3}{2-1.5} = 8 \rightarrow \delta_1$
2.5	10	
3	15	$\frac{15-10}{3-2.5} = 10 \rightarrow \delta_3$

$$\text{So that } S_i(x) = \begin{cases} (4x - 3) \text{ if } x \in [1, 1.5] \\ (8x - 9) \text{ if } x \in [1.5, 2] \\ (6x - 5) \text{ if } x \in [2, 2.5] \\ (10x - 15) \text{ if } x \in [2.5, 3] \end{cases}$$

The value of $x = 2.2$ lies in $[2, 2.5]$

$$f(2.2) = 6(2.2) - 5 = 8.2$$



Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Tanta University

Faculty of Engineering

Nature Cubic Splines:

نصل بين كل نقطتين في الجدول بكثيرة حدود من الدرجة الثالثة ويكون علي الشكل:

$$S_i(x) = a_i + b_i(x - x_i) + c_i(x - x_i)^2 + d_i(x - x_i)^3 \rightarrow i = 0, 1, 2, 3, \dots$$

Where:

a_i, b_i, c_i, d_i are constants

$$a_i = y_i, \quad b_i = \frac{y_{i+1} - y_i}{h} - \frac{h}{3}(c_{i+1} + 2c_i), \quad d_i = \frac{(c_{i+1} - c_i)}{3h}$$

To calculate c_i

$$c_{i-1} + 4c_i + c_{i+1} = \frac{3}{h^2}[y_{i+1} - 2y_i + y_{i-1}] \rightarrow i = 1, 2, 3, \dots$$

$$c_0 = c_n = 0$$

يمكن كتابتها علي الصورة :

$$\begin{bmatrix} 4 & 1 & 0 & 0 \\ 1 & 4 & 1 & 0 \\ 0 & 1 & 4 & 1 \\ 0 & 0 & 1 & 4 \end{bmatrix} \begin{bmatrix} c_1 \\ c_2 \\ c_3 \\ . \end{bmatrix} = \frac{3}{h^2} \begin{bmatrix} y_2 - 2y_1 + y_0 \\ y_3 - 2y_2 + y_1 \\ . \\ . \end{bmatrix}$$

Example (12):

Use the values given by $f(x) = x^3 + 2$ at $x = 0, 0.2, 0.4, 0.6, 0.8$ and 1 to find approximation of $f(x)$ at $x = 0.1, 0.3, 0.5, 0.7, 0.9$ using the Natural Cubic Spline Interpolation

Solution:

X	0	0.2	0.4	0.6	0.8	1
$y = F(x)$	2	2.008	2.064	2.216	2.512	3

$$C_0 = C_5 = 0$$



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

$$\therefore c_{i-1} + 4c_i + c_{i+1} = \frac{3}{h^2} [y_{i+1} - 2y_i + y_{i-1}]$$

At $i = 1$

$$\therefore c_0 + 4c_1 + c_2 = \frac{3}{h^2} [y_2 - 2y_1 + y_0]$$

$$0 + 4c_1 + c_2 = \frac{3}{(0.2)^2} [2.064 - 2 \times 2.008 + 2]$$

$$4c_1 + c_2 = 3.6 \rightarrow (1)$$

At $i = 2$

$$\therefore c_1 + 4c_2 + c_3 = \frac{3}{h^2} [y_3 - 2y_2 + y_1]$$

$$c_1 + 4c_2 + c_3 = \frac{3}{(0.2)^2} [2.216 - 2 \times 2.064 + 2.008]$$

$$c_1 + 4c_2 + c_3 = 7.2 \rightarrow (2)$$

At $i = 3$

$$\therefore c_2 + 4c_3 + c_4 = \frac{3}{h^2} [y_4 - 2y_3 + y_2]$$

$$c_2 + 4c_3 + c_4 = \frac{3}{(0.2)^2} [2.512 - 2 \times 2.216 + 2.0]$$

$$c_2 + 4c_3 + c_4 = 10.8 \rightarrow (3)$$

At $i = 4$

$$\therefore c_3 + 4c_4 + c_5 = \frac{3}{h^2} [y_5 - 2y_4 + y_3]$$

$$c_3 + 4c_4 + c_5 = \frac{3}{(0.2)^2} [3 - 2 \times 2.512 + 2.21]$$



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

$$c_3 + 4c_4 + c_5 = c_3 + 4c_4 + 0 = c_3 + 4c_4 = 14.4 \rightarrow (4)$$

بحل المعادلات 1 و 2 و 3 و 4 معا نحصل علي الاتي :

$$\begin{cases} C_0 = 0 \\ C_1 = 612/1045 \\ C_2 = 1314/1045 \\ C_3 = 1656/1045 \\ C_4 = 3348/1045 \\ C_5 = 0 \end{cases}$$

بمعرفة C_i يمكن حساب باقي الثوابت:

$$a_i = y_i = \begin{bmatrix} a_0 \\ a_1 \\ a_2 \\ a_3 \\ a_4 \end{bmatrix} = \begin{bmatrix} 2 \\ 2.008 \\ 2.064 \\ 2.216 \\ 2.512 \end{bmatrix}$$

$$\therefore b_i = \frac{y_{i+1} - y_i}{h} - \frac{h}{3}(c_{i+1} + 2c_i)$$

$$b_0 = \frac{y_1 - y_0}{0.2} - \frac{0.2}{3}[C_1 + 2C_0]$$

$$b_0 = \frac{2.0 - 2}{0.2} - \frac{0.2}{3}\left[612/1045 + 2(0)\right] = 9.56 * 10^{-4}$$

$$b_1 = \frac{y_2 - y_1}{0.2} - \frac{0.2}{3}[C_2 + 2C_1]$$

$$b_1 = \frac{2.064 - 2.0}{0.2} - \frac{0.2}{3}\left[1314/1045 + 2\left(612/1045\right)\right] = 617/5225$$

$$b_2 = \frac{y_3 - y_2}{0.2} - \frac{0.2}{3}[C_3 + 2C_2]$$

$$b_2 = \frac{2.216 - 2.064}{0.2} - \frac{0.2}{3}\left[1656/1045 + 2\left(1314/1045\right)\right] = 2543/5225$$



Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Tanta University

Faculty of Engineering

$$b_3 = \frac{y_4 - y_3}{0.2} - \frac{0.2}{3} [C_4 + 2C_3]$$

$$b_3 = \frac{2.512 - 2.216}{0.2} - \frac{0.2}{3} \left[3348/1045 + 2 \left(1656/1045 \right) \right] = 5513/5225$$

$$b_4 = \frac{y_5 - y_4}{0.2} - \frac{0.2}{3} [C_5 + 2C_4]$$

$$b_4 = \frac{3 - 2.512}{0.2} - \frac{0.2}{3} \left[0 + 2 \left(3348/1045 \right) \right] = 10517/5225$$

$$d_i = \frac{(c_{i+1} - c_i)}{3h}$$

$$d_0 = \frac{c_1 - c_0}{3(0.2)}$$

$$d_0 = \frac{612/1045 - 0}{3(0.2)} = \frac{204}{209}$$

$$d_1 = \frac{c_2 - c_1}{3(0.2)}$$

$$d_1 = \frac{1314/1045 - 612/1045}{3(0.2)} = \frac{234}{209}$$

$$d_2 = \frac{c_3 - c_2}{3(0.2)}$$

$$d_2 = \frac{1656/1045 - 1314/1045}{3(0.2)} = \frac{6}{11}$$

$$d_3 = \frac{c_4 - c_3}{3(0.2)}$$

$$d_3 = \frac{3348/1045 - 1656/1045}{3(0.2)} = \frac{564}{209}$$

$$d_4 = \frac{c_5 - c_4}{3(0.2)}$$

$$d_4 = \frac{0 - 3348/1045}{3(0.2)} = - \frac{1116}{209}$$



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

$$\therefore S_i(x) = a_i + b_i(x - x_i) + c_i(x - x_i)^2 + d_i(x - x_i)^3 \rightarrow i = 0, 1, 2, 3, \dots$$

At $i = 0$

$$\therefore S_0(x) = a_0 + b_0(x - x_0) + c_0(x - x_0)^2 + d_0(x - x_0)^3$$

$$\therefore S_0(x) = 2 + 0.001(x - 0) + 0(x - 0)^2 + 0.976(x - 0)^3$$

$$\therefore S_0(x) = 2 + 0.001x + 0.976x^3, x \in [0, 0.2]$$

At $i = 1$

$$\therefore S_1(x) = a_1 + b_1(x - x_1) + c_1(x - x_1)^2 + d_1(x - x_1)^3$$

$$\therefore S_1(x) = 2.008 + 0.118(x - 0.2) + 0.586(x - 0.2)^2 + 1.12(-0.2)^3$$

$$\therefore S_1(x) = \sqrt{}, x \in [0.2, 0.4]$$

$$S_2(x) = a_2 + b_2(x - x_2) + c_2(x - x_2)^2 + d_2(x - x_2)^3$$

$$= 2.064 + \frac{2543}{5225}(x - 0.4) + \frac{1314}{1045}(x - 0.4)^2 + \frac{6}{11}(x - 0.4)^3$$

$$S_3(x) = a_3 + b_3(x - x_3) + c_3(x - x_3)^2 + d_3(x - x_3)^3$$

$$= 2.216 + \frac{5513}{5225}(x - 0.6) + \frac{1656}{1045}(x - 0.6)^2 + \frac{564}{209}(x - 0.6)^3$$

$$S_4(x) = a_4 + b_4(x - x_4) + c_4(x - x_4)^2 + d_4(x - x_4)^3$$

$$= 2.512 + \frac{10517}{5225}(x - 0.8) + \frac{3348}{1045}(x - 0.8)^2 - \frac{1116}{209}(x - 0.8)^3$$

لحساب $S(0.1) \rightarrow \in [0, 0.2]$

$$\therefore S(0.1) = 2 + 0.001 \times 0.1 + 0.976(0.1)^3 = 2.001, x \in [0, 0.2]$$

لحساب $S(0.3) \rightarrow \in [0.2, 0.4]$

$$\therefore S(0.3) = 2.008 + 0.118(0.3 - 0.2) + 0.586(0.3 - 0.2)^2 + 1.12(0.3 - 0.2)^3 = 2.02678$$



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

At $x=0.5$

$$\therefore S_2(0.5) = 2.125789$$

At $x=0.7$

$$\therefore S_3(0.7) = 2.340057$$

At $x=0.9$

$$\therefore S_4(0.9) = 2.739981$$



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS127)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

Exercises

- 1- Find a polynomial of order (2) that interpolates the table

X	0.2	0.4	0.6
Y	-0.95	-0.82	-0.65

- 2- Determine a polynomial of degree ≤ 3 that interpolates the data

X	1.2	2.1	3	3.6
Y	0.7	8.1	27.7	45.1

- 3- Determine the Lagrange polynomial that interpolates the data in the following table

X	0	2	4	6
Y	1	-1	3	4

- 4- Let $f(x) = 2x^2 e^x + 1$ contrast a Lagrange polynomial of degree two or less using $x_0 = 0, x_1 = 0.5$ and $x_2 = 1$ approximate $f(0.8)$.

- 5- Determine a polynomial of degree ≤ 5 using Newton's divided differences that interpolate the data in the following table

X	1	2	3	4	5	6
Y	14.5	19.5	30.5	53.5	94.5	159.5

Use the resulting polynomial to estimate the value of $f(4.5)$. Compare of the exact value of $f(4.5) = 71.375$

- 6- To investigate the relationship between yield of Potatoes (y) and level of fertilizer application (x). An experimenter divided a field into (5) pots of equal size and applied differing amounts of fertilizers to each. the data recorded for each plot are given by the table (in Kgs)



Tanta University

Department of Physics and Engineering Mathematics
Numerical analysis (BAS1)
Mechatronics Engineering
Lecture (1)



Faculty of Engineering

X	1	2	3	4	5
Y	22	23	25	30	28

- Find the interpolation polynomial for this table.

According to the interpolating polynomial, approximately how many Kgs would you expect from a plot to which 2.5 Kgs of fertilizer had been applied?

Best wishes
Dr. Ashraf Almahallawy