

Observables



Observables provide support for passing messages between publishers and subscribers in your application. Observables offer significant benefits over other techniques for event handling, asynchronous programming, and handling multiple values.

Observables are declarative—that is, you define a function for publishing values, but it is not executed until a consumer subscribes to it. The subscribed consumer then receives notifications until the function completes, or until they unsubscribe.

An observable can deliver multiple values of any type—literals, messages, or events, depending on the context. The API for receiving values is the same whether the values are delivered synchronously or asynchronously. Because setup and teardown logic are both handled by the observable, your application

code only needs to worry about subscribing to consume values, and when done, unsubscribing. Whether the stream was keystrokes, an HTTP response, or an interval timer, the interface for listening to values and stopping listening is the same.

Because of these advantages, observables are used extensively within Angular, and are recommended for app development as well.

Basic usage and terms

As a publisher, you create an `Observable` instance that defines a *subscriber* function. This is the function that is executed when a consumer calls the `subscribe()` method. The subscriber function defines how to obtain or generate values or messages to be published.

To execute the observable you have created and begin receiving notifications, you call its `subscribe()` method, passing an *observer*. This is a JavaScript object that defines the handlers for the

notifications you receive. The `subscribe()` call returns a `Subscription` object that has an `unsubscribe()` method, which you call to stop receiving notifications.

Here's an example that demonstrates the basic usage model by showing how an observable could be used to provide geolocation updates.

Observe geolocation updates

```
// Create an Observable that will start  
listening to geolocation updates  
// when a consumer subscribes.  
const locations = new  
Observable((observer) => {  
    let watchId: number;  
  
    // Simple geolocation API check  
provides values to publish  
    if ('geolocation' in navigator) {  
        watchId =  
navigator.geolocation.watchPosition((pos  
Position) => {  
            observer.next(position);  
        }, (error: PositionError) => {  
            observer.error(error);  
        });  
    } else {  
        observer.error('Geolocation not  
available');  
    }  
}
```

```
// When the consumer unsubscribes,  
clean up data ready for next  
subscription.  
  
return {  
  unsubscribe() {  
  
navigator.geolocation.clearWatch(watchId  
  
    }  
  };  
});  
  
// Call subscribe() to start listening  
for updates.  
  
const locationsSubscription =  
locations.subscribe({  
  next(position) {  
    console.log('Current Position: ',  
position);  
  },  
  error(msg) {  
    console.log('Error Getting  
Location: ', msg);  
  }  
})
```

```
});
```

```
// Stop listening for location after 10  
seconds
```

```
setTimeout(() => {  
    locationsSubscription.unsubscribe();  
}, 10000);
```



Defining observers

A handler for receiving observable notifications implements the `Observer` interface. It is an object that defines callback methods to handle the three types of notifications that an observable can send:

NOTIFICATION TYPE	DESCRIPTION
<code>next</code>	Required. A handler for each delivered value. Called zero or more times after execution starts.
<code>error</code>	Optional. A handler for an error notification. An error halts execution of the observable instance.
<code>complete</code>	Optional. A handler for the execution-complete notification. Delayed values can continue to be delivered to the next handler after execution is complete.

An observer object can define any combination of these handlers. If you don't supply a handler for a

notification type, the observer ignores notifications of that type.

Subscribing

An `Observable` instance begins publishing values only when someone subscribes to it. You subscribe by calling the `subscribe()` method of the instance, passing an observer object to receive the notifications.

In order to show how subscribing works, we need to create a new observable. There is a constructor that you use to create new instances, but for illustration, we can use some methods from the RxJS library that create simple observables of frequently used types:

- `of(...items)`—Returns an `Observable` instance that synchronously delivers the values provided as arguments.
- `from(iterable)`—Converts its argument to an `Observable` instance. This method is commonly used to convert an array to an observable.

Here's an example of creating and subscribing to a simple observable, with an observer that logs the received message to the console:

Subscribe using observer

// Create simple observable that emits three values

```
const myObservable = of(1, 2, 3);
```

// Create observer object

```
const myObserver = {  
  next: x => console.log('Observer got  
a next value: ' + x),  
  error: err => console.error('Observer  
got an error: ' + err),  
  complete: () => console.log('Observer  
got a complete notification'),  
};
```

// Execute with the observer object

```
myObservable.subscribe(myObserver);
```

// Logs:

// Observer got a next value: 1

// Observer got a next value: 2

// Observer got a next value: 3

// Observer got a complete notification

Alternatively, the `subscribe()` method can accept callback function definitions in line, for `next`, `error`, and `complete` handlers. For example, the following `subscribe()` call is the same as the one that specifies the predefined observer:

Subscribe with positional arguments

```
myObservable.subscribe(  
  x => console.log('Observer got a next  
value: ' + x),  
  err => console.error('Observer got an  
error: ' + err),  
  () => console.log('Observer got a  
complete notification')  
);
```

In either case, a `next` handler is required. The `error` and `complete` handlers are optional.

Note that a `next()` function could receive, for instance, message strings, or event objects, numeric values, or structures, depending on context. As a

general term, we refer to data published by an observable as a *stream*. Any type of value can be represented with an observable, and the values are published as a stream.

Creating observables

Use the `Observable` constructor to create an observable stream of any type. The constructor takes as its argument the subscriber function to run when the observable's `subscribe()` method executes. A subscriber function receives an `Observer` object, and can publish values to the observer's `next()` method.

For example, to create an observable equivalent to the `of(1, 2, 3)` above, you could do something like this:

Create observable with constructor

```
// This function runs when subscribe() is called  
function sequenceSubscriber(observer) {  
    // synchronously deliver 1, 2, and 3, then complete  
    observer.next(1);  
    observer.next(2);  
    observer.next(3);  
    observer.complete();  
  
    // unsubscribe function doesn't need to do anything in this  
    // because values are delivered synchronously  
    return {unsubscribe() {}};  
}  
  
// Create a new Observable that will deliver the above sequence  
const sequence = new  
Observable(sequenceSubscriber);
```

```
// execute the Observable and print the  
result of each notification  
sequence.subscribe({  
  next(num) { console.log(num); },  
  complete() { console.log('Finished  
sequence'); }  
});  
  
// Logs:  
// 1  
// 2  
// 3  
// Finished sequence
```

To take this example a little further, we can create an observable that publishes events. In this example, the subscriber function is defined inline.

Create with custom fromEvent function

```
function fromEvent(target, eventName) {  
  return new Observable((observer) => {  
    const handler = (e) =>  
      observer.next(e);  
  
    // Add the event handler to the  
    target  
    target.addEventListener(eventName,  
      handler);  
  
    return () => {  
      // Detach the event handler from  
      the target  
  
      target.removeEventListener(eventName,  
        handler);  
    };  
  });  
}
```

Now you can use this function to create an observable that publishes keydown events:

Use custom fromEvent function

```
const ESC_KEY = 27;

const nameInput =
  document.getElementById('name') as
  HTMLInputElement;

const subscription =
  fromEvent(nameInput, 'keydown')
    .subscribe((e: KeyboardEvent) => {
      if (e.keyCode === ESC_KEY) {
        nameInput.value = '';
      }
    });
```

Multicasting

A typical observable creates a new, independent execution for each subscribed observer. When an observer subscribes, the observable wires up an

event handler and delivers values to that observer.

When a second observer subscribes, the observable then wires up a new event handler and delivers values to that second observer in a separate execution.

Sometimes, instead of starting an independent execution for each subscriber, you want each subscription to get the same values—even if values have already started emitting. This might be the case with something like an observable of clicks on the document object.

Multicasting is the practice of broadcasting to a list of multiple subscribers in a single execution. With a multicasting observable, you don't register multiple listeners on the document, but instead re-use the first listener and send values out to each subscriber.

When creating an observable you should determine how you want that observable to be used and whether or not you want to multicast its values.

Let's look at an example that counts from 1 to 3, with a one-second delay after each number emitted.

Create a delayed sequence

```
function sequenceSubscriber(observer) {  
  const seq = [1, 2, 3];  
  let timeoutId;  
  
  // Will run through an array of  
  // numbers, emitting one value  
  // per second until it gets to the  
  // end of the array.  
  function doSequence(arr, idx) {  
    timeoutId = setTimeout(() => {  
      observer.next(arr[idx]);  
      if (idx === arr.length - 1) {  
        observer.complete();  
      } else {  
        doSequence(arr, ++idx);  
      }  
    }, 1000);  
  }  
  
  doSequence(seq, 0);  
  
  // Unsubscribe should clear the
```

timeout to stop execution

```
    return {unsubscribe() {  
        clearTimeout(timeoutId);  
    }};  
}
```

*// Create a new Observable that will
deliver the above sequence*

```
const sequence = new  
Observable(sequenceSubscriber);
```

```
sequence.subscribe({  
    next(num) { console.log(num); },  
    complete() { console.log('Finished  
sequence'); }  
});
```

// Logs:

// (at 1 second): 1

// (at 2 seconds): 2

// (at 3 seconds): 3

// (at 3 seconds): Finished sequence

Notice that if you subscribe twice, there will be two separate streams, each emitting values every second. It looks something like this:

Two subscriptions

// Subscribe starts the clock, and will emit after 1 second

```
sequence.subscribe({
  next(num) { console.log('1st
subscribe: ' + num); },
  complete() { console.log('1st
sequence finished.')}
});
```

// After 1/2 second, subscribe again.

```
setTimeout(() => {
  sequence.subscribe({
    next(num) { console.log('2nd
subscribe: ' + num); },
    complete() { console.log('2nd
sequence finished.')}
  });
}, 500);
```

// Logs:

// (at 1 second): 1st subscribe: 1

// (at 1.5 seconds): 2nd subscribe: 1

```
// (at 2 seconds): 1st subscribe: 2
// (at 2.5 seconds): 2nd subscribe: 2
// (at 3 seconds): 1st subscribe: 3
// (at 3 seconds): 1st sequence
finished
// (at 3.5 seconds): 2nd subscribe: 3
// (at 3.5 seconds): 2nd sequence
finished
```

Changing the observable to be multicasting could look something like this:

Create a multicast subscriber

```
function multicastSequenceSubscriber()
{
    const seq = [1, 2, 3];
    // Keep track of each observer (one
for every active subscription)
    const observers = [];
    // Still a single timeoutId because
there will only ever be one
    // set of values being generated,
multicasted to each subscriber
    let timeoutId;

    // Return the subscriber function
(runs when subscribe()
function is invoked)
    return (observer) => {
        observers.push(observer);
        // When this is the first
subscription, start the sequence
        if (observers.length === 1) {
            timeoutId = doSequence({
                next(val) {
```

```
        // Iterate through observers
        and notify all subscriptions
        observers.forEach(obs =>
obs.next(val));
    },
    complete() {
        // Notify all complete
        callbacks

observers.slice(0).forEach(obs =>
obs.complete());
    }
    }, seq, 0);
}

return {
    unsubscribe() {
        // Remove from the observers
        array so it's no longer notified

observers.splice(observers.indexOf(obser
1);

        // If there's no more
        listeners, do cleanup
```



```

        if (observers.length === 0) {
            clearTimeout(timeoutId);
        }
    }
};

};

}

// Run through an array of numbers,
emitting one value
// per second until it gets to the end
of the array.
function doSequence(observer, arr, idx)
{
    return setTimeout(() => {
        observer.next(arr[idx]);
        if (idx === arr.length - 1) {
            observer.complete();
        } else {
            doSequence(observer, arr, ++idx);
        }
    }, 1000);
}

```

```
// Create a new Observable that will  
deliver the above sequence  
const multicastSequence = new  
Observable(multicastSequenceSubscriber())
```

```
// Subscribe starts the clock, and  
begins to emit after 1 second  
multicastSequence.subscribe({  
  next(num) { console.log('1st  
subscribe: ' + num); },  
  complete() { console.log('1st  
sequence finished.');}; }  
});
```

```
// After 1 1/2 seconds, subscribe again  
(should "miss" the first value).  
setTimeout(() => {  
  multicastSequence.subscribe({  
    next(num) { console.log('2nd  
subscribe: ' + num); },  
    complete() { console.log('2nd  
sequence finished.');}; }  
});
```

```
}, 1500);
```

```
// Logs:
```

```
// (at 1 second): 1st subscribe: 1
```

```
// (at 2 seconds): 1st subscribe: 2
```

```
// (at 2 seconds): 2nd subscribe: 2
```

```
// (at 3 seconds): 1st subscribe: 3
```

```
// (at 3 seconds): 1st sequence  
finished
```

```
// (at 3 seconds): 2nd subscribe: 3
```

```
// (at 3 seconds): 2nd sequence  
finished
```



Multicasting observables take a bit more setup, but they can be useful for certain applications. Later we will look at tools that simplify the process of multicasting, allowing you to take any observable and make it multicasting.

Error handling

Because observables produce values asynchronously, try/catch will not effectively catch errors. Instead, you handle errors by specifying an `error` callback on the observer. Producing an error also causes the observable to clean up subscriptions and stop producing values. An observable can either produce values (calling the `next` callback), or it can complete, calling either the `complete` or `error` callback.

```
myObservable.subscribe({
  next(num) { console.log('Next num: '
+ num)},
  error(err) { console.log('Received an
error: ' + err)}
});
```

Error handling (and specifically recovering from an error) is covered in more detail in a later section.