

Day 5 of training

CSS ATTRIBUTE SELECTOR

CSS attribute selectors allow you to select HTML elements based on the presence or value of their attributes.

Basic Syntax:

```
selector[attribute] {  
    /* CSS rules */  
}
```

Types of Attribute Selectors with Examples:

Selector	Meaning	Example	What it selects
-----	-----	-----	-----
<code>[attr]</code>	Has the attribute	<code>input[required]</code>	All <code><input></code> with <code>required</code>
<code>[attr="value"]</code>	Exact value	<code>a[target="_blank"]</code>	All <code><a></code> where <code>target = "_blank"</code>
<code>[attr~="value"]</code>	Word contains value	<code>[title~="fast"]</code>	Title with word "fast" in it
<code>[attr^="value"]</code>	Starts with	<code>img[src^="https"]</code>	All <code></code> with <code>src</code> starting with "https"
<code>[attr\$="value"]</code>	Ends with	<code>img[src\$=".jpg"]</code>	All <code></code> ending with ".jpg"
<code>[attr*="value"]</code>	Contains value	<code>a[href*="google"]</code>	All <code><a></code> containing "google" in href

CSS COLOR IN DIFFERENT WAYS

1. Color Names

You can directly use color names like:

color: red;

background-color: blue;

2. HEX Codes

Use a # followed by 6 characters (digits or A–F):

color: #ff0000; /* red */

color: #00ff00; /* green */

color: #0000ff; /* blue */

3. RGB (Red, Green, Blue)

Values from 0 to 255:

color: rgb(255, 0, 0); /* red */

color: rgb(0, 255, 0); /* green */

color: rgb(0, 0, 255); /* blue */

4. RGBA (RGB + Opacity)

Last value is transparency (0 = fully transparent, 1 = fully solid):

color: rgba(255, 0, 0, 0.5); /* semi-transparent red */

5. HSL (Hue, Saturation, Lightness)

color: hsl(0, 100%, 50%); /* red */

color: hsl(120, 100%, 50%); /* green */

color: hsl(240, 100%, 50%); /* blue */

B What is a CSS Border?

A border is the outer line around an element (like a box).

```
selector {  
  border: 2px solid red;  
}
```

Border Styles:

Style	Looks Like	
border: 1px dashed black;	-----	
border: 1px solid black;	——	
border: 1px dotted black;		
border: 1px dashed black;	— — —	
border: 3px double black;	==	
border: 3px groove black;		3D grooved border
border: 3px ridge black;		3D ridged border
border: 1px inset black;		Inside shadow
border: 1px outset black;		Outside shadow
border: none;		No border

Border Sides:

Apply borders to specific sides:

```
border-top: 2px dashed green;
```

```
border-right: 1px solid blue;
```

```
border-bottom: 3px dotted orange;
```

```
border-left: 4px double black;
```

What is Padding in CSS?

Padding is the space between the content and the border of an element.

PADDING: TOP ,RIGHT ,BOTTOM, LEFT; ---> CLOCK WISE WANT DIFFERNT VALUE OF EACH SIDE USE THAT WAY

PADDING; VALUE; --> IF WANT ALL SIDE EQUAL

What is Margin in CSS?

Margin is the space outside an element's border.

It pushes the element away from other elements.>`