

Day 7 of training

topics->

- 1). CSS OVERFLOW
- 2). CSS POSITION
- 3). CSS FLOAT
- 4). CSS PSEUDO CLASS use (:
- 5). CSS PSEUDO ELEMENTS use(: :)
- 6). CSS ANIMATION
- 7).CSS TRANSITION
- 8). CSS FLEX
- 9). CSS GRID

1) CSS OVERFLOW

What it does:

Controls what happens when content overflows an element's box.

Values:

visible – Default. Overflow is shown.

hidden – Cuts off extra content.

scroll – Adds scrollbars always.

auto – Adds scrollbars only when needed.

Example:

```
div {  
  width: 100px;  
  height: 100px;  
  overflow: auto;  
}
```

2) CSS POSITION

What it does: Controls how an element is placed in the document.

Types:

static – Default, normal flow.

relative – Moves relative to its normal position.

absolute – Positioned relative to the nearest positioned ancestor.

fixed – Fixed to the viewport.

sticky – Scrolls until a threshold.

Example:

```
div {  
    position: absolute;  
    top: 10px;  
    left: 20px;  
}
```

3) CSS FLOAT

What it does:

Makes elements "float" left or right, letting text wrap around.

Values: left, right, none

Example:

```
img {  
    float: left;  
    margin-right: 10px;  
}
```

4) CSS PSEUDO-CLASS (:)

What it does:

Styles elements in a special state.

Examples:

```
a:hover {
```

```
    color: red; /* when mouse hovers */
}
li: first-child {
    color: blue;
}
```

5) CSS PSEUDO-ELEMENT (::)

What it does:

Styles a part of an element.

Examples:

```
p::first-line {
    font-weight: bold;
}
p::before {
    content: " ";
}
```

6) CSS ANIMATION

What it does:

Animates elements by changing styles over time.

Example:

```
@keyframes fade {
    from { opacity: 0; }
    to { opacity: 1; }
}
div {
    animation: fade 2s ease-in-out;
}
```

7) CSS TRANSITION

What it does:

Smoothly animates property changes (on hover or interaction).

Example:

```
button {  
  background-color: blue;  
  transition: background-color 0.3s ease;  
}  
  
button:hover {  
  background-color: green;  
}
```

8) CSS FLEXBOX

What it does:

A layout model for arranging items in a row/column.

Example:

```
.container {  
  display: flex;  
  justify-content: space-between;  
  align-items: center;  
}
```

9) CSS GRID

What it does:

A powerful 2D layout system with rows and columns.

Example:

```
.grid {  
  display: grid;
```

```
grid-template-columns: repeat(3, 1fr);  
gap: 10px;  
}
```