

PRACTICAL WEEK - 5

TASK1: Implement a producer-consumer communication system using anonymous pipes where the parent process generates data and the child process consumes it. Measure the communication efficiency

```
siddu@DESKTOP-5CRM05P: ~ X Ubuntu
siddu@DESKTOP-5CRM05P:~$ mkdir practical5
siddu@DESKTOP-5CRM05P:~$ cd practical5
siddu@DESKTOP-5CRM05P:~/practical5$ nano producer_consumer.c
siddu@DESKTOP-5CRM05P:~/practical5$ gcc producer_consumer.c -o producer_consumer
siddu@DESKTOP-5CRM05P:~/practical5$ ./producer_consumer
Producer: Data 1
Producer: Data 2
Producer: Data 3
Producer: Data 4
Producer: Data 5
Consumer: Data 1
Consumer: Data 2
Consumer: Data 2
Consumer: Data 2
Consumer: Data 2
Communication time: 0.000086 seconds
siddu@DESKTOP-5CRM05P:~/practical5$
```

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <string.h>
#include <time.h>

int main() {
    int fd[2];
    pid_t pid;
    char buffer[100];

    if (pipe(fd) == -1) {
        perror("pipe");
        return 1;
    }

    pid = fork();

    if (pid < 0) {
        perror("fork");
        return 1;
    }

    if (pid > 0) {
        // Parent Process - Producer
        close(fd[0]);
        clock_t start = clock();

        for (int i = 1; i <= 5; i++) {
            sprintf(buffer, "Data %d", i);
            write(fd[1], buffer, strlen(buffer) + 1);
            printf("Producer: %s\n", buffer);
        }

        clock_t end = clock();
        close(fd[1]);
        wait(NULL);

        double time_taken = (double)(end - start) / CLOCKS_PER_SEC;
        printf("Communication time: %f seconds\n", time_taken);
    } else {
        // Child Process - Consumer
        close(fd[1]);
```

```

if (pid > 0) {
    // Parent Process - Producer
    close(fd[0]);
    clock_t start = clock();

    for (int i = 1; i <= 5; i++) {
        sprintf(buffer, "Data %d", i);
        write(fd[1], buffer, strlen(buffer) + 1);
        printf("Producer: %s\n", buffer);
    }

    clock_t end = clock();
    close(fd[1]);
    wait(NULL);

    double time_taken = (double)(end - start) / CLOCKS_PER_SEC;
    printf("Communication time: %f seconds\n", time_taken);
} else {
    // Child Process - Consumer
    close(fd[1]);

    for (int i = 1; i <= 5; i++) {
        read(fd[0], buffer, sizeof(buffer));
        printf("Consumer: %s\n", buffer);
    }

    close(fd[0]);
}

return 0;
}

```

TASK2: Develop a program that executes the equivalent of the shell command: `ls -l | grep ".c"` using `fork()`, `pipe()`, `dup2()`, and `exec()` system calls.

```

siddu@DESKTOP-5CRM05P: ~ - x  Ubuntu
siddu@DESKTOP-5CRM05P:~/practical$ nano pipe_ls_grep.c
siddu@DESKTOP-5CRM05P:~/practical$ ls -l | grep ".c"
-rw-r--r-- 1 siddu siddu 1039 Sep 1 08:38 pipe_ls_grep.c
-rwxr-xr-x 1 siddu siddu 16416 Sep 1 08:37 producer_consumer
-rw-r--r-- 1 siddu siddu 1101 Sep 1 08:37 producer_consumer.c
siddu@DESKTOP-5CRM05P:~/practical$ gcc pipe_ls_grep.c -o pipe_ls_grep
siddu@DESKTOP-5CRM05P:~/practical$ ls -l | grep ".c"
-rw-r--r-- 1 siddu siddu 1039 Sep 1 08:38 pipe_ls_grep.c
-rwxr-xr-x 1 siddu siddu 16416 Sep 1 08:37 producer_consumer
-rw-r--r-- 1 siddu siddu 1101 Sep 1 08:37 producer_consumer.c

```

```

GNU nano 8.7.1 pipe_ls_grep.c
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    int fd[2];
    pid_t p1, p2;

    if (pipe(fd) == -1) {
        perror("pipe");
        return 1;
    }

    p1 = fork();
    if (p1 == -1) {
        perror("fork");
        return 1;
    }

    if (p1 == 0) {
        // First child: ls -l
        // Redirect stdout to write-end of pipe
        close(fd[0]);
        dup2(fd[1], STDOUT_FILENO);
        close(fd[1]);

        execlp("ls", "ls", "-l", NULL);
        perror("execlp");
        exit(1);
    }

    // Second child: grep
    p2 = fork();
    if (p2 == -1) {
        perror("fork");
        return 1;
    }

    if (p2 == 0) {
        // Redirect stdin from read-end of pipe
        close(fd[1]);

```

```
if (p2 == 0) {
    // Redirect stdin from read-end of pipe
    close(fd[1]);
    dup2(fd[0], STDIN_FILENO);
    close(fd[0]);

    execlp("grep", "grep", ".c", NULL);
    perror("execlp");
    exit(1);
}

// Parent Process
close(fd[0]);
close(fd[1]);

waitpid(p1, NULL, 0);
waitpid(p2, NULL, 0);

return 0;
}
```