1. What is a function in Python? Why do we use functions?

---

2. What is the difference between defining a function and calling a function?

Give a simple example.

---

3. What is the difference between a parameter and an argument?

Give an example.

---

4. What is the difference between print() and return in a function?

Explain when you would use each one.

---

5. What is the difference between positional arguments and keyword arguments?

Give one example of each.

---

6. Write a function called check_even(number) that returns True if the number is even and False if it is odd.

Example:

check_even(10) → True
check_even(7) → False

---

7. Write a function called find_largest(a, b, c) that returns the largest of three numbers.

Do not use the max() function.

---

8. Write a function called calculate_discount(amount) that returns the final amount after applying the following discount rules:

- Amount ≥ ₹10,000 → 20% discount
- Amount ≥ ₹5,000 → 10% discount
- Amount ≥ ₹2,000 → 5% discount
- Otherwise → No discount

---

9. Write a function called count_even(numbers) that accepts a list of numbers and returns the number of even numbers in the list.

Use a loop.

Example:

Input: [10, 15, 20, 25, 30]

Output: 3

---

10. Write a function called find_largest(numbers) that finds and returns the largest number in a list.

Use a loop and do not use max().

---

11. Write a function called count_vowels(text) that accepts a string and returns the number of vowels in the string.

Example:

Input: "Python Programming"

Output: 4

---

12. Write a function called get_even_numbers(numbers) that accepts a list and returns a new list containing only the even numbers.

Example:

Input: [1, 2, 3, 4, 5, 6]

Output: [2, 4, 6]

---

13. Can one function call another function?

Explain with an example.

Then create the following two functions:

is_even(number)

count_even_numbers(numbers)

The count_even_numbers() function should call is_even() to determine whether each number is even.

---

14. What is a local variable in Python?

Consider the following code:

```
def test():
x = 100
print(x)

test()

print(x)
```

What will happen when this code is executed? Explain why.

---

15. Final Challenge – Employee Bonus System

Consider the following employee data:

```
employees = [
{"name": "Rahul", "experience": 3, "salary": 65000},
{"name": "Aisha", "experience": 5, "salary": 85000},
{"name": "Neha", "experience": 2, "salary": 55000}
]
```

Create a function called calculate_bonus(employee) that calculates and returns the employee's bonus.

Use the following rules:

- Experience ≥ 5 years → 15% bonus
- Experience ≥ 3 years → 10% bonus
- Experience < 3 years → 5% bonus

Then use a loop to calculate and display the bonus for every employee.

Example output format:

```
Rahul → Bonus: _____
Aisha → Bonus: _____
Neha → Bonus: _____
```