

OverTheWire

Leavel 1

***** Bandit 0 *****

ssh bandit0@**bandit.labs.overthewire.org** -p 2220

bandit0 pass -> ZjLjTmM6FvvyRnrb2rfNWOZOTa6ip5If

exit

***** Bandit level 1 -> level 2 *****

ls -alps

ssh bandit1@**bandit.labs.overthewire.org** -p 2220

cat readme

ZjLjTmM6FvvyRnrb2rfNWOZOTa6ip5If

- **ls -alps**: Lists all files (including hidden), shows detailed information, adds trailing slashes for directories, and displays file sizes in blocks.
- **cd**: Changes the current working directory.
- **cat**: Displays the contents of one or more files.
- **file**: Determines the type of a file based on its content.
- **du**: Displays disk usage of files and directories.
- **find**: Searches for files and directories based on various criteria (e.g., name, size, modification time).
- The **./** specifies the **current directory**.

- The `flag.txt` is a **filename**.

***** Bandit level 1 -> level 2 *****

ls -alps

cat ./-

exit

pass: 263JGJPfgU6LtdEvgfWU1XP5yac29mFx

Level 2

***** Bandit level 2 *****

pass: 263JGJPfgU6LtdEvgfWU1XP5yac29mFx

cat spaces\ in\ this\ filename

pass: MNk8KNH3Usiio41PRUEoDFPqfxLPLSmx

exit

level 3

Bandit level 3 -> level 4

pass: MNk8KNH3Usiio41PRUEoDFPqfxLPLSmx

ls -alps

cd /inhere

ls -al

cat ...Hiding-From-You

pass: 2WmrDFRmJlq3IPxneAaMGhap0pFhF3NJ

Basics

ip addr

Recursive Forcing

```
sudo rm -rff /
```

removal of all directories from root

```
sudo rm -rff / --no-preserve-root
```

all data will be deleted