Exp No:**14** Experiment to understand feature scaling. Description: Understand the importance of feature scaling

10/5/24, 8:09 PM 09.09.2024-sklearn.ipynb - Colab

```
import numpy as np
import pandas as pd
df=pd.read_csv('/content/pre-process_datasample.csv')
```

```
df
```

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	NaN	Yes
5	France	35.0	58000.0	Yes
6	Spain	NaN	52000.0	No
7	France	48.0	79000.0	Yes
8	NaN	50.0	83000.0	No
9	France	37.0	67000.0	Yes

Generate code with `df` toggle_off View recommended plots New interactive sheet

Next steps: `df.head()`

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40	0	NaN

Yes

recommended plots New interactive sheet

Next steps:
Generate code with `df` toggle_off View

```
df.Country.fillna(df.Country.mode()[0],inplace=True)
features=df.iloc[:,:-1].values
```

```
<ipython-input-5-20665a0bbaa1>:1: FutureWarning: A value is trying to be set on a copy of a DataFrame o
The behavior will change in pandas 3.0. This inplace method will never work because the intermediate ob

For example, when doing 'df[col].method(value, inplace=True)', try using 'df.method({col: value}, inpla
```

```
df.Country.fillna(df.Country.mode()[0],inplace=True)
```

```
label=df.iloc[:,-1].values
```

```
Start coding or generate with AI.
```



```
from sklearn.impute import SimpleImputer
```

```
age=SimpleImputer(strategy="mean",missing_values=np.nan)
```

```
Salary=SimpleImputer(strategy="mean",missing_values=np.nan)
```

```
age.fit(features[:,[1]])
```

```
▾ SimpleImputer i ?
SimpleImputer()
```

```
Salary.fit(features[:,[2]])
```

```
▾ SimpleImputer i ?
SimpleImputer()
```

```
SimpleImputer()
```

```
▾ SimpleImputer i ?
SimpleImputer()
```

```
features[:,[1]]=age.transform(features[:,[1]])
```

```
features[:,[2]]=Salary.transform(features[:,[2]])
```

```
features
```

```
array([['France', 44.0, 72000.0],
       ['Spain', 27.0, 48000.0],
       ['Germany', 30.0, 54000.0],
       ['Spain', 38.0, 61000.0],
       ['Germany', 40.0, 63777.77777777778],
       ['France', 35.0, 58000.0],
       ['Spain', 38.77777777777778, 52000.0],
       ['France', 48.0, 79000.0],
       ['France', 50.0, 83000.0],
       ['France', 37.0, 67000.0]], dtype=object)
```

```
from sklearn.preprocessing import OneHotEncoder
```

```
oh = OneHotEncoder(sparse_output=False)
```

```
Country=oh.fit_transform(features[:,[0]])
```

```
Country
```

```
array([[1., 0., 0.],
       [0., 0., 1.],
       [0., 1., 0.],
       [0., 0., 1.],
       [0., 1., 0.],
       [1., 0., 0.],
       [0., 0., 1.],
       [1., 0., 0.],
```



```
       [1., 0., 0.],
       [1., 0., 0.]])
```

```
final_set=np.concatenate((Country,features[:,[1,2]]),axis=1)
```

```
final_set
```

```
array([[1.0, 0.0, 0.0, 44.0, 72000.0],
       [0.0, 0.0, 1.0, 27.0, 48000.0],
       [0.0, 1.0, 0.0, 30.0, 54000.0],
       [0.0, 0.0, 1.0, 38.0, 61000.0],
       [0.0, 1.0, 0.0, 40.0, 63777.77777777778],
       [1.0, 0.0, 0.0, 35.0, 58000.0],
       [0.0, 0.0, 1.0, 38.77777777777778, 52000.0],
       [1.0, 0.0, 0.0, 48.0, 79000.0],
       [1.0, 0.0, 0.0, 50.0, 83000.0],
       [1.0, 0.0, 0.0, 37.0, 67000.0]], dtype=object)
```

```
from sklearn.preprocessing import StandardScaler
sc=StandardScaler()
sc.fit(final_set)
feat_standard_scaler=sc.transform(final_set)
```

```
feat_standard_scaler
```

```
array([[ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
         7.58874362e-01, 7.49473254e-01],
       [-1.00000000e+00, -5.00000000e-01, 1.52752523e+00,
       -1.71150388e+00, -1.43817841e+00],
       [-1.00000000e+00, 2.00000000e+00, -6.54653671e-01,
       -1.27555478e+00, -8.91265492e-01],
       [-1.00000000e+00, -5.00000000e-01, 1.52752523e+00,
       -1.13023841e-01, -2.53200424e-01],
       [-1.00000000e+00, 2.00000000e+00, -6.54653671e-01,
       1.77608893e-01, 6.63219199e-16],
       [ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
       -5.48972942e-01, -5.26656882e-01],
       [-1.00000000e+00, -5.00000000e-01, 1.52752523e+00,
       0.00000000e+00, -1.07356980e+00],
       [ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
       1.34013983e+00, 1.38753832e+00],
       [ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
       1.63077256e+00, 1.75214693e+00],
       [ 1.00000000e+00, -5.00000000e-01, -6.54653671e-01,
       -2.58340208e-01, 2.93712492e-01]])
```

```
from sklearn.preprocessing import MinMaxScaler
mms=MinMaxScaler(feature_range=(0,1))
mms.fit(final_set)
feat_minmax_scaler=mms.transform(final_set)
feat_minmax_scaler
```

```
array([[1. , 0. , 0. , 0.73913043, 0.68571429],
       [0. , 0. , 1. , 0. , 0. ],
       [0. , 1. , 0. , 0.13043478, 0.17142857],
       [0. , 0. , 1. , 0.47826087, 0.37142857],
```

```
       [0. , 1. , 0. , 0.56521739, 0.45079365],
       [1. , 0. , 0. , 0.34782609, 0.28571429],
       [0. , 0. , 1. , 0.51207729, 0.11428571],
       [1. , 0. , 0. , 0.91304348, 0.88571429],
       [1. , 0. , 0. , 1. , 1. ],
       [1. , 0. , 0. , 0.43478261, 0.54285714]])
```

Start coding or generate with AI.