

DB Auto Restore - SQL SERVER 2012

<https://gallery.technet.microsoft.com/scriptcenter/AUTO-RESTORE-SQL-SERVER-6a65b8ca>



DB Auto Restore Script - SQL Server.b

```
use master
go
```

```
IF EXISTS (
    SELECT type_desc, type
    FROM sys.procedures WITH(NOLOCK)
    WHERE NAME = 'dba_restore'
    AND type = 'P'
)
DROP PROCEDURE dba_restore
GO
```

--EXECUTE BELOW SP by giving 2 parameters:

--master..dba_restore 'H:\SQLBackups\Default\AdventureWorks2008R2-Full Database Backup.bak','Sample1'

--Parameter-1: Source DB Backup path & File Name which is to be used for DB Restore/Replace on top of Destination DB.

--Parameter-2: Destination DB name which is to be Restored (Replace) with Source Backup file.

--Note: Both Source DB & Destination DB should have EQUAL NO OF Files (Data & Log) OTHER the SP execution will get fail.

```
Create procedure dba_restore @backupFile varchar(max),@dbName varchar(256)
as
```

```
declare @headers table
(
    LogicalName nvarchar(128)
    ,PhysicalName nvarchar(260)
    ,Type char(1)
    ,FileGroupName nvarchar(128)
    ,Size numeric(20,0)
    ,MaxSize numeric(20,0),
    FileId tinyint,
    CreateLSN numeric(25,0),
    DropLSN numeric(25, 0),
    UniqueID uniqueidentifier,
    ReadOnlyLSN numeric(25,0),
    ReadWriteLSN numeric(25,0),
    BackupSizeInBytes bigint,
    SourceBlockSize int,
    FileGroupId int,
    LogGroupGUID uniqueidentifier,
    DifferentialBaseLSN numeric(25,0),
    DifferentialBaseGUID uniqueidentifier,
    IsReadOnly bit,
    IsPresent bit,
    TDEThumbprint varbinary(32)
)
```

```
/*preparing for the backup script */
```

```
insert into @headers exec('restore filelistonly from disk = "' + @backupFile + '"');
declare @h1count int=(select COUNT(*) from @headers )
declare @h2count int=(select COUNT(*) from sys.master_files where database_id=DB_ID(@dbName))
if (@h1count=@h2count) /*checking if there are equal number of files in both backup and destination db*/
begin
```

```
/*Bringing the database into single user mode , meaning killing all the users conneted to the database*/
```

```
print ('bringing database into single user mode')
declare @setsingle nvarchar(max)
set @setsingle =(select 'alter DATABASE '+@dbName+' SET SINGLE_USER WITH ROLLBACK IMMEDIATE')
exec sp_executesql @setsingle
print ('the database '+@dbName+' is put into single user mode')
```

```
BEGIN TRY
```

```
declare @temp table(query varchar (4000));
```

```
insert into @temp select 'restore database '+@dbName+' from disk="'+@backupFile+" with';
```

```
insert into @temp select 'move '"+h1.LogicalName+"' to '"+h2.physical_name+"' from @headers as h1 inner join
sys.master_files as h2 on h2.file_id=h1.FileId /*joining the logical name and physical name based on the fileid*/
where h2.database_id=DB_ID(@dbName);
```

```
insert into @temp select 'replace,stats=10;'
```

```
/*converting the multiple rows of the table into one single row which inturns form on big restore query
which will be executed using the sp_executesql */
```

```
declare @restore nvarchar(max)
set @restore=(SELECT STUFF((SELECT ' ' + query FROM @temp FOR XML PATH("") ,1,1,") AS Txt)
print ('startting the database restore command')
print @restore
exec sp_executesql @restore
```

```
END TRY
```

```
BEGIN CATCH
```

```
select ERROR_NUMBER() AS ErrorNumber
,ERROR_SEVERITY() AS ErrorSeverity
,ERROR_STATE() AS ErrorState
,ERROR_PROCEDURE() AS ErrorProcedure
,ERROR_LINE() AS ErrorLine
,ERROR_MESSAGE() AS ErrorMessage;
```

```
END CATCH;
```

```
/*Bringing the database into multi user mode */
```

```
declare @muluser nvarchar(max)
set @muluser =(select 'alter DATABASE '+@dbName+' SET MULTI_USER;')
exec sp_executesql @muluser
print ('the database '+@dbName+' is put into multi user mode')
```

```
/*fixing all the orphan users in the database which got refreshed*/
```

```
print ('updating the orphan users no new logins will be created')
declare @fixOrph nvarchar(4000)
set @fixOrph=(
'use '+@dbName+';
declare @query varchar(1000)
declare @executequery cursor
set @executequery=cursor for
select " sp_change_users_login "+CHAR(39)+"update_one"+CHAR(39)+",""+CHAR(39)+name+CHAR(39)+",""+CHAR(39)+name+CHAR(39)
from sysusers where issqluser = 1 and (sid is not null and sid <> 0x0) AND SUSER_SNAME(sid) IS NULL
open @executequery
fetch next from @executequery into @query
while @@fetch_status=0
begin
exec (@query)
print (@query)
fetch next from @executequery into @query
end
close @executequery;
deallocate @executequery;')
exec sp_executesql @fixOrph
```

end

/*if there is no database present as mentioned in the procedure you will get the below error*/

```
else if (@h2count=0)
print 'there is no database called '+@dbname+' in the present server and restore aborted'
```

```
/*if there are unequal number of files between the backup and the destination db you will get the below error*/
else print 'un equal number files ,restore aborted'
go
```

/*executing the procedure

-within the first quotes mention the full backup path and in the second quotes mention the database to which the backup has to be refreshed

-if no database is present you will get a error like

(there is no database called ITSM1 in the present server)

-if there are unequal number of files you will get a error like

(unequal number of files)

-IMPORTANT when you get a error like that please go with the manual refresh*/

--EXECUTE BELOW SP by giving 2 parameters:

--master..dba_restore 'H:\SQLBackups\Default\AdventureWorks2008R2-Full Database Backup.bak','Sample1'

--Parameter-1: Source DB Backup path & File Name which is to be used for DB Restore/Replace on top of Destination DB.

--Parameter-2: Destination DB name which is to be Restored (Replace) with Source Backup file.

--Note\Limitation: Both Source DB & Destination DB should have EQUAL NO OF Files (Data & Log) OTHER the SP execution will get fail.





