



RECOMMENDED PCB LAYOUT

NOTE:
MATERIAL:
HOUSING:PBT+30%G.F UL 94V-0
CONTACT:BRASS
SHELL:SPCC
PLATING:
CONTACT: GOLD AND TIN OVER NICKEL PLATING
SHELL: NICKEL OVER ALL PLATING
SPECIFICATION:
CURRENT-MAX[AMPS]:1.5A
VOLTAGE-MAX[VOLTS]:30V
WITHSTANDING VOLTAGE:500V AC
CONTACT RESISTANCE[OHMS]:30MΩ MIN
INSULATION RESISTANCE[OHMS]:1000MΩ MIN
INSULATION COLOR:WHITE
ENVIRONMENTAL:
TEMPERATURE RANGE:-40°C TO+105°C
PART NO.:

08/09/26	SYSTEM		變更尺寸	△	A1
08/05/27	SYSTEM		NEW DWG		A0
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差參考表			CnC Tech,LLC		
			TITLE: USB 4P A/M SMT H=6.00mm 成品針長2.25mm		
X.X	±0.30	X.X'	±3.00'	APPD:	PRODUCT NO: 1002-016-01101
X.XX	±0.15	X.XX'	±1.00'	CHECK:	DATE SCALE UNIT TYPE PAGE
X.XXX	±0.100	X.XXX'	±0.500'	DRAW:	2008.09.26 1:1 mm CD 1 / 1