```c
#include <stdio.h>
#define SIZE 5

int queue[SIZE];
int front = -1, rear = -1;

void enqueue()
{
    int job;

    if ((rear + 1) % SIZE == front)
    {
        printf("Printer Queue is Full!\n");
        return;
    }

    printf("Enter Print Job ID: ");
    scanf("%d", &job);

    if (front == -1)
        front = 0;

    rear = (rear + 1) % SIZE;
    queue[rear] = job;

    printf("Print Job Added Successfully!\n");
}

void dequeue()
{
    if (front == -1)
    {
        printf("Printer Queue is Empty!\n");
        return;
    }

    printf("Processing Print Job ID: %d\n", queue[front]);

    if (front == rear)
    {
        front = rear = -1;
    }
    else
    {
        front = (front + 1) % SIZE;
    }
}
```

```
void display()
{
    int i;

    if (front == -1)
    {
        printf("Printer Queue is Empty!\n");
        return;
    }

    printf("Pending Print Jobs: ");

    i = front;
    while (1)
    {
        printf("%d ", queue[i]);

        if (i == rear)
            break;

        i = (i + 1) % SIZE;
    }

    printf("\n");
}

int main()
{
    int choice;

    while (1)
    {
        printf("\n--- Printer Queue Manager ---\n");
        printf("1. Add Print Job\n");
        printf("2. Process Print Job\n");
        printf("3. Display Print Jobs\n");
        printf("4. Exit\n");
        printf("Enter your choice: ");
        scanf("%d", &choice);

        switch (choice)
        {
            case 1:
                enqueue();
                break;

            case 2:
                dequeue();
                break;

            case 3:
                display();
                break;

            case 4:
                return 0;

            default:
                printf("Invalid Choice!\n");
        }
    }

    return 0;
}
```