```c
#include <stdio.h>
#include <string.h>

#define MAX 5

typedef struct
{
    int job;
    char documentType[50];
} PrintJob;

PrintJob queue[MAX];

int front = -1;
int rear = -1;

void enqueue()
{
    PrintJob p;

    if(rear == MAX - 1)
    {
        printf("Queue Overflow! Print queue is full.\n");
        return;
    }

    printf("Enter Job ID: ");
    scanf("%d", &p.job);

    printf("Enter Document Type: ");
    scanf("%s", p.documentType);

    if(front == -1)
    {
        front = 0;
    }

    rear++;
    queue[rear] = p;

    if(rear == MAX - 1)
    {
        printf("All jobs inserted successfully until the queue reaches maximum capacity.\n");
    }
    else
    {
        printf("Print job added successfully.\n");
    }
```

```
}

void dequeue()
{
    if(front == -1 || front > rear)
    {
        printf("Queue Underflow! No print jobs available.\n");
        return;
    }

    printf("Job %d (%s) is processed and removed.\n",
           queue[front].job,
           queue[front].documentType);

    front++;

    if(front > rear)
    {
        front = -1;
        rear = -1;
    }
}

void dequeueAll()
{
    if(front == -1 || front > rear)
    {
        printf("Queue Underflow! No print jobs available.\n");
        return;
    }

    while(front <= rear)
    {
        printf("Job %d (%s) processed.\n",
               queue[front].job,
               queue[front].documentType);

        front++;
    }

    front = -1;
    rear = -1;

    printf("All jobs are processed one by one until the queue becomes empty.\n");
}

void display()
{
```

```
    int i;

    if(front == -1 || front > rear)
    {
        printf("No Pending Print Jobs.\n");
        return;
    }

    printf("All pending print jobs are displayed in FIFO order.\n");

    for(i = front; i <= rear; i++)
    {
        printf("[%d] Job ID: %d | Document: %s\n",
               i - front + 1,
               queue[i].job,
               queue[i].documentType);
    }
}

int main()
{
    int choice;

    printf("Queue initialized successfully.\n");

    do
    {
        printf("\n1. Enqueue\n");
        printf("2. Dequeue one\n");
        printf("3. Dequeue all\n");
        printf("4. Display\n");
        printf("0. Exit\n");

        printf("Enter your choice: ");
        scanf("%d", &choice);

        switch(choice)
        {
            case 1:
                enqueue();
                break;

            case 2:
                dequeue();
                break;

            case 3:
                dequeueAll();
                break;

            case 4:
                display();
                break;

            case 0:
                printf("Program terminated successfully.\n");
                break;

            default:
                printf("Invalid choice.\n");
        }

    } while(choice != 0);

    return 0;
}
```