Exp1 Study of Various Network command Used In Linux and Windows

1) arp -a

show IP Addres of your computer alone with IP Address and MAC address of you router.

O/P

Interface 192.168.156.1 . . . 0x7

Internet Address	Physical Address	Type
192.168.56.255	f.f.ff.ff.ff.ff	static
244.00.22.	01.00.5e.002	static
23.9.255.25.250	01.00.5e.ff.ff	static

2) hostname : Display name of your computer

O/P : Naveed

3) ipconfig/all : Display detailed configuration information about TCP/IP connection and type of ethernet adapter in the system.

Scanned with OKEN Scanner

o/p

Window IP Configuration

Hostname . . . . Naveed

Primary DNs suffix

Node type

4) nb stat -a : Display protocol statistic and current TCP/IP connection using NBT

o/p

NBTSTAT [[-a Remote Name] [-A IP address] [-

5) netstat Display a variety of statistics about a computer active TCP/IP Connection

o/p

Active Connection

Proto	local address	Foreign address	state
TCP	10.76.9.6.60:49175	10:76.96.163:domain	Timewait
TCP	10.76.96.60:52239	142.250.183.http	stubrshid
TCP	10.76.96.60:56954	10.76.96.163 domain	Time-wai

Scanned with OKEN Scanner

6) nslookup : Display DNS detail such as IP Address of the particular computer.

O/P:

Server : Unknown

Address : 10.76.196.163

7) PathPing : Traces the root to destination address the ranches a 25 second test of each routes along the way.

O/P

Pathping [-g host-list] [-n maximum-hops]

[-i address]

Linux Networking Commands.

1.) ip : Help from setting up new system and assigning IP to trouble shooting existing system.

2.) if config : The if Config is staple in many sys admins tool belt for configuring trouble shooting networks.

3.) mtr : MTR is program with CLI that are a network diagnostic and trouble shooting tool.

4.) tcpdump : The tcpdump command is designed for capturing displaying packets.

Scanned with OKEN Scanner

5.) Ping: Ping is tool that verifies IP-level connectivity to another TCP/IP computer by sending Internet control message Protocol (ICMP) Echo request Message protocol (ICMP) Echo request Message.

6.) If Config

lo: flags: 73 <UP: LOOK back, RUNNING> mtu 65536

inet 127.0.0.1 net mask 255.0.0.0

inet6 :: 1 prefix len 125 scope dx 10<host>

7.) mtr -to/p

My traceover [V0.87]

local host. local domain (:1)

Key help Displaymode Restat statistic

host Packets

1::1 loss % lost

0.0% 0.2

8) tcpdump -i

listening on enp 7s0 f 40I

IP 6 93.243.107.34.b.c. google user content.com

http > Nov 22 00:56:18, seq 5929, ack 35457, win 1043

9) Ping

Ping 8.8.8.8

64 bytes from 8.8.8.8 icmp. seq=1 ttl=113

time = 37.4ms

Result:

Thus the various command network used in linux and window are executed successfully.