IPL Data Analysis using SQL 🏏

- From Raw Data → Powerful Insights 📊

Real-world SQL queries & insights
By Siddharth Gadapkar

Dataset Overview

- 50 Players
- Multiple IPL Teams
- Roles: Batsman, Bowler, All-rounder
- Metrics: Runs, Wickets, Salary

- **Goal:**

  Analyze performance & salary using SQL

🏆 Highest Run Scorer

- Find the player who has scored the highest number of runs.

Query: SELECT player_name, runs

FROM ipl_players WHERE runs=(SELECT MAX(runs) FROM ipl_players);

Output:

	PLAYER_NAME	RUNS
▶	Shubman Gill	700

- Insight 💡 :Identifies the top performer.

Above Average Players

- Find Players with Above Average Runs

Query : SELECT player_name, runs FROM ipl_players
WHERE runs>(SELECT AVG(runs) FROM
ipl_players);

Output:

PLAYER_NAME	RUNS
AB de Villiers	500
Kane Williamson	400
Quinton de Kock	480
Ishan Kishan	420
Suryakumar Ya...	610
Shubman Gill	700
Ruturaj Gaikwad	550
Devdutt Padikkal	400
Sanju Samson	500
Nicholas Pooran	450
Marcus Stoinis	350
Faf du Plessis	600
Jos Buttler	650
Prithvi Shaw	400
Mayank Agarwal	420
Rahul Tripathi	450
Shreyas Iyer	500
Nitish Rana	420
Rinku Singh	380

- Insight 💡 : Filters players performing better than average.

Same Team as M.S. DHONI

- Find players from same team as M.S. DHONI (CSK)

Query : SELECT player_name, team FROM ipl_players WHERE team = (SELECT team FROM ipl_players WHERE player_name = 'MS Dhoni ');

Output:

PLAYER_NAME	TEAM
MS Dhoni	CSK
Ravindra Jadeja	CSK
Ben Stokes	CSK
Ruturaj Gaikwad	CSK
Deepak Chahar	CSK

- Insights 💡 : Finds players belonging to same team.

Teams with >3 Players

- Teams Having More Than 3 Players

Query : SELECT team FROM ipl_players
GROUP BY team HAVING COUNT(*) >3;

Output :

TEAM
RCB
MI
CSK
LSG
PBKS
GT
KKR
DC
RR
SRH

- Insight 💡 : Identifies teams with higher player count.

Players with Runs Greater Than Any Bowlers.

- Find players who have scored more runs than any bowlers.

Query:
```
SELECT player_name, runs FROM ipl_players
WHERE runs > ANY (SELECT runs
FROM ipl_players WHERE role = 'Bowler’
)
ORDER BY runs DESC
LIMIT 5;
```

Output:

PLAYER_NAME	RUNS
Shubman Gill	700
Jos Buttler	650
Virat Kohli	639
Suryakumar Yadav	610
David Warner	600

- **Insight** 💡 **:** Identifies players outperforming at least one bowler, useful for performance comparison.

Not Bowlers (Subquery)

- Players Who Are Not Bowlers (Using Subquery)

Query: SELECT player_name, role FROM ipl_players WHERE player_id NOT IN(SELECT player_id FROM ipl_players WHERE role = 'BOWLER');

Output:

PLAYER_NAME	ROLE
Virat Kohli	Batsman
Rohit Sharma	Batsman
MS Dhoni	Wicketkeeper
KL Rahul	Batsman
Shikhar Dhawan	Batsman
Hardik Pandya	All-rounder
Ravindra Jadeja	All-rounder
Andre Russell	All-rounder

- Insight 💡 : Demonstrates how subqueries can filter and exclude specific roles from a dataset.

Key Insights

- Top-performing players are not always the highest paid
- Several players outperform bowlers in terms of runs
- Teams like MI, RCB, and CSK have strong player distribution
- Subqueries help solve complex filtering problems efficiently
- SQL enables meaningful insights from structured data

- **Skills Used:**

SQL | Subqueries | GROUP BY | HAVING | Data Analysis