| | |
|---|---|
| **Status** | Finished |
| **Started** | Friday, 9 October 2026, 9:33 PM |
| **Completed** | Friday, 9 October 2026, 9:40 PM |
| **Duration** | 7 mins 19 secs |
| **Grade** | **15.00** out of 15.00 (**100**%) |

Question **1**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The encoding of the file
b. The buffer size for the file operations ✓
c. The access mode of the file
d. The file's read/write position

The correct answer is: The buffer size for the file operations

Question **2**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer five characters behind from the current position
b. move the file pointer five characters ahead from the current position ✓
c. moves the file pointer to the end of a file
d. move the file pointer to beginning of the file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **3**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

- a. 0 ✓
- b. 2
- c. null
- d. 1
- e. garbage

The correct answer is:
0

Question **4**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code if the file "example.txt" contains "Python Programming"?

```
f = open("example.txt", "r")
print(f.read(6))
f.close()
```

- a. Program
- b. An error is raised
- c. Python ✓
- d. Python Programming

The correct answer is: Python

Question **5**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
f = open("data.txt", "a")
f.write("Adding new data\n")
f.close()
```

a. Opens the file in read mode

b. Overwrites the file with "Adding new data"

c. Raises an error because the file is opened in append mode

d. Appends "Adding new data" to the end of the file ✓

The correct answer is: Appends "Adding new data" to the end of the file

Question **6**

Correct

Mark 1.00 out of 1.00

What does the following code do?

fo = open("foo.txt", "w")

a. Appends to an existing file

b. Opens an existing file in read mode

c. Opens a file in binary mode

d. Creates a new file for writing ✓

The correct answer is: Creates a new file for writing

Question **7**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

a. wb+
b. r
c. rw+ ✓
d. ab+

The correct answer is: rw+

Question **8**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

True ✓
False

The correct answer is 'True'.

Question **9**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

a. Text file
b. Both text and binary file ✓
c. none of the given choices
d. Binary file

The correct answer is: Both text and binary file

Question **10**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use ____

a. outfile = open("c:\\scores.txt", "w") ✓

b. outfile = open(file = "c:\scores.txt", "w")

c. outfile = open("c:\scores.txt", "w")

d. outfile = open(file = "c:\\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "w")

Question **11**

Correct

Mark 1.00 out of 1.00

What is the difference between r+ and w+ modes in file handling?

a. r+ is for read and write, w+ is for append only

b. r+ is for binary read and write, w+ is for text read and write

c. r+ is for read and append, w+ is for read and write

d. r+ is for read and write without truncating, w+ is for read and write with truncating ✓

The correct answer is: r+ is for read and write without truncating, w+ is for read and write with truncating

Question **12**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

a. Deletes the file

b. Reads the file line by line

c. Moves the file cursor to the specified position ✓

d. Writes data to the file

The correct answer is: Moves the file cursor to the specified position

Question **13**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

- a. infile = open("a.txt", "r") ✓
- b. infile = open(file = "a.txt", "r")
- c. infile = open(file, "a.txt", "r")
- d. infile = open(file = "a.txt", "r")

The correct answer is:
infile = open("a.txt", "r")

Question **14**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

- a. Hello, world! ✓
- b. world
- c. An error is raised
- d. Hello

The correct answer is: Hello, world!

Question **15**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

a. outfile = open(file = “c:\\scores.txt”, “w”)

b. outfile = open(file = “c:\scores.txt”, “w”)

c. outfile = open(“c:\\scores.txt”, “rw”)

d. outfile = open(“c:\\scores.txt”, “a”) ✓

The correct answer is:
outfile = open(“c:\\scores.txt”, “a”)