Status	Finished
Started	Friday, 21 August 2026, 10:11 AM
Completed	Friday, 21 August 2026, 10:37 AM
Duration	25 mins 25 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Rohit wants to add the last digits of two given numbers.

For example,

If the given numbers are 267 and 154, the output should be 11.

Below is the explanation:

Last digit of the 267 is 7

Last digit of the 154 is 4

Sum of 7 and 4 = 11

Write a program to help Rohit achieve this for any given two numbers.

Note: Tile sign of the input numbers should be ignored.

i.e.

if the input numbers are 267 and 154, the sum of last two digits should be 11

if the input numbers are 267 and -154, the slim of last two digits should be 11

if the input numbers are -267 and 154, the sum of last two digits should be 11

if the input numbers are -267 and -154, the sum of last two digits should be 11

For example:

Input	Result
267 154	11
267 -154	11

Answer: (penalty regime: 0 %)

```
import sys


def add_last_digits(num1, num2):
  # Convert numbers to positive to ignore negative signs
  num1 = abs(num1)
  num2 = abs(num2)

  # Extract the last digit using modulo 10
  last_digit1 = num1 % 10
  last_digit2 = num2 % 10

  # Return the sum of the last digits
  return last_digit1 + last_digit2


# Reading inputs
if __name__ == "__main__":
  input_data = sys.stdin.read().split()
  if len(input_data) >= 2:
    num1 = int(input_data[0])
    num2 = int(input_data[1])
    print(add_last_digits(num1, num2))
```

	Input	Expected	Got	
✓	267 154	11	11	✓
✓	267 -154	11	11	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Write a simple python program to find the square root of a given floating point number. The output should be displayed with 3 decimal places.

Sample Input:

8.00

Sample Output:

2.828

For example:

Input	Result
8.00	2.828
14.00	3.742

Answer: (penalty regime: 0 %)

```
import math

# Read the floating-point number from input
num = float(input())

# Calculate the square root
result = math.sqrt(num)

# Print the result formatted to 3 decimal places
print(f"{result:.3f}")
```

	Input	Expected	Got	
✓	8.00	2.828	2.828	✓
✓	14.00	3.742	3.742	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Note:

Dont use if-else. Operators alone must be used .

A team from the Rotract club had planned to conduct a rally to create awareness among the Coimbatore people to donate blood. They conducted the rally successfully. Many of the Coimbatore people realized it and came forward to donate their blood to nearby blood banks. The eligibility criteria for donating blood are people should be above or equal to 18 and his/ her weight should be above 40. There was a huge crowd and staff in the blood bank found it difficult to manage the crowd. So they decided to keep a system and ask the people to enter their age and weight in the system. If a person is eligible he/she will be allowed inside.

Write a program and feed it to the system to find whether a person is eligible or not.

Input Format:

Input consists of two integers that correspond to the age and weight of a person respectively.

Output Format:

Display True(IF ELIGIBLE)

Display False (if not eligible)

Sample Input

19

45

Sample Output

True

For example:

Input	Result
18 40	False

Answer: (penalty regime: 0 %)

```
# Read age and weight from the user
age = int(input())
weight = int(input())

# Use logical and relational operators directly without if
# The result of the condition will inherently be a boolear
is_eligible = (age >= 18) and (weight > 40)

# Print the boolean result
print(is_eligible)
```

	Input	Expected	Got	
✓	19 45	True	True	✓
✓	18 40	False	False	✓
✓	18 42	True	True	✓
✓	16 45	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

An online retailer sells two products: widgets and gizmos. Each widget weighs 75 grams. Each gizmo weighs 112 grams. Write a program that reads the number of widgets and the number of gizmos from the user. Then your program should compute and display the total weight of the parts.

Sample Input:

10

20

Sample Output:

The total weight of all these widgets and gizmos is 2990 grams.

Answer: (penalty regime: 0 %)

```
# Read the number of widgets and gizmos from the user
widgets = int(input())
gizmos = int(input())

# Calculate the total weight
total_weight = (widgets * 75) + (gizmos * 112)

# Display the result in the expected format
print(f"The total weight of all these widgets and gizmos is
```

	Input	Expected	Got	
✓	10 20	The total weight of all these widgets and gizmos is 2990 grams.	The total weight of all these widgets and gizmos is 2990 grams.	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

Write a program to find whether the given input number is Even.

If the given number is even, the function should return 2 else it should return 1.

Note: The number passed to the program can either be negative, positive or zero. Zero should be treated as Even.

For example:

Input	Result
100	2
1001	1

Answer: (penalty regime: 0 %)

```
# Read the number from the user
num = int(input())

# Check if the number is even using the modulo operator
if num % 2 == 0:
    print(2)
else:
    print(1)
```

	Input	Expected	Got	
✓	100	2	2	✓
✓	1001	1	1	✓
✓	0	2	2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

In the 1800s, the battle of Troy was led by Hercules. He was a superstitious person. He believed that his crew can win the battle only if the total count of the weapons in hand is in multiple of 3 and the soldiers are in an even number of count. Given the total number of weapons and the soldier's count, Find whether the battle can be won or not according to Hercules's belief. If the battle can be won print True otherwise print False.

Input format:

Line 1 has the total number of weapons

Line 2 has the total number of Soldiers.

Output Format:

If the battle can be won print True otherwise print False.

Sample Input:

32

43

Sample Output:'

False

For example:

Input	Result
32 43	False

Answer: (penalty regime: 0 %)

```
# Read the number of weapons and soldiers from the user
weapons = int(input())
soldiers = int(input())

# Check the conditions: weapons multiple of 3 AND soldiers
# Evaluating this directly results in a boolean (True or F
can_win = (weapons % 3 == 0) and (soldiers % 2 == 0)

# Print the boolean result
print(can_win)
```

	Input	Expected	Got	
✓	32 43	False	False	✓
✓	273 7890	True	True	✓
✓	800 4590	False	False	✓
✓	6789 32996	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Correct

Mark 1.00 out of 1.00

Mr.Ram has been given a problem kindly help him to solve it. The input of the program is either 0 or 1. IF 0 is the input he should display "C" if 1 is the input it should display "D".There is a constraint that Mr. Ram should use either logical operators or arithmetic operators to solve the problem, not anything else.

Hint:

Use ASCII values of C and D.

Input Format:

An integer x, 0<=x<=1. .

Output Format:

output a single character "C" or "D"depending on the value of x.

```
Input 1:
0
Output 1:
C
```

```
Input 2:
1

Output 1:
D
```

For example:

Input	Result
0	C

Answer: (penalty regime: 0 %)

```
# Read the input integer (0 or 1)
x = int(input())

# Calculate the ASCII value using arithmetic operators
# ASCII for 'C' is 67, and 'D' is 68.
# So, 67 + 0 = 67 ('C') and 67 + 1 = 68 ('D')
ascii_value = 67 + x

# Convert the ASCII value back to a character and print
print(chr(ascii_value))
```

	Input	Expected	Got	
✓	0	C	C	✓
✓	1	D	D	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

Write a python program that takes a integer between 0 and 15 as input and displays the number of '1' s in its binary form.(Hint:use python bitwise operator.

Sample Input

3

Sample Output:

2

Explanation:

The binary representation of 3 is 011, hence there are 2 ones in it. so the output is 2.

For example:

Input	Result
3	2

Answer: (penalty regime: 0 %)

```
# Read the integer from the user
num = int(input())

# Since the number is between 0 and 15, it can be represer
# We can use the bitwise right shift (>>) and bitwise AND
# to check the value of each of the 4 bits and sum them tc
ones_count = (num & 1) + ((num >> 1) & 1) + ((num >> 2) &

# Print the total count of 1s
print(ones_count)
```

	Input	Expected	Got	
✓	3	2	2	✓
✓	5	2	2	✓
✓	15	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

Write a program that returns the last digit of the given number. Last digit is being referred to the least significant digit i.e. the digit in the ones (units) place in the given number.

The last digit should be returned as a positive number.

For example,

if the given number is 197, the last digit is 7

if the given number is -197, the last digit is 7

For example:

Input	Result
197	7
-197	7

Answer: (penalty regime: 0 %)

```
# Read the number from the user
num = int(input())

# Get the absolute value of the number to handle negative i
# Then find the remainder when divided by 10 to get the las
last_digit = abs(num) % 10

# Print the last digit
print(last_digit)
```

	Input	Expected	Got	
✓	197	7	7	✓
✓	-197	7	7	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

Complete the program to convert days into years, month and days. (Ignoring leap year and considering 1 month is 30 days)

Sample Test Cases

Test Case 1

Input

375

Output

YEARS: 1 MONTH: 0 DAYS: 10

Test Case 2

Input

200

Output

YEARS: 0 MONTH: 6 DAYS: 20

Answer: (penalty regime: 0 %)

```
# Read the total number of days from the user
total_days = int(input())

# Calculate the number of years (assuming 365 days in a ye
years = total_days // 365

# Calculate the remaining days after subtracting the years
remaining_days = total_days % 365

# Calculate the number of months from the remaining days (
months = remaining_days // 30

# Calculate the final remaining days
days = remaining_days % 30

# Display the result in the specified format
print(f"YEARS: {years} MONTH: {months} DAYS: {days}")
```

	Input	Expected	Got	
✓	375	YEARS: 1 MONTH: 0 DAYS: 10	YEARS: 1 MONTH: 0 DAYS: 10	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.